

TS4-560 INDUSTRIAL ROBOT

HIGH-SPEED 6-AXIS FOR 3C & SMALL-PART WORK



OVERVIEW

The TS4-560 is a compact 6-axis robot built for high-speed, high-precision operations in the 3C industry. Standard cycle time under 0.33 s, IP67 wrist protection and floor/wall/ceiling mounting let it drop into tight cells for assembly, screwing, handling and inspection. It ships pre-integrated with our own inCube20 controller.

PRIMARY APPLICATIONS

3C
Assembly &
Testing

High-Speed
Handling

Screwing

Precision
Inspection

SPECIFICATIONS

Axes	6
Payload	4 kg
Max Reach	560 mm
Repeatability	±0.02 mm
Robot Weight	≈ 23 kg
Standard Cycle Time	< 0.33 s
Mounting	Floor / Wall / Ceiling
Protection	IP65 (IP67 optional)
Controller	inCube20 (in-house)

WORKING RANGE

J1 — Base rotation	−170° ... +170°
J2 — Shoulder	−110° ... +120°
J3 — Elbow	−108° ... +152°

J4 — Wrist roll	−200° ... +200°
J5 — Wrist pitch	−118° ... +118°
J6 — Tool rotation	−350° ... +350°

KEY HIGHLIGHTS

- Payload capacity 4 kg
- Maximum reach 560 mm
- Positional repeatability ± 0.02 mm
- Designed, manufactured and supported from Coimbatore, India
- In-house Texsonics RC series controller, drives and teach pendant
- Compatible with Texsonics CAM software and vision packages

WORK ENVELOPE & INSTALLATION

The TS4-560 delivers dependable performance across its work envelope with a maximum reach of 560 mm and payload of 4 kg. Every unit ships pre-integrated with the Texsonics RC series controller, teach pendant, safety I/O, and is supported locally by our engineering team from Coimbatore.

DISCLAIMER

Specifications and visuals may change without notice as part of ongoing product improvements. Images are for reference only; actual performance may vary by application. Unauthorized reproduction of this catalogue is prohibited without written permission from Texsonics Systems India Private Limited.