

TS6-0808 INDUSTRIAL ROBOT

SMALL FOOTPRINT. BIG WORK ENVELOPE.



OVERVIEW

The TS6-0808 is our compact general-purpose 6-axis platform — 8 kg payload in an 827 mm reach and only 42 kg body weight. IP65-rated, floor or ceiling mount, and small 200 × 300 mm base make it easy to drop into existing cells for CNC tending, pick-and-place, packaging and light assembly.

PRIMARY APPLICATIONS

CNC Tending	Pick & Place	Packaging	Light Assembly
----------------	-----------------	-----------	-------------------

SPECIFICATIONS	
Axes	6
Payload	8 kg
Max Reach	827 mm
Repeatability	±0.05 mm
Robot Weight	≈ 42 kg
Base Size	200 × 300 mm
Mounting	Floor / Ceiling
Protection	IP65
Controller	Texsonics RC series (in-house)

WORKING RANGE

J1 — Base rotation	$\pm 170^\circ$
J2 — Shoulder	$-145^\circ \dots +80^\circ$
J3 — Elbow	$-70^\circ \dots +180^\circ$

J4 — Wrist roll	$\pm 180^\circ$
J5 — Wrist pitch	$\pm 130^\circ$
J6 — Tool rotation	$\pm 360^\circ$

KEY HIGHLIGHTS

- Payload capacity 8 kg
- Maximum reach 827 mm
- Positional repeatability ± 0.05 mm
- Designed, manufactured and supported from Coimbatore, India
- In-house Texsonics RC series controller, drives and teach pendant
- Compatible with Texsonics CAM software and vision packages

WORK ENVELOPE & INSTALLATION

The TS6-0808 delivers dependable performance across its work envelope with a maximum reach of 827 mm and payload of 8 kg. Every unit ships pre-integrated with the Texsonics RC series controller, teach pendant, safety I/O, and is supported locally by our engineering team from Coimbatore.

DISCLAIMER

Specifications and visuals may change without notice as part of ongoing product improvements. Images are for reference only; actual performance may vary by application. Unauthorized reproduction of this catalogue is prohibited without written permission from Texsonics Systems India Private Limited.