

TS6-1215 INDUSTRIAL ROBOT

THE 12 KG CELL PARTNER WITH 1.46 M REACH



OVERVIEW

The TS6-1215 pairs a 12 kg payload with a wide 1463 mm activity radius, covering complex motion paths inside compact production layouts. Floor or ceiling mount, IP54 body with IP65 wrist, and our own controller keep integration simple across CNC tending, assembly and material handling cells.

PRIMARY APPLICATIONS

CNC Machine Tending	Loading / Unloading	Assembly	Material Handling
---------------------------	------------------------	----------	----------------------

SPECIFICATIONS	
Axes	6
Payload	12 kg
Max Reach	1463 mm
Repeatability	±0.05 mm
Robot Weight	≈ 116 kg
Base Size	290 × 300 mm
Mounting	Floor / Ceiling
Protection	IP54 body / IP65 wrist
Controller	Texsonics RC series (in-house)

WORKING RANGE

J1 — Base rotation	$\pm 180^\circ$
J2 — Shoulder	$-125^\circ \dots +90^\circ$
J3 — Elbow	$-84^\circ \dots +205^\circ$

J4 — Wrist roll	$\pm 170^\circ$
J5 — Wrist pitch	$-150^\circ \dots +116^\circ$
J6 — Tool rotation	$\pm 360^\circ$

KEY HIGHLIGHTS

- Payload capacity 12 kg
- Maximum reach 1463 mm
- Positional repeatability ± 0.05 mm
- Designed, manufactured and supported from Coimbatore, India
- In-house Texsonics RC series controller, drives and teach pendant
- Compatible with Texsonics CAM software and vision packages

WORK ENVELOPE & INSTALLATION

The TS6-1215 delivers dependable performance across its work envelope with a maximum reach of 1463 mm and payload of 12 kg. Every unit ships pre-integrated with the Texsonics RC series controller, teach pendant, safety I/O, and is supported locally by our engineering team from Coimbatore.

DISCLAIMER

Specifications and visuals may change without notice as part of ongoing product improvements. Images are for reference only; actual performance may vary by application. Unauthorized reproduction of this catalogue is prohibited without written permission from Texsonics Systems India Private Limited.