

TS6-2518 INDUSTRIAL ROBOT

25 KG PAYLOAD. 1.8 M REACH.



OVERVIEW

The TS6-2518 is our heavy-payload platform for palletizing, foundry and stamping automation, press-to-press transfer and large-part handling. A rigid cast structure and high-torque drives deliver dependable cycle times at 25 kg with a 1808 mm envelope — at a price point imported brands can't match, with local support they can't offer.

PRIMARY APPLICATIONS

Palletizing

Press /
Stamping
Tending

Foundry &
Die Casting

Large Part
Handling

SPECIFICATIONS	
Axes	6
Payload	25 kg
Max Reach	1808 mm
Repeatability	±0.08 mm
Robot Weight	≈ 191 kg
Base Size	300 × 420 mm
Mounting	Floor / Ceiling
Protection	IP54 body / IP67 wrist
Controller	Texsonics RC series (in-house)

WORKING RANGE

J1 — Base rotation	$\pm 180^\circ$
J2 — Shoulder	$-125^\circ \dots +90^\circ$
J3 — Elbow	$-77^\circ \dots +202^\circ$

J4 — Wrist roll	$\pm 180^\circ$
J5 — Wrist pitch	$\pm 125^\circ$
J6 — Tool rotation	$\pm 360^\circ$

KEY HIGHLIGHTS

- Payload capacity 25 kg
- Maximum reach 1808 mm
- Positional repeatability ± 0.08 mm
- Designed, manufactured and supported from Coimbatore, India
- In-house Texsonics RC series controller, drives and teach pendant
- Compatible with Texsonics CAM software and vision packages

WORK ENVELOPE & INSTALLATION

The TS6-2518 delivers dependable performance across its work envelope with a maximum reach of 1808 mm and payload of 25 kg. Every unit ships pre-integrated with the Texsonics RC series controller, teach pendant, safety I/O, and is supported locally by our engineering team from Coimbatore.

DISCLAIMER

Specifications and visuals may change without notice as part of ongoing product improvements. Images are for reference only; actual performance may vary by application. Unauthorized reproduction of this catalogue is prohibited without written permission from Texsonics Systems India Private Limited.