

TSCR-05E INDUSTRIAL ROBOT

WORKS WITH PEOPLE, NOT BEHIND FENCES



OVERVIEW

The TSCR-05E collaborative robot brings automation to workspaces shared with people. Harmonic-drive joints, hand-guided teaching and safety-rated monitored stop let it run fence-free machine tending, assembly, testing and packaging cells. A compact 1052 mm build height and 138 × 138 mm base make it easy to place beside operators on existing benches.

PRIMARY APPLICATIONS

Fence-free
Machine
Tending

Assembly

Testing &
Inspection

Packaging

SPECIFICATIONS

Axes	6
Payload	5 kg
Max Reach	800 mm
Repeatability	±0.03 mm
Joints	Harmonic drive, force-limited
Height	1052 mm
Base Size	138 × 138 mm
Teaching	Hand guiding + teach pendant
Safety	Collaborative operation per ISO/TS 15066 design intent
Programming	Graphical HMI / Offline CAM

WORKING RANGE

J1 — Base rotation	$\pm 170^\circ$
J2 — Shoulder	$\pm 170^\circ$
J3 — Elbow	$\pm 160^\circ$

J4 — Wrist 1	$\pm 170^\circ$
J5 — Wrist 2	$\pm 170^\circ$
J6 — Tool rotation	$\pm 175^\circ$

KEY HIGHLIGHTS

- Payload capacity 5 kg
- Maximum reach 800 mm
- Positional repeatability ± 0.03 mm
- Designed, manufactured and supported from Coimbatore, India
- In-house Texsonics RC series controller, drives and teach pendant
- Compatible with Texsonics CAM software and vision packages

WORK ENVELOPE & INSTALLATION

The TSCR-05E delivers dependable performance across its work envelope with a maximum reach of 800 mm and payload of 5 kg. Every unit ships pre-integrated with the Texsonics RC series controller, teach pendant, safety I/O, and is supported locally by our engineering team from Coimbatore.

DISCLAIMER

Specifications and visuals may change without notice as part of ongoing product improvements. Images are for reference only; actual performance may vary by application. Unauthorized reproduction of this catalogue is prohibited without written permission from Texsonics Systems India Private Limited.