

TS SERIES

MODEL

TS6-1215

The TS6-1215 pairs a 12 kg payload with a wide 1463 mm activity radius, covering complex motion paths inside compact production layouts. Floor or ceiling mount, IP54 body with IP65 wrist, and our own controller keep integration simple across CNC tending, assembly and material handling cells.

6-Axis	Repeatability	Texsonics RC	Site-ready
Payload 12 kg · Reach 1463 mm	±0.05 mm positional accuracy	In-house controller, drives and teach pendant	Floor / Wall / Ceiling mount, factory calibrated

01 SPECIFICATIONS

MECHANICAL		ENVIRONMENT / CONTROL	
AXES	6	BASE SIZE	290 × 300 mm
PAYLOAD	12 kg	MOUNTING	Floor / Ceiling
MAX REACH	1463 mm	PROTECTION	IP54 body / IP65 wrist
REPEATABILITY	±0.05 mm	CONTROLLER	Texsonics RC series (in-house)
ROBOT WEIGHT	≈ 116 kg		

02 PRODUCT



TS6-1215 · TS SERIES

03 WORKING RANGE

MOTION — GROUP A

J1 — BASE ROTATION	±180°
J2 — SHOULDER	−125° ... +90°
J3 — ELBOW	−84° ... +205°

MOTION — GROUP B

J4 — WRIST ROLL	±170°
J5 — WRIST PITCH	−150° ... +116°
J6 — TOOL ROTATION	±360°

04 OVERVIEW

ENGINEERED FOR THE
FACTORY FLOOR.

The TS6-1215 is a 6-axis industrial robot built for CNC Machine Tending and related production work. Factory-calibrated, floor or ceiling mount, and pre-integrated with the Texsonics RC series controller and teach pendant.

01 HIGH-CYCLE MOTION

Repeatability ±0.05 mm across a 1463 mm envelope — dependable for line-rate production.

02 INTEGRATED STACK

Ships with the Texsonics RC controller, safety I/O, teach pendant and offline programming environment — no third-party integration needed.

03 LOCAL SUPPORT

Engineered and assembled in Coimbatore. Field service and spares within India — no import lead times.

05 CONTROL & INTEGRATION

CONTROLLER

Texsonics RC series
in-house motion controller,
dual-kernel real-time OS

TEACH PENDANT

11.5" touch tablet
drag-teaching, Wi-Fi,
on-device offline
programming

FIELDBUS

**EtherCAT / Modbus
TCP**
industrial fieldbus,
dual-protocol support

SOFTWARE

TEXCAM offline CAM
toolpath generation, digital
twin simulation, vision

06 APPLICATIONS

Deployable across the primary applications the TS6-1215 was engineered for — full production-line integration with the Texsonics control stack.

CNC Machine Tending	Loading / Unloading	Assembly	Material Handling	
Gluing & Dispensing	Machine Tending	CNC Loading	Palletizing	Packaging
Vision Inspection				

07

BUILT FOR THE OPERATOR

- Live 3D position display
- Online command execution
- Position editor
- Variable monitor
- I/O monitor
- Error diagnostics
- Dynamic teach-in
- Digital twin simulation

08

SERVICE & SUPPORT**Made in Coimbatore.
Supported from
Coimbatore.**

Every TS6-1215 is engineered, built and calibrated in our Coimbatore facility. Field service, spares and applications engineering ship from the same address — no import lead times, no time-zone escalations.

STANDARD WARRANTY

12 months on the mechanical assembly, 12 months on the controller.

APPLICATIONS ENGINEERING

Cell design, cycle-time studies and end-of-arm tooling by our in-house team, included on every project.

SPARES & FIELD SERVICE

Direct-to-plant spares from Coimbatore, with pan-India field service engineers on 24-hour dispatch.

09

READY TO INTEGRATE**Talk to an engineer about
integrating the TS6-1215
into your line.**

Applications engineering, cycle-time sizing, and turnkey cell design are included on every project.

CONTACT**Dharmar R**

Managing Director

+91 94426 24304

dharmar@texsonics.net

www.texsonics.net

SPECIFICATIONS AND VISUALS MAY CHANGE WITHOUT NOTICE AS PART OF ONGOING PRODUCT IMPROVEMENTS. IMAGES ARE FOR REFERENCE ONLY.
UNAUTHORIZED REPRODUCTION OF THIS CATALOGUE IS PROHIBITED WITHOUT WRITTEN PERMISSION FROM TEXSONICS SYSTEMS INDIA PRIVATE LIMITED.

TS6-1215

Texsonics Systems India Private Limited

1/6-1, Keerakaran Thottam, Keeranatham, Coimbatore 641035 • Ph: +91 94426 24304

TS SERIES

6-AXIS • PAYLOAD 12 kg • REACH 1463 mm

dharmar@texsonics.net • www.texsonics.net