

TS SERIES

MODEL

TS6-2518

The TS6-2518 is our heavy-payload platform for palletizing, foundry and stamping automation, press-to-press transfer and large-part handling. A rigid cast structure and high-torque drives deliver dependable cycle times at 25 kg with a 1808 mm envelope — at a price point imported brands can't match, with local support they can't offer.

6-Axis	Repeatability	Texsonics RC	Site-ready
Payload 25 kg · Reach 1808 mm	±0.08 mm positional accuracy	In-house controller, drives and teach pendant	Floor / Wall / Ceiling mount, factory calibrated

01 SPECIFICATIONS

MECHANICAL		ENVIRONMENT / CONTROL	
AXES	6	BASE SIZE	300 × 420 mm
PAYLOAD	25 kg	MOUNTING	Floor / Ceiling
MAX REACH	1808 mm	PROTECTION	IP54 body / IP67 wrist
REPEATABILITY	±0.08 mm	CONTROLLER	Texsonics RC series (in-house)
ROBOT WEIGHT	≈ 191 kg		

02 PRODUCT



TS6-2518 · TS SERIES

03 WORKING RANGE

MOTION — GROUP A

J1 — BASE ROTATION	±180°
J2 — SHOULDER	−125° ... +90°
J3 — ELBOW	−77° ... +202°

MOTION — GROUP B

J4 — WRIST ROLL	±180°
J5 — WRIST PITCH	±125°
J6 — TOOL ROTATION	±360°

04 OVERVIEW

ENGINEERED FOR THE
FACTORY FLOOR.

The TS6-2518 is a 6-axis industrial robot built for Palletizing and related production work. Factory-calibrated, floor or ceiling mount, and pre-integrated with the Texsonics RC series controller and teach pendant.

01 HIGH-CYCLE MOTION

Repeatability ±0.08 mm across a 1808 mm envelope — dependable for line-rate production.

02 INTEGRATED STACK

Ships with the Texsonics RC controller, safety I/O, teach pendant and offline programming environment — no third-party integration needed.

03 LOCAL SUPPORT

Engineered and assembled in Coimbatore. Field service and spares within India — no import lead times.

05 CONTROL & INTEGRATION

CONTROLLER

Texsonics RC series
in-house motion controller,
dual-kernel real-time OS

TEACH PENDANT

11.5" touch tablet
drag-teaching, Wi-Fi,
on-device offline
programming

FIELDBUS

**EtherCAT / Modbus
TCP**
industrial fieldbus,
dual-protocol support

SOFTWARE

TEXCAM offline CAM
toolpath generation, digital
twin simulation, vision

06 APPLICATIONS

Deployable across the primary applications the TS6-2518 was engineered for — full production-line integration with the Texsonics control stack.

Palletizing	Press / Stamping Tending	Foundry & Die Casting	Large Part Handling	
Machine Tending	CNC Loading	Assembly	Packaging	Vision Inspection

07

BUILT FOR THE OPERATOR

- Live 3D position display
- Online command execution
- Position editor
- Variable monitor
- I/O monitor
- Error diagnostics
- Dynamic teach-in
- Digital twin simulation

08

SERVICE & SUPPORT

Made in Coimbatore. Supported from Coimbatore.

Every TS6-2518 is engineered, built and calibrated in our Coimbatore facility. Field service, spares and applications engineering ship from the same address — no import lead times, no time-zone escalations.

STANDARD WARRANTY

12 months on the mechanical assembly, 12 months on the controller.

APPLICATIONS ENGINEERING

Cell design, cycle-time studies and end-of-arm tooling by our in-house team, included on every project.

SPARES & FIELD SERVICE

Direct-to-plant spares from Coimbatore, with pan-India field service engineers on 24-hour dispatch.

09

READY TO INTEGRATE

Talk to an engineer about integrating the TS6-2518 into your line.

Applications engineering, cycle-time sizing, and turnkey cell design are included on every project.

CONTACT

Dharmar R

Managing Director

+91 94426 24304

dharmar@texsonics.net

www.texsonics.net

SPECIFICATIONS AND VISUALS MAY CHANGE WITHOUT NOTICE AS PART OF ONGOING PRODUCT IMPROVEMENTS. IMAGES ARE FOR REFERENCE ONLY.
UNAUTHORIZED REPRODUCTION OF THIS CATALOGUE IS PROHIBITED WITHOUT WRITTEN PERMISSION FROM TEXSONICS SYSTEMS INDIA PRIVATE LIMITED.

TS6-2518

Texsonics Systems India Private Limited

1/6-1, Keerakaran Thottam, Keeranatham, Coimbatore 641035 • Ph: +91 94426 24304

TS SERIES

6-AXIS • PAYLOAD 25 kg • REACH 1808 mm

dharmar@texsonics.net • www.texsonics.net