

TS SERIES

MODEL

TS6-0808

The TS6-0808 is our compact general-purpose 6-axis platform — 8 kg payload in an 827 mm reach and only 42 kg body weight. IP65-rated, floor or ceiling mount, and small 200 × 300 mm base make it easy to drop into existing cells for CNC tending, pick-and-place, packaging and light assembly.

6-Axis	Repeatability	Texsonics RC	Site-ready
Payload 8 kg · Reach 827 mm	±0.05 mm positional accuracy	In-house controller, drives and teach pendant	Floor / Wall / Ceiling mount, factory calibrated

01 SPECIFICATIONS

MECHANICAL

AXES	6
PAYLOAD	8 kg
MAX REACH	827 mm
REPEATABILITY	±0.05 mm
ROBOT WEIGHT	≈ 42 kg

ENVIRONMENT / CONTROL

BASE SIZE	200 × 300 mm
MOUNTING	Floor / Ceiling
PROTECTION	IP65
CONTROLLER	Texsonics RC series (in-house)

02 PRODUCT



TS6-0808 · TS SERIES

03 WORKING RANGE

MOTION — GROUP A

J1 — BASE ROTATION	±170°
J2 — SHOULDER	−145° ... +80°
J3 — ELBOW	−70° ... +180°

MOTION — GROUP B

J4 — WRIST ROLL	±180°
J5 — WRIST PITCH	±130°
J6 — TOOL ROTATION	±360°

04 OVERVIEW

ENGINEERED FOR THE
FACTORY FLOOR.

The TS6-0808 is a 6-axis industrial robot built for CNC Tending and related production work. Factory-calibrated, floor or ceiling mount, and pre-integrated with the Texsonics RC series controller and teach pendant.

01 HIGH-CYCLE MOTION

Repeatability ±0.05 mm across a 827 mm envelope — dependable for line-rate production.

02 INTEGRATED STACK

Ships with the Texsonics RC controller, safety I/O, teach pendant and offline programming environment — no third-party integration needed.

03 LOCAL SUPPORT

Engineered and assembled in Coimbatore. Field service and spares within India — no import lead times.

05 CONTROL & INTEGRATION

CONTROLLER

Texsonics RC series
in-house motion controller,
dual-kernel real-time OS

TEACH PENDANT

11.5" touch tablet
drag-teaching, Wi-Fi,
on-device offline
programming

FIELDBUS

**EtherCAT / Modbus
TCP**
industrial fieldbus,
dual-protocol support

SOFTWARE

TEXCAM offline CAM
toolpath generation, digital
twin simulation, vision

06 APPLICATIONS

Deployable across the primary applications the TS6-0808 was engineered for — full production-line integration with the Texsonics control stack.

CNC Tending	Pick & Place	Packaging	Light Assembly	Machine Tending
CNC Loading	Palletizing	Assembly	Vision Inspection	

07

BUILT FOR THE OPERATOR

- Live 3D position display
- Online command execution
- Position editor
- Variable monitor
- I/O monitor
- Error diagnostics
- Dynamic teach-in
- Digital twin simulation

08

SERVICE & SUPPORT**Made in Coimbatore.
Supported from
Coimbatore.**

Every TS6-0808 is engineered, built and calibrated in our Coimbatore facility. Field service, spares and applications engineering ship from the same address — no import lead times, no time-zone escalations.

STANDARD WARRANTY

12 months on the mechanical assembly, 12 months on the controller.

APPLICATIONS ENGINEERING

Cell design, cycle-time studies and end-of-arm tooling by our in-house team, included on every project.

SPARES & FIELD SERVICE

Direct-to-plant spares from Coimbatore, with pan-India field service engineers on 24-hour dispatch.

09

READY TO INTEGRATE**Talk to an engineer about
integrating the TS6-0808
into your line.**

Applications engineering, cycle-time sizing, and turnkey cell design are included on every project.

CONTACT**Dharmar Krishnan**

Managing Director

+91 94426 24304

dharmar@texsonics.net

www.texsonics.net

SPECIFICATIONS AND VISUALS MAY CHANGE WITHOUT NOTICE AS PART OF ONGOING PRODUCT IMPROVEMENTS. IMAGES ARE FOR REFERENCE ONLY. UNAUTHORIZED REPRODUCTION OF THIS CATALOGUE IS PROHIBITED WITHOUT WRITTEN PERMISSION FROM TEXSONICS SYSTEMS INDIA PRIVATE LIMITED.

TS6-0808

Texsonics Systems India Private Limited

1/6-1, Keerakaran Thottam, Keeranatham, Coimbatore 641035 • Ph: +91 94426 24304

TS SERIES

6-AXIS • PAYLOAD 8 kg • REACH 827 mm

dharmar@texsonics.net • www.texsonics.net