



JOB SHEET 9

ARRAY 1

1. Objective

- Students are able to understand one-dimensional Array creation and accessing its elements in Java
- Students are able to make programs using the concept of one-dimensional arrays

2. Laboratory

2.1 Experiment 1: Fill in Array Element Experiment

Time: 20 minutes

1. Open a text editor, create a new Java class with the name **arrayNumbersXX**.
(XX=student ID number)
2. Write the basic structure of the Java programming language which contains the **main()** function

3. Create an array of integer type named **num** with a capacity of 4 elements

```
int[] num = new int[4];
```

4. Fill each element of the array with numbers 5, 12, 7, 20

```
num[0] = 5;  
num[1] = 12;  
num[2] = 7;  
num[3] = 20;
```

5. Display all contents of the elements to the screen

```
System.out.println(num[0]);  
System.out.println(num[1]);  
System.out.println(num[2]);  
System.out.println(num[3]);
```

6. Compile and run the program. Match the results of the running programs that you have created according to the following display



5
12
7
20

7. Commit and push the changes to GitHub.

Questions!

1. If the contents of each element of the array **num** are changed with numbers 5.0, 12867,

7.5, 2000000. What happens? How can it be like that?

Answer : The program wont ran because the array's data type is integer and there is a decimal number.

2. Modify the program code by initializing the array elements at the same time when declaring the array.

Answer : The output will be printed, because we use a loop to print all of the index at once.

3. Change the statement in step 6 to be like this

```
for (int i = 0; i < 4; i++) {
    System.out.println(num[i]);
}
```

What is the result? How can it be like that?

Answer : The program will ran to an error because the element of the index is only from 0 to 3.

4. If the condition in the for-loop statement is changed to $i \leq 4$, what is the output of the program? Why is the result like that?

Answer : the loop will print

```
Element 0: 5
Element 1: 12
Element 2: 7
Element 3: 20
```

- an array of size 4 has indices 0, 1, 2, 3. $i \leq 4$ includes $i = 4$, which is **outside the valid range**. The program crashes because it tries to access memory that isn't allocated for the array
5. Commit and push the changes to GitHub.



2.2 Experiment 2: Requesting User Input to Fill in an Array Element Experiment

Time: 40 minutes

1. Open a text editor, create a Java file then save it with the name **arrayValueXX**.
(XX=student ID number)
2. Write the basic structure of the Java programming language which contains the **main()** function
3. Add the Scanner library
4. Create an array of integer type with the name **finalScore**, with a capacity of 10 elements

```
int[] finalScore = new int[10];
```

5. Using a loop, create an input to fill in the **finalScore** array element

```
for (int i = 0; i < 10; i++) {  
    System.out.print("Enter the final score " + i + ": ");  
    finalScore[i] = sc.nextInt();  
}
```

6. Using a loop, display all the contents of the elements from the **finalScore** array

```
for (int i = 0; i < 10; i++) {  
    System.out.println("Final score " + i + " is " + finalScore[i]);  
}
```

7. Compile and run the program. Match the results of the running programs that you have created according to the following display



```
Enter the final score 0: 78
Enter the final score 1: 89
Enter the final score 2: 94
Enter the final score 3: 85
Enter the final score 4: 79
Enter the final score 5: 87
Enter the final score 6: 93
Enter the final score 7: 72
Enter the final score 8: 86
Enter the final score 9: 91
Final score 0 is 78
Final score 1 is 89
Final score 2 is 94
Final score 3 is 85
Final score 4 is 79
Final score 5 is 87
Final score 6 is 93
Final score 7 is 72
Final score 8 is 86
Final score 9 is 91
```

8. Commit and push the changes to GitHub.

Questions!

1. Change the statement in step 5 to be like this

```
for (int i = 0; i < finalScore.length; i++) {
    System.out.print("Enter the final score " + i + ": ");
    finalScore[i] = sc.nextInt();
}
```

Run the program. Have there been any changes? How can it be like that?

Answer : No there are no changes, because the array length is still 10.

2. Apa yang dimaksud dengan kondisi `i < finalScore.length`?

Answer : `i < finalScore.length` means that `i` is less than the length of the array elements.

3. Change the statement in step 6 to be like this, so that the program only displays the grades of students who passed, students who have a score `> 70`



```
for (int i = 0; i < finalScore.length; i++) {  
    if (finalScore[i] > 70) {  
        System.out.println("Student " + i + " Passed!");  
    }  
}
```

Run the program and describe the flow of the program!

4. Modify the program so that it displays all students, and mark which one passed, and which did not!

```
Enter the final score 0: 87  
Enter the final score 1: 65  
Enter the final score 2: 78  
Enter the final score 3: 95  
Enter the final score 4: 92  
Enter the final score 5: 58  
Enter the final score 6: 89  
Enter the final score 7: 67  
Enter the final score 8: 85  
Enter the final score 9: 78  
Student 0 Passed!  
Student 1 Failed!  
Student 2 Passed!  
Student 3 Passed!  
Student 4 Passed!  
Student 5 Failed!  
Student 6 Passed!  
Student 7 Failed!  
Student 8 Passed!  
Student 9 Passed!
```

5. Commit and push the changes to GitHub.

2.3 Experiment 3: Perform Arithmetic Operations on Array Elements

Experiment Time: 75 minutes

This experiment is done to add array elements. The program will accept input of 10 student scores. Then the program will display the average score of 10 students.

1. Open a text editor, create a Java file then save it with the name **arrayAverageScoreXX**. (XX=student ID number)
2. Write the basic structure of the Java programming language which contains the **main()** function



3. Add the Scanner library and make a **Scanner** declaration for input purposes
4. Create an array of integer types with the name **score** with a capacity of 10. Then declare the variables total and average

```
int[] score = new int[10];  
double total = 0;  
double average;
```

5. Using a loop, create an input to fill in the **score** array element

```
for (int i = 0; i < score.length; i++) {  
    System.out.print("Enter student score " + (i + 1) + ": ");  
    score[i] = sc.nextInt();  
}
```

6. Using a loop, calculate the total number of scores.

```
for (int i = 0; i < score.length; i++) {  
    total += score[i];  
}
```

7. Calculate the average value by dividing **total** by the number of elements of **score**

```
average = total / score.length;  
System.out.println("The class average score is " + average);
```

8. Compile and run the program. Match the results of the running programs that you have created according to the following display

```
Enter student score 1: 98  
Enter student score 2: 73  
Enter student score 3: 86  
Enter student score 4: 82  
Enter student score 5: 95  
Enter student score 6: 68  
Enter student score 7: 90  
Enter student score 8: 71  
Enter student score 9: 78  
Enter student score 10: 84  
The class average score is 82.5
```

9. Commit and push the changes to GitHub

Questions!

1. Modify the program in Experiment 3 so that the program can display the number of students who passed, students who have a score greater than 70 (>70)



2. Modify the program in Experiment 3 so that it can produce output like the following display

```
Enter the number of students: 5
Enter the final score 0: 81
Enter the final score 1: 76
Enter the final score 2: 90
Enter the final score 3: 68
Enter the final score 4: 63
The average score of students who passed is 82.33333333333333
The average score of students who failed is 65.5
```

3. Commit and push the changes to GitHub

2.4 Experiment 4: Searching

Experiment Time: 45 minutes

1. Open a text editor, create a Java file then save it with the name **linearSearchXX**.
(XX=student ID number)
2. Add the following code

```
6   public static void main(String[] args) {
7       int[] arrayInt = { 34, 18, 26, 48, 72, 20, 56, 63 };
8       int key = 20;
9       int result = 0;
10      for (int i = 0; i < arrayInt.length; i++) {
11          if (arrayInt[i] == key) {
12              result = i;
13              break;
14          }
15      }
16      System.out.println("The key in the array is located at index position " + result);
17  }
18  }
```

3. Compile and run the program. Match the results of the running programs that you have created according to the following display

```
The key in the array is located at index position 5
```

4. Commit and push the changes to GitHub

Questions!

1. Explain the meaning of the **break;** statement on line 13 of the program code in Experiment 4.

Answer : the function of the break line is to break the loop once the loop is finished.



2. Modify the program code in experiment 4 so that the program can receive input in the form of the number of array elements, the contents of the array, and the key you want to search for. Then, print to the screen the index of the element positions of the searched key. Example of program results:

```
Enter the number of array elements: 8
Enter the array element 0: 12
Enter the array element 1: 18
Enter the array element 2: -6
Enter the array element 3: 10
Enter the array element 4: 6
Enter the array element 5: 15
Enter the array element 6: 11
Enter the array element 7: 9
Enter the key you want to search for: 10
The key in the array is located at index position 3
```

3. Modify the program in experiment 4 so that the program will give the message "key not found" if the key is not in the array. Example of program results:

```
Enter the number of array elements: 6
Enter the array element 0: 19
Enter the array element 1: 23
Enter the array element 2: 29
Enter the array element 3: 31
Enter the array element 4: 37
Enter the array element 5: 43
Enter the key you want to search for: 11
Key not found
```

3. Assignment

1. You are asked to create a program that can store and manage student grades. The grades are integers. The program must provide features for:
 - entering the number of student grades to be entered,
 - entering each student's grade,
 - calculating the average grade,
 - displaying the highest and lowest grades, and
 - displaying all grades entered.



2. Create a program that can manage food and beverage orders at a cafe. The program will allow users to enter orders, calculate the total cost of the order, and display a list of the orders that have been placed.
 - Input:
 - number of orders (input by the user).
 - name of the food/drink and the price for each order (input by the user).
 - Process:
 - store the order data in a one-dimensional array for the order names; and a separate one-dimensional array for the prices.
 - calculate the total cost of all orders entered.
 - display a list of orders that have been entered along with the total cost.
 - Output:
 - list of orders and the total cost of all orders.
3. Continuing with the example of ordering food at a cafe, create a program that allows users to order food from the cafe's menu. The program must store a list of food items in an array and provide an option to search for the desired item using a linear search method.
 - Input:
 - a predefined menu item in array form. The item names are initialized during the array declaration. For example:

`String[] menu = {"Fried Rice", "Fried Noodles", "Toasted Bread", "Fried Potatoes", "Teh Tarik", "Cappuccino", "Chocolate Ice"};`
 - the name of the item to be searched for (user input).
 - Process:
 - the program searches for the item entered by the user using a linear search algorithm.
 - if the item is found, the program informs the user that it is available. If not, the program informs the user that the item is not on the menu.
 - Output:
 - display the search results to the user.