
Nils Hagner 4346038 Felix Karg 4342014 Michael Fleig 4340085 Anush Davtyan 4368689

Solutions for Excercise sheet 2

Exercise 1 - OCL

```
i S = (\{Int\}, TreeNode, Object, \{key : Int, left\_Child : TreeNode, right_Child : TreeNode, parent : TreeNode, value : Object\}, \{TreeNode \mapsto \{key, left\_Child, right\_Child, parent, \{\}\}, \{\}, \{TreeNode \mapsto \emptyset, Object \mapsto \{\}\}\})\mathcal{D}(Int) = Z, \mathcal{D}(TreeNode) = \{T1, T2, T3, ...\}, \mathcal{D}(Object) = \{O1, O2, O3, ...\}
a)
\sigma_1 = \{T_1 \mapsto \{key \mapsto 20, left\_Child \mapsto \{T2\}, right\_Child \mapsto \{T3\}, parent \mapsto \emptyset, value \mapsto O_1\}
T_2 \mapsto \{key \mapsto 10, left\_Child \mapsto \emptyset, right\_Child \mapsto \emptyset, parent \mapsto \{T1\}, value \mapsto O_2\}
T_3 \mapsto \{key \mapsto 20, left\_Child \mapsto \emptyset, right\_Child \mapsto \emptyset, parent \mapsto \{T1\}, value \mapsto O_3\}
O_1 \mapsto \{\}
O_2 \mapsto \{\}
O_3 \mapsto \{\}
```



The system state σ_1 evaluates to true because $key(left_Child(T_1)) \leq key(T_1) \leq key(right_Child(T_1))$

$$\sigma_{2} = \{T_{1} \mapsto \{key \mapsto 20, left_Child \mapsto \{T2\}, right_Child \mapsto \{T3\}, parent \mapsto \emptyset, value \mapsto O_{1}\}$$


$$T_{2} \mapsto \{key \mapsto 10, left_Child \mapsto \emptyset, right_Child \mapsto \emptyset, parent \mapsto \{T1\}, value \mapsto O_{2}\}$$

$$T_{3} \mapsto \{key \mapsto 10, left_Child \mapsto \emptyset, right_Child \mapsto \emptyset, parent \mapsto \{T1\}, value \mapsto O_{3}\}$$

$$O_{1} \mapsto \{\}$$

$$O_{2} \mapsto \{\}$$

$$O_{3} \mapsto \{\}$$



The system state σ_2 evaluates to false because $key(left_Child(T_1)) < key(right_Child(T_1)) = key(T_1)$

$$\sigma_3 = \{\}$$

The system state σ_3 evaluates to \perp because there are no Instances of TreeNode and the formula can not be evaluated to true or false.

iii

- a) $\forall o \in allInstances_{Object} \bullet \forall t_1 \in allInstances_{TreeNode} \bullet \forall t_2 \in allInstances_{TreeNode} \bullet (value(t_1) = o \Rightarrow value(t_2) \neq o)$
- b) $\forall t_1 \in allInstances_{TreeNode} \bullet \forall t_2 \in allInstances_{TreeNode} \bullet (t_1 = leftChild(t_2) \Leftrightarrow t_2 = parent(t_1))$

Some System States:

