

Comprehensive Analysis of Fundamental Algorithms in Rust

Thor

November 4, 2025

Contents

1	Insertion Sort	2
1.1	Idea	2
1.2	Pseudocode (CLRS)	2
1.3	Complexity	2
2	Example: Insertion Sort (Inline)	3
2.1	Implementation Listing	3
	References	4

Chapter 1

Insertion Sort

1.1 Idea

Insertion Sort builds the final sorted array one element at a time by shifting larger elements to the right.

1.2 Pseudocode (CLRS)

Algorithm 1 INSERTION-SORT(A)

```
1: Input: Array  $A[1..n]$ 
2: for  $j \leftarrow 2$  to  $n$  do
3:    $key \leftarrow A[j]$ 
4:    $i \leftarrow j - 1$ 
5:   while  $i > 0$  and  $A[i] > key$  do
6:      $A[i + 1] \leftarrow A[i]$ 
7:      $i \leftarrow i - 1$ 
8:   end while
9:    $A[i + 1] \leftarrow key$ 
10: end for
```

1.3 Complexity

Worst-case time $\Theta(n^2)$; space $\Theta(1)$.

Chapter 2

Example: Insertion Sort (Inline)

2.1 Implementation Listing

```
pub fn insertion_sort<T>(arr: &mut [T])
where
    T: Ord + Clone,
{
    if arr.len() < 2 { return; }
    for i in 1..arr.len() {
        let key = arr[i].clone();
        let mut j = i;
        while j > 0 && arr[j - 1] > key {
            arr[j] = arr[j - 1].clone();
            j -= 1;
        }
        arr[j] = key;
    }
}
```

Listing 2.1: Insertion Sort in Rust (algorithms crate)

References