

BAYESIAN MODEL SELECTION IN SENSORIMOTOR TASKS

Tim Genewein

Sensorimotor Learning and Decision Making Group



MAX-PLANCK-GESELLSCHAFT

Max Planck Institute for Biological Cybernetics
Max Planck Institute for Intelligent Systems





BIOLOGISCHE KYBERNETIK

Outline

- How to select among learned structures?
 - Bayesian model selection
- Study I
 - Test for consistency with Bayesian model selection
- Study II
 - Test for preference of simpler models - Occam's razor

Model Selection



- How does one select between several learned structures/models with tunable parameters?
 - Probabilistic formulation of this question

$$P(M_i | d) = ?$$

Bayesian model selection

Compare the probability of two models M_1 and M_2 , given the observations d :

$$\frac{P(M_1|d)}{P(M_2|d)} = \frac{P(d|M_1) P(M_1)}{P(d|M_2) P(M_2)}$$


Posterior odds = Bayes factor \times Prior odds

if $P(M_1) = P(M_2)$

$$\dots = \frac{P(d|M_1)}{P(d|M_2)}$$

*Marginal likelihood or evidence for model M_i
by integration over parameters θ :*

$$P(d|M_i) = \int P(d|M_i, \theta) P(\theta|M_i) d\theta$$




Study I

A sensorimotor paradigm for Bayesian model selection

Genewein, Braun (2012): *A sensorimotor paradigm for Bayesian model selection*, Frontiers in Human Neuroscience

Experimental Apparatus




- 3D virtual reality environment for sensorimotor tasks



Experimental Demands


- Separate model- and parameter-dimension
- “Integrating out” of the parameters

Model Selection – Experimental Setup





Probe Trials

- Probe trials with **ambiguous** visual feedback
 - Requires “integrating out” all possible shifts
 - Indicate model choice without indicating belief about parameter



Results – Bayes Factors



Conclusions

- Subjects were consistent with predictions given by Bayesian model selection
- Subjects' behavior was inconsistent with the predictions of nonprobabilistic heuristics:
 - Average shift – shift is in the middle of the cursor-array
 - Biggest shift – shift lies at the end of the cursor-array
 - Halfway shift – shift is halfway between the end and the middle

Study II


Occam's razor in a sensorimotor model selection task

Bayesian Occam's Razor

- Occam's razor
 - “If two models explain the observations equally well, prefer the simpler model.”
- Bayesian model selection embodies Occam's razor
 - Previous study did not allow to directly test for Occam's razor because:


$$P(d|\theta, M_i) = P(d|\theta)$$

$$P(d|M_i) = \int P(d|\theta, M_i)P(\theta|M_i)d\theta$$




Model Selection - Regression

- Show Occam's razor in a more natural task
- Standard textbook task to illustrate complexity: regression
- Models: Gaussian processes with different length-scales





Regression Task

- Feedback at the end of standard trials
- Color- and landscape-cue




Regression Task

- Feedback at the end of standard trials
- Color- and landscape-cue





Regression – Probe Trials

- Ambiguous stimulus (neutral color and landscape)
- No feedback on model choice









Preliminary Results


- (I) - Predicted vs. observed choice probabilities
- (II) - Choice probabilities in equal-fit condition



6 subjects – (I)



6 subjects – (II)



Summary

- We have developed a paradigm to test the predictive power of Bayesian Model Selection in a sensorimotor task
 - Observed choice behavior could be predicted by a Bayesian model
- We have also tested against alternative hypotheses (see publication)
- We have designed another paradigm to test for the preference of simpler models (Occam's razor)
 - Recorded data supports the application of the Bayesian framework for modelling human behavior in sensorimotor choice tasks

Sensorimotor Learning and Decision Making Group

Max Planck Institute for Biological Cybernetics

Max Planck Institute for Intelligent Systems

Tübingen, Germany

Daniel Braun

Pedro Ortega

Jordi Grau

Tim Genewein

Zhen Peng

Felix Leibfried

Gaussian Processes

Noisy observations are drawn from a Gaussian posterior:

$$\mathbf{y} \sim \mathcal{N}(\mathbf{0}, K + \sigma_n^2 I)$$

Log marginal likelihood (evidence) as required for computing the Bayes factor:

$$\log p(\mathbf{y}|X) = \underbrace{-\frac{1}{2}\mathbf{y}^\top (K + \sigma_n^2 I)^{-1}\mathbf{y}}_{\text{observation dependent term}} - \underbrace{\frac{1}{2} \log |K + \sigma_n^2 I| - \frac{n}{2} \log 2\pi}_{\text{complexity (volume)}}$$

with:

$K = \text{kernel}(X, X)$

\mathbf{y} ... observed (noisy) values

X ... input (or training) locations

n ... number of input locations

σ_n^2 ... variance of observation noise

Modeling

- Bayesian model selection – Bayes factors

Marginal likelihood



$$P(d|M_i) = \int P(d|s, M_i)P(s|M_i)ds$$

Softmax with
Bayes factor

$$P(a = M_1|d) = \frac{1}{1 + e^{-\alpha \log \frac{P(d|M_1)}{P(d|M_2)}}}$$

Modeling – Likelihood Model

- $P(d|s, M_i) = P(d|s)$
- For given shift s , all array-widths d are equally probable; but the array must contain the shift (i.e. $d \geq s$)!



Modeling – Alternative Models

- Bayesian policy inference

$$P(a = M_1 | d) = \int P(a = M_1 | s) P(s | d) ds$$



- Stochastic superposition of given policies
- i.e. weighted average of all shifts inside the cursor-array

- Heuristics



- Average shift $P(a = M_1 | d) = P(a = M_1 | s = 0)$
- Biggest shift $P(a = M_1 | d) = P\left(a = M_1 \middle| s = \frac{d}{2}\right)$
- Halfway shift $P(a = M_1 | d) = P\left(a = M_1 \middle| s = \frac{d}{4}\right)$

Modeling – Individual Fits

- Psychometric functions fitted to the standard trials
- $P(a = M_1 | s)$




Results – Bayesian Policy Inference




Results - Heuristics

Average shift



Biggest shift



Results – Halfway-Shift Heuristic

