

Web scraping

Week 13

AEM 2850 / 5850 : R for Business Analytics
Cornell Dyson
Spring 2025

Announcements

Only two full weeks left!

Remaining deadlines:

- Homework-13 will be due Monday
- Homework-14 will be our example in class next Thursday
- Prelim 2 on May 6 in class (two weeks from today)

Questions before we get started?

Plan for today

Web scraping basics

Web scraping with rvest

- Cornell sports
- College rankings

Group project debrief

Prelim 2

Web scraping basics

What is web scraping?

Getting data or "content" off the web and onto our computers

We get content off the web all the time!

- Copy and paste
- Read and take notes
- Screenshot

The goal of web **scraping** is to write computer code to help us automate this process and store the results in a machine-readable format

Why would we want to scrape data?

When is web scraping useful?

- When the data is publicly available
- When you can't get the data in a more convenient format

When is web scraping not useful?

- When data is publicly available in other formats (e.g., csv)
- When the site owner offers a way to access data directly (e.g., via an API)

Web scraping is time consuming and costly (for both you and "them")

Server-side vs client-side content

1. Server-side

- Host server "builds" site and sends HTML code that our browser renders
- All the information is embedded in the website's HTML

2. Client-side

- Site contains an empty template of HTML and CSS
- When we visit, our browser sends a *request* to the host server
- The server sends a *response* script that our browser uses to populate the HTML template with information we want

We will focus on server-side web scraping due to time constraints

What is HTML?

HTML stands for "HyperText Markup Language" and looks like this:

```
<html>
<head>
  <title>Page title</title>
</head>
<body>
  <h1 id='first'>A heading</h1>
  <p>Some text & <b>some bold text.</b></p>
  <img src='myimg.png' width='100' height='100'>
</body>
```


What is HTML?

HTML has a hierarchical structure formed by **elements** that consist of:

1. a start tag
 - optional attributes
2. contents
3. an end tag

What is HTML?

HTML has a hierarchical structure formed by **elements** that consist of:

1. a start tag (e.g., `<h1>`)
 - optional attributes (e.g., `id='first'`)
2. contents in between tags (e.g., `A heading`)
3. an end tag (e.g., `</h1>`)

```
<html>
<head>
  <title>Page title</title>
</head>
<body>
  <h1 id='first'>A heading</h1>
  <p>Some text & <b>some bold text.</b></p>
  <img src='myimg.png' width='100' height='100'>
</body>
```

What is HTML?

Elements

- There are over 100 HTML elements
- Google tags to learn about them as needed

Contents

- Most elements can have content in between start and end tags
- Content can be text or more elements (as **children**)

Attributes

- Attributes like **id** and **class** are used with CSS to control page appearance
- These attributes are useful for scraping data

What is CSS?

CSS stands for **C**ascading **S**tyle **S**heets

- Tool for defining visual appearance of HTML

CSS selectors help identify what we want to scrape

We will learn by example using the extension/bookmarklet **SelectorGadget**

Web scraping with rvest

The rvest package

rvest (as in "harvest") is part of the tidyverse

```
library(rvest) # installed with tidyverse but needs to be loaded
```


We will cover several functions that make it easy to scrape data from web pages:

- **read_html** reads HTML, much like **read_csv** reads .csv files
- **html_element(s)** find HTML elements using CSS selectors or XPath expressions
- **html_text2** retrieves text from HTML elements
- **html_table** parses HTML tables into data frames

Let's learn these commands by working through two examples

Example 1: Cornell Big Red on Wikipedia

How could we scrape a list of varsity sports?



WIKIPEDIA
The Free Encyclopedia

- [Main page](#)
- [Contents](#)
- [Current events](#)
- [Random article](#)
- [About Wikipedia](#)
- [Contact us](#)
- [Donate](#)

Contribute

- [Help](#)
- [Learn to edit](#)
- [Community portal](#)
- [Recent changes](#)
- [Upload file](#)

Tools

- [What links here](#)
- [Related changes](#)
- [Special pages](#)
- [Permanent link](#)
- [Page information](#)
- [Cite this page](#)

Article [Talk](#)

Read [Edit](#) [View history](#)

Cornell Big Red

From Wikipedia, the free encyclopedia

The **Cornell Big Red** is the informal name of the sports teams, and other competitive teams, that represent [Cornell University](#), located in [Ithaca, New York](#). The university sponsors 36 varsity sports, as well as numerous [intramural](#) and club teams. Cornell participates in [NCAA Division I](#) as part of the [Ivy League](#). The [men's](#) and women's ice hockey teams compete in the [ECAC Hockey League](#). Additionally, teams compete in the [National Intercollegiate Women's Fencing Association](#), the [Collegiate Sprint Football League](#), the [Eastern Association of Rowing Colleges](#) (EARC), the [Eastern Association of Women's Rowing Colleges](#) (EAWRC), the [Middle Atlantic Intercollegiate Sailing Association](#), and the [Eastern Intercollegiate Wrestling Association](#) (EIWA).

Contents [hide]

- 1 [History](#)
 - 1.1 [Fight songs](#)
- 2 [Sports sponsored](#)
 - 2.1 [Championship teams](#)
 - 2.2 [Other teams](#)
 - 2.3 [Club teams](#)
- 3 [Facilities](#)
- 4 [Rivalries](#)
- 5 [See also](#)
- 6 [References](#)
- 7 [External links](#)

Cornell Big Red



University	Cornell University
Conference	Ivy League ECAC Hockey NIWFA Collegiate Sprint Football League EARC EAWRC MAISA EIWA College Squash Association

Option 1: use dt tag to get headings

Championship teams [edit]

Baseball

Main article: [Cornell Big Red baseball](#)

- Ivy 1972, 1977, 1979, 1982, 2012
- EIBL 1939, 1940, 1952, 1972, 1977^[6]

Men's basketball

Main article: [Cornell Big Red men's basketball](#)

- Ivy 1988,^[7] 2008, 2009,^[8] 2010^[9]

Women's basketball

Main article: [Cornell Big Red women's basketball](#)

- Ivy 2008^[10]

Men's cross country

- Heptagonal Champions 1939, 1940, 1953, 1954, 1955, 1957, 1961, 1963, 1993
- Ivy Champions 1957, 1961, 1963, 1992, 1993^[11]

Women's cross country

- Heptagonal Champions 1991, 1992, 1993, 1998, 2011, 2012^[12]

Football

Main article: [Cornell Big Red football](#)

- National 1915, 1921, 1922, 1939



Poster illustration of a Cornell baseball player, 1908.

Men's sports	Women's sports
Baseball	Basketball
Basketball	Cross country
Cross country	Equestrian
Football	Fencing
Golf	Field hockey

dt

Clear (77)

Toggle Position

XPath

Help

X

Scraping text using dt tag

Step 1: use `read_html()` to read in html from the url of interest

```
big_red <- read_html("https://en.wikipedia.org/wiki/Cornell_Big_Red")
```

```
big_red
```

```
## {html_document}
```

```
## <html class="client-nojs vector-feature-language-in-header-enabled vector-feature-language-in-main-page
```

```
## [1] <head>\n<meta http-equiv="Content-Type" content="text/html; charset=UTF-8 ...
```

```
## [2] <body class="skin--responsive skin-vector skin-vector-search-vue mediawik ...
```

Scraping text using dt tag

Step 2: use `html_elements()` to extract every instance of a `dt` tag

```
big_red <- read_html("https://en.wikipedia.org/wiki/Cornell_Big_Red")  
big_red |>  
  html_elements("dt") |> # dt tag is for terms in a description list  
  head(8)
```

```
## {xml_nodeset (8)}  
## [1] <dt>Baseball</dt>  
## [2] <dt>Men's basketball</dt>  
## [3] <dt>Women's basketball</dt>  
## [4] <dt>Men's cross country</dt>  
## [5] <dt>Women's cross country</dt>  
## [6] <dt>Women's fencing</dt>  
## [7] <dt>Football</dt>  
## [8] <dt>Sprint football</dt>
```

Scraping text using dt tag

Step 3: use `html_text2()` to convert the sports to a character vector

```
big_red <- read_html("https://en.wikipedia.org/wiki/Cornell_Big_Red")
big_red_text <- big_red |>
  html_elements("dt") |> # dt tag is for terms in a description list
  html_text2()           # convert html to text
head(big_red_text)      # looks good!
```

```
## [1] "Baseball"          "Men's basketball"    "Women's basketball"
## [4] "Men's cross country" "Women's cross country" "Women's fencing"
```

```
length(big_red_text) # hmm...
```

```
tail(big_red_text) # uh-oh...
```

```
## [1] 83
```

```
## [1] "WFTDA" "MRDA" "USARL" "NARL" "USAR" "WTT"
```

That doesn't seem right...

What went wrong?

1. Got irrelevant data

Sports teams based in New York State	
Baseball	MLB: New York Mets · New York Yankees · IL: Buffalo Bisons · Rochester Red Wings · Syracuse Brooklyn Cyclones · Hudson Valley Renegades · ALPB: Long Island Ducks · Staten Island Ferry New York Boulders · Tri-City ValleyCats · ACBL: Hampton Whalers · NYCBL: Cortland Crush · G Rochester Ridgemen · Rome Generals · Sherrill Silversmiths · Syracuse Salt Cats · Syracuse Sp Jamestown Jammers · Newark Pilots
Basketball	NBA: Brooklyn Nets · New York Knicks · WNBA: New York Liberty · G League: Long Island Nets Jamestown Jackals · IBA: Schenectady Legends · Entertainment Teams: Harlem Wizards
Esports	CDL: New York Subliners · OWL: New York Excelsior
Football	NFL: Buffalo Bills · NAL: Albany Empire · WFA: New York Sharks · EFL: Watertown Red & Black
Hockey	NHL: Buffalo Sabres · New York Islanders · New York Rangers · AHL: Rochester Americans · Sy Adirondack Thunder · PHF: Buffalo Beauts · FPHL: Binghamton Black Bears · Watertown Wolves Buffalo Jr. Sabres · Entertainment Teams: Buffalo Sabres Alumni Hockey Team
Soccer	MLS: New York City FC · USLC: Queensboro FC (2023) · MLSNP: Rochester New York FC · Ne Flower City Uni (2023) · New Amsterdam FC · New York Cosmos · USL EFL: Empire State Manhattan SC New York Shot

What went wrong?

1. Got irrelevant data
2. Didn't get relevant data

Volleyball

- Ivy 1991, 1992, 1993, 2004, 2005, 2006

Men's wrestling^[30]

Main article: [Cornell Big Red wrestling](#)

See also: [Collegiate wrestling](#), [Eastern Ir](#)

- EIWA champions 1910, 1912–1917, 1921
- Ivy League champions 1957–1960, 1962
- NCAA Runner-up 2010, 2011^[34]

Other teams [\[edit \]](#)

- Equestrian
- Women's Fencing
- Men's Golf
- Gymnastics
- Men's Squash

Option 2: use `.wikitable` tag to get table

- Ivy 2008^[10]

Men's cross country

- Heptagonal Champions 1939, 1940, 1953, 1954, 1955, 1957, 1961, 1963, 1993
- Ivy Champions 1957, 1961, 1963, 1992, 1993^[11]

Women's cross country

- Heptagonal Champions 1991, 1992, 1993, 1998, 2011, 2012^[12]

Football

Main article: [Cornell Big Red football](#)

- National 1915, 1921, 1922, 1939^{[13][14]}
- Ivy 1971, 1988, 1990

Sprint football

- [CSFL](#) 1975(Co-Champs), 1978, 1982, 1984(Tri-Champs), 1986(Tri-Champs), 2006

Field Hockey

- Ivy 1991

Men's ice hockey

Main article: [Cornell Big Red men's ice hockey](#)

- NCAA 1967, 1970
- ECAC 1967, 1968, 1969, 1970, 1973, 1980, 1986, 1996, 1997, 2003, 2005, 2010
- Ivy 1966, 1967, 1968, 1969, 1970, 1971, 1972, 1973, 1977, 1978, 1983, 1984*, 1985*, 1996, 1997, 2002, 2003, 2004*, 2005, 2012, 2014, 2018, 2019, 2020^[15] (*shared title)
- [Ned Harkness Cup](#) 2003, 2005, 2008, 2013

Women's ice hockey

Main article: [Cornell Big Red women's ice hockey](#)

- NCAA Frozen Four 2010, 2011, 2012, 2013, 2014
- ECAC 2010, 2011, 2013, 2014

Men's sports	Women's sports
Baseball	Basketball
Basketball	Cross country
Cross country	Equestrian
Football	Fencing
Golf	Field hockey
Ice hockey	Gymnastics
Lacrosse	Ice hockey
Polo	Lacrosse
Rowing (heavyweight)	Polo
Rowing (lightweight)	Rowing
Soccer	Sailing
Sprint Football	Soccer
Squash	Softball
Swimming & diving	Squash
Tennis	Swimming & diving
Track and field[†]	Tennis
Wrestling	Track and field[†]
	Volleyball
[†] – Track and field includes both indoor and outdoor.	

div table

.wikitable

Clear (1)

Toggle Position

XPath

Help

X

Scraping tables using `.wikitable` tag

Step 1: use `read_html()` to read in html from the url of interest

```
big_red <- read_html("https://en.wikipedia.org/wiki/Cornell_Big_Red")
```

Step 2: use `html_element()` to extract the first table element

```
big_red |>  
  html_element(".wikitable") # extract the first .wikitable
```

```
## {html_node}  
## <table class="wikitable" style="">  
## [1] <tbody>\n<tr>\n<th scope="col" style="background-color:#B31B1B;color:#FFF ...
```

Scraping tables using `.wikitable` tag

Step 3: use `html_table()` to convert the table into a data frame

```
big_red_table <- big_red |>
  html_element(".wikitable") |> # extract the first .wikitable
  html_table()                  # convert html to a data frame

head(big_red_table, 8)
```

```
## # A tibble: 8 × 2
##   `Men's sports` `Women's sports`
##   <chr>          <chr>
## 1 Baseball      Basketball
## 2 Basketball    Cross country
## 3 Cross country Equestrian
## 4 Football      Fencing
## 5 Golf          Field hockey
## 6 Ice hockey    Gymnastics
## 7 Lacrosse      Ice hockey
## 8 Polo          Lacrosse
```


Scraped data frames are data frames

```
tidy_big_red <- big_red_table |>
  pivot_longer(everything(), names_to = "gender", values_to = "sport") |>
  filter(sport != "" & !str_detect(sport, "^†")) # remove things that aren't sports
```

```
tidy_big_red
```

```
## # A tibble: 35 × 2
##   gender      sport
##   <chr>      <chr>
## 1 Men's sports Baseball
## 2 Women's sports Basketball
## 3 Men's sports Basketball
## 4 Women's sports Cross country
## 5 Men's sports Cross country
## 6 Women's sports Equestrian
## 7 Men's sports Football
## 8 Women's sports Fencing
## 9 Men's sports Golf
## 10 Women's sports Field hockey
## # i 25 more rows
```

Scraped data frames are data frames

What function(s) could we use to determine how many gender category-sport pairs there are in `tidy_big_red`?

```
tidy_big_red |>  
  count()
```

```
## # A tibble: 1 × 1  
##       n  
##   <int>  
## 1    35
```

```
tidy_big_red |>  
  nrow()
```

```
## [1] 35
```

(Or we could have gone back one slide to look at the tibble header...)

Scraped data frames are data frames

What function(s) could we use to determine how many distinct sports there are in `tidy_big_red`?

```
tidy_big_red |>  
  distinct(sport) |>  
  count()
```

```
## # A tibble: 1 × 1  
##       n  
##   <int>  
## 1    25
```

```
tidy_big_red |>  
  select(sport) |>  
  n_distinct()
```

```
## [1] 25
```

Scraped data frames are data frames

What function could we use to determine how many distinct sports are there for each gender category?

```
tidy_big_red |>  
  count(gender)
```

```
## # A tibble: 2 × 2  
##   gender          n  
##   <chr>        <int>  
## 1 Men's sports    17  
## 2 Women's sports  18
```

Example 2: College rankings on Wikipedia

How could we scrape college rankings?



The screenshot shows the Wikipedia article titled "College and university rankings in the United States". The page layout includes a left sidebar with navigation links such as "Main page", "Contents", "Current events", "Random article", "About Wikipedia", "Contact us", "Donate", "Contribute", "Help", "Learn to edit", "Community portal", "Recent changes", "Upload file", "Tools", "What links here", "Related changes", "Special pages", "Permanent link", "Page information", "Cite this page", and "Wikidata item". The main content area features the article title, a sub-header "From Wikipedia, the free encyclopedia", and a notice about a suggested merge of "Criticism of college and university rankings (North America)". Below this, the article text discusses various college rankings, mentioning "U.S. colleges and universities", "U.S. News & World Report", "Academic Influence rankings", "Academic Ranking of World Universities", "Council for Aid to Education", "Forbes college rankings", "Niche rankings", "The Princeton Review Dream Colleges", "QS World University Rankings: USA", "Social Mobility Index (SMI) rankings", "The Top American Research Universities", "The Wall Street Journal/Times Higher Education College Rankings", and "Washington Monthly Rankings". A "Contents" section is also visible, listing these rankings with numbered links.

*The site has changed over time, so we will scrape an archive from **The Wayback Machine**. One of web scraping's many challenges!*

Use `.wikitable` tag to get the first table

```
rankings <- read_html("https://web.archive.org/web/20220405170508/https://en.wikipedia.org/wiki/Col  
first_table <- rankings |>  
  html_element(".wikitable") |> # extract the first .wikitable  
  html_table()                  # convert html to a data frame  
  
first_table
```

```
## # A tibble: 21 × 5  
##   Top national universit...1 `2022 rank` `` Top liberal arts col...2 `2022 rank`  
##   <chr>                <int> <lgl> <chr>                <int>  
## 1 Princeton University      1 NA Williams College      1  
## 2 Columbia University       2 NA Amherst College      2  
## 3 Harvard University        2 NA Swarthmore College   3  
## 4 Massachusetts Institute... 2 NA Pomona College      4  
## 5 Yale University           5 NA Wellesley College    5  
## 6 Stanford University       6 NA Bowdoin College     6  
## 7 University of Chicago     6 NA United States Naval A... 6  
## 8 University of Pennsylv...  8 NA Claremont McKenna Col... 8  
## 9 California Institute of... 9 NA Carleton College     9  
## 10 Duke University          9 NA Middlebury College   9  
## # i 11 more rows
```

Scraped data frames are data frames

How does Cornell stack up?

How could we find it within a table with many other schools?

```
first_table |>
  select(uni = 1, rank = 2) |>      # select and rename the first two columns
  filter(str_detect(uni, "Cornell")) # use pattern matching to find Cornell
```

```
## # A tibble: 1 × 2
##   uni          rank
##   <chr>        <int>
## 1 Cornell University    17
```

What if CSS selectors match multiple tables?

Top national universities ^[13]	2022 rank
Princeton University	1
Columbia University	2
Harvard University	2
Massachusetts Institute of Technology	2
Yale University	5
Stanford University	6
University of Chicago	6
University of Pennsylvania	8
California Institute of Technology	9

University	Parents' Dream College Ranking
Stanford University	1
Princeton University	2
Massachusetts Institute of Technology	3
Harvard University	4
New York University	5
University of Pennsylvania	6
University of Michigan	7
Duke University	8
University of California, Los Angeles	9
Cornell University	10

What if CSS selectors match multiple tables?

Multiple options:

- 1. Tweak CSS selectors to uniquely identify element (if possible)**
- 2. Scrape all of them, then use familiar R tools to extract data**

Let's try option 2

Scrape all the tables

Use `html_elements()` to extract all matching elements

```
all_tables <- rankings |>  
  html_elements(".wikitable") |> # extract all the .wikitable  
  html_table()                  # convert html to a data frame
```

```
class(all_tables) # we get a list of tables
```

```
## [1] "list"
```

```
length(all_tables) # 11 tables, to be exact
```

```
## [1] 11
```

How could we extract individual tables?

```
## # A tibble: 3 × 2
##   `Top national universities[13]` `2022 rank`
##   <chr>                           <int>
## 1 Princeton University           1
## 2 Columbia University            2
## 3 Harvard University             2
```

```
## # A tibble: 3 × 2
##   University                        `Students' Dream College Ranking`
##   <chr>                             <int>
## 1 Stanford University              1
## 2 Harvard University              2
## 3 University of California, Los Angeles 3
```

```
## # A tibble: 3 × 2
##   University                        `Parents' Dream College Ranking`
##   <chr>                             <int>
## 1 Stanford University              1
## 2 Princeton University            2
## 3 Massachusetts Institute of Technology 3
```

String matching again!

```
# use str_detect() to search for tables with "Parents"  
str_detect(all_tables, "Parents")
```

```
## [1] FALSE FALSE FALSE FALSE FALSE FALSE FALSE TRUE FALSE FALSE FALSE
```

```
# or use str_which() to get position of matching object(s)  
str_which(all_tables, "Parents")
```

```
## [1] 8
```

You are fulfilling your parents' dreams

```
# now extract table(s) with "Parents"  
# below we use `[]` syntax to extract the table by index  
# this is because because all_tables is a list, not a data frame  
all_tables[str_detect(all_tables, "Parents")]
```

```
## [[1]]
```

```
## # A tibble: 10 × 2
```

##	University	`Parents' Dream	College Ranking`
##	<chr>		<int>
##	1 Stanford University		1
##	2 Princeton University		2
##	3 Massachusetts Institute of Technology		3
##	4 Harvard University		4
##	5 New York University		5
##	6 University of Pennsylvania		6
##	7 University of Michigan		7
##	8 Duke University		8
##	9 University of California, Los Angeles		9
##	10 Cornell University		10

Group project

Overall feedback

Good job!

Overall we were pleased with everyone's work

This assignment was meant to push you, and it was interesting to see the approaches different groups took

Group project highlights

Many groups included things like executive summaries, a table of contents, etc. to tie the report together

One group went above and beyond by providing a secondary visualization that they thought improved on the one we had asked for

AEM 5850 groups produced clear slide decks with key results

- Groups rose to the challenge of using our old tools to output something new
- One group added some real polish in post-processing
- Fun fact: quarto can use powerpoint templates

Grading

Median grade was 90%

We posted scores along with feedback on canvas

Please email me, Victor, and Xiaorui if you have any questions about grading

- Do this in a single email so we all have access to the same information

Questions?

Prelim 2

Motivation

Use prelims to assess what you have each learned this semester

Benefit from using a mix of assessments that provide more signal, less noise

Learn from experience of other programming courses on campus

Prelim 2 last year

Last year, prelim 2 was a mix of data visualization and programming concepts

Roughly 1/2 of the points did not require writing any code

Examples:

1. "Describe four changes you would make to improve this data visualization without losing any information."
2. "Describe three changes you could make to this visualization to better illustrate the ideas in the text above."

Prelim 2 this year

This year, prelim 2 will emphasize the same content

Format: paper exam, closed-book (-notes, -computer, etc.)

It will stress concepts more than syntax (but will test both)

We will have multiple question types, including but not limited to:

1. improve this data visualization
2. explain how you would approach a coding task
3. explain what this function call would return
4. explain whether/why this code would fail
5. write code snippets

If we ask you to write code snippets, we will provide a function reference sheet

Prelim 2 preparation

We will provide practice questions next week

I will offer extra office hours by appointment

The TAs will have regular open office hours May 2 and May 5

We are working to schedule an extra review session on May 5 in the late afternoon

Questions?