

LOAD BALANCING UNSTRUCTURED MESHES FOR MASSIVELY PARALLEL
TRANSPORT SWEEPS

A Thesis
by
TAREK HABIB GHADDAR

Submitted to the Office of Graduate and Professional Studies of
Texas A&M University
in partial fulfillment of the requirements for the degree of
MASTER OF SCIENCE

Chair of Committee, Dr. Jean C. Ragusa
Committee Members, Dr. Jim E. Morel
Dr. Bojan Popov
Head of Department, Dr. Yassin Hassan

May 2016

Major Subject: Nuclear Engineering

Copyright 2016 Tarek Habib Ghaddar

ABSTRACT

When running any massively parallel code, load balancing is a priority in order to achieve the best possible parallel efficiency. A load balanced problem has an equal number of degrees of freedom per processor. Load balancing is important in order to minimize idle time for all processors by equally distributing (as much as possible) the work each processor has to do. An unstructured meshing capability was implemented in PDT, Texas A&M University's massively parallel deterministic transport code, utilizing the Triangle mesh generator, hence allowing the user to define more realistic problem geometries and to define 3D problems through the extrusion of 2D meshes. However, unstructured grids are significantly harder to load balance than Cartesian rectangular meshes. A load balancing algorithm was implemented in PDT to minimize a metric that determines how unbalanced a mesh is based on the number of mesh cells per processor.

ACKNOWLEDGEMENTS

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Integer lectus quam, condimentum quis bibendum eu, sollicitudin eget lacus. Praesent non sodales odio. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos himenaeos. Nulla ac luctus sapien. Morbi cursus sapien eget lorem fermentum hendrerit. Nam ac erat dui, in cursus velit. Vivamus hendrerit porttitor nisi, ut porttitor lorem volutpat eget. In ligula ligula, euismod ut condimentum sit amet, pulvinar sit amet diam. Pellentesque interdum, ipsum ullamcorper consequat dignissim, sem arcu egestas mauris, vitae interdum sem tortor ut ante. Nunc blandit laoreet nisi, non rutrum lorem hendrerit quis. Cras nunc diam, convallis et feugiat at, auctor id libero. Nunc facilisis massa eu eros imperdiet vestibulum. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Donec non velit vitae tortor blandit semper.

Etiam vitae dolor nulla. Ut eros odio, rhoncus eget placerat vitae, elementum ac ante. Proin vitae odio eu nisl pharetra mattis. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Phasellus fermentum lacus consectetur neque consequat ullamcorper. Cras blandit urna non dui consequat molestie. Curabitur viverra nibh at nisi semper faucibus. Nam egestas mauris a enim dignissim nec consectetur tortor rutrum. Mauris at nisi in est luctus congue ut mattis est. Ut pretium, mi quis elementum cursus, ante eros suscipit ligula, ut porttitor elit leo sed turpis. Nam sed dui ligula.

TABLE OF CONTENTS

	Page
ABSTRACT	ii
ACKNOWLEDGEMENTS	iii
TABLE OF CONTENTS	iv
LIST OF FIGURES	v
LIST OF TABLES	vii
1. INTRODUCTION	1
2. THE TRANSPORT EQUATION	3
3. PARALLELIZATION OF TRANSPORT SWEEPS	8
3.1 KBA Partitioning for Structured Grids	10
3.2 The Structured Transport Sweep in PDT	11
3.3 The Unstructured Transport Sweep	15
3.3.1 Cycle Detection	16
4. MOTIVATION AND METHODS	18
5. RESULTS	23
5.1 Test Cases for Metric Behavior and Convergence	23
5.2 Metric Behavior and Convergence	25
5.3 Solution Verification	34
5.3.1 The 1D Pure Absorber Slab	36
5.3.2 The 1D Pure Scatterer Slab	39
5.4 2D and 2D Extruded Meshing Capability	41
6. CONCLUSION	44
APPENDIX A. TABULATED CONVERGENCE STUDY DATA	45
REFERENCES	54

LIST OF FIGURES

5.10	The difference in metric behavior of the third test case with no load balancing iterations.	32
5.11	The difference in metric behavior of the third test case after ten load balancing iterations.	33
5.12	The difference in metric behavior of the third test case with no iteration and 10 iterations. The closer the z-value to zero, the better the improvement.	34
5.13	The geometry and mesh used in solution verification problems.	35
5.14	The pure absorber solution with four different angular refinements.	38
5.15	The pure absorber solution run with 70 positive polar angles.	39
5.16	The pure scatterer solution run with 40 positive polar angles.	41
5.17	The 2D mesh of the IM1 problem.	42
5.18	The 2D extruded view of the IM1 problem.	43

LIST OF TABLES

TABLE	Page
A.1 The metric behavior of the first test case run with no load balancing iterations.	45
A.2 The metric behavior of the first test case after 10 load balancing iterations.	46
A.3 The difference in metric behavior between no iteration and 10 iterations. The closer the z-value to zero, the better the improvement.	47
A.4 The metric behavior of the second test case after no load balancing iterations.	48
A.5 The metric behavior of the second test case after 10 load balancing iterations.	49
A.6 The difference in metric behavior between no iteration and 10 iterations. The closer the z-value to zero, the better the improvement.	50
A.7 The metric behavior of the third test case after no load balancing iterations.	51
A.8 The metric behavior of the third test case after 10 load balancing iterations.	52
A.9 The difference in metric behavior between no iteration and 10 iterations. The closer the z-value to zero, the better the improvement.	53

1. INTRODUCTION

When running any massively parallel code, load balancing is a priority in order to achieve the best possible parallel efficiency. A load balanced problem has an equal number of degrees of freedom per processor. Load balancing is important in order to minimize idle time for all processors by equally distributing (as much as possible) the work each processor has to do.

The concepts and results presented in this thesis are used by PDT, Texas A&M University's massively parallel deterministic transport code. It is capable of multi-group simulations and employs discrete ordinates for angular discretization. PDT features steady-state, time-dependent, criticality, and depletion simulations. It solves the transport equation for neutron, thermal, gamma, coupled neutron-gamma, electron, and coupled electron-photon radiation. PDT has been shown to scale on logically Cartesian grids out to 750,000 cores. Logically Cartesian grids contain regular convex grid units that allow for vertex motion inside them, in order to conform to curved shapes.

The following are the completed goals of this thesis:

- Implement unstructured meshing capability in PDT for 2D and 2D extruded problems.
- Generate unstructured mesh in parallel using the same partitioning scheme and number of processors as the Cartesian-grid transport sweep.
- Perform stitching between meshed subdomains to preserve interface continuity.
- Implement load balancing algorithms for unstructured meshes in PDT. A load balanced problem would be defined by *f* is *f* really referencing the problem, not the metric? in the pseudocode, or the subset with the maximum number of cells, divided by the average number of cells per subset.

- Verify and test code to prove load balancing algorithm effectiveness. I thought some of the verification was for the unstructured grid feature as well?
- Show results what kind of results? I would say load balancing of the parallel transport sweeps for benchmark problems.

The unstructured meshing capability being added into PDT was of paramount importance because it allows the user to define the problem geometry without having to conform the mesh to the problem geometry. The need to move vertices within convex grids is no longer needed, so the user only needs to define the geometry of the problem. A 2D unstructured mesh is created utilizing the Triangle mesh generator. The resulting mesh can be extruded in the third spatial dimension. The 2D extruded grid is not as generic as a fully tetrahedral grid (such implementation is left as future work). i have added some here

In Chapters 2 and 3, an introduction to radiation transport and massively parallel transport sweeps on Cartesian meshes and moderately parallel unstructured meshes is reviewed the subject is introduction. can an introduction be reviewed? I would not use passive tense here, but say that we introduce and review Chapter 4 reviews describes is better the load balancing algorithm that was implemented, and Chapter 5 presents the behavior of the algorithm for three test cases, in addition to verifying the solution to two benchmark problems and showcasing the unstructured meshing capability.

2. THE TRANSPORT EQUATION

The steady-state neutron transport equation describes the behavior of neutrons in a medium and is given by Eq. (2.1):

$$\vec{\Omega} \cdot \vec{\nabla} \psi(\vec{r}, E, \vec{\Omega}) + \Sigma_t(\vec{r}, E) \psi(\vec{r}, E, \vec{\Omega}) = \int_0^\infty dE' \int_{4\pi} d\Omega' \Sigma_s(\vec{r}, E' \rightarrow E, \Omega' \rightarrow \Omega) \psi(\vec{r}, E', \vec{\Omega}') + S_{ext}(\vec{r}, E, \vec{\Omega}), \quad (2.1)$$

where $\vec{\Omega} \cdot \vec{\nabla} \psi$ is the leakage term and $\Sigma_t \psi$ is the total collision term (absorption, outscatter, and within group scattering). These are the loss terms of the neutron transport equation. The right hand side of Eq. (2.1) represents the gain terms, where S_{ext} is the external source of neutrons and $\int_0^\infty dE' \int_{4\pi} d\Omega' \Sigma_s(E' \rightarrow E, \Omega' \rightarrow \Omega) \psi(\vec{r}, E', \vec{\Omega}')$ is the inscatter term, which represents all neutrons scattering from energy E' and direction $\vec{\Omega}'$ into energy dE about energy E and $d\Omega$ about direction $\vec{\Omega}$. **the primes are on the starting E and omega, not the ending ones, so your sentence is not entirely correct**

Without loss of generality for the research problem at hand, we assume isotropic scattering for simplicity. The double differential scattering cross section, $\Sigma_s(E' \rightarrow E, \Omega' \rightarrow \Omega)$, no longer depends on direction and is divided by 4π to reflect isotropic behavior. This yields:

$$\begin{aligned} \vec{\Omega} \cdot \vec{\nabla} \psi(\vec{r}, E, \vec{\Omega}) + \Sigma_t(\vec{r}, E) \psi(\vec{r}, E, \vec{\Omega}) &= \frac{1}{4\pi} \int_0^\infty dE' \Sigma_s(\vec{r}, E' \rightarrow E) \int_{4\pi} d\Omega' \psi(\vec{r}, E', \vec{\Omega}') + S_{ext}(\vec{r}, E, \vec{\Omega}) \\ &= \frac{1}{4\pi} \int_0^\infty dE' \Sigma_s(\vec{r}, E' \rightarrow E) \phi(\vec{r}, E') + S_{ext}(\vec{r}, E, \vec{\Omega}), \end{aligned} \quad (2.2)$$

where we have introduced the scalar flux as the integral of the angular flux:

$$\phi(\vec{r}, E') = \int_{4\pi} d\Omega' \psi(\vec{r}, E', \vec{\Omega}'). \quad (2.3)$$

The next step to solving the transport equation is to discretize in energy, yielding Eq. (2.4) the multigroup transport equation:

$$\vec{\Omega} \cdot \vec{\nabla} \psi_g(\vec{r}, \vec{\Omega}) + \Sigma_{t,g}(\vec{r}) \psi_g(\vec{r}, \vec{\Omega}) = \frac{1}{4\pi} \sum_{g'} \Sigma_{s,g' \rightarrow g}(\vec{r}) \phi_{g'}(\vec{r}) + S_{ext,g}(\vec{r}, \vec{\Omega}), \quad \text{for } 1 \leq g \leq G \quad (2.4)$$

where the multigroup transport equations now form a system of coupled equations.

Next, we discretize in angle using the discrete ordinates method [3] **no way, do not cite denovo as the origin of angular quadratures!**, whereby an angular quadrature $(\vec{\Omega}_m, w_m)_{1 \leq m \leq M}$ is used to solve the above equations along a given set of directions $\vec{\Omega}_m$:

$$\vec{\Omega}_m \cdot \vec{\nabla} \psi_{g,m}(\vec{r}) + \Sigma_{t,g}(\vec{r}) \psi_{g,m}(\vec{r}) = \frac{1}{4\pi} \sum_{g'} \Sigma_{s,g' \rightarrow g}(\vec{r}) \phi_{g'}(\vec{r}) + S_{ext,g,m}(\vec{r}), \quad (2.5)$$

where the subscript m is introduced to describe the angular flux in direction m . We notice that the subscript is not added to our inscatter term because of the isotropic scattering assumption and because the scalar flux does not depend on angle. However, in order to evaluate the scalar flux, we employ the angular weights w_m and the angular flux solutions ψ_m to numerically perform the angular integration:

$$\phi_g(\vec{r}) \approx \sum_{m=1}^{m=M} w_m \psi_{g,m}(\vec{r}). \quad (2.6)$$

From Equation (2.4), it is clear that we are solving a sequence of transport equations, one equation per group. Therefore, all transport equations are of the following form:

$$\vec{\Omega}_m \cdot \vec{\nabla} \psi_m(\vec{r}) + \Sigma_t(\vec{r}) \psi_m(\vec{r}) = \frac{1}{4\pi} \Sigma_s(\vec{r}) \phi(\vec{r}) + q_m^{ext+inscat}(\vec{r}) = q_m(\vec{r}), \quad (2.7)$$

where the group index notation is omitted for brevity.

In order to obtain the solution for this discrete form of the transport equation, an iter-

ative process called source iteration is introduced. This is shown below for the one-group transport equation, Eq. (2.8):

$$\vec{\Omega}_m \cdot \vec{\nabla} \psi_m^{(l+1)}(\vec{r}) + \Sigma_t \psi_m^{(l+1)}(\vec{r}) = q_m^{(l)}(\vec{r}), \quad (2.8)$$

where the right hand side terms of Eq. (2.5) have been combined into one general source term, q_m . The angular flux of iteration $(l+1)$ is calculated using the (l^{th}) value of the scalar flux.

After the angular and energy dependence have been accounted for, Eq. (2.8) must be discretized in space as well. This is done by meshing the domain and solving the spatial problem one cell at a time for a given direction **the "one cell at a time" doesn't make sense if you do not first say that we use a discontinuous Galerkin approximation in space and that upwinding is used to connect cells based on the flow of physical information. THEN, your sentence makes sense. Please fix the order of presentation here.** The solution across a cell interface is connected based on an upwind approach, where face outflow radiation becomes face inflow radiation for the downwind cells. Sweeping the mesh and solving one cell at a time is possible utilizing one of three popular discretization techniques: finite difference[4], finite volume[4], or discontinuous finite element[6]. Figure 2.1 shows the sweep ordering for a given direction on both a structured and unstructured mesh.




Figure 2.1: A demonstration of a sweep on a structured and unstructured mesh.

The number in each cell represents the order in which the cells are solved. All cells must receive the solution downwind from them before solving for their own solution. This dependency can be represented and stored as a task dependence graph, shown in Fig. 2.2.




Figure 2.2: A task dependence graph of the unstructured mesh example in Fig. 2.1.

3. PARALLELIZATION OF TRANSPORT SWEEPS

As mentioned in the previous section, a transport sweep is set up by overlaying a domain with a finite element mesh. The sweep then solves the transport equation cell by cell using a discontinuous finite element approach. The order of which cell to solve first is given by a task dependence graph, as shown in Fig. 2.2. The transport sweep can be solved in parallel in order to obtain the solution faster, as well as distribute the memory to many processors for memory intensive cases. In PDT, a transport sweep can be performed on a structured Cartesian mesh, and the work proposed utilizes transport sweeps on an unstructured mesh. Performing a transport sweep on an unstructured mesh presents two big challenges: performing a transport sweep on a massively parallel scale in an efficient manner and keeping non-concave sub-domains due to the nature of the transport sweep itself. PDT has already proven the ability to perform massively parallel transport sweeps on structured meshes. As part of previous efforts in PDT, researchers have come to outline three important properties for parallel sweeps.

A parallel sweep algorithm is defined by three properties[2] :

- partitioning: dividing the domain among available processors
- aggregation: grouping cells, directions, and energy groups into tasks
- scheduling: choosing which task to execute if more than one is available

The basic concepts of parallel transport sweeps, partitioning, aggregation, and scheduling, are most easily described in the context of a structured transport sweep. A structured transport sweep takes place on a Cartesian mesh. Furthermore, the work proposed utilizes aspects of the structured transport sweep.

If M is the number of angular directions per octant, G is the total number of energy groups, and N is the total number of cells, then the total fine grain work units is $8MGN$.

The factor of 8 is present as M directions are swept for all 8 octants of the domain. The finest grain work unit is the calculation of a single direction and energy groups unknowns in a single cell, or $\psi_{m,g}$ for a single cell.

In a regular grid, we have the number of cells in each Cartesian direction: N_x, N_y, N_z . These cells are aggregated into “cellsets”. If M is the total number of angular directions, G is the total number of energy groups, and N is the total number of cells, then the total fine grain work units is $8MGN$. The factor of 8 is present as M directions are swept for all 8 octants of the domain. The finest grain work unit is the calculation of a single direction and energy groups unknowns in a single cell, or $\psi_{m,g}$ for a single cell.

Fine grain work units are aggregated into coarser-grained units called *tasks*. A few terms are defined that describe how each variable is aggregated.

- $A_x = \frac{N_x}{P_x}$, where N_x is the number of cells in x and P_x is the number of processors in x
- $A_y = \frac{N_y}{P_y}$, where N_y is the number of cells in y and P_y is the number of processors in y
- $N_g = \frac{G}{A_g}$
- $N_m = \frac{M}{A_m}$
- $N_k = \frac{N_z}{P_x P_y P_z}$
- $N_k A_x A_y A_z = \frac{N_x N_y N_z}{P_x P_y P_z}$

It follows that each process owns N_k cell-sets (each of which is A_z planes of $A_x A_y$ cells), $8N_m$ direction-sets, and N_g group-sets for a total of $8N_m N_g N_k$ tasks.

One task contains $A_x A_y A_z$ cells, A_m directions, and A_g groups. Equivalently, a task is the computation of one cellset, one groupset, and one angleset. One task takes a stage to complete. This is particularly important when comparing sweeps to the performance models.

Equation (3.1) approximately defines parallel sweep efficiency. This can be calculated for specific machinery and partitioning parameters by substituting in values calculated

using Eqs. (3.5), (3.6), and (3.7).

$$\begin{aligned}\varepsilon &= \frac{T_{\text{task}}N_{\text{tasks}}}{[N_{\text{stages}}][T_{\text{task}} + T_{\text{comm}}]} \\ &= \frac{1}{[1 + \frac{N_{\text{idle}}}{N_{\text{tasks}}}] [1 + \frac{T_{\text{comm}}}{T_{\text{task}}}]}\end{aligned}\quad (3.1)$$

Equations (3.2) and 3.3 show how T_{comm} and T_{task} are calculated:

$$T_{\text{comm}} = M_L T_{\text{latency}} + T_{\text{byte}} N_{\text{bytes}} \quad (3.2)$$

$$T_{\text{task}} = A_x A_y A_z A_m A_g T_{\text{grind}} \quad (3.3)$$

where T_{latency} is the message latency time, T_{byte} is the time required to send one byte of message, N_{bytes} is the total number of bytes of information that a processor must communicate to its downstream neighbors at each stage, and T_{grind} is the time it takes to compute a single cell, direction, and energy group. M_L is a latency parameter that is used to explore performance as a function of increased or decreased latency. If a high value of M_L is necessary for the **performance** model to match computational results, improvements should be made in code implementation.

3.1 KBA Partitioning for Structured Grids

Several parallel transport sweep codes use KBA partitioning in their sweeping, such as Denovo [3] and PARTISN [1]. The KBA partitioning scheme and algorithm was developed by Koch, Baker, and Alcouffe [1].

The KBA algorithm traditionally chooses $P_z = 1, A_m = 1, G = A_g = 1, A_x = N_x/P_x, A_y = N_y/P_y$, with A_z being the selectable number of z-planes to be aggregated into each task. With $N_k = N_z/A_z$, each processor performs $N_{\text{tasks}} = 8MN_k$ tasks. With the KBA algorithm, $2MN_k$ tasks are pipelined from a given corner of the 2D processor layout. The far corner

processor remains idle for the first $P_x + P_y - 2$ stages, which means that an octant-pair (or quadrant) sweep completes in $2MN_k + P_x + P_y - 2$ stages. If an octant-pair sweep does not begin until the previous pair's finishes, the full sweep requires $8MN_k + 4(P_x + P_y - 2)$ stages, which means the KBA parallel efficiency is:

$$\epsilon_{KBA} = \frac{1}{[1 + \frac{4(P_x+P_y-2)}{8MN_k}][1 + \frac{T_{\text{comm}}}{T_{\text{task}}}]}$$
 (3.4)

in the next section, you talk about stages, minimum number of stages to reach the center-most proc, ..., it would be good that to discuss KBA and PDT sweeps with as much as possible the same language. Add a few things here to allow for an easier comparison with the PDT text below

3.2 The Structured Transport Sweep in PDT

The minimum possible number of stages for given partitioning parameters P_i and A_j is $2N_{\text{fill}} + N_{\text{tasks}}$. N_{fill} is both the minimum number of stages before a sweepfront can reach the center-most processors and the number needed to finish a direction's sweep after the center-most processors have finished. Equations (3.5), (3.6), and (3.7) define N_{fill} , N_{idle} , and N_{tasks} :

$$N_{\text{fill}} = \frac{P_x + \delta_x}{2} - 1 + \frac{P_y + \delta_y}{2} - 1 + N_k \left(\frac{P_z + \delta_z}{2} - 1 \right)$$
 (3.5)

$$N_{\text{idle}} = 2N_{\text{fill}}$$
 (3.6)

$$N_{\text{tasks}} = 8N_m N_g N_k$$
 (3.7)

where δ_u is 1 for P_u odd, and 0 for P_u even.

next, you start discussing volumetric overloaded and non-overloaded but it feels that the discussion above doesn't naturally lead to this. Can you explain the logic a bit more. First, why do you call it volumetric? Are they not all volumetric? To me, volumetric also

implies no long skinny columns ... so is this a got term? Also, you give an efficiency in eq. 3.8 but it may not be clear how you compare it to KBA. I feel there is a bit of a mix in between the MC2013 and MC2015 papers of Michael, but try to get the bottom line to be evident. Later, you say hybrid-KBA but explain how it is related to the SQO discussion below, I was under the impression hybrid was mainly $P_z=2$...

Figure 3.1 shows three different partitioning schemes used in transport sweeps, KBA (which is defined in the previous section), volumetric non-overloaded, and volumetric overloaded. Volumetric non-overloaded requires that all cells owned by a processor are contiguous, where as volumetric non-overloaded partitioning does not have this restriction.



Figure 3.1: Three different partitioning schemes in 2D, from left to right: KBA, volumetric non-overloaded, and volumetric overloaded.

The overloaded volumetric partitioning proceeds as follows:

1. In a 2D (3D) domain, cellsets are divided into 4 (8) spatial quadrants (octants), with an equal number of cellsets in each SQO (SQO is defined as a spatial quadrant or octant).
2. Assign 1/4 of the processors (1/8) in 3D to each SQO.
3. Choose the individual overload factors ω_x , ω_y , and ω_z and individual processor counts P_x , P_y , and P_z , such that $\omega_x \omega_y \omega_z = \omega_r$ and $P_x P_y P_z = P$, with all P_u even. ω_u is defined as the number of cellsets assigned to each P_u .
4. An array of $\omega_x \cdot \omega_y \cdot \omega_z$ “tiles” in each SQO. Each tile is an array of $1/2P_x \cdot 1/2P_y \cdot 1/2P_z$ cellsets. These cellsets are mapped one-to-one to the $1/2P_x \cdot 1/2P_y \cdot 1/2P_z$

processors assigned to the SQO, using the same mapping in each tile.

Each tile has a logically identical layout of cellsets, and each processor owns exactly one cellset in each tile in its SQO. This makes each processor responsible for ω_r cellsets.

In order to properly outline the optimal scheduling rules, the variables X, Y , and Z are defined as $P_u/2$ for each respective direction $u = x, y, z$. This splits up the processor layout into octants, where each processor has an index (i, j, k) determining where it is in the layout. Tiles are also indexed and referred to in the same way with the notation $T(i, j, k)$.

The optimal scheduling algorithm rules are as follows:

1. If $i \leq X$, then tasks with $\Omega_x > 0$ have priority, while for $i > X$, tasks with $\Omega_x < 0$ have priority.
2. If multiple ready tasks have the same sign on Ω_x , apply rule 1 to j, Y, Ω_y .
3. If multiple ready tasks have the same sign on Ω_x and Ω_y , apply rule 1 to k, Z, Ω_z .
4. If multiple tasks are ready in the same octant, then priority goes to the cellset for which the priority octant has greatest downstream depth.
5. If multiple ready tasks are in the same octant and have the same downstream depth of graph in x , then priority goes to the cellset for which the priority octant has greatest downstream depth of graph in y .
6. If multiple ready tasks are in the same octant and have the same downstream depth of graph in x and y , then priority goes to the cellset for which priority octant has greatest depth of graph in z .

This ensures that each SQO orders the octants: the one it can start right away (A), three that have one sign difference from A (B, C , and D), three that have two sign differences ($\bar{D}, \bar{C}, \bar{B}$), and one in opposition to its primary (\bar{A}). For example, if octant A is octant $(+x, +y, +z)$, then its secondary octants (only one sign change at a time) would be octants $(-x, +y, +z)$, $(+x, -y, +z)$ and $(+x, +y, -z)$.

There are three constraints in order to achieve the optimal stage count. In these con-

straints, $M = \omega_g \omega_m / 8$, which is the number of tasks per octant per cellset.

1. $M \geq 2(Z - 1)$
2. $\omega_z M \geq 2(Y - 1)$
3. If $\omega_x > 1$, then $\omega_y \omega_z M \geq X$

Constraint 1 ensures that there is no idle time between a processor finishing an octant's work in one tile and beginning that octant's work on the next tile in the same tile-column; processor $P(1, Y, 1)$ finishing its tile $T(1, \omega_y, 1)$ octant C work and beginning its octant B work; processor $P(X, 1, 1)$ finishing its tile $T(\omega_x, 1, 1)$ octant D work and beginning its octant B work. Constraint 2 ensures that there is no idle time time between a processor finishing an octant's work for one z column of tiles and beginning that octant's work on the next column; processor $P(X, 1, 1)$ finishing its tile $T(\omega_x, 1, 1)$ octant D work available to it and beginning its octant C work. Constraint 3 ensures that there is no idle time between a processor finishing an octant's work for one yz plane of tiles and beginning that octant's work in the next plane.

As a result of these constraints, there is no idle time for a variety of situations. At large processor counts, the product $\omega_m \omega_g$ must be large, which requires $N_m N_g$ be large. This means that a weak scaling series refined only in space, but only coarsely refined in angle and energy, will eventually fail the constraints.

The optimal efficiency formula changes slightly from the KBA and hybrid KBA partitioning method in order to account for the overload factors. The only change is in the $\frac{N_{idle}}{N_{tasks}}$ term, as shown in Eq. (3.8).

$$\epsilon_{opt} = \frac{1}{[1 + \frac{P_x + P_y + P_z - 6}{\omega_g \omega_m \omega_r}][1 + \frac{T_{comm}}{T_{task}}]} \quad (3.8)$$

3.3 The Unstructured Transport Sweep

In an unstructured mesh, the number of cells cannot be described in the same way as an unstructured mesh. In PDT specifically we initially subdivide the domain into subsets, which are just rectangular subdomains. Within each subset, an unstructured mesh is created. This creates a pseudo-regular grid. These subsets become the N_x, N_y, N_z equivalent for an unstructured mesh. The spatial aggregation in a PDT unstructured mesh is done by aggregating subsets into cellsets.

While the structured PDT transport sweep has scaled well out to 750,000 cores, similar levels of parallel scaling have not been achieved using unstructured sweeps yet. Pautz proposed a new list scheduling algorithm has been constructed for modest levels of parallelism (up to 126 processors)[5] .

There are three requirements for a sweep scheduling algorithm to have. First, the algorithm should have low complexity, since millions of individual tasks are swept over in a typical problem. Second, the algorithm should schedule on a set of processors that is small in comparison to the number of tasks in the sweep graph. Last, the algorithm should distribute work in the spatial dimension only, so that there is no need to communicate during the calculation of the scattering source.

Here is the pseudocode for the algorithm:

```
Assign priorities to every cell-angle pair
Place all initially ready tasks in priority queue
While (uncompleted tasks)
    For i=1,maxCellsPerStep
        Perform task at top of priority queue
        Place new on-processor tasks in queue
    Send new partition boundary data
```

Receive new partition boundary data

Place new tasks in queue

An important part of the algorithm above is the assigning priorities to tasks. Specialized prioritization heuristics generate partition boundary data as rapidly as possible in order to minimize the processor idle time.

Nearly linear speedups were obtained on up to 126 processors. Further work is being done for scaling to thousands of processors. **I would cite again Pautz here so it is clear that the 126 procs results are part of that study**

3.3.1 Cycle Detection

A cycle is a loop in a directed graph and they can occur commonly in unstructured meshes. However, they do not exist in 2D triangular extruded problems and, because our domain partitioning is convex, arbitrary degenerate polygons appearing on subdomain boundaries will not produce cycles. Even though they are not applicable to this application of unstructured transport sweeps, they are discussed here for completeness.

Cycles can cause hang time in the problem, as a processor will wait for a message that might never come. This means that the computation for one or more elements will never be completed. The solution to this is to “break” any cycles that exist by removing an edge of the task dependence graph (TDG). Old flux information is used on a particular element face in the domain. Most of the time, the edge removed is oriented obliquely with respect to the radiation direction.

Algorithms for finding cycles are called *cycle detection* algorithms. This must be done efficiently in parallel, both because the task dependence graph is distributed and because the finite element grid may be deforming every timestep and changing the associated TDG.

Cycle detection utilizes two operations: trim and mark. Trimming identifies and discards elements which are not in cycles. At the beginning of cycle detection, graphs are

trimmed in the downwind direction, then the remaining graphs are trimmed in the upwind direction. A pivot vertex is then selected in each graph. Graph vertices are then marked as upwind, downwind, or unmarked. Then, if any vertices are both upwind and downwind, the cycle is these vertices plus the pivot vertex. An edge is removed between 2 cycle vertices, and 4 new graphs are created: a new cycle, the upwind vertices without the cycle, the downwind vertices without the cycle, and a set of unmarked vertices. This recursively continues until all cycles are eliminated.

4. MOTIVATION AND METHODS

The capability for PDT to generate and run on an unstructured mesh is important because it allows us to run problems without having to conform our mesh to the problem as much. The idea is to have a logically Cartesian grid (creating orthogonal “subsets”) with an unstructured mesh inside each subset. These logically Cartesian subdomains are obtained using cut planes in 3D and cut lines in 2D. Figure 4.1 demonstrates this functionality, with the first two subsets meshed using the Triangle Mesh Generator[7], a 2D mesh generator.




Figure 4.1: A PSLG describing a fuel lattice, and with an orthogonal “subset” grid imposed on it.

describe more the number of subset you want to have in this example. I think it is 3 in x and 4 in y. Also, introduce the notion of cut lines/cut planes here. it seems like it is a good place to do that This orthogonal grid is superimposed and each subset is meshed in parallel. Subsets are now the base structured unit when calculating our parallel efficiency. Discontinuities along the boundary are fixed by “stitching” hanging nodes, creating degenerate polygons along subset boundaries. Because PDT’s spatial discretization employs

Piece-Wise Linear Discontinuous (PWLD) finite element basis functions, there is no problem solving on degenerate polygons.

When using the unstructured meshing capability in PDT, the input geometry is described by a Planar Straight Line Graph (PSLG). After superimposing the orthogonal grid, a PSLG is created for each subset, and meshed. Because the input's and each subset's PSLG must be described and meshed in 2D, the mesh can be extruded in the z dimension in order to give us the capability to run on 3D problems. Obviously, this is not as good as an unstructured tetrahedral mesh, but for many problems, it is a great capability to have.

When discussing the parallel scaling of transport sweeps, a load balanced problem is of great importance. A load balanced problem has an equal number of degrees of freedom per processor. Load balancing is important in order to minimize idle time for all processors by equally distributing (as much as possible) the work each processor has to do. For the purposes of unstructured meshes in PDT, we are looking to “balance” the number of cells. Ideally, each processor will be responsible for an equal number of cells.

If the number of cells in each subset can be reasonably balanced, then the problem is effectively load balanced. The Load Balance algorithm described below details how the subsets will be load balanced. In summary, the procedure of the algorithm involves moving the initially user specified x and y cut planes, re-meshing, and iterating until a reasonably load balanced problem is obtained. Equation 4.1 shows the equation for calculating the load balancing metric, which dictates how balanced or unbalanced the problem is.

$$f = \frac{\max_{ij}(N_{ij})}{\frac{N_{tot}}{I \cdot J}}, \quad (4.1)$$

where f is the load balance metric, N_{ij} is the number of cells in subset i, j , N_{tot} is the global number of cells in the problem, and I and J are the total number of in the x and y direction, respectively. The metric is a measure of the maximum number of cells per subset divided

by the average number of cells per subset. it would be useful to add two short paragraphs that give the essence of the algorithms rather than having the reader try to determine this on their own

Load Balance: A load balancing algorithm that attempts at equalizing the number of triangles per subset.

I, J subsets specified by user

Mesh all subsets

N_{tot} = total number of triangles

N_{ij} = number of triangles in subset ij

$f = \max_{ij}(N_{ij}) / \frac{N_{tot}}{I \cdot J}$ { //Check if all subsets meet the tolerance }

if $f < \text{tol}_{\text{subset}}$ **then**

DONE with load balancing

else

$f_I = \max_i[\sum_j N_{ij}] / \frac{N_{tot}}{I}$

$f_J = \max_j[\sum_i N_{ij}] / \frac{N_{tot}}{J}$

if $f_I > \text{tol}_{\text{row}}$ **then**

Redistribute(X_i)

end if

if $f_J > \text{tol}_{\text{col}}$ **then**

Redistribute(Y_j)

end if

if redistribution occurred **then**

REMESH and repeat algorithm

end if

end if

if There is still a discrepancy amongst subsets **then**

Move cutplane segments on the subset level and remesh (may require changes to scheduling algorithm)

end if

Redistribute: A function that moves cut lines in either X or Y.

Input: CutLines (X or Y vector that stores cut lines).

Input: num_tri_row or num_tri_col, a pArray containing number of triangles in each row or column

Input: The total number of triangles in the domain, N_{tot}

stapl::array_view num_tri_view, over num_tri_row/column

stapl::array_view offset_view

stapl::partial_sum(num_tri_view) {Perform prefix sum} {We now have a cumulative distribution stored in offset_view}

for $i = 1 : \text{CutLines.size()}-1$ **do**

 vector <double> pt1 = [CutLines(i-1), offset_view(i-1)]

 vector <double> pt2 = [CutLines(i), offset_view(i)]

 ideal_value = $i \cdot \frac{N_{tot}}{\text{CutLines.size()}-1}$

 X-intersect(pt1,pt2,ideal_value) {Calculates the X-intersect of the line formed by pt1 and pt2 and the line $y = \text{ideal_value}$.}

 CutLines(i) = X-intersect

end for

5. RESULTS

The following sections will showcase the metric behavior and convergence for three test cases, solution verification for pure absorber and pure scatterer 2D slab problems, and the new unstructured meshing capability both in 2D and 3D.

5.1 Test Cases for Metric Behavior and Convergence

In order to showcase the behavior of the load balancing metric, calculated by Eq. 4.1 three test cases are presented. Figure 5.1 shows the first test case, a 20 cm by 20 cm domain with two pins in opposite corners of the domain. Figure 5.2 shows the same size domain but with the pins on the same side. These are two theoretically very unbalanced cases, as geometrically there are two features located distantly from each other with an empty geometry throughout the rest of the domain. Figure 5.3 shows a lattice and reflector, which due to it's denser and repeated geometry, theoretically is a more balanced problem.

A series of 162 inputs was constructed for each case the reader may wonder why 162. do not let the reader ever wonder. say why 162, what is the span of parameters that you investigate, thus leading to 162 inputs, so it could be simple as rephrasing it as a parametric study as a function of the max triangle area for each test case. The tabulated data in Appendix A show the the the ??? parameters that will change in each input. The maximum triangle area varied from the coarsest possible to 0.01 cm^2 , and the number of subsets, N , varies from 2×2 to 10×10 wouldn't × be better here?.




Figure 5.1: The first test case used in order to test effectiveness and convergence of the load balancing metric.




Figure 5.2: The second test case used in order to test effectiveness and convergence of the load balancing metric.




Figure 5.3: The third test case used in order to test effectiveness and convergence of the load balancing metric.

5.2 Metric Behavior and Convergence

For each test case, the 162 input inputs are run twice, once with no load balancing iterations, and once with ten load balancing iterations. The best metric is reported and recorded. Three figures for each test cases are presented below: the first figure will show the metric behavior for no iterations, the second figure will show the metric behavior for each input run with ten load balancing iterations, and the third figure will show a ratio of the ten iteration runs over the no iteration runs.

Figure 5.4 shows the metric behavior for Fig. 5.1. The maximum metric value is 24.7650, and occurs when Fig. 5.1 is run with 8x8 subsets and a maximum triangle area of 1.6 cm^2 . The minimum metric value is 1.0016 and occurs when Fig. 5.1 is run with 4x4 subsets and a maximum triangle area of 0.04 cm^2 .

Metric Behavior with no Load Balancing Iterations




Figure 5.4: The metric behavior of the first test case run with no load balancing iterations.

Figure 5.5 shows the metric behavior for Fig. 5.1 after 10 load balancing iterations. The maximum metric value is 5.0538 and occurs when Fig. 5.1 is run with 10x10 subsets and a maximum triangle area of 1.2 cm^2 . The minimum metric value is 1.0017 and occurs when Fig. 5.1 is run with 4x4 subsets and a maximum triangle area of 0.04 cm^2 .

Metric Behavior with 10 Load Balancing Iterations




Figure 5.5: The metric behavior of the first test case run with 10 load balancing iterations.

Figure 5.6 shows the difference in metric behavior for Fig. 5.1. This difference is calculated by dividing the metric with no iterations by the metric with 10 iterations. The maximum improvement has a value of 0.1097 and occurs for Fig. 5.1 is run with 8x8 subsets with a maximum triangle area of 1.6 cm^2 . The minimum improvement has a value of very close to 1.0 and occurs for many of the inputs.




Figure 5.6: The difference in metric behavior between no iteration and 10 iterations. The closer the z-value to zero, the better the improvement.

Figure 5.7 shows the metric behavior for Fig. 5.2. The maximum metric is 22.6654 and occurs when Fig. 5.2 is run with 8x8 subsets with a maximum triangle area of 1.8 cm². The minimum metric is 1.0024 and occurs when Fig. 5.2 is run with 2x2 subsets with a maximum triangle area of 0.01 cm².

Metric Behavior with no Load Balancing Iterations




Figure 5.7: The metric behavior of the second test case run with no load balancing iterations.

Figure 5.8 shows the metric behavior for Fig. 5.2 after ten load balancing iterations. The maximum metric is 3.9929 and occurs when Fig. 5.2 is run with 10x10 subsets with a maximum triangle area of 1.8 cm². The minimum metric is 1.0024 and occurs when Fig. 5.2 is run with 2x2 subsets with a maximum triangle area of 0.01 cm².

Metric Behavior with 10 Load Balancing Iterations




Figure 5.8: The metric behavior of the second test case run with 10 load balancing iterations.

Figure 5.9 shows the difference in metric behavior for Fig. 5.2. The maximum improvement has a value of 0.1090 and occurs for Fig. 5.2 is run with 8x8 subsets with Triangle's coarsest possible mesh generation settings. The minimum improvement has a value of very close to 1.0 and occurs for many of the inputs.




Figure 5.9: The difference in metric behavior of the second test case with no iteration and 10 iterations. The closer the z-value to zero, the better the improvement.

Figure 5.10 shows the metric behavior for Fig. 5.3. The maximum metric is 2.6489 and occurs when Fig. 5.3 is run with 10x10 subsets with a maximum triangle area of 1.8 cm². The minimum metric is 1.0179 and occurs when Fig. 5.3 is run with 2x2 subsets with a maximum triangle area of 0.08 cm².




Figure 5.10: The difference in metric behavior of the third test case with no load balancing iterations.

Figure 5.11 shows the metric behavior for Fig. 5.3 after ten load balancing iterations. The maximum metric is 2.2660 and occurs when Fig. 5.3 is run with 10x10 subsets with a maximum triangle area of 0.4 cm^2 . The minimum metric is 1.0021 and occurs when Fig. 5.3 is run with 2x2 subsets with the Triangle's coarsest possible mesh.

Metric Behavior with 10 Load Balancing Iterations




Figure 5.11: The difference in metric behavior of the third test case after ten load balancing iterations.

Figure 5.12 shows the difference in metric behavior for Fig. 5.3. The maximum improvement has a value of 0.4476 and occurs for Fig. 5.3 is run with 2x2 subsets with Triangle's coarsest possible mesh generation settings. The minimum improvement has a value of very close to 1.0 and occurs for many of the inputs.




Figure 5.12: The difference in metric behavior of the third test case with no iteration and 10 iterations. The closer the z-value to zero, the better the improvement.

Because Fig. 5.3 has more features and is more symmetric of a problem, the initial load balancing metric will not be as large as the load balancing metric of Figs. 5.2 and 5.1. As a result, the improvement in the load balancing metric after 10 iterations will not be as great in problems similar to Fig. 5.3.

okay, that was a ton of results, now you need to draw conclusions from all of that before moving on. add them here.

5.3 Solution Verification

For solution verification, two simple problems were chosen: a 1D pure absorber slab and a 1D pure scatterer slab. These problems were chosen because their analytical so-

lutions are easily obtained, thus making a comparison between PDT's solution and the analytical solution easy and informative. The same geometry and mesh were used for both problems, and are shown in Figure 5.13.




Figure 5.13: The geometry and mesh used in solution verification problems.

The problem geometry is a 1 cm by 1 cm square. In order to simulate a 1D slab, opposing reflecting boundaries were placed on the both y boundaries, effectively forcing the problem to be infinite in the y direction. At the x minimum boundary, an incident isotropic flux was used, and a vacuum boundary was enforced at the x max boundary. No

source was used in either problem.

In order to measure how close the numerical and analytical solutions an error estimate, represented by, Eq. (5.1), is used:

$$\epsilon = \frac{\|\text{Analytical} - \text{Numerical}\|_{l2}}{\|\text{Analytical}\|_{l2}}, \quad (5.1)$$

where the $l2$ norm of the absolute error is divided by the $l2$ norm of the analytical solution.

5.3.1 The 1D Pure Absorber Slab

For monoenergetic neutrons, a source free, 1D pure absorber slab, the transport equation is represented by Eq. (5.2):

$$\mu \frac{d\psi(x, \mu > 0)}{dx} + \Sigma_a \psi(x, \mu > 0) = 0, \quad (5.2)$$

where ψ is the angular flux, Σ_a is the macroscopic absorption cross section, and μ is the cosine of the polar angle. The boundary conditions for this problem are expressed in Eq. (5.3): this is confusing. why is the angular flux for mu<0 at x=0 equal to Psi inc /2 ? Why not just say it is Psi inc and it is the same value to all positive mu's? I think you are making it harder than it is.

$$\begin{aligned} \psi(0, \mu > 0) &= \int_0^{2\pi} d\gamma \int_0^1 \frac{\psi_{inc}}{4\pi} d\mu = \frac{\psi_{inc}}{2} \text{ (incident isotropic)} \\ \psi(x_{\max}, \mu < 0) &= 0 \text{ (vacuum)}, \end{aligned} \quad (5.3)$$

where ψ_{inc} is the defined incident angular flux. Equation (5.4) solves the transport equation via separation of variables to get the angular flux for this problem:

$$\frac{d\psi(x, \mu > 0)}{dx} = -\frac{\Sigma_a}{\mu} x$$

$$\begin{aligned}
\frac{d\psi(x, \mu > 0)}{\psi(x, \mu > 0)} &= -\frac{\Sigma_a}{\mu} x dx \\
\int_{\psi(0, \mu > 0)}^{\psi(x, \mu > 0)} \frac{d\psi(x, \mu > 0)}{\psi(x, \mu > 0)} &= \int_0^x -\frac{\Sigma_a}{\mu} x' dx' \\
\ln\left[\frac{\psi(x, \mu > 0)}{\psi(0, \mu > 0)}\right] &= -\frac{\Sigma_a}{\mu} x \\
\psi(x, \mu > 0) &= \psi(0, \mu > 0) \exp\left(-\frac{\Sigma_a}{\mu} x\right) \\
\psi(x, \mu > 0) &= \frac{\psi_{inc}}{2} \exp\left(-\frac{\Sigma_a}{\mu} x\right)
\end{aligned} \tag{5.4}$$

Using the fact that the scalar flux in this pure absorber is simply the angular flux integrated for $\mu > 0$, the scalar flux with our boundary conditions is represented by Eq. (5.5):

$$\begin{aligned}
\phi(x) &= \int_0^1 \psi(x, \mu > 0) d\mu \\
&= \int_0^1 \frac{\psi_{inc}}{2} \exp\left(-\frac{\Sigma_a}{\mu} x\right) d\mu = \frac{\psi_{inc}}{2} E_2(\Sigma_a x),
\end{aligned} \tag{5.5}$$

where ϕ is the scalar flux and E_2 is the exponential integral function with $n = 2$.

The pure absorber was run with $\psi_{inc} = 7 \frac{\text{n}}{\text{cm}^2 \cdot \text{s} \cdot \text{ster}}$ and $\Sigma_a = 5 \text{ cm}^{-1}$. Figure 5.14 shows a comparison of the analytical solution with PDT's solution for four different angular refinements. All four PDT runs used only 1 azimuthal angle per quadrant, but varied the number of positive polar angles, because the problem is not azimuthally dependent. The number of positive polar angles used were 1, 5, 10, and 70.




Figure 5.14: The pure absorber solution with four different angular refinements.

It is immediately clear that not many polar angles are necessary for agreement with the analytical solution. Figure 5.15 examines the 70 positive polar angle case exclusively in comparison with the analytical solution. It is immediately clear graphically that the solutions are in agreement, and the relative error of the numerical solution is 0.012, as defined by Eq. (5.1).




Figure 5.15: The pure absorber solution run with 70 positive polar angles.

5.3.2 The 1D Pure Scatterer Slab

For an optically thick, source free 1D pure absorber with monoenergetic neutrons, the transport solution will reach the diffusion limit. The diffusion equation for this problem is represented by Eq. (5.6):

$$\frac{d^2\phi}{dx^2} = 0, \quad (5.6)$$

where ϕ is the scalar flux. The boundary conditions for this problem are expressed in Eq. (5.7):

$$\phi(-2D) = 4j_{inc}$$

$$\phi(x_{\max} + 2D) = 0, \quad (5.7)$$

where j_{inc} is the incident partial current and D is the diffusion coefficient, which is equivalent to $\frac{1}{3\Sigma_t}$, where Σ_t is the total macroscopic cross section. The first boundary condition is the extrapolated boundary condition, and the second is the extrapolated vacuum condition. The incident partial current is calculated from the incident angular flux, as shown in Eq. (5.8):

$$j_{inc} = \int_0^{2\pi} d\gamma \int_0^1 \mu \frac{\psi_{inc}}{4\pi} d\mu = \frac{\psi_{inc}}{4}. \quad (5.8)$$

there could be different values of jinc due to the angular quadrature. can you add a table to show how jinc converges towards a unique value

Equation (5.9) solves Eq. (5.6):

$$\begin{aligned} \frac{d\phi(x)}{dx} &= A \\ \phi(x) &= Ax + B, \end{aligned} \quad (5.9)$$

where A and B are integration constants. Using our boundary conditions in Eq (5.7) to solve for A and B:

$$\phi(-2D) = -2DA + B = 4j_{inc}$$

$$\phi(x_{\max} + 2D) = A(x_{\max} + 2D) + B = 0,$$

the scalar flux, represented by Eq. (5.10), is:

$$\phi(x) = \frac{4j_{inc}}{1+4D}(-x + x_{\max} + 2D). \quad (5.10)$$

This problem was run with $\Sigma_t = 100 \text{ cm}^{-1}$ and $j_{inc} = \frac{7}{4} \frac{\text{n}}{\text{cm}^2 \cdot \text{s}}$. Figure 5.16 shows the

agreement between the analytical solution and PDT's solution. An angular refinement of 40 polar angles was used, with one azimuthal angle in each quadrant.




Figure 5.16: The pure scatterer solution run with 40 positive polar angles.

It is immediately clear graphically that the two solutions are in agreement, and the relative error of the numerical solution is 4.25E-04, as defined by Eq. (5.1). in the defense, it would be good to show angular convergence as well

5.4 2D and 2D Extruded Meshing Capability

To showcase, the newly implemented unstructured meshing capability in PDT, Texas A&M Nuclear Engineering's Impurity Model 1 (IM1) problem is used. Figure 5.17 showcases the 2D mesh of the IM1 problem,




Figure 5.17: The 2D mesh of the IM1 problem.

In order to get from the 2D mesh to the 2D extruded mesh, an extrusion file is supplied to PDT. This extrusion file supplies two critical pieces of information: the number of z layers and their locations, and how each region of the 2D mesh is mapped to these z

layers. The combination of the 2D mesh and the extrusion file yield the full 3D problem, shown in Fig. 5.18.




Figure 5.18: The 2D extruded view of the IM1 problem.

6. CONCLUSION

In conclusion, the load balancing algorithm outlined in Chapter 4 works well for more symmetric problems with a lot of features, and even works well for particularly unbalanced problems. As shown in Chapter 5, its effectiveness depends on the maximum triangle area used, and the number of subsets the user chooses to decompose the problem domain into.

any recommendation for future work? this is somewhat mandatory. Good research should always lead to new questions

APPENDIX A

TABULATED CONVERGENCE STUDY DATA

	Area	N=4	N=9	N=16	N=25	N=36	N=49	N=64	N=81	N=100
1	Coarse	1.95	4.12	6.76	9.60	12.44	14.21	16.44	8.60	6.77
2	1.8	1.46	2.32	4.11	4.64	7.84	8.61	24.77	6.14	4.58
3	1.6	1.42	2.21	4.20	4.64	6.86	8.52	24.71	5.94	4.58
4	1.4	1.32	2.05	2.98	4.64	6.23	8.58	19.98	5.90	4.51
5	1.2	1.30	1.95	3.02	4.93	4.51	7.25	19.97	4.30	4.51
6	1	1.35	1.75	2.90	4.93	4.52	6.02	20.01	4.62	4.51
7	0.8	1.26	1.65	2.95	3.31	4.45	4.40	19.74	4.58	2.92
8	0.6	1.14	1.45	2.05	3.01	3.55	4.22	14.28	2.87	3.10
9	0.4	1.09	1.35	1.79	2.02	2.74	3.33	14.09	2.80	2.06
10	0.2	1.05	1.14	1.34	1.55	1.65	2.05	8.78	1.82	1.45
11	0.1	1.02	1.04	1.11	1.17	1.29	1.36	4.43	1.41	1.24
12	0.08	1.01	1.03	1.09	1.19	1.21	1.29	3.39	1.32	1.18
13	0.06	1.01	1.03	1.04	1.10	1.09	1.20	2.93	1.28	1.06
14	0.05	1.02	1.02	1.06	1.09	1.08	1.11	2.61	1.22	1.09
15	0.04	1.00	1.01	1.00	1.06	1.07	1.07	2.20	1.17	1.11
16	0.03	1.00	1.02	1.02	1.05	1.07	1.05	1.93	1.13	1.03
17	0.02	1.00	1.01	1.01	1.03	1.02	1.03	1.57	1.08	1.05
18	0.01	1.00	1.01	1.01	1.01	1.04	1.02	1.28	1.04	1.01

Table A.1: The metric behavior of the first test case run with no load balancing iterations.

	Area	N=4	N=9	N=16	N=25	N=36	N=49	N=64	N=81	N=100
1	Coarse	1.95	1.60	3.37	2.10	2.28	2.68	2.53	2.81	3.05
2	1.8	1.46	1.94	2.81	2.59	2.98	2.89	2.97	4.50	4.33
3	1.6	1.42	1.95	2.43	2.42	3.00	3.05	2.71	4.11	4.09
4	1.4	1.32	1.87	2.65	3.13	2.45	3.03	4.14	4.39	4.15
5	1.2	1.30	1.77	2.46	2.66	2.59	3.18	4.02	4.28	5.05
6	1	1.35	1.64	2.26	2.33	2.35	3.01	3.93	3.67	4.34
7	0.8	1.26	1.51	2.02	2.79	2.02	2.61	3.27	3.37	3.63
8	0.6	1.14	1.45	1.79	2.41	2.81	2.09	2.90	2.87	3.63
9	0.4	1.09	1.35	1.45	1.87	2.40	1.84	1.96	2.35	2.26
10	0.2	1.05	1.14	1.34	1.55	1.65	2.05	1.40	1.79	1.71
11	0.1	1.02	1.04	1.11	1.17	1.29	1.36	1.32	1.41	1.22
12	0.08	1.01	1.03	1.09	1.19	1.21	1.29	1.20	1.32	1.38
13	0.06	1.01	1.03	1.04	1.10	1.09	1.20	1.15	1.28	1.07
14	0.05	1.02	1.02	1.06	1.09	1.08	1.11	1.14	1.22	1.18
15	0.04	1.00	1.01	1.00	1.06	1.07	1.07	1.16	1.17	1.17
16	0.03	1.00	1.02	1.02	1.05	1.07	1.05	1.93	1.13	1.04
17	0.02	1.00	1.01	1.01	1.03	1.02	1.03	1.57	1.08	1.09
18	0.01	1.00	1.01	1.01	1.01	1.04	1.02	1.28	1.04	1.02

Table A.2: The metric behavior of the first test case after 10 load balancing iterations.

	Area	N=4	N=9	N=16	N=25	N=36	N=49	N=64	N=81	N=100
1	Coarse	1.00	0.39	0.50	0.22	0.18	0.19	0.15	0.33	0.45
2	1.8	1.00	0.83	0.68	0.56	0.38	0.34	0.12	0.73	0.95
3	1.6	1.00	0.88	0.58	0.52	0.44	0.36	0.11	0.69	0.89
4	1.4	1.00	0.91	0.89	0.67	0.39	0.35	0.21	0.74	0.92
5	1.2	1.00	0.90	0.81	0.54	0.58	0.44	0.20	1.00	1.12
6	1	1.00	0.93	0.78	0.47	0.52	0.50	0.20	0.79	0.96
7	0.8	1.00	0.92	0.68	0.84	0.45	0.59	0.17	0.74	1.24
8	0.6	1.00	1.00	0.87	0.80	0.79	0.50	0.20	1.00	1.17
9	0.4	1.00	1.00	0.81	0.93	0.88	0.55	0.14	0.84	1.10
10	0.2	1.00	1.00	1.00	1.00	1.00	1.00	0.16	0.99	1.19
11	0.1	1.00	1.00	1.00	1.00	1.00	1.00	0.30	1.00	0.98
12	0.08	1.00	1.00	1.00	1.00	1.00	1.00	0.35	1.00	1.17
13	0.06	1.00	1.00	1.00	1.00	1.00	1.00	0.39	1.00	1.00
14	0.05	1.00	1.00	1.00	1.00	1.00	1.00	0.44	1.00	1.08
15	0.04	1.00	1.00	1.00	1.00	1.00	1.00	0.52	1.00	1.05
16	0.03	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.01
17	0.02	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.04
18	0.01	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.01

Table A.3: The difference in metric behavior between no iteration and 10 iterations. The closer the z-value to zero, the better the improvement.

	Area	N=4	N=9	N=16	N=25	N=36	N=49	N=64	N=81	N=100
1	Coarse	1.95	4.12	6.76	9.60	12.44	14.21	16.44	8.60	6.77
2		1.80	1.45	2.31	4.10	4.91	7.90	8.61	22.67	6.37
3		1.60	1.42	2.24	4.19	4.91	6.94	8.50	20.91	6.29
4		1.40	1.31	2.12	2.97	4.41	6.22	8.58	19.84	6.25
5		1.20	1.30	1.96	3.02	4.65	4.53	7.09	19.83	4.30
6		1.00	1.34	1.78	2.90	4.35	4.49	5.88	19.85	4.62
7		0.80	1.26	1.64	2.95	3.09	4.47	4.45	17.42	4.58
8		0.60	1.14	1.42	2.05	2.72	3.50	4.09	12.90	4.18
9		0.40	1.09	1.34	1.79	2.08	2.73	3.34	11.39	2.83
10		0.20	1.06	1.15	1.34	1.56	1.72	2.03	7.02	1.85
11		0.10	1.02	1.04	1.15	1.22	1.29	1.37	4.12	1.36
12		0.08	1.01	1.04	1.08	1.15	1.20	1.30	3.47	1.33
13		0.06	1.01	1.03	1.04	1.10	1.08	1.20	2.79	1.26
14		0.05	1.02	1.03	1.05	1.07	1.06	1.12	2.57	1.23
15		0.04	1.00	1.03	1.01	1.06	1.08	1.07	2.22	1.18
16		0.03	1.01	1.02	1.01	1.04	1.07	1.05	1.86	1.11
17		0.02	1.01	1.02	1.01	1.04	1.04	1.03	1.57	1.09
18		0.01	1.00	1.01	1.02	1.02	1.02	1.02	1.29	1.04
										1.02

Table A.4: The metric behavior of the second test case after no load balancing iterations.

	Area	N=4	N=9	N=16	N=25	N=36	N=49	N=64	N=81	N=100
1	Coarse	1.85	1.36	1.76	1.48	1.74	1.60	1.79	1.82	1.92
2	1.8	1.15	1.33	1.65	2.08	2.58	2.41	2.69	3.83	3.99
3	1.6	1.12	1.34	1.65	2.35	2.67	2.47	2.96	2.59	2.97
4	1.4	1.12	1.37	1.79	1.86	1.83	2.71	2.82	2.58	3.74
5	1.2	1.15	1.50	1.54	1.56	1.71	2.13	2.81	2.79	2.87
6	1	1.15	1.45	1.73	1.74	1.74	2.39	2.48	2.81	3.07
7	0.8	1.14	1.40	1.47	1.44	1.58	2.26	2.38	2.60	3.39
8	0.6	1.05	1.31	1.49	1.85	1.57	1.81	1.81	2.42	2.36
9	0.4	1.09	1.19	1.37	1.77	1.71	1.87	1.57	1.72	2.26
10	0.2	1.06	1.15	1.18	1.35	1.63	1.67	1.73	1.52	1.72
11	0.1	1.02	1.04	1.15	1.22	1.29	1.34	1.25	1.26	1.37
12	0.08	1.01	1.04	1.08	1.15	1.20	1.30	1.22	1.21	1.26
13	0.06	1.01	1.03	1.04	1.10	1.08	1.20	1.18	1.26	1.19
14	0.05	1.02	1.03	1.05	1.07	1.06	1.12	1.15	1.23	1.16
15	0.04	1.00	1.03	1.01	1.06	1.08	1.07	1.13	1.18	1.11
16	0.03	1.01	1.02	1.01	1.04	1.07	1.05	1.32	1.11	1.08
17	0.02	1.01	1.02	1.01	1.04	1.04	1.03	1.15	1.09	1.07
18	0.01	1.00	1.01	1.02	1.02	1.02	1.02	1.29	1.04	1.02

Table A.5: The metric behavior of the second test case after 10 load balancing iterations.

	Area	N=4	N=9	N=16	N=25	N=36	N=49	N=64	N=81	N=100
1	Coarse	0.95	0.33	0.26	0.15	0.14	0.11	0.11	0.21	0.28
2	1.8	0.79	0.57	0.40	0.42	0.33	0.28	0.12	0.60	0.65
3	1.6	0.79	0.60	0.39	0.48	0.38	0.29	0.14	0.41	0.48
4	1.4	0.85	0.64	0.60	0.42	0.29	0.32	0.14	0.41	0.62
5	1.2	0.89	0.77	0.51	0.34	0.38	0.30	0.14	0.65	0.46
6	1	0.85	0.81	0.60	0.40	0.39	0.41	0.12	0.61	0.62
7	0.8	0.91	0.85	0.50	0.47	0.35	0.51	0.14	0.57	0.81
8	0.6	0.92	0.92	0.73	0.68	0.45	0.44	0.14	0.86	0.57
9	0.4	1.00	0.89	0.76	0.85	0.63	0.56	0.14	0.61	0.84
10	0.2	1.00	1.00	0.89	0.86	0.95	0.82	0.25	0.82	1.00
11	0.1	1.00	1.00	1.00	1.00	1.00	0.98	0.30	0.92	1.00
12	0.08	1.00	1.00	1.00	1.00	1.00	1.00	0.35	0.91	1.00
13	0.06	1.00	1.00	1.00	1.00	1.00	1.00	0.42	1.00	1.00
14	0.05	1.00	1.00	1.00	1.00	1.00	1.00	0.45	1.00	1.00
15	0.04	1.00	1.00	1.00	1.00	1.00	1.00	0.51	1.00	1.00
16	0.03	1.00	1.00	1.00	1.00	1.00	1.00	0.71	1.00	1.00
17	0.02	1.00	1.00	1.00	1.00	1.00	1.00	0.74	1.00	1.00
18	0.01	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00

Table A.6: The difference in metric behavior between no iteration and 10 iterations. The closer the z-value to zero, the better the improvement.

	Area	N=4	N=9	N=16	N=25	N=36	N=49	N=64	N=81	N=100
1	Coarse	2.24	2.24	2.28	2.27	2.24	2.29	2.32	2.26	2.29
2	1.8	2.13	2.13	2.16	2.42	2.13	2.43	2.23	2.17	2.65
3	1.6	2.11	2.12	2.15	2.40	2.11	2.42	2.22	2.16	2.63
4	1.4	2.09	2.10	2.13	2.38	2.10	2.39	2.20	2.12	2.61
5	1.2	2.07	2.07	2.11	2.35	2.08	2.37	2.18	2.11	2.59
6	1	2.04	2.04	2.07	2.32	2.04	2.33	2.15	2.08	2.54
7	0.8	1.99	1.99	2.02	2.27	1.99	2.28	2.10	2.03	2.50
8	0.6	1.91	1.92	1.95	2.18	1.92	2.20	2.03	1.96	2.41
9	0.4	1.78	1.79	1.82	2.04	1.79	2.06	1.90	1.83	2.27
10	0.2	1.47	1.48	1.51	1.70	1.49	1.72	1.59	1.52	1.91
11	0.1	1.09	1.10	1.12	1.28	1.11	1.29	1.21	1.16	1.45
12	0.08	1.03	1.02	1.03	1.13	1.02	1.15	1.07	1.03	1.31
13	0.06	1.03	1.04	1.04	1.15	1.04	1.18	1.09	1.08	1.28
14	0.05	1.02	1.02	1.03	1.11	1.03	1.13	1.09	1.06	1.20
15	0.04	1.06	1.06	1.06	1.12	1.08	1.12	1.09	1.10	1.20
16	0.03	1.08	1.08	1.09	1.12	1.10	1.11	1.10	1.11	1.15
17	0.02	1.02	1.03	1.03	1.03	1.03	1.03	1.03	1.03	1.06
18	0.01	1.03	1.03	1.03	1.04	1.03	1.04	1.04	1.03	1.05

Table A.7: The metric behavior of the third test case after no load balancing iterations.

	Area	N=4	N=9	N=16	N=25	N=36	N=49	N=64	N=81	N=100
1	Coarse	1.00	1.01	1.04	1.05	1.01	1.06	1.06	1.06	1.08
2	1.8	1.02	1.03	1.15	1.21	1.20	1.23	1.36	1.42	1.54
3	1.6	1.03	1.04	1.08	1.20	1.18	1.23	1.54	1.69	1.58
4	1.4	1.02	1.06	1.09	1.25	1.32	1.39	1.37	1.52	1.62
5	1.2	1.03	1.06	1.24	1.24	1.30	1.32	1.48	1.56	1.84
6	1	1.02	1.05	1.15	1.25	1.31	1.35	1.49	1.80	2.15
7	0.8	1.04	1.06	1.10	1.23	1.27	1.53	1.79	1.84	1.95
8	0.6	1.03	1.11	1.13	1.38	1.51	1.61	1.79	1.96	2.17
9	0.4	1.04	1.19	1.26	1.39	1.66	1.47	1.90	1.83	2.27
10	0.2	1.06	1.17	1.16	1.33	1.49	1.62	1.59	1.52	1.78
11	0.1	1.09	1.10	1.12	1.14	1.11	1.19	1.21	1.16	1.19
12	0.08	1.03	1.02	1.03	1.13	1.02	1.15	1.07	1.03	1.14
13	0.06	1.03	1.04	1.04	1.15	1.04	1.18	1.09	1.08	1.28
14	0.05	1.02	1.02	1.03	1.11	1.03	1.13	1.09	1.06	1.20
15	0.04	1.06	1.06	1.06	1.12	1.08	1.12	1.09	1.10	1.20
16	0.03	1.08	1.08	1.09	1.12	1.10	1.11	1.10	1.11	1.15
17	0.02	1.02	1.03	1.03	1.03	1.03	1.03	1.03	1.03	1.06
18	0.01	1.03	1.03	1.03	1.04	1.03	1.04	1.04	1.03	1.05

Table A.8: The metric behavior of the third test case after 10 load balancing iterations.

	Area	N=4	N=9	N=16	N=25	N=36	N=49	N=64	N=81	N=100
1	Coarse	0.45	0.45	0.46	0.46	0.45	0.46	0.45	0.47	0.47
2	1.8	0.48	0.48	0.53	0.50	0.56	0.51	0.61	0.65	0.58
3	1.6	0.49	0.49	0.50	0.50	0.56	0.51	0.69	0.78	0.60
4	1.4	0.49	0.50	0.51	0.52	0.63	0.58	0.62	0.72	0.62
5	1.2	0.50	0.51	0.59	0.53	0.62	0.56	0.68	0.74	0.71
6	1	0.50	0.51	0.56	0.54	0.64	0.58	0.69	0.86	0.85
7	0.8	0.52	0.53	0.54	0.54	0.64	0.67	0.85	0.90	0.78
8	0.6	0.54	0.58	0.58	0.63	0.79	0.73	0.88	1.00	0.90
9	0.4	0.59	0.66	0.70	0.68	0.93	0.71	1.00	1.00	1.00
10	0.2	0.72	0.79	0.77	0.78	1.00	0.94	1.00	1.00	0.93
11	0.1	1.00	1.00	1.00	0.89	1.00	0.92	1.00	1.00	0.83
12	0.08	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.87
13	0.06	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
14	0.05	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
15	0.04	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
16	0.03	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
17	0.02	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
18	0.01	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00

Table A.9: The difference in metric behavior between no iteration and 10 iterations. The closer the z-value to zero, the better the improvement.

REFERENCES

- [1] RE Alcouffe, RS Baker, SA Turner, and JA Dahl. Partisn manual. Technical report, LA-UR-02-5633, Los Alamos National Laboratory, 2002.
- [2] Michael P. Adams et al. Provably optimal parallel transport sweeps on regular grids. In *International Conference on Mathematics and Computational Methods Applied to Nuclear Science & Engineering*, 2013.
- [3] Thomas M. Evans et al. Denovo: A new three-dimensional parallel discrete ordinates code in scale. *Nuclear Technology*, 171:171–200, 2010.
- [4] Christian Grossman and Hans-Gorg Roos. *Numerical Treatment of Partial Differential Equations*. Springer, 2007.
- [5] Shawn D. Pautz. An algorithm for parallel sn sweeps on unstructured meshes. *Los Alamos National Laboratory Publications*, LA-UR-01-1420.
- [6] W. H. Reed and T. R. Hill. Triangular mesh methods for the neutron transport equation. *Los Alamos National Laboratory Publications*, LA-UR-73-379.
- [7] Jonathan Richard Shewchuk. Triangle: Engineering a 2D Quality Mesh Generator and Delaunay Triangulator. In Ming C. Lin and Dinesh Manocha, editors, *Applied Computational Geometry: Towards Geometric Engineering*, volume 1148 of *Lecture Notes in Computer Science*, pages 203–222. Springer-Verlag, May 1996. From the First ACM Workshop on Applied Computational Geometry.