

# A32F South (Latin) America and WATRS Reference Guide

## FLIGHT PLANNING

- ☐ Flight PlanFlt/Date STA
- ☐ Flight PlanDesignate
- ☐ TPS .....CCI or WBD Flt/Date/STA
- ☐ Chart Change Notices/NOTAMS
- ☐ Crew List.....CCI or NS/Flt#/Date/STA
- ☐ AIREP Form
- ☐ Obtain Weather ChartsWSI  
(Wind Prog FL 340, High Level Sig Prog, Volcanic Ash)
- ☐ Track MessageEvaluate and crosscheck with flight plan
- ☐ Preflight EFB
- ☐ Current Crew Passports

### A321NX/NY — ETOPS-180:

Max diversion time 180 min (~1,263 nm from suitable airport).  
Confirm ETOPS authorization in ops specs. ETOPS  
pre-departure check required per AML.

## PRE-DEPARTURE AT AIRCRAFT

- ☐ Fit for Duty (CCI or ACARS>PREFLT>page 2)
- ☐ Gen Dec and Customs Forms (if required) FA1/Purser Briefing
- ☐ ETOPS Pre-Departure Check (PDC) in AML (also Transit Check, MEL(s)/CDL(s))
- ☐ Water/LAV Service ReportVerify accomplished
- ☐ Security InspectionVerify accomplished
- ☐ ATC Route Clearance Verification
- ☐ CCI – Verify all required CCI documents on iPad
- ☐ Takeoff Briefing including TA, Noise Abatement, Terrain, Engine Out SIDs

### SATCOM Setup:

SATCOM #1 → IOC    SATCOM #2 → Controlling OCA

## CLIMB - CRUISE

- ☐ Update winds when new updates available (0000Z, 0600Z, 1200Z, 1800Z)

- ☐ Perform Navigation Accuracy Check

- ☐ Review Jeppesen country pages

### Position Reports (if ADS is Unavailable)

Use AIREP Form as a reference for the phraseology and order for making position reports.

- ☐ Report each compulsory fix (filled-in solid waypoints only): aircraft ID/position/time/flight level/next compulsory fix/ETA next compulsory fix

If ▲ symbol located at fix: meteorological report required (temperature, wind, any significant weather)

### RVSM Altimeter Crosscheck (A321XLR addition)

When established in cruise at or above FL290: crosscheck each PFD altimeter and the standby altimeter. Record results. Repeat hourly. Select AP1 / Transponder 1 for RVSM.

### Diversion Airports

- ☐ Continually evaluate weather for enroute diversion airports and arrival routings

Approximately one hour prior to OEP: captain reviews all potential enroute diversion airports using most recent weather.

### Weather Radar

- ☐ Ensure weather radar ON during IMC or night

## CLIMB-CRUISE

### Fly the CLEARANCE not the Flight Plan.

- ☐ PM compares Oceanic Clearance to FMS; notes any differences

- ☐ PF compares Oceanic Clearance to FMS; differences corrected immediately while PM confirms accuracy

- ☐ Circle & Tick — one pilot reads waypoint names from FMS aloud; other checks against Oceanic Clearance and MFP, places a circle (O) next to waypoint on MFP or chart

NOTE: Crosscheck FMS coordinates by comparing oceanic waypoint expanded coordinates against flight plan coordinates.

- ☐ Update winds in FMS (if rerouted)
- ☐ Set assigned MACH and cleared cruise altitude in FMS
- ☐ Plot route and label each waypoint
- ☐ Evaluate potential enroute diversion airport(s) WX/services
- ☐ Obtain alternate airports WX, forecast, and NOTAMS
- ☐ Check A/C Systems Status / ETOPS Significant Systems

☐ ETOPS Inflight Verification Check(s) prior to ETOPS entry (e.g., APU inflight start) — AML entry required. Contact Dispatch if unsuccessful.

☐ Verify ETA to OCA Entry Point (compare FMS and FPR)

☐ Verify GPS Primary

☐ Determine Altitude Capability — WAH for KZWY, LPPO

Step Altitudes (MCDU): F-PLN > vertical revision > STEP ALTS [5R] — predicts time/distance for selected altitude.

☐ Log on CPDLC 10–25 minutes prior to airspace entry

A321XLR MCDU path: MCDU MENU > ATSU [6L] > AOC MENU [2R] > ATS > CONNECTION > NOTIFICATION.

☐ HF/SELCAL check (as required)

☐ Verify next leg (circle & tick)

### After Oceanic Entry Point (OEP)

☐ HF/SELCAL check (if not already done)

• One HF SELCAL Inoperative. Place the primary HF frequency in the HF radio with the operating SELCAL. In this configuration continuous monitoring of the HF is not required.

• Both HF SELCALs Inoperative. If unable to obtain a SELCAL check on either HF radio, then a pilot will continuously monitor the primary HF frequency.

☐ Enter nearest Diversion Airport on PM PROG Page

☐ Set left VHF radio to 121.5 and right to 123.45

☐ Transponder to 2000 when 30 min. past radar service

☐ Perform strategic lateral offset procedure (SLOP)

☐ CPDLC Confirm Assigned Route Message – PGE+ or PRINT, \* appears then SEND

## OCEANIC PROCEDURES

### Strategic Lateral Offset Procedure (SLOP)

This procedure is recommended to be used on every oceanic flight and is Standard Operating Procedure throughout the NAT Region.

- Fly 1 NM or 2 NM offset / RIGHT only.
- Decision to OFFSET based on TCAS traffic observation.
- Offset using LNAV / NAV, not heading select.
- Do not advise ATC or request ATC clearance.
- Return to course by oceanic exit point.

### Approaching Each Waypoint

1. Both pilots must verify that the subsequent full waypoint Lat/Long, course and distance agree with the flight plan or current ATC clearance.

2. Perform the Circle & Tick procedure by drawing a diagonal line thru the circle beside the waypoint if not previously accomplished to indicate verification was accomplished. ☒

### Waypoint Passage

- Verify autopilot is coupled to NAV
- Confirm the next waypoint becomes the active waypoint.
- Verify autopilot is receiving guidance from the FMS, and that it did not revert to heading or track mode.
- Draw a second diagonal line thru the circle beside the waypoint just passed forming an X indicating passage. ☒
- Record time and fuel on FPR / MFP.
- Complete AIREP form/ Transmit report (if required).

### Position Check

Aircraft position and time must be checked 10 minutes (or 2 Degrees) beyond each waypoint passage to verify the correct track is being flown. (Plotting not required)

### Midpoint Check

- Check ETA to the next waypoint. If waypoint crossing time changed by 3 minutes or more from the last estimate given to ATC, a revised estimate should be transmitted using CPDLC ATC free text, or voice, as appropriate.
- Check for satisfactory fuel quantity/balance and trend.

### Track Exit

- Confirm ATC Clearance
- Request desired altitude and MACH from ATC.
- Confirm SLOP offset is zero.

## Oceanic Clearance – Eastbound

### Flights Transiting WATRS (NY Oceanic) into NAT MNPS Airspace

1. Clearance received at the departing station (voice or PDC) is a valid clearance through NAT MNPS airspace.
2. No other route clearance will be issued unless there is a change.
3. ATC will assign an altitude and Mach # prior to Oceanic Entry Point.
4. These two items plus the pre-departure clearance routing constitute a valid clearance.
- 5c. Voice Procedures  
All crewmembers in the cockpit should copy and crosscheck any voice clearance.  
— Initial contact to clearance delivery: “Gander Clearance, American 123, request track  
Whiskey, flight level 370, Mach .82, estimating CARPE at 0440, max flight level 390.”  
— Oceanic clearance on organized track: “American 123, CARPE, track Whiskey, flight level 370, Mach decimal 82, TMI 182.”  
Note: Random route or clearance given over HF, full readback.

#### New York OCA

1. ATC will normally issue altitude and speed assignment unsolicited.
2. The last assigned route, altitude, and speed are to be maintained.
3. Expect to receive oceanic clearance on the last radar sector frequency within the domestic area.  
Be prepared to give WAH

### 5d. Eastbound Techniques

#### Entering Gander OCA - CZQX

- Be ready to write down HF Primary and Secondary frequencies.  
Initial VHF contact when told to contact Gander Radio, example:
- Gander RADIO, <call sign>
  - after acknowledgment <call sign> C-P-D-L-C, <OCA Name>
- NEXT  
Entering New York OCA – KZWY  
Transitioning from New York to Gander, you may be told to contact Gander at 4430 North on <HF Freq.>. The boundary is at 44° 30' North, shown on JeppFD-Pro  
ENTERING LAST OCA, example:
- <OCA Name> RADIO on <HF Freq>
  - after acknowledgment <call sign> C-P-D-L-C, [TRACK \_\_, OR Random Route AND last TWO Exit Points] SELCAL CHECK XX-XX  
CHANGE SATCOM #2 to new OCA

## Oceanic Clearance via Datalink Techniques

**Request Oceanic Clearance as CLOSE TO but NO GREATER than 90 MINUTES prior to entry, but > 30 minutes from oceanic boundary**

MCDU Menu - ATSU[6L] - AOC Menu[2R] – Messages [2R] – OCEANIC CLNC Request[4L] (or AOC Menu – ATS – OCEANIC CLX)

(SELECT ATC FIR) select OCEANIC CENTER

On AOC OCEAN CLR REQUEST page, fill in prompts:

- Ensure MCDU is displayed [5R].
- ENTER OPTIONAL FREE TEXT. Remarks may indicate the preferred alternative to the requested clearance and maximum flight level (e.g. Max F380) that can be accepted at the boundary.

The crew should expect A CLEARANCE CONFIRMED message within a few minutes. If no confirmation is received within 15 minutes revert to voice procedures.

**EXPECT** clearance 1 hr. prior to entry EAST; 10 Min. from request WEST (VOICE, if within 30min of entry point EAST, 15 min from request or entry point, WEST)  
**ACCEPT** the Clearance, **THEN** request any changes required, Print, then:

- PF and PM separately **VERIFY** each point expanded coordinates on FMS to Track Msg
- **SEND** copy of clearance to OCC **EXCEPT** from Gander
- **SET** Constant MACH for Track
- **FILL IN** AIREP Form - another pilot to check  
Status Message **MUST** be received - Clearance Confirmed  
If not received contact via voice immediately - <center>American # - Standing By  
Notify OCEANIC Center 10-25 minutes prior to ENTRY for CPDLC.  
If DCDU does not show ACTIVE you still may have capability. ADS is always active. A SELCAL requesting missing position report will confirm the system is not working.

## ARRIVAL BRIEFING

- ☐ Review airport specific 10-7 page unique engine failure during missed approach procedures
- ☐ Review transition altitude, country, and airport specific speed restrictions
- ☐ TERR feature on for any airport with significant terrain features  
International Terminal Operations  
Return to gate/remote parking: ability to deplane no later than 4 hours international. Coordinate deplane PA; notify dispatcher via ACARS plain text message.

## DEPARTING TRACK - CONTINGENCIES

If immediate action is not required, request an amended ATC clearance. Otherwise:

1. Leave the assigned route by turning at least 45 DEG to the left or right.
  - a. If Unable to maintain altitude, minimize altitude loss until 15 NM offset, Descend below FL280 before diverting, Fly normal altitude + 500'
  - b. If Able to maintain altitude, after 10 NM off (on way to 15NM offset), climb/descend+ 500', If intention to acquire opposite direction offset track, consider turning more than 180 DEG in order to re-intercept the offset contingency track.
2. Accomplish appropriate checklists.
3. 4. Advise other aircraft on 121.5, turn exterior lights on. Advise ATC, (MAYDAY – Grave & Imminent danger) or (PAN PAN - Urgency) preferably spoken 3 times, shall be used as appropriate. Distress Freq – VHF 121.5, HF 4125 (Maritime Mobil Service), SATCOM 83642182 (Maritime Services)

**FOR ADDITIONAL INFORMATION SEE THE ATLANTIC ORIENTATION CHART**

### Loss of Engine

- To minimize initial descent:
1. Accomplish Unable to Maintain Altitude – Loss of Engine Thrust (QRH).
  2. FMC ENG OUT / GREEN DOT speed may be used until 15 NM offset.
  3. Turn towards a suitable airport when appropriate (below MNPS (FL280)).
  4. Select cruise FL that differs  $\pm 500'$  from normal..

### Loss of Cabin Pressure

**CAUTION – See procedures on Greenland Critical Terrain Orientation Chart.**

### Other Emergencies (Medical, Passenger, etc.)

If Able to maintain altitude, after 10 NM off (on way to 15NM offset), climb/descend+ 500', If Intention to acquire opposite direction offset track, consider turning more than 180 DEG in order to re-intercept the offset contingency track.

## WEATHER DEVIATIONS

- Request weather deviation clearance from ATC.
- If clearance is denied or no communication is established and if the deviation is:
  - A. 10 nm or less: remain at ATC assigned FL
  - B. Deviation greater than 10 nm:
    - Track East (000–179°): Left of course – DESCEND 300' / Right of course – CLIMB 300'
    - Track West (180–359°): Left of course – CLIMB 300' / Right of course – DESCEND 300'
- Memory device: “The South will rise again” — if turning south, CLIMB.
  - Advise ATC and other aircraft on 121.5 and/or 123.45 of intentions. Turn on external lights. Maintain traffic watch visually and via TCAS.
  - When returning to route/track, be at assigned FL when within 10 nm of centerline.
  - Keep ATC updated on intentions and inform when deviation is complete.

NAV ACCURACY CHECK

△ ENTRY

EXIT

Station

Primary

Secondary

SelCal

△

△

△



# AIREP FORM

SELCAL: \_\_\_\_\_

Station

Primary

Secondary

SelCal

△

△

△

|                                   |                    |                    |                    |                    |                    |                    |                    |
|-----------------------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|
| STATION:                          |                    |                    |                    |                    |                    |                    |                    |
| FREQ / TYPE:<br>(Voice/ADS/CPDLC) |                    |                    | △                  |                    |                    |                    |                    |
| CALLSIGN                          | Position, Callsign | Position, Callsign | Position, Callsign | Position, Callsign | Position, Callsign | Position, Callsign | Position, Callsign |
| POSITION                          | Lat                |                    |                    |                    |                    |                    |                    |
|                                   | Long               |                    |                    |                    |                    |                    |                    |
| FLIGHT LEVEL                      | Flt                | Flt                | Flt                | Flt                | Flt                | Flt                | Flt                |
|                                   | Lvl                | Lvl                | Lvl                | Lvl                | Lvl                | Lvl                | Lvl                |
| ESTIMATING                        | Lat                | Est                | Est                | Est                | Est                | Est                | Est                |
|                                   | Long               |                    |                    |                    |                    |                    |                    |
|                                   | Time:              |                    |                    |                    |                    |                    |                    |
| NEXT                              | Lat                | Next               | Next               | Next               | Next               | Next               | Next               |
|                                   | Long               |                    |                    |                    |                    |                    |                    |
| FUEL                              | Fuel               | Fuel               | Fuel               | Fuel               | Fuel               | Fuel               | Fuel               |
| * Temp:                           |                    |                    |                    |                    |                    |                    |                    |
| * Wind:                           | /                  | /                  | /                  | /                  | /                  | /                  | /                  |
| ** Sig WX (Opt):                  |                    |                    |                    |                    |                    |                    |                    |

Comm Notes