

Deployment, CI/CD, And DigitalOcean Guide

TGIR QuantLib Tools

TG Investments and Research

2026-04-06

Contents

1 Purpose	2
2 Target Architecture	2
3 Files Added For Deployment	2
4 CI Pipeline	2
4.1 Objective	2
4.2 Recommended CI Stages	2
5 CD Pipeline	3
5.1 One-Time Bootstrap	3
5.2 Automated Release Flow	3
6 Droplet Preparation	3
6.1 Packages	3
6.2 Apache Modules	4
6.3 Filesystem Layout	4
7 Production Configuration	4
7.1 WSGI Entry Point	4
7.2 Production Dependencies	4
7.3 Service Template	4
8 GitHub Secrets	4
9 Suggested Release Procedure	4
10 Rollback	5
11 Operational Smoke Checks	5
12 TLS	5
13 Notes	5

1 Purpose

This guide describes a practical production path for the repo using GitHub Actions for CI/CD and a single DigitalOcean droplet for runtime hosting.

2 Target Architecture

The recommended production layout is:

1. GitHub repository for source control and CI/CD,
2. one Ubuntu-based DigitalOcean droplet,
3. Apache as the public HTTPS reverse proxy,
4. one local WSGI process managed by systemd,
5. a release directory layout with a **current** symlink, and
6. a shared server-side **.env** file that is never committed.

3 Files Added For Deployment

This repo now contains deployment-supporting assets:

- `wsgi.py`,
- `requirements-production.txt`,
- `deploy/systemd/tgir-quantlib-tools.service.template`,
- `deploy/apache/tgir-quantlib-tools.conf.template`,
- `deploy/env/production.env.example`,
- `.github/workflows/ci.yml`, and
- `.github/workflows/deploy_digitalocean.yml`.

4 CI Pipeline

4.1 Objective

CI should prove that the code installs, compiles, the LaTeX docs build, and the quantitative tests pass before deployment is allowed.

4.2 Recommended CI Stages

1. checkout and Python setup,
2. virtual-environment creation,
3. dependency installation,

4. Python syntax compilation,
5. targeted unittest execution,
6. LaTeX PDF build for the doc set, and
7. artifact upload of generated PDFs.

5 CD Pipeline

5.1 One-Time Bootstrap

Before automated deployment, bootstrap the droplet manually:

1. create the application root such as `/opt/tgir_quantlib_tools`,
2. create a shared `.env` file under `/opt/tgir_quantlib_tools/shared/.env`,
3. install Apache and enable proxy-related modules,
4. install the systemd service using the template in `deploy/systemd/`,
5. install the Apache site configuration using the template in `deploy/apache/`, and
6. confirm that `/health` works on the local WSGI bind port and through Apache.

5.2 Automated Release Flow

The deployment workflow should:

1. run after CI succeeds on `main` or manual dispatch,
2. upload the repository as a release tarball,
3. create a timestamped or commit-hash release directory on the droplet,
4. create a fresh `.venv` inside that release,
5. install `requirements-production.txt`,
6. link the shared `.env` and debug directories into the new release,
7. repoint `current` to the new release,
8. restart the systemd service, and
9. smoke-check `/health`.

6 Droplet Preparation

6.1 Packages

On Ubuntu, the typical bootstrap is:

```
sudo apt-get update
sudo apt-get install -y python3 python3-venv python3-pip apache2
```

6.2 Apache Modules

Enable the required modules:

```
sudo a2enmod proxy proxy_http headers rewrite ssl
```

6.3 Filesystem Layout

Recommended layout:

```
/opt/tgir_quantlib_tools/
  current -> /opt/tgir_quantlib_tools/releases/<release-id>
  releases/
  shared/
  .env
  debug/
```

7 Production Configuration

7.1 WSGI Entry Point

Use `wsgi.py` as the production entrypoint so the `systemd` service can run a local WSGI server cleanly.

7.2 Production Dependencies

Use `requirements-production.txt`. It extends the development requirements with `gunicorn` for the production process manager.

7.3 Service Template

The `systemd` template starts `gunicorn` on a loopback port such as `127.0.0.1:8008`. Apache proxies public HTTPS requests to that local port.

8 GitHub Secrets

The deployment workflow assumes these secrets or environment variables:

Secret	Purpose
DO_HOST	Droplet ID
DO_USER	SSH user
DO_SSH_KEY	Private key
DO_APP_ROOT	App root
DO_HEALTHCHECK_URL	Public URL

9 Suggested Release Procedure

1. Open a pull request and let CI pass.
2. Merge to `main`.
3. Let the deployment workflow publish the new release to the droplet.

4. Verify `/health`, login, dashboard rendering, and the cliquet page.
5. If needed, roll back by repointing the `current` symlink to the previous release and restarting the service.

10 Rollback

Rollback is intentionally simple:

1. list prior release directories,
2. repoint `current` to the previous known-good release,
3. restart the systemd service,
4. re-run the local and public health checks.

11 Operational Smoke Checks

After every deploy, run:

```
curl -fsS http://127.0.0.1:8008/health
curl -fsS https://your-hostname.example.com/health
```

Then confirm interactive behavior by logging in and opening:

- `/dashboard`,
- `/trade/equity_cliquet`, and
- `/quantlib-data-model`.

12 TLS

For HTTPS, use Apache with a real certificate. On a public hostname, `certbot` is the lowest-friction path:

```
sudo apt-get install -y certbot python3-certbot-apache
sudo certbot --apache -d your-hostname.example.com
```

13 Notes

This deployment model intentionally stays small and inexpensive:

- one droplet,
- local filesystem storage,
- no database,
- no extra worker host, and
- no paid external platform dependencies beyond the droplet itself.