Programming your GPU with OpenMP
A Hands-on Introduction

Tim Mattson
University of Bristol

While we wait to get started, setup an account on the system we'll use for our GPUs

To get an account on our cluster (AMD AAC6 HPC cluster), open this URL:
https://tinyurl.com/OpenMPAMDSC2026

This web-form will ask for name, email address, and SSH public key.
Your SSH public key is on your laptop (usually in ~/.ssh/id_rsa.pub

Or scan this code to fill the form on your phone:
(first copy your SSH public key to your phone so you can paste it)

git clone https://github.com/tgmattso/OMP_SC.git

Content based on tutorials created with Tom Deakin and Simon McIntosh-Smith of the University of Bristol

Preliminaries: Part 1

- Disclosures
  - The views expressed in this tutorial are those of the people delivering the tutorial.
    - We are not speaking for our employers.
    - We are not speaking for the OpenMP ARB

- We take these tutorials VERY seriously:
  - Help us improve … tell us how you would make this tutorial better.

Nothing in these slides should be taken as saying ANYTHING about future products from anyone.


Data presented in these slides were NOT generated as a formal benchmarking effort. Hence, any performance numbers must NOT be used for comparing systems.

Preliminaries: Part 2

- Our plan ... Active learning!
  - We will mix short lectures with short exercises.
  - The HPC team at AMD is donating time on one of their clusters for this tutorial.

- Please follow these simple rules
  - Do the exercises that we assign and then change things around and experiment.
    - Embrace active learning!
  - Don't cheat: Do Not look at the solutions before you complete an exercise … even if you get really frustrated.

OpenMP Basic Definitions: Basic Solution Stack




OpenMP started with a focus on CPUs as Symmetric Multiprocessors ….
i.e., lots of threads with “equal cost access” to memory


The growth of complexity in OpenMP

- OpenMP started out in 1997 as a simple interface for the application programmers more versed in their area of science than computer science.

- The complexity has grown considerably over the years!



Numerical integration: the Pi program



Mathematically, we know that:

$$\int_0^1 \frac{4.0}{(1+x^2)}\,dx = \pi$$

We can approximate the integral as a sum of rectangles:

$$\sum_{i=0}^{N} F(x_i)\Delta x \approx \pi$$

Where each rectangle has width Δx and height $F(x_i)$ at the middle of interval i.

Serial Pi program

```
static long num_steps = 100000;
double step;
int main ()
{           int i;      double x, pi, sum = 0.0;

            step = 1.0/(double) num_steps;

            for (i=0; i< num_steps; i++){
                        x = (i+0.5)*step;
                        sum = sum + 4.0/(1.0+x*x);
            }
            pi = step * sum;
}
```

Example: Pi in OpenMP with a loop & reduction

```
#include <omp.h>
static long num_steps = 100000;  double step;
void main ()
{    int i;           double x, pi, sum = 0.0;
     step = 1.0/(double) num_steps;

#pragma omp parallel for private(x) reduction(+:sum)
     for (i=0; i< num_steps; i++){
        x = (i+0.5)*step;
        sum = sum + 4.0/(1.0+x*x);
     }

     pi = step * sum;
}
```

Include file to hold function prototypes, types and other items needed to support OpenMP

Create a team of threads (parallel)… share the work of the for loop between the threads (for).

Note … the loop index (i) of the parallel loop is made local to each thread.

Create a variable local to each thread for the value of x at the center of each interval

Create a copy of the variable, sum, for each thread. Initialize it with the identity of the reduction operator (+ is the operator, 0 is the identity)

Threads wait here until all threads complete their work (a barrier).

Finish the reduction … combine sum from each thread using the reduction operator (+). Then combine with the "original" value of sum using the reduction operator.

Example: combining loops to create more work for the parallel loop.

Matrix multiplication: C = C + A * B where $C \in R^{N,M}$, $A \in R^{N,P}$, $B \in R^{P,M}$

```
void mm_ikj_par(int N, int M, int P, float *A, float *B, float *C)
{

    #pragma omp parallel for collapse(2)
    for (int i=0;  i<N;  i++)
       for (int j=0;  j<M;  j++)
          for(int k=0; k<P; k++)
               *(C+(i*M+j)) += *(A+(i*P+k)) *  *(B+(k*M+j));
}
```


If N and M are not large, you may not have enough work to keep all the threads busy.

collapse(2) will collapse the following 2 nested loops into one larger loop … therefore giving the parallel loop more work to do.

The growth of complexity in OpenMP


- OpenMP started out in 1997 as a simple interface for the application programmers more versed in their area of science than computer science.

- The complexity has grown considerably over the years!



What are Tasks?

- Tasks are independent units of work
- Tasks are composed of:
  - code to execute
  - data to compute with



- You fill a queue with tasks and then a team of threads does the work … Supports irregular workflows.

```
#pragma omp parallel
{
  #pragma omp single
   {
    p = listhead ;
    while (p) {
       #pragma omp task firstprivate(p)
       {
         process (p);
       }
       p=next (p) ;
     }
   }
}
```

Create a team of threads

One thread walks the list. The others wait at the barrier at the end of the single construct


Create a task, a private copy of p for each task, and assign p the value of p when the task is created (i.e. firstprivate)

An implied barrier at the end of the single construct

The growth of complexity in OpenMP


- OpenMP started out in 1997 as a simple interface for the application programmers more versed in their area of science than computer science.

- The complexity has grown considerably over the years!



NUMA: non-uniform memory architecture

OpenMP basic definitions: the solution stack



Why is OpenMP so important?

OpenMP is the **only** model with **full** GPU support from **all** vendors for C/C++ and Fortran

	CUDA*		HIP		SYCL		OpenACC		OpenMP			Standard		Kokkos		ALPAKA	
	C	F	C	F	C	F	C	F	C	F	P	C	F	C	F	C	F
NVIDIA	● 1	● 2	◒ 3	★ / 4	▲ 5	/ 6	● 7	● 8	■ ▲ 9	■ ● 10	▲ 48	● 11	● 12	▲ 13	★ 14	▲ 15	/ 16
AMD	◒ ★ 19	★ 20	● 21	★ / 4	▲ 22	/ 6	▲ 23	▲ ★ 24	● ▲ 25	● 26		▲ ■ ★ 27	■ 28	▲ 29	★ 14	▲ 30	/ 16
Intel	◒ ▲ 33	/ 34	▲ 35	/ 36	● 37	/ 6	★ 38	★ 39	● 40	● 41	★ 48	● ■ 42	● 43	▲ 44	★ 14	▲ 45	/ 16

- ● Full vendor support
- ◒ Indirect, but comprehensive support, by vendor
- ■ Vendor support, but not (yet) entirely comprehensive
- ▲ Comprehensive support, but not by vendor
- ★ Limited, probably indirect support -- but at least some
- / No direct support available, but of course one could ISO-C-bind your way through it or directly link the libraries
- C C++ (sometimes also C)
- F Fortran
- P Python

***While not shown in the table, CUDA supports Python as well through CuPy**

Table updated Feb 11, 2025. The numbers in the table refer to notes about each listed option. The Table is available at the following URL: https://x-dev.pages.jsc.fz-juelich.de/models/
Table from https://doi.org/10.1145/3624062.3624178 "Many Cores, Many Models: GPU Programming Model vs. Vendor compatibility Overview", Andreas Herten.
The table was modified by adding the python column for OpenMP (ref: **48**, PyOMP, https://ieeexplore.ieee.org/document/9658236)

The “BIG idea” Behind GPU programming

Traditional Loop based vector addition (vadd)


```
int main() {
   int N = . . . ;
   float *a, *b, *c;

   a* =(float *) malloc(N * sizeof(float));

   // ... allocate other arrays (b and c)
   // and fill with data

   for (int i=0;i<N; i++)
      c[i] = a[i] + b[i];

}
```



Data Parallel vadd with HIP

```
// Compute sum of length-N vectors: C = A + B
void __global__
vecAdd (float* a, float* b, float* c, int N) {
    int i = blockIdx.x * blockDim.x + threadIdx.x;
    if (i < N) c[i] = a[i] + b[i];
}

int main () {
    int N = ... ;
    float *a, *b, *c;
    hipMalloc (&a,  sizeof(float) * N);
  // ... allocate other arrays (b and c)
  // and fill with data

  // Use thread blocks with 256 threads each
    vecAdd <<< (N+255)/256, 256 >>> (a, b, c, N);
}
```

Assume a GPU with unified shared memory … allocate on host, visible on device too

How do we execute code on a GPU: The SIMT model (Single Instruction Multiple Thread)

1. Turn kernel code into a scalar work-item

```
// Compute sum of order-N matrices: C = A + B
void __global__
matAdd (float* a, float* b, float* c, int N) {
    int i = blockIdx.x * blockDim.x + threadIdx.x;
    int j = blockIdx.y * blockDim.y + threadIdx.y;
    if (i < N && j<N) c[i][j] == a[i][j] + b[i][j];
}


int main () {
    int N = ... ;
    float *a, *b, *c;
    hipMalloc (&a,  sizeof(float) * N);
  // ... allocate other arrays (b and c)
  // and fill with data

  // define threadBlocks and the Grid
   dim3 dimBlock(4,4);
   dim3 dimGrid(4,4);

  // Launch kernel on Grid
    matAdd <<< digGrid,dimBlock>>> (a, b, c, N);
}
```


This is HIP code

2. Map work-items onto an N dim index space.




3. Map data structures onto the same index space

4. Run on GPU hardware designed around the SIMT execution model



SIMT: One instruction stream maps onto many Processing Elements

- SIMT model: Individual scalar instruction streams are grouped together for SIMD execution on hardware



GPU nomenclature is really messed up. (sorry about that … we tried to unify around OpenCL but failed).


Instruction stream at finest grain	**work-item**, CUDA Thread
Blocks for scheduling work-items	**work-group**, thread block
Execution width for work-items	Subgroup, warp, **wavefront**
Finest grained processing element (PE) in a GPU	**SIMD Lane**, Processing Element, CUDA Core
Block of PEs driven by a single Instruction sequencer	multithreaded SIMD processor, **Compute Unit**, Streaming multiprocessor

These names are particularly awful since they conflict with established names from CPU Computing.

AMD terminology, in bold font, tracks the OpenCL terminology (which is great!!)

What is a core?

Core 0



Frontend processes instructions for execution.


Maps them into micro-operations (**µop**) and manages them (and the register file) so they retire "in order"


Backend executes decoded instructions.

Instructions are pipelined and include multiple ports and SIMD execution units.

Execution is "out of order" to give the scheduler maximum flexibility to maximize instruction-level parallelism

A Generic GPU (following Hennessey and Patterson)






A multithreaded SIMD processor

… or for OpenCL and AMD, a compute unit

… or in "Nvidia-speak" a streaming multiprocessor


Computer Architecture: A Quantitative Approach, John L. Hennessy and David A. Patterson.

A Generic GPU (following Hennessey and Patterson)



Computer Architecture: A Quantitative Approach, John L. Hennessy and David A. Patterson.

A Generic Host/Device Platform Model*




- One ***Host*** and one or more ***Devices***
  - Each Device is composed of one or more Compute Units
  - Each Compute Unit is divided into one or more ***Processing Elements***

- Memory divided into ***host memory*** and ***device memory***

*using OpenCL terminology

Running code on the GPU:
The target construct and default data movement



Based on figure 6.4 in **Using OpenMP – The Next Step** by van der Pas, Stotzer and Terboven, MIT Press, 2017

Default Data Sharing: example

```
int main(void) {
  int N = 1024;
  double A[N], B[N];

  #pragma omp target
  {

    for (int ii = 0; ii < N; ++ii) {

      A[ii] = A[ii] + B[ii];

    }

  } // end of target region
}
```

1. Variables created in host memory.

2. Scalar **N** and stack arrays **A** and **B** are copied *to* device memory. Execution transferred to device.

3. **ii** is **private** on the device as it's declared within the target region

4. Execution on the device.

5. stack arrays **A** and **B** are copied *from* device memory back to the host. Host resumes execution.

Now let's run code in parallel on the device

```
int main(void) {
  int N = 1024;
  double A[N], B[N];

  #pragma omp target
  {
    #pragma omp loop
    for (int ii = 0; ii < N; ++ii) {

      A[ii] = A[ii] + B[ii];

    }

  } // end of target region
}
```

The loop construct tells the compiler:

"this loop will execute correctly if the loop iterations run in any order. You can safely run them concurrently. And the loop-body doesn't contain any OpenMP constructs. So do whatever you can to make the code run fast"

The loop construct is a declarative construct. You tell the compiler what you want done but you DO NOT tell it how to "do it". This is new for OpenMP

Let’s get ready for our hands-on exercises.

To do this, we’ll need to get you accounts on our system and show you how to compile and run code on the sysem

System for hands-on Exercises

- AMD has made their AAC6 cluster available to us.

- We will use their HIP (**H**eterogenous-compute **I**nterface for **P**ortability) programing environment

To get an account on our cluster (AMD AAC6 HPC cluster), open this URL:

https://tinyurl.com/OpenMPAMDSC2026

This web-form will ask for name, email address, and SSH public key.
Your SSH public key is on your laptop (usually in ~/.ssh/id_rsa.pub


Or scan this code to fill the form on your phone:
(first copy your SSH public key to your phone so you can paste it)

[Public]

What is HIP?

AMD's **H**eterogeneous-compute **I**nterface for **P**ortability, or **HIP**, is a C++ runtime API and kernel language that allows developers to create portable applications that can run on AMD accelerators as well as CUDA accelerators

- **Open-source**
- Syntactically similar to CUDA. Most CUDA API calls can be converted in place from CUDA to HIP.
- Supports a strong subset of CUDA runtime functionality



AMD
together we advance_

[Public]

AAC6

AAC6 is has pre-production and production parts

Login or Control Node

aac6:
aac6-fe2

You are here after logging in

SLURM

`srun`
`salloc`
`sbatch`

MI300A CPU:
24 "Zen 4" cores (3 CCDs × 8)
Shares the 128 GB HBM3

Queue MI300A_SPX

Queue PPAC_MI300A_CPX (Default)

ppac-pl1-s24-35

4xMI300A (CPX*)
24 logical GPUs
48 CPUs
128 GB memory

Queue PPAC_MI300A_SPX

ppac-pl1-s24-16

c-pl1-s24-26

pl1-s24-30

Queue SMC_MI300A_SPX

smc300a-ccs1-p03-28 • • •

4xMI300A (SPX)
4 logical GPUs
192 CPUs
512 GB memory

Queue SH5_MI300A_CPX

sh5-pl1-s12-12

sh5-pl1-s12-33

1xMI300A (CPX*)
6 logical GPUs
48 CPUs
128 GB memory

Queue MI250

gct-ccs1-d21-03

gct-ccs1-d21-05 • • •

* CPX compute partitioning exposes each XCD of the MI300A as single GPU device allowing to make more GPUs available for training purposes.
See: Deep dive into the MI300 compute and memory partition modes — ROCm Blogs

AMD
together we advance_

Using the GPUs in the AAC6 cluster

- HIP (hetereogeneous compute interface for portability) is designed to be a higher-level portability layer between ROCm and CUDA. HIP/ROCm compilers are based on amdclang++ and LLVM.
- Compilers are named amdclang, amdclang++, and amdflang. Hipcc is basically amdclang++ --x hip
- HIP libraries are a wrapper on top of ROCm and CUDA libraries – interfaces are mostly compatible, but the underlying code for ROCm is customized for AMD GPUs.

Compile for For OpenMP

```
module load rocm amdclang
amdclang++ -fopenmp --offload-arch=gfx942  <prog_name>.c  -lm
```

Compile For HIP

```
module load rocm
hipcc --offload-arch=gfx942 <prog_name>.cpp  -lm
```

- The cluster is managed with slurm. Use an interactive session with salloc or prepare a batch-queue file and submit jobs with: sbatch, srun

```
salloc -N1 –gpus=1 -t 10:00 –p MI300A_CPX
```

Other options for partitions include:
[MI300A_SPX | PPAC_MI300A_SPX | SH5_MI300A_SPX | SH5_MI300A_CPX | MI250]

```
#!/bin/bash
#SBATCH -p MI300A_CPX
#SBATCH -N 1
#SBATCH --gpus=1
#SBATCH -t 10:00

module load rocm
module load amdclang
./myprog
```

The CPX partition exposes the 4 physical GPUs as 24 distinct GPUs. Use this partition for code development and testing.
The SPX partition exposes 4 distinct GPUs and is the partition to use for formal benchmarking

We are now ready for our first exercise ... which is mostly a chance for you to get on the system and compile/run a program on a GPU.

To get an account on our cluster (AMD AAC6 HPC cluster), open this URL:

https://tinyurl.com/OpenMPAMDSC2026

This web-form will ask for name, email address, and SSH public key.
Your SSH public key is on your laptop (usually in ~/.ssh/id_rsa.pub

Or scan this code to fill the form on your phone:
(first copy your SSH public key to your phone so you can paste it)

Exercise: Parallel vector addition on a GPU

- Make a copy of the vadd.c program in OMP_GPU_Exercises
  - vadd.c Adds together two arrays, element by element:

for(i=0;i<N;i++) c[i]=a[i]+b[i];

- Parallelize your vadd program for a GPU.
  - module load rocm
  - module load amdclang
  - $CC –fopenmp –offload-arch=gfx942 vadd.c -lm
- If the system gave you a GPU that isn't gfx942, figure out which one to use with the command
  - rocminfo | grep gfx
- Time it for large N and save the result. How does it compare to the CPU version?
  - double omp_get_wtime();
  - #pragma omp target
  - #pragma omp teams loop
  - sbatch gpu_job.sh
- Fetch an interactive session for a GPU node
  - salloc -N1 --gpus=1 -t 10:00 -p PPAC_MI300A_CPX

For tiny programs, OpenMP may opt to run the code on the host. You can force the OpenMP runtime to use the GPU by setting the OMP_TARGET_OFFLOAD environment variable when you run the program (./a.out)

> OMP_TARGET_OFFLOAD=MANDATORY ./a.out

gpu_job.sh

```
#!/bin/bash
#SBATCH -p MI300A_CPX
#SBATCH -N 1
#SBATCH --gpus=1
#SBATCH -t 10:00

module load rocm
module load amdclang

OMP_TARGET_OFFLOAD=MANDATORY ./a.out
```

git clone https://github.com/tgmattso/OMP_SC.git

Solution: Simple vector add in OpenMP on GPU

```
int main()
{
    float a[N], b[N], c[N], res[N];
    int err=0;


   // fill the arrays
   #pragma omp parallel for
   for (int i=0; i<N; i++){
      a[i] = (float)i;
      b[i] = 2.0*(float)i;
      c[i] = 0.0;
      res[i] = i + 2*i;
   }


   // add two vectors
   #pragma omp target
   #pragma omp teams loop
   for (int i=0; i<N; i++){
      c[i] = a[i] + b[i];
   }

   // test results
   #pragma omp parallel for reduction(+:err)
   for(int i=0;i<N;i++){
      float val = c[i] - res[i];
      val = val*val;
      if(val>TOL) err++;
   }
   printf("vectors added with %d errors\n", err);
   return 0;
}
```

Let’s compare/contrast concurrency on a CPU and a GPU


Executing a program on CPUs and GPUs






One work-group per compute-unit executing

Executing a program on CPUs and GPUs



CPU/GPU execution modesl




For a CPU, the threads are all active and able to make forward progress.

For a GPU, any given work-group might be in the queue waiting to execute.

No single processor is best at everything

- The idea that you should move everything to the GPU makes no sense

- **Heterogeneous Computing**: Run sub-problems in parallel on the hardware best suited to them.



Implicit data movement covers a small subset of the cases you need in a real program.


To be more general … we need to manage data movement explicitly

Explicit data movement

- Previously, we described the rules for *implicit* data movement.
- We can *explicitly* control the movement of data using the **map** clause.
- **Data allocated on the heap needs to be explicitly copied to/from the device**:

```
int main(void) {
   int  ii=0, N = 1024;
   int* A = (int *)malloc(sizeof(int)*N);

   #pragma omp target
   {
     // N, ii and A all exist here
     // The data that A points to (*A , A[ii]) DOES NOT exist here!
   }
}
```



A **process**: An OS managed instance of a program execution

Moving data with the map clause

```
int main(void) {
   int  N = 1024;
   int* A = malloc(sizeof(int)*N);

   #pragma omp target map(A[0:N])
   {
     // N, ii and A all exist here
     // The data that A points to DOES exist here!
   }
}
```

Default mapping **map(tofrom: A[0:N])**

Copy **to** the GPU at start of the target region and **from** the GPU onto the CPU at the end of target region.

Controlling data movement

```
int i, a[N], b[N], c[N];
#pragma omp target map(to:a,b) map(tofrom:c)
```

Data movement defined from the *host* perspective.

- The various forms of the map clause
  - **map(to:list)**: On entering the region, variables in the list are initialized on the device using the original values from the host (host to device copy).
  - **map(from:list)**: At the end of the target region, the values from variables in the list are copied into the original variables on the host (device to host copy). On entering the region, the initial value of the variables on the device is not initialized.
  - **map(tofrom:list)**: the effect of both a map-to and a map-from (host to device copy at start of region, device to host copy at end).
  - **map(alloc:list)**: On entering the region, data is allocated and uninitialized on the device.
  - **map(list)**: equivalent to **map(tofrom:list)**.

Vector add with dynamic memory on GPU

```
int main()
{
    float *a   = (float *) malloc(sizeof(float) * N);
    float *b   = (float *) malloc(sizeof(float) * N);
    float *c   = (float *) malloc(sizeof(float) * N);
    float *res = (float *) malloc(sizeof(float) * N);
    int err=0;

   // fill the arrays <<<code not shown>>>>

   // add two vectors
   #pragma omp target map(to: a[0:N],b[0:N]) map (tofrom: c[0:N])
   #pragma omp teams loop
   for (int i=0; i<N; i++){
      c[i] = a[i] + b[i];
   }

  // test results <<<code not shown>>>>

  printf("vectors added with %d errors\n", err);
  return 0;
}
```

Commonly used clauses on target and loop constructs

- The basic construct* is:

  #pragma omp target *[clause[[,]clause]...]*

  #pragma omp loop *[clause[[,]clause]...]*

  for-loops

- The most commonly used clauses are:
  - **map(to | from | tofrom list)** ← default is tofrom
  - **private(***list***)** **firstprivate(***list***)** **lastprivate(***list***)** **shared(***list***)**
    - behave as data environment clauses in the rest of OpenMP, but note values are only created or copied into the region, not back out “at the end”.
  - **reduction(***reduction-identifier* **:** *list***)**
    - behaves as in the rest of OpenMP
  - **collapse(***n***)**
    - Combines loops before the distribute directive splits up the iterations between teams

Going beyond simple vector addition …

Using OpenMP for GPU application programming … the heat diffusion problem

5-point stencil: the heat program

- The heat equation models changes in temperature over time.

$$\frac{\partial u}{\partial t} - \alpha \nabla^2 u = 0$$

- We'll solve this numerically on a computer using an explicit **finite difference** discretisation.
- $u = u(t, x, y)$ is a function of space and time.
- Partial differentials are approximated using diamond difference formulae:


$$\frac{\partial u}{\partial t} \approx \frac{u(t+1, x, y) - u(t, x, y)}{dt}$$

$$\frac{\partial^2 u}{\partial x^2} \approx \frac{u(t, x+1, y) - 2u(t, x, y) + u(t, x-1, y)}{dx^2}$$

  - Forward finite difference in time, central finite difference in space.

5-point stencil: the heat program

- Given an initial value of u, and any boundary conditions, we can calculate the value of u at time t+1 given the value at time t.
- Each update requires values from the north, south, east and west neighbours only:



- Computation is essentially a weighted average of each cell and its neighbouring cells.
- If on a boundary, look up a boundary condition instead.

Method of Manufactured Solution

- Stencil codes are notoriously difficult to **know** if the answer is “correct”.

- Analytic solutions hard to come by:
  - It’s why you’re using a computer to solve the equation approximately after all!

- Method of Manufactured Solution (MMS) is a way to help determine if the code does the correct thing.
- An approach often used to find errors in CFD codes and check convergence properties.

Method of Manufactured Solution

- **Choose** a function for $u(t, x, y)$, substitute into the equation and work through the algebra.

- Ideally like the equation to evaluate to zero so don't need to consider a right-hand side to the equation.

- $u(0, x, y)$ gives the initial conditions.
- Can evaluate boundary conditions, e.g. bottom boundary $u(0,0, y)$

- Because u is **known** for all timesteps (it was chosen!), the exact solution is **known**.

- Compare the **computed** solution to the known u to compute an error.
- Any differences come from approximations in the method, or a bug in your code.


Method of Manufactured Solution

- For the problem of length l, choose u:

$$u(t,x,y) = e^{\frac{-2\alpha\pi^2 t}{l^2}} \sin\frac{\pi x}{l} \sin\frac{\pi y}{l}$$

- Boundary conditions: u is always zero on the boundaries

- Initial value of grid is then $u(0,x,y) = \sin\frac{\pi x}{l} \sin\frac{\pi y}{l}$



Heat program …

```
// Loop over time steps
for (int t = 0; t < nsteps; ++t) {

  // solve over spatial domain for step t
  solve(n, alpha, dx, dt, u, u_tmp);

  // Pointer swap to get ready for next step
  tmp = u;
  u = u_tmp;
  u_tmp = tmp;
}
```

Note: Swapping pointers on the host before entering the target region on the next iteration works on a GPU.

When you map pointers between the host and the device, OpenMP remembers the address.

Swapped addresses on the hosts swaps addresses on the device

- Takes two optional command line arguments: <ncells> <nsteps>
  - E.g. ./heat 1000 10
  - 1000x1000 cells, 10 timesteps (the default problem size).
- If no command line arguments are provided, it uses a default:
  - These two commands both run the default problem size of 1000x1000 cells, 10 timesteps.
  - ./heat
  - ./heat 1000 10
- A sensible bigger problem is 8000 x 8000 cells and 10 timesteps.

Serial CPU code

Heat diffusion problem: 5-point stencil code

```
const double r = alpha * dt / (dx * dx);
 const double r2 = 1.0 - 4.0*r;

 // malloc and initialize u_tmp and u (code not shown)

 for (int t = 0; t < nsteps; ++t) {

    for (int i = 0; i < n; ++i) {
      for (int j = 0; j < n; ++j) {
        u_tmp[i+j*n] =  r2 * u[i+j*n]          +
            r * ((i < n-1) ? u[i+1+j*n]   : 0.0) +
            r * ((i > 0)   ? u[i-1+j*n]   : 0.0) +
            r * ((j < n-1) ? u[i+(j+1)*n] : 0.0) +
            r * ((j > 0)   ? u[i+(j-1)*n] : 0.0);
      }
    }
    // Pointer swap to get ready for next step
    tmp = u;
    u = u_tmp;
    u_tmp = tmp;
 }
}
```

Loop over time steps

Loop over NxN spatial domain

Update the 5-point stencil. Boundary conditions on the edges of the domain are fixed at zero.

Heat diffusion problem: 5-point stencil code


Parallel CPU code, n=4000

```
const double r = alpha * dt / (dx * dx);
const double r2 = 1.0 - 4.0*r;

// malloc and initialize u_tmp and u (code not shown)

for (int t = 0; t < nsteps; ++t) {

    #pragma omp parallel for collapse(2)
    for (int i = 0; i < n; ++i) {
      for (int j = 0; j < n; ++j) {
        u_tmp[i+j*n] =  r2 * u[i+j*n]           +
            r * ((i < n-1) ? u[i+1+j*n]   : 0.0) +
            r * ((i > 0)   ? u[i-1+j*n]   : 0.0) +
            r * ((j < n-1) ? u[i+(j+1)*n] : 0.0) +
            r * ((j > 0)   ? u[i+(j-1)*n] : 0.0);
      }
    }
    // Pointer swap to get ready for next step
    tmp = u;
    u = u_tmp;
    u_tmp = tmp;
  }
}
```



Intel® Xeon™ Gold 5218 @ 2.3 Ghz, 8 cores. Nvidia HPC Toolkit compiler
nvc –fast –fopenmp heat.c

Exercise: parallel stencil (heat)

- Take the provided heat stencil code (heat.c)
- Add OpenMP directives to parallelize the loops on the GPU
- Most of the runtime occurs in the solve() routine. Focus on that function. The rest of the code is there to just support the work inside solve.

```
module load rocm
module load amdclang
$CC –fopenmp –offload-arch=gfx942 vadd.c
sbatch job_gpu.sh
```

gpu_job.sh

```
#!/bin/bash
#SBATCH -p MI300A_CPX
#SBATCH -N 1
#SBATCH --gpus=1
#SBATCH -t 10:00

module load rocm
module load amdclang

OMP_TARGET_OFFLOAD=MANDATORY ./a.out
```

… or fetch an interactive session

```
salloc -N1 --gpus=1 -t 10:00 -p MI300A_CPX
```

- double omp_get_wtime();
- #pragma omp parallel
- #pragma omp for
- #pragma omp parallel for
- #pragma omp task
- #pragma omp taskwait
- #pragma single
- #pragma omp target
- #pragma omp teams loop
- Plus the clauses
  - private(), firstprivate(), reduction(+:var), collapse(n)
  - map(to:vptr[Lower:Count]) map(from:vptr[Lower:Count]) map(tofrom:vptr[Lower:Count])

Default is tofrom: map(vptr[Lower:Count])

Parallel GPU code, n=4000

Heat diffusion problem: 5-point stencil code

```
  const double r = alpha * dt / (dx * dx);
  const double r2 = 1.0 - 4.0*r;

  // malloc and initialize u_tmp and u (code not shown)

  for (int t = 0; t < nsteps; ++t) {
     #pragma omp target map(tofrom: u[0:n*n], u_tmp[0:n*n])
     #pragma omp loop
     for (int i = 0; i < n; ++i) {
       for (int j = 0; j < n; ++j) {
         u_tmp[i+j*n] =  r2 * u[i+j*n]          +
             r * ((i < n-1) ? u[i+1+j*n]   : 0.0) +
             r * ((i > 0)   ? u[i-1+j*n]   : 0.0) +
             r * ((j < n-1) ? u[i+(j+1)*n] : 0.0) +
             r * ((j > 0)   ? u[i+(j-1)*n] : 0.0);
       }
     }
     // Pointer swap to get ready for next step
     tmp = u;
     u = u_tmp;
     u_tmp = tmp;
  }
}
```

When you map pointers between the host and the device, OpenMP remembers the address.

Swapped addresses on the hosts swaps addresses on the device

```
GPU Solver time = 1.40 secs
```

This isn't much better than the runtime for a single CPU (1.8 secs) and worse than 8 cores on a CPU (0.29 secs).

Why is the performance so bad?

```
NVIDIA T4 GPU, 16 Gbyte, Turing Arch.
Nvidia HPC Toolkit compiler
nvc –fast –mp=gpu –gpu=cc75 heat.c
```

Heat diffusion problem: 5-point stencil code

Parallel GPU code, n=4000

```
const double r = alpha * dt / (dx * dx);
const double r2 = 1.0 - 4.0*r;

// malloc and initialize u_tmp and u (code not shown)

for (int t = 0; t < nsteps; ++t) {
   #pragma omp target map(tofrom: u[0:n*n], u_tmp[0:n*n])
   #pragma omp loop
   for (int i = 0; i < n; ++i) {
     for (int j = 0; j < n; ++j) {
       u_tmp[i+j*n] =  r2 * u[i+j*n]          +
           r * ((i < n-1) ? u[i+1+j*n]   : 0.0) +
           r * ((i > 0)   ? u[i-1+j*n]   : 0.0) +
           r * ((j < n-1) ? u[i+(j+1)*n] : 0.0) +
           r * ((j > 0)   ? u[i+(j-1)*n] : 0.0);
     }
   }
   // Pointer swap to get ready for next step
   tmp = u;
   u = u_tmp;
   u_tmp = tmp;
  }
}
```

With a runtime of 1.4 secs (worse than the CPU time) we see that Data Movement dominates performance.

At the beginning of each iteration, copy $(2*N^2)*sizeof(TYPE)$ bytes to the device

At the end of each iteration, copy $(2*N^2)*sizeof(TYPE)$ bytes from the device

Finer control over data movement

- Recall that data is mapped to/from the device at start/end of target region
  - #pragma omp target map(tofrom: A[0:N])
    {
      …
    }

- Inefficient to move data around all the time

- We need to keep data resident on the device *between* target regions.

- We need to manage the device data environment independently from the target regions that launch kernels.

Target enter/exit data constructs

- Create a data region on the target device (a device data environment) with two standalone directives:

```
#pragma omp target enter data map(…)
#pragma omp target exit data map(…)
```

- The **target enter data** maps variables to the device data environment.

- The **target exit data** unmaps variables from the device data environment.

- Once created, subsequent **target** regions inherit the existing data environment.

Target enter/exit data example

```
void init_array(int *A, int *B, int N) {
   for (int i = 0; i < N; ++i) { A[i] = i;  B[i]=2*I;}

  #pragma omp target enter data map(to: A[0:N], B[0:N])
}

int main(void) {

   int N = 1024;
   int *A = malloc(sizeof(int) * N);
   int *B = malloc(sizeof(int) * N);
   init_array(A, B, N);

   #pragma omp target
   #pragma omp teams loop
   for (int i = 0; i < N; ++i)
      A[i] = A[i] * B[i];

 #pragma omp target exit data map(from: A[0:N])
}
```

Exercise

- Modify your parallel heat code from the last exercise.
- Use the ‘target data’ constructs to control the device data environment.
- Think about the map clauses and how to use them to minimize data movement.
- Question … will the pointer swap on the host still work?
  - #pragma omp target
  - #pragma omp target enter data map(to: list)
  - #pragma omp target exit data map(from: list)
  - #map(to:list) map(from:list) map(tofrom:list)
  - #pragma omp target teams loop

If your runtimes are tiny, you may want to work with a larger problem.

Try a 4000 by 4000 gird for 10 steps:

./heat 4000 100

```
module load rocm
module load amdclang
$CC –fopenmp –offload-arch=gfx942 vadd.c
sbatch job_gpu.sh
```

```
#!/bin/bash
#SBATCH -p PPAC_MI300A_CPX
#SBATCH -N 1
#SBATCH --gpus=1
#SBATCH -t 10:00

module load rocm
module load amdclang

OMP_TARGET_OFFLOAD=MANDATORY ./a.out
```

… or fetch an interactive session

```
salloc -N1 --gpus=1 -t 10:00 -p PPAC_MI300A_CPX
```

Heat diffusion problem: 5-point stencil code

Parallel GPU code, n=4000

```
const double r = alpha * dt / (dx * dx);
const double r2 = 1.0 - 4.0*r;
// malloc and initialize u_tmp and u (code not shown)
#pragma omp target enter data map(to: u[0:n*n], u_tmp[0:n*n])

for (int t = 0; t < nsteps; ++t) {
   #pragma omp target
   #pragma omp teams loop
   for (int i = 0; i < n; ++i) {
     for (int j = 0; j < n; ++j) {
       u_tmp[i+j*n] =  r2 * u[i+j*n]          +
           r * ((i < n-1) ? u[i+1+j*n]   : 0.0) +
           r * ((i > 0)   ? u[i-1+j*n]   : 0.0) +
           r * ((j < n-1) ? u[i+(j+1)*n] : 0.0) +
           r * ((j > 0)   ? u[i+(j-1)*n] : 0.0);
     }
    }
    // Pointer swap to get ready for next step
    tmp = u;
    u = u_tmp;
    u_tmp = tmp;
  }
 #pragma omp target exit data map(from: u[0:n*n])
}
```

Create a data region and map indicated data on entry

GPU Solver time* = **0.42** secs

This is a general principal … if you want performance, you must optimize data movement.

*includes time for target enter/exit data

Exit the data region and map indicated data

```
NVIDIA T4 GPU, 16 Gbyte, Turing Arch.
Nvidia HPC Toolkit compiler
nvc -fast -mp=gpu -gpu=cc75 heat.c
```

Getting the data movement between host memory and device memory is key.


What are the other major issues to consider when optimizing performance?

Occupancy: Keep all the GPU resources busy

- In our "GPU cartoon" we have 16 multithreaded SIMD processors each with 16 SIMD lanes …. For a total of 16^2=256 processing elements.

- You want all resources busy at all times. You do that by keeping excess work for the multithreaded SIMD processors … if they are other busy on some high latency operation, you want a new work-group is ready to be scheduled for execution.

- *Occupancy* having enough work-groups to keep the GPU busy. To support high occupancy, you need many more work-items than SIMD-lanes.



A multithreaded SIMD processor

```
#pragma omp parallel for
for(int i=0;i<N;i++)
  for(int j=0;j<N;j++)
    for(int k=0;k<N;k++)
      *(C+(i*N+j)) += *(A+(i* N +k)) *  *(B+(k* N +j));
```

Parallelize i-loop parallelism O(N)

```
#pragma omp parallel for collapse(2)
for(int i=0;i<N;i++)
  for(int j=0;j<N;j++)
    for(int k=0;k<N;k++)
      *(C+(i*N+j)) += *(A+(i* N +k)) *  *(B+(k* N +j));
```


Parallelize combined i/j-loops parallelism O(N^2)

Occupancy: Keep all the GPU resources busy

- In our "GPU cartoon" we have 16 multithreaded SIMD processors each with 16 SIMD lanes …. For a total of 16^2=256 processing elements.

- You want all resources busy at all times. You do that by keeping excess work for the multithreaded SIMD processors … if they are other busy on some high latency operation, you want a new work-group is ready to be scheduled for execution.

- *Occupancy* having enough work-groups to keep the GPU busy. To support high occupancy, you need many more work-items than SIMD-lanes.



For our AMD system … There are 208 compute units (2 GCDs x 104) on an MI250 and 228 compute units (6 XCDs x 38) on an MI300A

The MI300A can be a single GPU (SPX mode) or six GPUs (CPX mode).

The MI250 is always two GCDs (GPUs)

In all cases, a compute unit has 64 SIMD Lanes (a wavefront).

```
#pragma omp parallel for
for(int i=0;i<N;i++)
  for(int j=0;j<N;j++)
    for(int k=0;k<N;k++)
      *(C+(i*N+j)) += *(A+(i* N +k)) *  *(B+(k* N +j));
```

Parallelize i-loop parallelism O(N)




```
#pragma omp parallel for collapse(2)
for(int i=0;i<N;i++)
  for(int j=0;j<N;j++)
    for(int k=0;k<N;k++)
      *(C+(i*N+j)) += *(A+(i* N +k)) *  *(B+(k* N +j));
```

Parallelize combined i/j-loops parallelism O(N^2)

Memory Resources that affect Occupancy

Compute Units have finite resources that are shared between work items


- Local Data Share (LDS)
- Vector General Purpose Registers (VGPRs)
- Scalar General Purpose Registers (SGPRs)



The GPU can only schedule more work if there are enough resources available

Converged Execution: Single Instruction Multiple Data

- Individual work-items of a warp start together at the same program address
- Each work-item has its own instruction address counter and register state
  - Each work-item is free to branch and execute independently
  - Supports the Single Program Multiple Data (SPMD) pattern.
- Branch behavior
  - Each branch will be executed serially
  - Work-items not following the current branch will be disabled



Converged Execution: Branching

- GPUs tend not to support speculative execution, which means that branch instructions have high latency
- This latency can be hidden by switching to alternative work-items/work-groups, but avoiding branches where possible is still a good idea to improve performance
- When different work-items executing within the same SIMD ALU array take different paths through conditional control flow, we have ***divergent branches*** *(vs.* ***uniform branches****)*
- Divergent branches are bad news: some work-items will stall while waiting for the others to complete
- We can use predication, selection and masking to convert conditional control flow into straight line code and significantly improve the performance of code that has lots of conditional branches

Branching

Conditional execution

```
// Only evaluate expression
// if condition is met
if (a > b)
{
  acc += (a - b*c);
}
```

Selection and masking

```
// Always evaluate expression
// and mask result
temp = (a - b*c);
mask = (a > b ? 1.f : 0.f);
acc += (mask * temp);
```

Coalesced memory accesses

- ***Coalesced memory accesses*** are key for high performance code, especially on GPUs
- In principle, it's very simple, but frequently requires transposing or transforming data on the host before sending it to the GPU
- Sometimes this is an issue of Array of Structures vs. Structure of Arrays (AoS vs. SoA)

Memory layout is critical to performance

- Structure of Arrays vs. Array of Structures
  - Array of Structures (AoS) more natural to code:

```
struct Point{ float x, y, z, a; };
Point *Points;
```

x	y	z	a	…	x	y	z	a	…	x	y	z	a	…	x	y	z	a	…


  - Structure of Arrays (SoA) suits memory coalescence in vector units

```
struct { float *x, *y, *z, *a; } Points;
```

x	x	x	x	…	y	y	y	y	…	z	z	z	z	…	a	a	a	a	…


Adjacent work-items/vector-lanes like to access adjacent memory locations

Memory access patterns



Memory access patterns


```
float val1 = memA[id];
```



64 Byte Boundary


Memory access patterns

```
const int c = 3;
float val2 = memA[id + c];
```



Memory access patterns

```
float val3 = memA[3*id];
```




Strided access results in multiple memory transactions (and kills throughput)

Memory access patterns

```
const int loc =
  some_strange_func(id);

float val4 = memA[loc];
```



64 Byte Boundary

Coalescence

- **Coalesce** - to combine into one
- Coalesced memory accesses are key for high bandwidth
- Simply, it means, if thread *i* accesses memory location *n* then thread *i+1* accesses memory location *n+1*
- In practice, it's not quite as strict…

```
for (int id = 0; id < size; id++)
{
  // ideal
     float val1 = memA[id];

  // still pretty good
     const int c = 3;
     float val2 = memA[id + c];

  // stride size is not so good
     float val3 = memA[c*id];

  // terrible
     const int loc =
       some_strange_func(id);

     float val4 = memA[loc];
}
```

Exercise

- Optimize the stencil ‘solve’ kernel.
- Start with your code with optimized memory movement from the last exercise.
- Experiment with the optimizations we’ve discussed.
- Focus on the memory access pattern.
- Try different input sizes to see the effect of the optimizations.
- Keep an eye on the solve time as reported by the application.

- #pragma omp target
- #pragma omp target enter data map(to: list)
- #pragma omp target exit data map(from: list)
- #map(to:list) map(from:list) map(tofrom:list)
- #pragma omp target teams loop

```
module load rocm
module load amdclang
$CC –fopenmp –offload-arch=gfx942 vadd.c
sbatch job_gpu.sh
```

gpu_job.sh

```
#!/bin/bash
#SBATCH -p PPAC_MI300A_CPX
#SBATCH -N 1
#SBATCH --gpus=1
#SBATCH -t 10:00

module load rocm
module load amdclang

OMP_TARGET_OFFLOAD=MANDATORY ./a.out
```

… or fetch an interactive session

```
salloc -N1 --gpus=1 -t 10:00 -p PPAC_MI300A_CPX
```

Heat diffusion problem: 5-point stencil code

Parallel CPU and GPU results, n=4000

```
const double r = alpha * dt / (dx * dx);
const double r2 = 1.0 - 4.0*r;
// malloc and initialize u_tmp and u (code not shown)


for (int t = 0; t < nsteps; ++t) {

    #pragma omp parallel for
    for (int i = 0; i < n; ++i) {
      for (int j = 0; j < n; ++j) {
        u_tmp[i+j*n] =  r2 * u[i+j*n]          +
            r * ((i < n-1) ? u[i+1+j*n]   : 0.0) +
            r * ((i > 0)   ? u[i-1+j*n]   : 0.0) +
            r * ((j < n-1) ? u[i+(j+1)*n] : 0.0) +
            r * ((j > 0)   ? u[i+(j-1)*n] : 0.0);
      }
    }
    // Pointer swap for  next step
    tmp = u;
    u = u_tmp;
    u_tmp = tmp;
  }

}
```

This is the ij loop order. Swap these loops to get the ji order.

What if I optimize the CPU code?

… just swap the i and j loops. Using collapse(2) did not help on the GPU or the CPU

CPU

Num threads	ij loop order	ji loop order
1	1.512849	0.262260
2	0.776229	0.132453
4	0.400822	0.064220
8	0.227317	0.046586

Intel® Xeon™ Gold 5218 @ 2.3 Ghz, 8 cores.
Nvidia HPC Toolkit compiler nvc –fast –fopenmp heat.c

All times in seconds

GPU

ij without timing enter and exit data	ij loop order	ji without timing enter and exit data	ji loop order
0.056830	0.417887	0.020123	0.358905

This GPU code used the target enter data and target exit data

NVIDIA T4 GPU, 16 Gbyte, Turing Arch.
Nvidia HPC Toolkit compiler. nvc -fast -mp=gpu heat.c

Solution: collapse + swap loop order

```
// Compute the next timestep, given the current timestep
void solve(const int n, const double alpha, const double dx, const double dt, const double * restrict u,
double * restrict u_tmp) {
  // Finite difference constant multiplier
  const double r = alpha * dt / (dx * dx);
  const double r2 = 1.0 - 4.0*r;

  // Loop over the nxn grid
  #pragma omp target
  #pragma omp teams loop collapse(2)
  for (int j = 0; j < n; ++j) {
    for (int i = 0; i < n; ++i) {



      // Update the 5-point stencil, using boundary conditions on the edges of the domain.
      // Boundaries are zero because the MMS solution is zero there.
      u_tmp[i+j*n] =  r2 * u[i+j*n] +
      r * ((i < n-1) ? u[i+1+j*n] : 0.0) +
      r * ((i > 0)   ? u[i-1+j*n] : 0.0) +
      r * ((j < n-1) ? u[i+(j+1)*n] : 0.0) +
      r * ((j > 0)   ? u[i+(j-1)*n] : 0.0);
}}}
```

Create more work … to better fill the processing elements of the GPU

Swap the i and j loops so that the i+j*n memory accesses are contiguous

The loop construct is great, but sometimes you want more control.

Our host/device Platform Model and OpenMP



Parallel for simd to run each block of loop iterations on the processing elements

Teams construct to create a league of teams with one team of threads on each compute unit.

Target construct to get onto a device

Distribute construct to assign blocks of loop iterations to teams.

teams and distribute constructs


- The **teams** construct
  - Similar to the **parallel** construct
  - It starts a league of thread teams
  - Each team in the league starts as one initial thread – a team of one
  - Threads in different teams cannot synchronize with each other
  - The construct must be “perfectly” nested in a **target** construct

- The **distribute** construct
  - Similar to the **for** construct
  - Loop iterations are workshared across the initial threads in a league
  - No implicit barrier at the end of the construct
  - **dist_schedule(*kind[, chunk_size]*)**
    - If specified, scheduling kind must be static
    - Chunks are distributed in round-robin fashion in chunks of size ***chunk_size***
    - If no chunk size specified, chunks are of (almost) equal size; each team receives at least one chunk

Create a league of teams and distribute a loop among them

- teams construct
- distribute construct

```
#pragma omp target
#pragma omp teams
#pragma omp distribute
 for (i=0;i<N;i++)
   …
```




- Transfer execution control to MULTIPLE device initial threads
- Workshare loop iterations across the initial threads.

Create a league of teams and distribute a loop among them and run each team in parallel with its partition of the loop

- teams distribute
- parallel for

```
#pragma omp target
#pragma omp teams
#pragma omp distribute
#pragma omp parallel for
 for (i=0;i<N;i++)
    …
```




- Transfer execution control to MULTIPLE device initial threads
  - Workshare loop iterations across the initial threads (teams distribute)
- Each initial thread becomes the primary* thread in a thread team
  - Workshare loop iterations across the threads in a team (parallel for)

Create a league of teams and distribute a loop among them and run each team in parallel with its partition of the loop

- loop

```
#pragma omp target
#pragma omp teams
#pragma omp loop
 for (i=0;i<N;i++)
    …
```




- Transfer execution control to MULTIPLE device initial threads
  - Workshare loop iterations across the initial threads (teams distribute)
- Each initial thread becomes the primary* thread in a thread team
  - Workshare loop iterations across the threads in a team (parallel for)

Create a league of teams and distribute a loop among them and run each team in parallel with its partition of the loop

- teams distribute
- parallel for simd

```
#pragma omp target
#pragma omp teams num_teams(3) thread_limit(5)
#pragma omp distribute
#pragma omp parallel for
 for (i=0;i<N;i++)
   …
```

Explicit control of number and size of teams




- Transfer execution control to MULTIPLE device initial threads
  - Workshare loop iterations across the initial threads (teams distribute)
- Each initial thread becomes the primary* thread in a thread team
  - Workshare loop iterations across the threads in a team (parallel for)

Create a league of teams and distribute a loop among them and run each team in parallel with its partition of the loop

- Combined construct

```
#pragma omp target  teams loop
for (i=0;i<N;i++)
    …
```




- Transfer execution control to MULTIPLE device initial threads
  - Workshare loop iterations across the initial threads (teams distribute)
- Each initial thread becomes the primary* thread in a thread team
  - Workshare loop iterations across the threads in a team (parallel for)

Create a league of teams and distribute a loop among them and run each team in parallel with its partition of the loop

- teams distribute
- parallel for simd

Works with nested loops as well

```
#pragma omp target
#pragma omp teams distribute
 for (i=0;i<N;i++)
 #pragma omp parallel for
 for (j=0;j<M;i++)
   ...
```



- Transfer execution control to MULTIPLE device initial threads
  - Workshare loop iterations across the initial threads (teams distribute)
- Each initial thread becomes the primary* thread in a thread team
  - Workshare loop iterations across the threads in a team (parallel for)

Exercise

- Consider the HIP code for vector addition.
- Create a version of that code that uses OpenMP to explicitly address the work-groups and work-items (as you do in HIP/CUDA kernel programming.

```
module load rocm
module load amdclang
$CC –fopenmp –offload-arch=gfx942 vadd.c
sbatch job_gpu.sh
```

```
#!/bin/bash
#SBATCH -p PPAC_MI300A_CPX
#SBATCH -N 1
#SBATCH --gpus=1
#SBATCH -t 10:00

module load rocm
module load amdclang

OMP_TARGET_OFFLOAD=MANDATORY ./a.out
```

gpu_job.sh

… or fetch an interactive session

```
salloc -N1 --gpus=1 -t 10:00 -p PPAC_MI300A_CPX
```

- #pragma omp target
- #pragma omp teams
- #pragma omp distribute
- #pragma omp parallel for
- num_teams(), thread_limit(), simd

```
// Compute sum of length-N vectors: C = A + B
void __global__
vecAdd (float* a, float* b, float* c, int N) {
    int i = blockIdx.x * blockDim.x +
  threadIdx.x;
    if (i < N) c[i] = a[i] + b[i];
}
int main () {
    int N = ... ;
    float *a, *b, *c;
    cudaMalloc (&a,  sizeof(float) * N);
  // ... allocate other arrays (b and c)
  // and fill with data

  // Use thread blocks with 256 threads each
    vecAdd <<< (N+255)/256, 256 >>> (a, b, c,
  N);
}
```

vaddHIP.c

Solution: vadd exposing teams and threads

```
#define BLKSZ 256
#define MIN(a,b)(((a)<(b))?(a)(b))
int main()
{
     float a[N], b[N], c[N], res[N];
     int numTeams = (N+(BLKSZ-1))/BLKSZ;
     int err=0;

   // fill the arrays
   #pragma omp parallel for
   for (int i=0; i<N; i++){
      a[i] = (float)i;
      b[i] = 2.0*(float)i;
      c[i] = 0.0;
      res[i] = i + 2*i;
   }
```

```
// add two vectors
   #pragma omp target
   #pragma omp teams num_teams(numTeams) \
                     thread_limit(BLKSZ)
   #pragma omp distribute
   for (int ib=0;ib<numTeams; ib++){
     #pragma omp parallel for
     for (int i=ib; i<MIN((ib+1)*BLKSZ,N); i++){
       c[i] = a[i] + b[i];
     }
   }
  // test results
  #pragma omp parallel for reduction(+:err)
  for(int i=0;i<N;i++){
     float val = c[i] - res[i];
     val = val*val;
     if(val>TOL) err++;
  }
  printf("vectors added with %d errors\n", err);
  return 0;
}
```

There is MUCH more … beyond what have time to cover

- Do as much as you can with a simple loop construct. It's portable and as compilers improve over time, it will keep up with compiler driven performance improvements.
- But sometimes you need more:
  - Control over number of teams in a league and the size of the teams
  - Explicit scheduling of loop iterations onto the the teams
  - Management of data movement across the memory hierarchy: global vs. shared vs. private …
  - Calling optimized math libraries (such as cuBLAS)
  - Multi-device programming
  - Asynchrony
- Ultimately, you may need to master all those advanced features of GPU programming. But start with loop. Start with how data on the host maps onto the device (i.e. the GPU). Master that level of GPU programming before worrying about the complex stuff.

The book, "Programming your GPU with OpenMP", Tom Deakin and Tim Mattson, MIT Press, 2023 covers these additional topics.

Summary

- Portable Parallel computing for a GPU works … if you use an open standard such as OpenMP.


- It can be as easy as changing
  - #pragma omp parallel for
- To a GPU variant
  - #pragma omp target
  - #pragma omp loop

- Of course there is more work to do in practice, but that’s mostly just getting the map clauses right and, when needed, setup target data regions

To learn more about OpenMP

The OpenMP web site has a great deal of material to help you with OpenMP www.openmp.org
Reading the spec is painful … but each spec has a collection of examples. Study the examples, don't try to read the specs


Since the specs are written ONLY for implementors … programmers need the OpenMP Books to master OpenMP.



Start here … learn the basics and build a foundation for the future



Learn advanced features in OpenMP including tasking and GPU programming (up to version 4.5)



Learn all the details of GPU programming with OpenMP
(up to version 5.2)
Released in November 2023