




M6 (a) - Composition


Jin L.C. Guo

Image source: https://cdn.pixabay.com/photo/2017/11/05/21/21/container-2921882_960_720.jpg

Objective


- Design Principle:
Divide and Conquer
 - Programming mechanism:
Aggregation and Delegation
 - Design Techniques:
Sequence Diagram
 - Patterns and Anti-patterns:
Composite Pattern, Decorator Pattern, God class
- 

Design Problem – Drawing Editor



Design Problem

The users need to be able to change the color of the lines, circles and rectangles, as well as their position.




Line
- int x_start
- int y_start
- int x_end
- int y_end;
- Color currentColor
Line(int, int, int, int)


Circle

Rectangle

```
void respondUserMoveInput(int x, int y, Shape pShape) {  
    pShape.move(x, y);  
}
```




Activity 1: Design Problem



Add the function of grouping shapes so that the users can move or change the color for more than one element, e.g., circle and rectangle.

Solution 1:



```
void respondUserMoveInput(int x, int y, List<Shape> pShapes) {  
    for(Shape aShape: pShapes) {  
        aShape.move(x, y);  
    }  
}
```

*causes
some
complications*

Client code has to treat a single shape
and a group of shapes differently.

*even though the action is similar
additional selection step*



Solution 2:

Large number of possible structures.

Each option requires a class definition, even rare cases.
Impossible to accommodate all situations.

lots of things to write

doesn't need to change



new objects that represent grouped objects


client side is more stable

Another Solution




Image Source: https://upload.wikimedia.org/wikipedia/commons/6/61/Lego_blocks.jpg


Another Solution:




Another Solution:




Another Solution:






Objective

- Design Principle:
Divide and Conquer
 - Programming mechanism:
Aggregation and Delegation
 - Design Techniques:
Sequence Diagram
 - Patterns and Anti-patterns:
Composite Pattern, Decorator Pattern, God class
- 

Composite Pattern

- Intent
 - Compose objects into tree structures to represent part-whole hierarchies.
Composite lets clients treat individual objects and compositions of objects uniformly
- Participants:
 - Primitive (Component)
Declares the interface for objects in the composition.
 - Leaf
concrete Defines behaviour for primitives atomic shapes
 - Composite
concrete Defines behaviour for primitives to have children

Composite Pattern



Implement Composite Pattern

```
public class CompositeShape implements Shape
{
    private List<Shape> aElements = new ArrayList<>();

    @Override
    public void changeColor(Color pColor){/* ... */}

    @Override
    public void move(int pX, int pY) {/* ... */}
}
```

*of atomic shapes
enables client to
add a shape
to it*

Activity2: how to add Primitive instances to Composite?

```
public class CompositeShape implements Shape
{
    ... ..
```

```
    public void add(Shape pShape)
    {
        aElements.add(pShape);
    }
```

```
}
```

What are other options?
What are their tradeoffs?

put add
method
in interface
↳ but leafs
do not need
add method
(could provide
empty body)

Other considerations

- Is the order of accessing the children important? *- iterator?*
- Should the references to the parent be maintained from the children?
should children point to the parent
- Should a child be allowed to be added to more than one component?


Object Collaboration

```
public class CompositeShape implements Shape
{
    private List<Shape> aElements = new ArrayList<>();

    @Override
    public void changeColor(Color pColor){
        for(Shape shape : aElements)
        {
            shape.changeColor(pColor);
        }
    }
}
```

The use of composition implies that we are designing how objects collaborate with each other, through methods calls.

Modeling object call sequences?




Objective


- Design Principle:
Divide and Conquer
- Programming mechanism:
Aggregation and Delegation
- Design Techniques:
Sequence Diagram
- Patterns and Anti-patterns:
Composite Pattern, Decorator Pattern, God class



Sequence Diagram



Activity 3: Attach additional responsibility dynamically to **changeColor** of **Line**?



Remember the previous color of the line before changing.


```
public class MemoryLine implements Shape
{
    private int x_start;
    private int y_start;
    private int x_end;
    private int y_end;
    private Color aColor;
    private Color aPreviousColor;

    @Override
    public void changeColor(Color pColor)
    {
        aPreviousColor = aColor;
        aColor = pColor;
    }
}
```

Specialized Class, hard to extend

Cannot turn responsibility on and off at runtime

Other design options?

Separate the essential and additional state and behavior

```
public class MemoryLine implements Shape
```

```
{
```

```
    private int x_start;
```

```
    private int y_start;
```

```
    private int x_end;
```

```
    private int y_end;
```

```
    private Color aColor;
```

```
    private Color aPreviousColor;
```

```
    ChangeColor();
```

```
}
```

Skin Versus Gut

functionalities
that don't change
fundamentals

performing
essential
things

Separate the essential and additional state and behavior

```
public class MemoryLine implements Shape
{
```

```
    private Line aLine;
```

← composite of gvt

1. Delegate the original request

```
    private Color aPreviousColor;
```

2. Implement additional feature

```
    @Override
```

```
    public void changeColor(Color pColor)
```

```
    {
```

```
        aPreviousColor = aLine.getColor();
```

```
        aLine.chageColor(pColor);
```


```
    }
```

```
}
```

← additional stuff

↳ delegated to gvt object


Objective

- Design Principle:
Divide and Conquer
 - Programming mechanism:
Aggregation and Delegation
 - Design Techniques:
Sequence Diagram
 - Patterns and Anti-patterns:
Composite Pattern, Decorator Pattern, God class
- 

Decorator Pattern

- Intent:
 - Attach additional responsibilities to an object dynamically. Decorators provide a flexible alternative to subclassing for extending functionality.
- Participants:
 - Primitive
 - Declares the interface for objects that can have responsibilities added to them dynamically*
 - Leaf
 - Defines the class to which additional responsibilities can be attached.*
 - Decorator
 - Maintains a reference to the primitive and defines the interface that confirms the primitive's interface

Similar to
composite
pattern




Adding functionality
to a single shape
- could pass in a composite to
decorate more than one


```
public class BlinkDecorator implements Shape
{
    .....
    @Override
    public void move(int pX, int pY)
    {
        aShape.move(pX, pY);
        this.blink(aShape);
    }
}
```


Activity 4

- Draw the object and sequence diagram when executing the last line of the following client code.

```
Shape line = new Line(3,3,10,10); //start x, start y, end x, end y
Shape memorizingLine = new MemorizingColorDecorator(line);
Shape blinkMemorizingLine = new BlinkDecorator(memorizingLine);
blinkMemorizingLine.move(15, 15);
```





Identity of decorator and decorated object


```
Shape line = new Line(3,3,10,10); //start x, start y, end x, end y
Shape memorizingLine = new MemorizingColorDecorator(line);
Shape blinkMemorizingLine = new BlinkDecorator(memorizingLine);
blinkMemorizingLine.move(15, 15);
```

```
System.out.println(line == blinkMemorizingLine); // true or false?
```

Decorated object identity lost

Combining Decorator and Composite?

all implement shape



decorators
can
decorate
leaves
or/and
composites

Combining Decorator and Composite

- Allow decorating behaviors of the composite, e.g., blinking the group of shapes.

Objective

- Design Principle:

Divide and Conquer

- Programming mechanism:

Aggregation and Delegation

- Design Techniques:

Sequence Diagram

- Patterns and Anti-patterns:

Composite Pattern, Decorator Pattern, God class




See M6-b


Manage Complexity -- Divide and conquer

- Modularization

- Decomposable




- Composable




Purpose 1

- Aggregation: Representation of collections



Purpose 2


- Delegation: Redirect duties



GameModel in Solitaire

13 piles of cards?

God Class



The elements are both the component, and also entities providing services.

Class Diagram

