



COMP 307
Principles
of Web
Development

MCGILL UNIVERSITY

COMP 307

Principles of Web Development

Lecture 10

Unit 3 – Frontend Design

Dynamic Website (Part A)

Contents

Elements
Environments



Class Outline

- Elements of responsive design
- Responsive vs Liquid
- DIY Methods

Contents

Elements
Environments



Readings

- Full Stack Developer
 - Chapters 4, 6 and 8
- Internet Resources
 - https://www.w3schools.com/html/html_responsive.asp
 - <https://www.toptal.com/designers/responsive/responsive-design-best-practices>



What are Dynamic Websites?

- **Two Forms**
 - Responsive Design
How should the layout of the website change for different types of screens or for windows that vary in size?
(Part A)
 - Generated Content Design
Software that automatically creates webpages programmatically.
(Part B)

This lecture focuses on Responsive Design.



COMP 307
Principles
of Web
Development

Elements of responsive design

Dynamic Website (Part A)

Contents

Elements
Environments



What is Responsive Design?

- Using HTML, CSS and JS to automatically resize and reformat a website to look good on any device and window size
 - PC
 - Mobile
 - Tablet
 - Other specialty device

This is different from “interactive web pages”, which respond to events, like mouseover.



What is Responsive Design?

- Responsive Design comes in two forms:
 - Responsive Design Proper
Using the concept of a **viewport** to classify different screen sizes and attach each classification to a custom layout. **Benefits:** Exactly what you want. **Drawbacks:** More coding.
 - Liquid Design
Using the **natural** reorganization flow of the browser (or library) to automatically cascade the webpage elements following a strategy. **Benefits:** Very little coding. **Drawbacks:** May not result in what I wanted.



COMP 307
Principles
of Web
Development

Liquid Layout



Auto Scaling

Using percentages in CSS:

```
<style>
```

```
body {  
    font-family: sans-serif; line-height: 1.5; padding: 0 16px;  
}  
  
article {  
    width: 66%;  
    float: left;  
}  
  
aside {  
    width: 33%;  
    float: right;  
}
```

When in a row, important to
sum to 100%

```
</style>
```



Using percentages

In HTML the % value permits the tag to **auto adjust its size**:

- ``
 - **Infinite scaling** in both width and height based on viewport limits
- ``
 - Height **maxes out at image's pixel height**



Auto Scaling

See Example 1 & 2 Liquid

Let's break this down



COMP 307
Principles
of Web
Development

Basics of Responsive



Define the “viewport”

Replaces browser default behavior with
device specifications:

```
<meta name      = "viewport"  
      content    = "width=device-width, initial-scale = 1.0">
```

- width = readjusts max width to be device screen resolution
- initial-scale = zoom



“vw” = Viewport Width

Define sizes based on the viewport:

```
<h1 style="font-size: 10vw">Hello World</h1>
```

Automatically scales

1vw = 1% viewport width



The Media Query

(Entire webpage)

Define multiple style sheets depending on the screen size:

```
<style>
  .left, .right {
    float: left;
    width: 20%; /* The width is 20%, by default */
  }

  .main {
    float: left;
    width: 60%; /* The width is 60%, by default */
  }

  /* Use a media query to add a breakpoint at 800px: */
  @media screen and (max-width: 800px) {
    .left, .main, .right {
      width: 100%;
      /* The width is 100%, when the viewport is 800px or smaller */
    }
  }
</style>
```

default

McGill



<picture> tag media control

(Micro Control)

Permits you to define image sizes for different screen resolutions:

```
<html><body>
  <picture>

    <source media="(min-width:800px)" srcset="img_pink_flowers.jpg">

    <source media="(min-width:600px)" srcset="img_white_flowers.jpg">

  </picture>
</body></html>
```

- Orange flowers below 600px
- White flowers below 800px
- Pink flower above 800px
- Can specify max-width as well



<video> tag media control

(Micro Control)

Permits you to define video sizes for different screen resolutions:

```
<html><head>
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<style>
  video {
    max-width: 100%; // compare with width: 100%;
    height: auto;
  }
</style>
</head>
<body>
  <video width="400" controls>
    <source src="mov_bbb.mp4" type="video/mp4">
    <source src="mov_bbb.ogv" type="video/ogg">
    Your browser does not support HTML5 video.
  </video>
</body></html>
```

<https://developer.mozilla.org/en-US/docs/Web/HTML/Element/video>



Examples

https://www.w3schools.com/html/tryit.asp?filename=tryhtml_responsive_media_query3

https://www.w3schools.com/howto/tryit.asp?filename=tryhow_css_sidebar_responsive

Let's break this down



Other useful examples

- https://www.w3schools.com/css/tryit.asp?filename=tryresponsive_mediaquery_breakpoints
Exploring Media Query Sizes
- https://www.w3schools.com/css/tryit.asp?filename=trycss_mediaqueries_hide
Hiding elements on smaller screens
- https://www.w3schools.com/css/tryit.asp?filename=trycss_mediaqueries_fontsize
Changing the font size on smaller screens



JS Nav Bar Example

https://www.w3schools.com/howto/tryit.asp?filename=tryhow_js_topnav

Let's break this down



COMP 307
Principles
of Web
Development

CSS Grid View

Dynamic Website (Part A)


Contents

Elements
Bootstrap



What is Grid View

- A technique of laying out your webpage in a way that is flexible in relation to screen sizes
 - Design your page using the 12-column technique



Notice there
are 12
columns in
this page.





Steps to create a Grid View

1. Make sure **all measurements included**

```
* { box-sizing: border-box; }
```

2. **Define the 12 columns** ($100\% / 12 = ?$)

Classes:

```
.col-1 {width: 8.33%;}  
.col-2 {width: 16.66%;}  
.col-3 {width: 25%;}  
.col-4 {width: 33.33%;}  
.col-5 {width: 41.66%;}  
.col-6 {width: 50%;}  
.col-7 {width: 58.33%;}  
.col-8 {width: 66.66%;}  
.col-9 {width: 75%;}  
.col-10 {width: 83.33%;}  
.col-11 {width: 91.66%;}  
.col-12 {width: 100%;}
```

Wrap each row in a
<div class="">

3. The 12 columns need to float freely

```
[class*="col-"] {float: left; padding: 15px; border: 1px solid red;}
```

4. Since floating left can overlap...

```
.row::after {content: ""; clear: both; display: table;}
```



Example

https://www.w3schools.com/css/tryit.asp?filename=tryresponsive_col-s

Let's break this down



Question

Using Grid View, create a webpage with:

- A header
- 4 columns for desktop
- 2 columns for tablet
- 1 column for phone
- A footer



Prepare for Next Class

- Assignments
 - Mini 5 given
 - Mini 4 due tonight
- Lab B
 - Lab B out Thursday, but TA will cover it after the break
- Do on your own
 - Try to build a simple page with CSS Grid from scratch

Contents