



Port assignments for FC switches when using ONTAP 9.0

ONTAP MetroCluster

aherbin, Megan Bock, netapp-ivanad, netapp-martyh
April 16, 2021

This PDF was generated from https://docs.netapp.com/us-en/ontap-metrocluster/maintain/concept_port_assignments_for_fc_switches_when_using_ontap_9_0.html on April 28, 2021. Always check docs.netapp.com for the latest.

Table of Contents

Port assignments for FC switches when using ONTAP 9.0	1
Overall cabling guidelines	1
Brocade port usage for controller connections in an eight-node MetroCluster configuration running ONTAP 9.0	1
Brocade port usage for FC-to-SAS bridge connections in an eight-node MetroCluster configuration running ONTAP 9.0	1
Brocade port usage for ISLs in an eight-node MetroCluster configuration running ONTAP 9.0	2
Brocade port usage for controllers in a four-node MetroCluster configuration running ONTAP 9.0	2
Brocade port usage for bridges in a four-node MetroCluster configuration running ONTAP 9.0	2
Brocade port usage for ISLs in a four-node MetroCluster configuration running ONTAP 9.0	2
Brocade port usage for controllers in a two-node MetroCluster configuration running ONTAP 9.0	2
Brocade port usage for bridges in a two-node MetroCluster configuration running ONTAP 9.0	3
Brocade port usage for ISLs in a two-node MetroCluster configuration running ONTAP 9.0	3
Cisco port usage for controllers in an eight-node MetroCluster configuration running ONTAP 9.0	3
Cisco port usage for FC-to-SAS bridges in an eight-node MetroCluster configuration running ONTAP 9.0 ..	3
Cisco port usage for ISLs in an eight-node MetroCluster configuration running ONTAP 9.0	4
Cisco port usage for controllers in a four-node MetroCluster configuration	4
Cisco port usage for FC-to-SAS bridges in a four-node MetroCluster configuration running ONTAP 9.0	4
Cisco 9148 and 9148S port usage for ISLs on a four-node MetroCluster configuration running ONTAP 9.0	4
Cisco 9250i port usage for ISLs on a four-node MetroCluster configuration running ONTAP 9.0	5
Cisco port usage for controllers in a two-node MetroCluster configuration	5
Cisco port usage for FC-to-SAS bridges in a two-node MetroCluster configuration running ONTAP 9.0	5
Cisco 9148 or 9148S port usage for ISLs on a two-node MetroCluster configuration running ONTAP 9.0 ...	5
Cisco 9250i port usage for ISLs on a two-node MetroCluster configuration running ONTAP 9.0	5

Port assignments for FC switches when using ONTAP 9.0

You need to verify that you are using the specified port assignments when you cable the FC switches. The port assignments are different between ONTAP 9.0 and later versions of ONTAP.

Ports that are not used for attaching initiator ports, FC-VI ports, or ISLs can be reconfigured to act as storage ports. However, if the supported RCFs are being used, the zoning must be changed accordingly.

If the supported RCF files are used, ISL ports may not connect to the same ports shown here and may need to be reconfigured manually.

Overall cabling guidelines

You should be aware of the following guidelines when using the cabling tables:

- The Brocade and Cisco switches use different port numbering:
 - On Brocade switches, the first port is numbered 0.
 - On Cisco switches, the first port is numbered 1.
- The cabling is the same for each FC switch in the switch fabric.
- AFF A300 and FAS8200 storage systems can be ordered with one of two options for FC-VI connectivity:
 - Onboard ports 0e and 0f configured in FC-VI mode.
 - Ports 1a and 1b on an FC-VI card in slot 1.

Brocade port usage for controller connections in an eight-node MetroCluster configuration running ONTAP 9.0

The cabling is the same for each FC switch in the switch fabric.

The following table shows controller port usage on Brocade models Brocade 6505, 6510, or DCX 8510-8:

Unresolved directive in <stdin> - include::_include/mc_8n_fc_cabling_brocade_6505_6510_dcx8510-8_90.csv[]

Brocade port usage for FC-to-SAS bridge connections in an eight-node MetroCluster configuration running ONTAP 9.0

The following table shows bridge port usage when using FibreBridge 7500 bridges:

Unresolved directive in <stdin> - include::_include/mc_8n_fc_cabling_brocade_7500N_90.csv[]

The following table shows bridge port usage when using FibreBridge 6500 bridges with Brocade 6505, 6510, or DCX 8510-8 switches:

Unresolved directive in <stdin> - include::_include/mc_8n_fc_cabling_brocade_6500N_90.csv[]

Brocade port usage for ISLs in an eight-node MetroCluster configuration running ONTAP 9.0

The following table shows ISL port usage for Brocade 6505, 6510, or DCX 8510-8 switches:

Unresolved directive in <stdin> - include::_include/mc_8n_fc_cabling_brocade_isls_90.csv[]

Brocade port usage for controllers in a four-node MetroCluster configuration running ONTAP 9.0

The cabling is the same for each FC switch in the switch fabric. The following table shows usage for the Brocade 6505, 6510, and DCX 8510-8 switches.

Unresolved directive in <stdin> - include::_include/mc_4n_fc_cabling_brocade_6505_6510_dcx8510-8_90.csv[]

Brocade port usage for bridges in a four-node MetroCluster configuration running ONTAP 9.0

The cabling is the same for each FC switch in the switch fabric.

The following table shows bridge port usage up to port 17 when using FibreBridge 7500 bridges. Additional bridges can be cabled to ports 18 through 23.

Unresolved directive in <stdin> - include::_include/mc_4n_fc_cabling_brocade_7500N_90.csv[]

The following table shows bridge port usage when using FibreBridge 6500 bridges:

Unresolved directive in <stdin> - include::_include/mc_4n_fc_cabling_brocade_6500N_90.csv[]

Brocade port usage for ISLs in a four-node MetroCluster configuration running ONTAP 9.0

The following table shows ISL port usage:

Unresolved directive in <stdin> - include::_include/mc_4n_fc_cabling_brocade_isls_90.csv[]

Brocade port usage for controllers in a two-node MetroCluster configuration running ONTAP 9.0

The cabling is the same for each FC switch in the switch fabric. The following table shows the cabling for Brocade 6505, 6510, and DCX 8510-8 switches.

Unresolved directive in <stdin> - include::_include/mc_2n_fc_cabling_brocade_6505_6510_dcx8510-8_90.csv[]

Brocade port usage for bridges in a two-node MetroCluster configuration running ONTAP 9.0

The cabling is the same for each FC switch in the switch fabric.

The following table shows bridge port usage up to port 17 when using FibreBridge 7500 bridges with Brocade 6505, 6510, and DCX 8510-8 switches. Additional bridges can be cabled to ports 18 through 23.

Unresolved directive in <stdin> - include::_include/mc_2n_fc_cabling_brocade_7500N_90.csv[]

The following table shows bridge port usage when using FibreBridge 6500 bridges with Brocade 6505, 6510, and DCX 8510-8 switches:

Unresolved directive in <stdin> - include::_include/mc_2n_fc_cabling_brocade_6500N_90.csv[]

Brocade port usage for ISLs in a two-node MetroCluster configuration running ONTAP 9.0

The following table shows ISL port usage for Brocade 6505, 6510, and DCX 8510-8 switches:

Unresolved directive in <stdin> - include::_include/mc_2n_fc_cabling_brocade_isls_90.csv[]

Cisco port usage for controllers in an eight-node MetroCluster configuration running ONTAP 9.0

The following table shows controller port usage on Cisco 9148 and 9148S switches:

Unresolved directive in <stdin> - include::_include/mc_8n_fc_cabling_cisco_9148_90.csv[]

Cisco port usage for FC-to-SAS bridges in an eight-node MetroCluster configuration running ONTAP 9.0

The following table shows bridge port usage up to port 23 when using FibreBridge 7500 bridges when using Cisco 9148 or 9148S switches. Additional bridges can be attached using ports 25 through 48.

Unresolved directive in <stdin> - include::_include/mc_8n_fc_cabling_cisco_7500N_90.csv[]

Additional bridges can be attached using ports 25 through 48 following the same pattern.

The following table shows bridge port usage up to port 23 when using FibreBridge 6500 bridges with Cisco 9148 or 9148S switches. Additional bridges can be attached using ports 25-48.

Unresolved directive in <stdin> - include::_include/mc_8n_fc_cabling_cisco_6500N_90.csv[]

Additional bridges can be attached using ports 25 through 48 following the same pattern.

Cisco port usage for ISLs in an eight-node MetroCluster configuration running ONTAP 9.0

The following table shows ISL port usage for Cisco 9148 and 9148S switches:

Unresolved directive in <stdin> - include::_include/mc_8n_fc_cabling_cisco_isls_90.csv[]

Cisco port usage for controllers in a four-node MetroCluster configuration

The cabling is the same for each FC switch in the switch fabric.

The following table shows controller port usage on Cisco 9148, 9148S, and 9250i switches:

Unresolved directive in <stdin> - include::_include/mc_4n_fc_cabling_cisco_9148_90.csv[]

Cisco port usage for FC-to-SAS bridges in a four-node MetroCluster configuration running ONTAP 9.0

The following table shows bridge port usage up to port 14 when using FibreBridge 7500 bridges with Cisco 9148, 9148S, or 9250i switches. Additional bridges can be attached to ports 15 through 32 following the same pattern.

Unresolved directive in <stdin> - include::_include/mc_4n_fc_cabling_cisco_7500N_90.csv[]

The following table shows bridge port usage when using FibreBridge 6500 bridges up to port 14 on Cisco 9148, 9148S, or 9250i switches. Additional bridges can be attached to ports 15 through 32 following the same pattern.

Unresolved directive in <stdin> - include::_include/mc_4n_fc_cabling_cisco_6500N_90.csv[]

Additional bridges can be attached to ports 15 through 32 following the same pattern.

Cisco 9148 and 9148S port usage for ISLs on a four-node MetroCluster configuration running ONTAP 9.0

The cabling is the same for each FC switch in the switch fabric.

The following table shows ISL port usage for Cisco 9148 and 9148S switches:

Unresolved directive in <stdin> - include::_include/mc_4n_fc_cabling_cisco_isls_90.csv[]

Cisco 9250i port usage for ISLs on a four-node MetroCluster configuration running ONTAP 9.0

The Cisco 9250i switch uses the FCIP ports for the ISL.

Ports 40 through 48 are 10 GbE ports and are not used in the MetroCluster configuration.

Cisco port usage for controllers in a two-node MetroCluster configuration

The cabling is the same for each FC switch in the switch fabric.

The following table shows controller port usage on Cisco 9148, 9148S, and 9250i switches:

```
Unresolved directive in <stdin> - include::_include/mc_2n_fc_cabling_cisco_9148O_9250i_90.csv[]
```

Cisco port usage for FC-to-SAS bridges in a two-node MetroCluster configuration running ONTAP 9.0

The following table shows bridge port usage up to port 14 when using FibreBridge 7500 bridges with Cisco 9148, 9148S, and 9250i switches. Additional bridges can be attached to ports 15 through 32 following the same pattern.

```
Unresolved directive in <stdin> - include::_include/mc_2n_fc_cabling_cisco_7500N_90.csv[]
```

The following table shows bridge port usage when using FibreBridge 6500 bridges up to port 14 on Cisco 9148, 9148S, or 9250i switches. Additional bridges can be attached to ports 15 through 32 following the same pattern.

```
Unresolved directive in <stdin> - include::_include/mc_2n_fc_cabling_cisco_6500N_90.csv[]
```

Additional bridges can be attached to ports 15 through 32 following the same pattern.

Cisco 9148 or 9148S port usage for ISLs on a two-node MetroCluster configuration running ONTAP 9.0

The cabling is the same for each FC switch in the switch fabric.

The following table shows ISL port usage for Cisco 9148 or 9148S switches:

```
Unresolved directive in <stdin> - include::_include/mc_2n_fc_cabling_cisco_isls_90.csv[]
```

Cisco 9250i port usage for ISLs on a two-node MetroCluster configuration running ONTAP 9.0

The Cisco 9250i switch uses the FCIP ports for the ISL.

Ports 40 through 48 are 10 GbE ports and are not used in the MetroCluster configuration.

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.