

University of Central Florida
Department of Computer Science
COP 3402: System Software
Summer 2018

Homework #3 (Parser- Code Generator)

Due on July 14th, 2018 by 11:59 p.m.

This is a team project (max. two people per team)

REQUIRMENT:

All assignments must compile and run on the Eustis server. Please see course website for details concerning use of Eustis.

Objective:

In this assignment, you must implement a Recursive Descent Parser and an Intermediate Code Generator for tiny PL/0. In addition, you must create a compiler driver to combine all of the compiler parts into one single program.

Your compiler driver must support the following compiler directives:

- l : print the list of lexemes/tokens (scanner output) to the screen
- a : print the generated assembly code (parser/codegen output) to the screen
- v : print virtual machine execution trace (virtual machine output) to the screen

Example commands:

- | | |
|---------------------------------|--|
| <code>./compile -l -a -v</code> | Print all types of output to the console |
| <code>./compile -v</code> | Print only the VM execution trace to the console |
| <code>./compile</code> | Print nothing to the console except for “in” and “out” |

Note: You may want to also print all forms of output to a single output file in order to avoid losing points on the other requirements if your implementation of compiler directives does not work.

Example of a program written in PL/0:

```
var x, w;  
begin  
  x:= 4;  
  in w;  
  if w > x then  
    w:= w + 1  
  else  
    w:= x;  
  out w;  
end
```

Component Descriptions:

The **compiler driver** is a program that manages the parts of the compiler. It must handle the input, output, and execution of the Scanner (HW2), the Parser (HW3), the Intermediate Code Generator (HW3) and the Virtual Machine (HW1).

The **Parser** is a program that reads in the output of the Scanner (HW2) and parses the lexemes (tokens). It must be capable of reading in the tokens produced by your Scanner (HW2) and produce, as output, a message that states whether the PL/0 program is well-formed (syntactically correct) if it follows the grammar rules in Appendix B. Otherwise, if the program does not follow the grammar, a message indicating the type of error present must be printed. A list of the errors to be considered can be found in Appendix C. In addition, the Parser must fill out the Symbol Table, which contains all of the variables, procedure and constants names within the PL/0 program. See Appendix E for more information regarding the Symbol Table. If the program is syntactically correct and the Symbol Table is created without error, the execution of the compiler driver continues with intermediate code generation.

The **Intermediate Code Generator** is a program that takes, as input, the output from the Parser, i.e. the Symbol Table and parsed code. As output, it produces the assembly language for your Virtual Machine (HW1). This functionality may be interleaved with the Parser functionality (i.e. generate assembly code as you parse the token list). Once the code

has been generated for your Virtual Machine, the execution of the compiler driver continues by executing the generated assembly code on your Virtual Machine

Submission Instructions:

1.- Submit via WebCourses:

1. Source code of the tiny- PL/0 compiler.
2. A text file with instructions on how to use your program entitled readme.txt. **(This is important. If your build instructions are not clear enough to build the code, we will not be able to grade the assignment)**
3. A text file composed of the input file to your Scanner and the output of your Parser to demonstrate a correctly formed tiny- PL/0 program. The Parser output should indicate the program is syntactically correct. Following the statement that the program is syntactically correct, the text file should contain the generated code from your intermediate code generator and the stack output from your Virtual Machine running your code.
4. A text file composed of the input file to your Scanner and the output of your Parser to demonstrate all possible errors. This may require many runs and the Parser output should indicate which error is being identified.
5. All files should be compressed into a single .zip format.
6. Late assignments will not be accepted.
7. Name your program: hw3tc.c

Appendix A:

Traces of Execution:

Example 1, if the input is:

```
var x, y;  
begin  
  x := y + 56;  
end.
```

The output should look like:

1.- A print out of the token (internal representation) file:

```
29 2 x 17 2 y 18 21 2 x 20 2 y 4 3 56 18 22 19
```

And its symbolic representation:

```
varsym identsym x commasy identsym y semicolon beginsym identsym x  
  becomessym identsym y plussym numbersym 56 semicolonsym endsym  
  periodsym
```

2.- Print out the message “ No errors, program is syntactically correct”

3.- Print out the generated code

4.- Run the program on the virtual machine (HW1)

Example 2, if the input is:

```
var x, y;  
begin  
  x := y + 56;  
end           ← ( notice period expected after the “end” reserved word)
```

The output should look like:

1.- A print out of the token (internal representation) file:

```
29 2 x 17 2 y 18 21 2 x 20 2 y 4 3 56 18 22
```

And its symbolic representation:

```
intsym identsym x commasym identsym y semicolonsym beginsym identsym x  
    becomessym identsym y plussym numbersym 56 semicolonsym endsym
```

2.- Print the message “Error number xxx, period expected”

```
var x, y;  
begin  
    x := y + 56;  
end  
    ***** Error number xxx, period expected
```

Appendix B:

EBNF of tiny PL/0:

program ::= block "." .
block ::= const-declaration var-declaration statement.
constdeclaration ::= ["const" ident "=" number {"," ident "=" number} ";"].
var-declaration ::= ["var" ident {"," ident} ";"].
statement ::= [ident ":" expression
 | "begin" statement { ";" statement } "end"
 | "if" condition "then" statement
 | "while" condition "do" statement
 | "read" ident
 | "write" ident
 | e] .
condition ::= "odd" expression
 | expression rel-op expression.
rel-op ::= "=" | "<" | "<=" | ">" | ">=" .
expression ::= ["+" | "-"] term { ("+" | "-") term } .
term ::= factor { ("*" | "/") factor } .
factor ::= ident | number | "(" expression ")".
number ::= digit {digit} .
ident ::= letter {letter | digit} .
digit ::= "0" | "1" | "2" | "3" | "4" | "5" | "6" | "7" | "8" | "9".
letter ::= "a" | "b" | ... | "y" | "z" | "A" | "B" | ... | "Y" | "Z".

Based on Wirth's definition for EBNF we have the following rule:

[] means an optional item.

{ } means repeat 0 or more times.

Terminal symbols are enclosed in quote marks.

A period is used to indicate the end of the definition of a syntactic class.

Appendix C:

Error messages for the tiny PL/0 Parser:

1. Use = instead of :=.
2. = must be followed by a number.
3. Identifier must be followed by =.
4. **const**, **var**, **procedure** must be followed by identifier.
5. Semicolon or comma missing.
6. Incorrect symbol after procedure declaration.
7. Statement expected.
8. Incorrect symbol after statement part in block.
9. Period expected.
10. Semicolon between statements missing.
11. Undeclared identifier.
12. Assignment to constant or procedure is not allowed.
13. Assignment operator expected.
14. **call** must be followed by an identifier.
15. Call of a constant or variable is meaningless.
16. **then** expected.
17. Semicolon or } expected.
18. **do** expected.
19. Incorrect symbol following statement.
20. Relational operator expected.
21. Expression must not contain a procedure identifier.
22. Right parenthesis missing.
23. The preceding factor cannot begin with this symbol.
24. An expression cannot begin with this symbol.
25. This number is too large.
26. Identifier too long.
27. Invalid symbol.

Note:

1. Identifiers: Maximum 11 characters.
2. Numbers: Maximum 5 digits.
3. Invalid symbols are not accepted (or example % does not belong to PL/0 grammar).
4. Comments and invisible characters must be ignored and not tokenized.

Note: Not all of these error messages may be used, and you may choose to create some error messages of your own to more accurately represent certain situations.

Appendix D:

Recursive Descent Parser for a PL/0 like programming language in pseudo code:

As follows you will find the pseudo code for a PL/0 like parser. This pseudo code will help you out to develop your parser and intermediate code generator for tiny PL/0:

```
procedure PROGRAM;
begin
  GET(TOKEN);
  BLOCK;
  if TOKEN != "periodsym" then ERROR
end;

procedure BLOCK;
begin
  if TOKEN = "constsym" then begin
    repeat
      GET(TOKEN);
      if TOKEN != "identsym" then ERROR;
      GET(TOKEN);
      if TOKEN != "eqsym" then ERROR;
      GET(TOKEN);
      if TOKEN != NUMBER then ERROR;
      GET(TOKEN)
    until TOKEN != "commasym";
    if TOKEN != "semicolomsym" then ERROR;
    GET(TOKEN)
  end;
  if TOKEN = "intsym" then begin
    repeat
      GET(TOKEN);
      if TOKEN != "identsym" then ERROR;
      GET(TOKEN)
    until TOKEN != "commasym";
    if TOKEN != "semicolomsym" then ERROR;
    GET(TOKEN)
  end;
  while TOKEN = "procsym" do begin
    GET(TOKEN);
    if TOKEN != "identsym" then ERROR;
```

```

    GET(TOKEN);
    if TOKEN != "semicolon" then ERROR;
    GET(TOKEN);
    BLOCK;
    if TOKEN != "semicolon" then ERROR;
    GET(TOKEN);
end;
STATEMENT
end;

```

```

procedure STATEMENT;
begin
    if TOKEN = "ident" then begin
        GET(TOKEN);
        if TOKEN != "becomes" then ERROR;
        GET(TOKEN);
        EXPRESSION
    end
    else if TOKEN = "call" then begin
        GET(TOKEN);
        if TOKEN != "ident" then ERROR;
        GET(TOKEN);
    end
    else if TOKEN = "begin" then begin
        GET(TOKEN);
        STATEMENT;
        while TOKEN = "semicolon" do begin
            GET(TOKEN);
            STATEMENT
        end;
        if TOKEN != "end" then ERROR;

        GET(TOKEN);
    end
    else if TOKEN = "if" then begin
        GET(TOKEN);
        CONDITION;
        if TOKEN != "then" then ERROR;
        GET(TOKEN);
        STATEMENT
    end
    else if TOKEN = "while" then begin
        GET(TOKEN);
        CONDITION;
        if TOKEN != "do" then ERROR;

```

```

        GET(TOKEN);
        STATEMENT
    end
end;

procedure CONDITION;
begin
    if TOKEN = "oddsym" then begin
        GET(TOKEN);
        EXPRESSION
    else begin
        EXPRESSION;
        if TOKEN != RELATION then ERROR;
        GET(TOKEN);
        EXPRESSION
    end
end;

procedure EXPRESSION;
begin
    if TOKEN = "plussym" or "minussym" then GET(TOKEN);
    TERM;
    while TOKEN = "plussym" or "minussym" do begin
        GET(TOKEN);
        TERM
    end
end;

procedure TERM;
begin
    FACTOR;
    while TOKEN = "multsym" or "slashsym" do begin
        GET(TOKEN);
        FACTOR
    end
end;

procedure FACTOR;
begin
    if TOKEN = "identsym" then
        GET(TOKEN)
    else if TOKEN = NUMBER then
        GET(TOKEN)
    else if TOKEN = "(" then begin
        GET(TOKEN);

```

```
    EXPRESSION;  
    if TOKEN != ")" then ERROR;  
    GET(TOKEN)  
end  
else ERROR  
end;
```

Appendix E:

Symbol Table

Recommended data structure for the symbol.

```
typedef struct
{
    int kind;           // const = 1, var = 2, proc = 3
    char name[10];      // name up to 11 chars
    int val;            // number (ASCII value)
    int level;          // L level
    int addr;           // M address
    int mark;           // to indicate that code has been generated already for a block.
} symbol;
```

```
symbol_table[MAX_SYMBOL_TABLE_SIZE];
```

For constants, you must store kind, name and value.

For variables, you must store kind, name, L and M.

For procedures, you must store kind, name, L and M.

Appendix F:

To test your compiler we recommend testing as many programs as you need to generate all errors in the error list.

Grading Rubric:

Deduction	Description
-100	Does not compile on Eustis.
-100	Does not accept input filename from command line.
-100	If the compiler follows a different grammar. (procedure and else must not be implemented. Not even as a comment)
-15	Does not handle file i/o or resource errors gracefully.
-15	Crashes handling statements (-15 for each statement that is not handled).
-10	Crashes handling directive. (-10 for per directive)