

NAME: VEENA T.G.S ROLL NO: 225229145

step-1

```
import numpy as np
import matplotlib.pyplot as plt
%matplotlib inline
import keras
from keras.datasets import cifar10
from keras.utils import to_categorical
from keras.backend import categorical_crossentropy
from keras.models import Sequential
from keras.layers import Dense, Activation, Dropout, Flatten, Conv2D, MaxPooling2D
from keras.optimizers import RMSprop
from keras.preprocessing.image import ImageDataGenerator
```

step-2

```
(X_train, y_train), (X_test, y_test) = cifar10.load_data()
```

```
Downloading data from https://www.cs.toronto.edu/~kriz/cifar-10-python.tar.gz
170498071/170498071 [=====] - 3s 0us/step
```

```
print('Shape of X_train is {}'.format(X_train.shape))
print('Shape of X_test is {}'.format(X_test.shape))
print('Shape of y_train is {}'.format(y_train.shape))
print('Shape of y_test is {}'.format(y_test.shape))

Shape of X_train is (50000, 32, 32, 3)
Shape of X_test is (10000, 32, 32, 3)
Shape of y_train is (50000, 1)
Shape of y_test is (10000, 1)
```

step-3

```
num_classes = 10
y_train = to_categorical(y_train, num_classes)
y_test = to_categorical(y_test, num_classes)
```

step-4

```
X_train = X_train.astype('float32')
X_test = X_test.astype('float32')
X_train /= 255
X_test /= 255

print('Shape of one sample of X_train is {}'.format(X_train[37].shape))
print('Shape of one sample of y_train is {}'.format(y_train[37].shape))

Shape of one sample of X_train is (32, 32, 3)
Shape of one sample of y_train is (10,)
```

X_train[37]

```
array([[0.37254903, 0.4117647 , 0.49803922],
       [0.34509805, 0.38039216, 0.47058824],
       [0.3372549 , 0.3764706 , 0.4627451 ],
       ...,
       [0.39607844, 0.45490196, 0.5647059 ],
       [0.35686275, 0.42352942, 0.53333336],
       [0.4117647 , 0.4862745 , 0.6156863 ]],

       [[0.32156864, 0.3529412 , 0.43137255],
       [0.29411766, 0.3254902 , 0.40784314],
       [0.29803923, 0.32941177, 0.40784314],
       ...,
       [0.36862746, 0.4       , 0.48235294],
       [0.2       , 0.23921569, 0.3137255 ],
       [0.32941177, 0.38039216, 0.47843137]],

       [[0.3019608 , 0.33333334, 0.40392157],
       [0.2901961 , 0.31764707, 0.38431373],
       [0.2784314 , 0.30588236, 0.37254903],
       ...,
       [0.2784314 , 0.2901961 , 0.3372549 ],
```

```
[0.18431373, 0.20392157, 0.24705882],
[0.34509805, 0.37254903, 0.43529412]],

...,

[[0.38039216, 0.37254903, 0.28235295],
[0.36078432, 0.36078432, 0.27058825],
[0.38039216, 0.3647059 , 0.27450982],
...,
[0.3372549 , 0.35686275, 0.25490198],
[0.36862746, 0.38039216, 0.28235295],
[0.3529412 , 0.38039216, 0.2784314 ]],

[[0.37254903, 0.3529412 , 0.25490198],
[0.32941177, 0.3372549 , 0.23137255],
[0.34901962, 0.34901962, 0.24313726],
...,
[0.3764706 , 0.38039216, 0.29803923],
[0.4       , 0.3764706 , 0.3019608 ],
[0.38039216, 0.36862746, 0.28627452]],

[[0.35686275, 0.32941177, 0.24705882],
[0.3254902 , 0.31764707, 0.22352941],
[0.32156864, 0.31764707, 0.21568628],
...,
[0.39215687, 0.3764706 , 0.30588236],
[0.4117647 , 0.38039216, 0.3137255 ],
[0.42352942, 0.4       , 0.3254902 ]]], dtype=float32)

y_train[37]

array([0., 0., 0., 0., 0., 0., 0., 1., 0., 0.], dtype=float32)

model = Sequential()
model.add(Conv2D(32, (5,5), strides=(2,2), padding='same', input_shape=X_train.shape[1:]))
model.add(Activation('relu'))
model.add(Conv2D(32, (5,5), strides=(2,2)))
model.add(Activation('relu'))
model.add(MaxPooling2D(pool_size=(2,2)))
model.add(Dropout(0.25))
model.add(Flatten())
model.add(Dense(512))
model.add(Activation('relu'))
model.add(Dropout(0.5))
model.add(Dense(num_classes))
model.add(Activation('softmax'))
model.summary()

Model: "sequential"

```

Layer (type)	Output Shape	Param #
conv2d (Conv2D)	(None, 16, 16, 32)	2432
activation (Activation)	(None, 16, 16, 32)	0
conv2d_1 (Conv2D)	(None, 6, 6, 32)	25632
activation_1 (Activation)	(None, 6, 6, 32)	0
max_pooling2d (MaxPooling2D)	(None, 3, 3, 32)	0
dropout (Dropout)	(None, 3, 3, 32)	0
flatten (Flatten)	(None, 288)	0
dense (Dense)	(None, 512)	147968
activation_2 (Activation)	(None, 512)	0
dropout_1 (Dropout)	(None, 512)	0
dense_1 (Dense)	(None, 10)	5130
activation_3 (Activation)	(None, 10)	0

```

Total params: 181162 (707.66 KB)
Trainable params: 181162 (707.66 KB)
Non-trainable params: 0 (0.00 Byte)

```

step-5

```
X_train, X_val, y_train, y_val = train_test_split(X_train, y_train, test_size=0.2, random_state=42)
```

```
batch_size=32
```


```
opt = tf.keras.optimizers.RMSprop(learning_rate=0.0005)
```

```
model.compile(loss='categorical_crossentropy', optimizer=opt, metrics=['accuracy'])
```

```
history = model.fit(X_train, y_train, batch_size=32, epochs=15, verbose=2, validation_data=(X_val, y_val))
```

```
Epoch 1/15
1250/1250 - 30s - loss: 1.0626 - accuracy: 0.6371 - val_loss: 0.8827 - val_accuracy: 0.6938 - 30s/epoch - 24ms/step
Epoch 2/15
1250/1250 - 27s - loss: 1.0560 - accuracy: 0.6370 - val_loss: 0.9474 - val_accuracy: 0.6826 - 27s/epoch - 21ms/step
Epoch 3/15
1250/1250 - 25s - loss: 1.0527 - accuracy: 0.6409 - val_loss: 0.8871 - val_accuracy: 0.6928 - 25s/epoch - 20ms/step
Epoch 4/15
1250/1250 - 32s - loss: 1.0461 - accuracy: 0.6436 - val_loss: 0.9089 - val_accuracy: 0.6873 - 32s/epoch - 25ms/step
Epoch 5/15
1250/1250 - 27s - loss: 1.0442 - accuracy: 0.6425 - val_loss: 0.9362 - val_accuracy: 0.6807 - 27s/epoch - 22ms/step
Epoch 6/15
1250/1250 - 25s - loss: 1.0362 - accuracy: 0.6461 - val_loss: 0.9597 - val_accuracy: 0.6699 - 25s/epoch - 20ms/step
Epoch 7/15
1250/1250 - 26s - loss: 1.0316 - accuracy: 0.6508 - val_loss: 0.9582 - val_accuracy: 0.6707 - 26s/epoch - 20ms/step
Epoch 8/15
1250/1250 - 27s - loss: 1.0312 - accuracy: 0.6522 - val_loss: 0.9770 - val_accuracy: 0.6638 - 27s/epoch - 22ms/step
Epoch 9/15
1250/1250 - 26s - loss: 1.0369 - accuracy: 0.6498 - val_loss: 1.0392 - val_accuracy: 0.6416 - 26s/epoch - 21ms/step
Epoch 10/15
1250/1250 - 25s - loss: 1.0301 - accuracy: 0.6520 - val_loss: 1.0188 - val_accuracy: 0.6486 - 25s/epoch - 20ms/step
Epoch 11/15
1250/1250 - 26s - loss: 1.0307 - accuracy: 0.6533 - val_loss: 1.0006 - val_accuracy: 0.6639 - 26s/epoch - 21ms/step
Epoch 12/15
1250/1250 - 25s - loss: 1.0305 - accuracy: 0.6536 - val_loss: 0.9396 - val_accuracy: 0.6767 - 25s/epoch - 20ms/step
Epoch 13/15
1250/1250 - 25s - loss: 1.0335 - accuracy: 0.6493 - val_loss: 0.9873 - val_accuracy: 0.6629 - 25s/epoch - 20ms/step
Epoch 14/15
1250/1250 - 26s - loss: 1.0239 - accuracy: 0.6520 - val_loss: 0.9887 - val_accuracy: 0.6585 - 26s/epoch - 21ms/step
Epoch 15/15
1250/1250 - 25s - loss: 1.0286 - accuracy: 0.6535 - val_loss: 1.0001 - val_accuracy: 0.6636 - 25s/epoch - 20ms/step
```

```
fig = plt.figure(figsize=(20, 5))
fig.add_subplot(1,2,1)
plt.plot(history.history['loss'])
plt.plot(history.history['val_loss'])
plt.title('Model Loss')
plt.ylabel('loss')
plt.xlabel('epoch')
plt.legend(['train', 'validation'], loc='upper left')
fig.add_subplot(1,2,2)
plt.plot(history.history['accuracy'])
plt.plot(history.history['val_accuracy'])
plt.title('Model Accuracy')
plt.ylabel('accuracy')
plt.xlabel('epoch')
plt.legend(['train', 'validation'], loc='upper left')
plt.show()
```



step-6

```
model1 = Sequential()
model1.add(Conv2D(32, (5,5), strides=(2,2), padding='same', input_shape=X_train.shape[1:]))
model1.add(Activation('relu'))
model1.add(Conv2D(32, (5,5), strides=(2,2)))
model1.add(Activation('relu'))
model1.add(MaxPooling2D(pool_size=(2,2)))
model1.add(Dropout(0.25))
model1.add(Flatten())
model1.add(Dense(512))
model1.add(Activation('relu'))
model1.add(Dropout(0.5))
model1.add(Dense(num_classes))
model1.add(Activation('softmax'))
model1.summary()
```

Model: "sequential_1"

Layer (type)	Output Shape	Param #
conv2d_2 (Conv2D)	(None, 16, 16, 32)	2432
activation_4 (Activation)	(None, 16, 16, 32)	0
conv2d_3 (Conv2D)	(None, 6, 6, 32)	25632
activation_5 (Activation)	(None, 6, 6, 32)	0
max_pooling2d_1 (MaxPoolin g2D)	(None, 3, 3, 32)	0
dropout_2 (Dropout)	(None, 3, 3, 32)	0
flatten_1 (Flatten)	(None, 288)	0
dense_2 (Dense)	(None, 512)	147968
activation_6 (Activation)	(None, 512)	0
dropout_3 (Dropout)	(None, 512)	0
dense_3 (Dense)	(None, 10)	5130
activation_7 (Activation)	(None, 10)	0

=====
Total params: 181162 (707.66 KB)
Trainable params: 181162 (707.66 KB)
Non-trainable params: 0 (0.00 Byte)

step-7

```
model1 = Sequential()
model1.add(Conv2D(32, (5,5), strides=(2,2), padding='same', input_shape=X_train.shape[1:]))
model1.add(Activation('relu'))
model1.add(Conv2D(32, (5,5), strides=(2,2)))
model1.add(Activation('relu'))
model1.add(MaxPooling2D(pool_size=(2,2)))
model1.add(Dropout(0.25))
model1.add(Flatten())
model1.add(Dense(512))
model1.add(Activation('relu'))
model1.add(Dropout(0.5))
model1.add(Dense(num_classes))
model1.add(Activation('softmax'))
model1.summary()
```

Model: "sequential_2"

Layer (type)	Output Shape	Param #
conv2d_4 (Conv2D)	(None, 16, 16, 32)	2432
activation_8 (Activation)	(None, 16, 16, 32)	0
conv2d_5 (Conv2D)	(None, 6, 6, 32)	25632
activation_9 (Activation)	(None, 6, 6, 32)	0
max_pooling2d_2 (MaxPoolin g2D)	(None, 3, 3, 32)	0

dropout_4 (Dropout)	(None, 3, 3, 32)	0
flatten_2 (Flatten)	(None, 288)	0
dense_4 (Dense)	(None, 512)	147968
activation_10 (Activation)	(None, 512)	0
dropout_5 (Dropout)	(None, 512)	0
dense_5 (Dense)	(None, 10)	5130
activation_11 (Activation)	(None, 10)	0

=====
Total params: 181162 (707.66 KB)
Trainable params: 181162 (707.66 KB)
Non-trainable params: 0 (0.00 Byte)

Double-click (or enter) to edit

```
datagen = ImageDataGenerator(featurewise_center=False,  
samplewise_center=False,  
  
featurewise_std_normalization=False,  
samplewise_std_normalization=False,  
zca_whitening=False,  
rotation_range=0,  
width_shift_range=0.1,  
height_shift_range=0.1,  
horizontal_flip=True,  
vertical_flip=False)  
  
datagen.fit(X_train)  
  
batch_size=32  
opt = RMSprop(learning_rate=0.0005)  
model1.compile(loss='categorical_crossentropy', optimizer=opt, metrics=['accuracy'])
```