

# Swinging Monkeys

## Objective

The objective of this problem is to test the students' understanding on **Stack**.

## Problem Description

Monkeys like to swing from tree to tree. They can swing from one tree to another directly as long as there is no tree in between that is taller than or have the same height as either one of the two trees. For example, if there are 5 trees with heights 19m, 17m, 20m, 20m and 20m lining up in that order, then the monkey will be able to swing from one tree to the other as shown below:

1. from first tree to second tree
2. from first tree to third tree
3. from second tree to third tree
4. from third tree to fourth tree
5. from fourth tree to fifth tree

Tarzan, the king of jungle who is able to communicate with the monkeys, wants to test the monkeys to see if they know how to count the total number of pairs of trees that they can swing directly from one to the other. But he himself is not very good in counting. So he turns to you, the best Java programmer in the country, to write a program for getting the correct count for the trees in different parts of the jungle.

## Input

The first line contains  $N$ , the number of trees in the path. The next line contains  $N$  integers  $a_1 a_2 a_3 \dots a_N$ , where  $a_i$  represents the height of the  $i$ -th tree in the path,  $0 < a_i \leq 2^{31}$  and  $2 \leq N \leq 500,000$ .

## Output

The total number of pairs of trees which the monkeys can swing directly from one to the other with the given list of tree heights.

### Sample Input 1

```
4
3 4 1 2
```

### Sample Output 1

```
4
```

### Sample Input 2

```
5
19 17 20 20 20
```

### Sample Output 2

```
5
```

### Sample Input 3

4

12 21 21 12

### Sample Output 3

3

### Sample Explanation

Sample 1:

- (3, 4): from 1<sup>st</sup> tree, it can only swing to the 2<sup>nd</sup> tree directly but not all the other tree as the 2<sup>nd</sup> tree blocks it.
- (4, 1) and (4, 2): from the 2<sup>nd</sup> tree, it can swing directly to the 3<sup>rd</sup> and 4<sup>th</sup> tree directly.
- (1, 2): It can swing from the 3<sup>rd</sup> tree to the 4<sup>th</sup> tree.

Sample 2:

- (19, 17) and (19, 20): from 1<sup>st</sup> tree, it can swing directly to 2<sup>nd</sup> and 3<sup>rd</sup> tree but not the rest.
- (17, 20): from the 2<sup>nd</sup> tree, it can only swing to the 3<sup>rd</sup> tree but not the rest.
- (20, 20): from the 3<sup>rd</sup> tree, it can only swing to the 4<sup>th</sup> tree but not the 5<sup>th</sup>.
- (20, 20): from the 4<sup>th</sup> tree, it can swing to the 5<sup>th</sup> tree.

Sample 3:

- (12, 21): from 1<sup>st</sup> tree, it can only swing to the 2<sup>nd</sup> tree but not the rest.
- (21, 21): from the 2<sup>nd</sup> tree, it can swing to the 3<sup>rd</sup> tree but not the 4<sup>th</sup>.
- (21, 12): obvious.

### Note

- The results should be in long long range.
- An efficient program is required. You may try some given test cases to see if your program is fast enough.
- For example, if you check all the pairs to see if there is any tree in between them that will block the swing, it might be too slow to pass some of the test cases.
- You can improve the efficiency by using a stack.