

THE RADON TRANSFORM

ELIAS MINDLBERGER

ABSTRACT. This is an overview of a project for the subject "Wavelets - Functional Analytical Basics" in the summer semester of 2025 @ JKU Linz.

When a beam of X-Ray photons travels through a homogeneous material, the intensity of photons at the time of entering the material is high compared to the intensity at the moment of exit. This is described by the equation

$$I = I_0 e^{-\mu w}$$

where I_0 is the input intensity and I is the observed intensity after the beam passes the distance w through the material. The *attenuation* coefficient μ depends (among other things) on the density of the material. When the material is inhomogeneous, i.e. μ represents a varying density, the corresponding equation for the observed intensity becomes

$$I = I_0 \exp \left(- \int_L \mu(x, y) \, ds \right)$$

where L is the beam path parametrised by s . By moving the source of the photons around the material, one obtains a set of line integrals over the density μ and by taking logarithms, one obtains samples of Radon transforms where the d -dimensional Radon transform of an integrable function $f : \mathbb{R}^d \rightarrow \mathbb{R}$ is defined as

$$\mathbf{R} f(\sigma, \theta) \stackrel{\text{def}}{=} \int_{\langle x | \theta \rangle = \sigma} f(x) \, dx, \quad (\sigma, \theta) \in \mathbb{R} \times \mathbb{S}^{d-1}$$

where λ^{d-1} is the $(d-1)$ -dimensional Lebesgue measure.

Date: June 29, 2025.

Key words and phrases. Radon Transform, Wavelets.