

This is a companion notebook for the book [Deep Learning with Python, Second Edition](#). For readability, it only contains runnable code blocks and section titles, and omits everything else in the book: text paragraphs, figures, and pseudocode.

**If you want to be able to follow what's going on, I recommend reading the notebook side by side with your copy of the book.**

This notebook was generated for TensorFlow 2.6.

## ▼ Deep learning for timeseries

### Different kinds of timeseries tasks

## ▼ A temperature-forecasting example

```
!wget https://s3.amazonaws.com/keras-datasets/jena_climate_2009_2016.csv.zip
!unzip jena_climate_2009_2016.csv.zip
```

### Inspecting the data of the Jena weather dataset

```
import os
fname = os.path.join("jena_climate_2009_2016.csv")

with open(fname) as f:
    data = f.read()

lines = data.split("\n")
header = lines[0].split(",")
lines = lines[1:]
print(header)
print(len(lines))
```

### Parsing the data

```
import numpy as np
temperature = np.zeros((len(lines),))
raw_data = np.zeros((len(lines), len(header) - 1))
for i, line in enumerate(lines):
    values = [float(x) for x in line.split(",")[1:]]
    temperature[i] = values[1]
    raw_data[i, :] = values[2:]
```

## Plotting the temperature timeseries

```
from matplotlib import pyplot as plt
plt.plot(range(len(temperature)), temperature)
```

## Plotting the first 10 days of the temperature timeseries

```
plt.plot(range(1440), temperature[:1440])
```

## Computing the number of samples we'll use for each data split

```
num_train_samples = int(0.5 * len(raw_data))
num_val_samples = int(0.25 * len(raw_data))
num_test_samples = len(raw_data) - num_train_samples - num_val_samples
print("num_train_samples:", num_train_samples)
print("num_val_samples:", num_val_samples)
print("num_test_samples:", num_test_samples)
```

## ▼ Preparing the data

### Normalizing the data

```
mean = raw_data[:num_train_samples].mean(axis=0)
raw_data -= mean
std = raw_data[:num_train_samples].std(axis=0)
raw_data /= std
```

```
import numpy as np
from tensorflow import keras
int_sequence = np.arange(10)
dummy_dataset = keras.utils.timeseries_dataset_from_array(
    data=int_sequence[:-3],
    targets=int_sequence[3:],
    sequence_length=3,
    batch_size=2,
)

for inputs, targets in dummy_dataset:
    for i in range(inputs.shape[0]):
        print([int(x) for x in inputs[i]], int(targets[i]))
```

## Instantiating datasets for training, validation, and testing

```
sampling_rate = 6
```

```

sequence_length = 120
delay = sampling_rate * (sequence_length + 24 - 1)
batch_size = 256

train_dataset = keras.utils.timeseries_dataset_from_array(
    raw_data[:-delay],
    targets=temperature[delay:],
    sampling_rate=sampling_rate,
    sequence_length=sequence_length,
    shuffle=True,
    batch_size=batch_size,
    start_index=0,
    end_index=num_train_samples)

val_dataset = keras.utils.timeseries_dataset_from_array(
    raw_data[:-delay],
    targets=temperature[delay:],
    sampling_rate=sampling_rate,
    sequence_length=sequence_length,
    shuffle=True,
    batch_size=batch_size,
    start_index=num_train_samples,
    end_index=num_train_samples + num_val_samples)

test_dataset = keras.utils.timeseries_dataset_from_array(
    raw_data[:-delay],
    targets=temperature[delay:],
    sampling_rate=sampling_rate,
    sequence_length=sequence_length,
    shuffle=True,
    batch_size=batch_size,
    start_index=num_train_samples + num_val_samples)

```

## Inspecting the output of one of our datasets

```

for samples, targets in train_dataset:
    print("samples shape:", samples.shape)
    print("targets shape:", targets.shape)
    break

```

## ▼ A common-sense, non-machine-learning baseline

### Computing the common-sense baseline MAE

```

def evaluate_naive_method(dataset):
    total_abs_err = 0.
    samples_seen = 0
    for samples, targets in dataset:
        preds = samples[:, -1, 1] * std[1] + mean[1]
        total_abs_err += np.sum(np.abs(preds - targets))

```

```

        samples_seen += samples.shape[0]
    return total_abs_err / samples_seen

print(f"Validation MAE: {evaluate_naive_method(val_dataset):.2f}")
print(f"Test MAE: {evaluate_naive_method(test_dataset):.2f}")

```

## ▼ Let's try a basic machine-learning model

### Training and evaluating a densely connected model

```

from tensorflow import keras
from tensorflow.keras import layers

inputs = keras.Input(shape=(sequence_length, raw_data.shape[-1]))
x = layers.Flatten()(inputs)
x = layers.Dense(16, activation="relu")(x)
outputs = layers.Dense(1)(x)
model = keras.Model(inputs, outputs)

callbacks = [
    keras.callbacks.ModelCheckpoint("jena_dense.keras",
                                    save_best_only=True)
]
model.compile(optimizer="rmsprop", loss="mse", metrics=["mae"])
history = model.fit(train_dataset,
                    epochs=10,
                    validation_data=val_dataset,
                    callbacks=callbacks)

model = keras.models.load_model("jena_dense.keras")
print(f"Test MAE: {model.evaluate(test_dataset)[1]:.2f}")

```

### Plotting results

```

import matplotlib.pyplot as plt
loss = history.history["mae"]
val_loss = history.history["val_mae"]
epochs = range(1, len(loss) + 1)
plt.figure()
plt.plot(epochs, loss, "bo", label="Training MAE")
plt.plot(epochs, val_loss, "b", label="Validation MAE")
plt.title("Training and validation MAE")
plt.legend()
plt.show()

```

## ▼ Let's try a 1D convolutional model

```

inputs = keras.Input(shape=(sequence_length, raw_data.shape[-1]))

```

```

x = layers.Conv1D(8, 24, activation="relu")(inputs)
x = layers.MaxPooling1D(2)(x)
x = layers.Conv1D(8, 12, activation="relu")(x)
x = layers.MaxPooling1D(2)(x)
x = layers.Conv1D(8, 6, activation="relu")(x)
x = layers.GlobalAveragePooling1D()(x)
outputs = layers.Dense(1)(x)
model = keras.Model(inputs, outputs)

callbacks = [
    keras.callbacks.ModelCheckpoint("jena_conv.keras",
                                    save_best_only=True)
]
model.compile(optimizer="rmsprop", loss="mse", metrics=["mae"])
history = model.fit(train_dataset,
                    epochs=10,
                    validation_data=val_dataset,
                    callbacks=callbacks)

model = keras.models.load_model("jena_conv.keras")
print(f"Test MAE: {model.evaluate(test_dataset)[1]:.2f}")

```

## ▼ A first recurrent baseline

### A simple LSTM-based model

```

inputs = keras.Input(shape=(sequence_length, raw_data.shape[-1]))
x = layers.LSTM(16)(inputs)
outputs = layers.Dense(1)(x)
model = keras.Model(inputs, outputs)

callbacks = [
    keras.callbacks.ModelCheckpoint("jena_lstm.keras",
                                    save_best_only=True)
]
model.compile(optimizer="rmsprop", loss="mse", metrics=["mae"])
history = model.fit(train_dataset,
                    epochs=10,
                    validation_data=val_dataset,
                    callbacks=callbacks)

model = keras.models.load_model("jena_lstm.keras")
print(f"Test MAE: {model.evaluate(test_dataset)[1]:.2f}")

```

## ▼ Understanding recurrent neural networks

### NumPy implementation of a simple RNN

```

import numpy as np
timesteps = 100
input_features = 32
output_features = 64
inputs = np.random.random((timesteps, input_features))
state_t = np.zeros((output_features,))
W = np.random.random((output_features, input_features))
U = np.random.random((output_features, output_features))
b = np.random.random((output_features,))
successive_outputs = []
for input_t in inputs:
    output_t = np.tanh(np.dot(W, input_t) + np.dot(U, state_t) + b)
    successive_outputs.append(output_t)
    state_t = output_t
final_output_sequence = np.stack(successive_outputs, axis=0)

```

## ▼ A recurrent layer in Keras

### An RNN layer that can process sequences of any length

```

num_features = 14
inputs = keras.Input(shape=(None, num_features))
outputs = layers.SimpleRNN(16)(inputs)

```

### An RNN layer that returns only its last output step

```

num_features = 14
steps = 120
inputs = keras.Input(shape=(steps, num_features))
outputs = layers.SimpleRNN(16, return_sequences=False)(inputs)
print(outputs.shape)

```

### An RNN layer that returns its full output sequence

```

num_features = 14
steps = 120
inputs = keras.Input(shape=(steps, num_features))
outputs = layers.SimpleRNN(16, return_sequences=True)(inputs)
print(outputs.shape)

```

## Stacking RNN layers

```

inputs = keras.Input(shape=(steps, num_features))
x = layers.SimpleRNN(16, return_sequences=True)(inputs)
x = layers.SimpleRNN(16, return_sequences=True)(x)
outputs = layers.SimpleRNN(16)(x)

```

## ▼ Advanced use of recurrent neural networks

### ▼ Using recurrent dropout to fight overfitting

#### Training and evaluating a dropout-regularized LSTM

```
inputs = keras.Input(shape=(sequence_length, raw_data.shape[-1]))
x = layers.LSTM(32, recurrent_dropout=0.25)(inputs)
x = layers.Dropout(0.5)(x)
outputs = layers.Dense(1)(x)
model = keras.Model(inputs, outputs)

callbacks = [
    keras.callbacks.ModelCheckpoint("jena_lstm_dropout.keras",
                                    save_best_only=True)
]
model.compile(optimizer="rmsprop", loss="mse", metrics=["mae"])
history = model.fit(train_dataset,
                    epochs=50,
                    validation_data=val_dataset,
                    callbacks=callbacks)

inputs = keras.Input(shape=(sequence_length, num_features))
x = layers.LSTM(32, recurrent_dropout=0.2, unroll=True)(inputs)
```

### ▼ Stacking recurrent layers

#### Training and evaluating a dropout-regularized, stacked GRU model

```
inputs = keras.Input(shape=(sequence_length, raw_data.shape[-1]))
x = layers.GRU(32, recurrent_dropout=0.5, return_sequences=True)(inputs)
x = layers.GRU(32, recurrent_dropout=0.5)(x)
x = layers.Dropout(0.5)(x)
outputs = layers.Dense(1)(x)
model = keras.Model(inputs, outputs)

callbacks = [
    keras.callbacks.ModelCheckpoint("jena_stacked_gru_dropout.keras",
                                    save_best_only=True)
]
model.compile(optimizer="rmsprop", loss="mse", metrics=["mae"])
history = model.fit(train_dataset,
                    epochs=50,
                    validation_data=val_dataset,
                    callbacks=callbacks)
```

```
model = keras.models.load_model("jena_stacked_gru_dropout.keras")  
print(f"Test MAE: {model.evaluate(test_dataset)[1]:.2f}")
```

## ▼ Using bidirectional RNNs

### Training and evaluating a bidirectional LSTM

```
inputs = keras.Input(shape=(sequence_length, raw_data.shape[-1]))  
x = layers.Bidirectional(layers.LSTM(16))(inputs)  
outputs = layers.Dense(1)(x)  
model = keras.Model(inputs, outputs)  
  
model.compile(optimizer="rmsprop", loss="mse", metrics=["mae"])  
history = model.fit(train_dataset,  
                    epochs=10,  
                    validation_data=val_dataset)
```

Going even further

Summary