

Introduction to DataBases

Albert Bifet



Albert Bifet

- Associate Professor at Telecom ParisTech
- Worked at Yahoo Labs, Huawei, University of Waikato
- Doing Research in
 - Data Stream Mining, Machine Learning, Artificial Intelligence
 - Leading Open Source Projects
 - MOA, Apache SAMOA, StreamDM

Course

- Introduction to Databases and Relational Model
- Relational Algebra
- SQL, Views and Updates
- Functional Dependencies and Normalization
- E/R Design

Labs: Jupyter

- Jupyter notebooks are interactive shells which **save output in a nice notebook format**
- Notebooks will be in **python**
- **1 Lab: Functional Dependencies**
- **2 Lab: SQL**
- **3 Lab: SQL**



Resources

- Website
 - <http://albertbifet.com/teaching/>
- MOOC Videos
- References on the Website

Databases

Data-driven Society





ORACLE®



SNCF

CIV 1187

**BILLET-RESERVATION
THALYS****KOLOBOVA/DEUX
01 ADULTE**

		Départ	-> Arrivée			Classe
25/12 *	17H16 *	AMSTERDAM CENTRAA	-> PARIS NORD *	25/12 *	20H35 *	2 *
TRAIN 9354 TGH VOITURE 15 PLACE ASSISE 57 A UTILISER DANS CE TRAIN SALLE DUO 01 COULOIR NON FUMEUR						
NI ECHANGEABLE NI REMBOURSABLE SMOOVE			TRANSPORTEURS 1284 1088 1187	Prix EUR **45.00 FRF **295.18		

BG D030AD

THBGSM1
184152857910
00701161150966

INTERNET TGV EURO

IV 415285791 TS 476433350 C00540
251110 11H38 Dossier RWINQX Page 1/1

All business manage data

Walmart 
Save money. Live better.

(210) 377 - 1899
MANAGER SCOTT REDMAN
8500 JONES MALTSBERGER RD
SAN ANTONIO TX 78216

ST# 2404	OP# 00008097	TE# 01	TR# 01680
GARD GARLRYE	001600019333	F	2.18 N
CHEETOS	002840023985	F	1.98 N
CHEETOS	002840023986	F	1.98 N
CHEETOS	002840023988	F	1.98 N
SUBTOTAL			8.12
TOTAL			8.12
CASH TEND			8.12
CHANGE DUE			0.00

ITEMS SOLD 4

TC# 1422 8092 2433 0422 083



Our Guaranteed Low Prices
Are Unbeatable with Ad Match!
05/03/14 21:21:56

All business manage data

Big Data

www.wipro.com

BIG DATA

Big Data is data that is too large, complex and dynamic for any conventional data tools to capture, store, manage and analyze.

The right use of Big Data allows analysts to spot trends and gives niche insights that help create value and innovation much faster than conventional methods.

The "three V's", i.e the Volume, Variety and Velocity of the data coming in is what creates the challenge.

VOLUME



Amount of Big Data stored across the world (in petabytes)

VARIETY



PEOPLE TO PEOPLE

NETIZENS, VIRTUAL COMMUNITIES, SOCIAL NETWORKS, WEB LOGS...



PEOPLE TO MACHINE

ARCHIVES, MEDICAL DEVICES, DIGITAL TV, E-COMMERCE, SMART CARDS, BANK CARDS, COMPUTERS, MOBILES...



MACHINE TO MACHINE

SENSORS, GPS DEVICES, BAR CODE SCANNERS, SURVEILLANCE CAMERAS, SCIENTIFIC RESEARCH...

VELOCITY



2.9 MILLION

EMAILS SENT EVERY SECOND



20 HOURS

OF VIDEO UPLOADED EVERY MIN




50 MILLION

TWEETS PER DAY

CASE STUDY - Healthcare

\$300 billion is the potential annual value to Healthcare



VALUE



40% PROJECTED GROWTH IN GLOBAL DATA CREATED PER YEAR



5% PROJECTED GROWTH IN GLOBAL IT SPENDING PER YEAR

The estimated size of the digital universe in 2011 was 1.8 zettabytes. It is predicted that between 2009 and 2020, this will grow 44 fold to 35 zettabytes per year. A well defined data management strategy is essential to successfully utilize Big Data.

Sources: ① Reaping the Rewards of Big Data - Wipro Report ② Big Data: The Next Frontier for Innovation, Competition and Productivity - McKinsey Global Institute Report ③ ecomScore, Radicati Group ④ Measuring the Business Impacts of Effective Data - study by University of Texas, Austin ⑤ US Department of Labour

DO BUSINESS BETTER

NYSE:WIT | OVER 130,000 EMPLOYEES | 54 COUNTRIES | CONSULTING | SYSTEM INTEGRATION | OUTSOURCING



Data-intensive Applications

- Store data (databases)
- Speed up reads, remembering results (caches)
- Search data by keywords (search index)
- Send messages to another process asynchronously (stream application)
- Periodically crunch a large amount of accumulated data (batch processing)

Popular SQL Databases

- Open Source Databases

- MySQL
- PostgreSQL
- MariaDB

- Commercial Databases

- Oracle 12c
- Microsoft SQL Server
- IBM DB2
- SAP Hana



Small Data

- SQLite is a self-contained, high-reliability, embedded, full-featured, public-domain, SQL database engine.
- SQLite is the most used database engine in the world
- SQLite competes with fopen().



Let's build a database!

Simplest Database

```
#!/bin/bash
```

```
db_set () {
```

```
echo "$1,$2" >> database
```

```
}
```

```
db_get () {
```

```
grep "^$1," database | sed -e "s/^$1,/" | tail -n 1
```

```
}
```

Simplest Database

```
db_set 1324 'John Doe, Rue Barrault, Paris'
```

```
db_set 4324 'Paul Ryan, Avenue Italie, Paris'
```


```
db_get 4324
```

```
Paul Ryan, Avenue Italie, Paris
```


What is missing?


Database Indexing

Database Index



- Large binary search trees can be divided into “pages”

Database Index




- **B-Trees** are **balanced search trees** designed to work on disks and other storage devices

Motivation

B-Tree is a data structure that makes it possible to

- search
- update


a large file with guaranteed efficiency, in time $O(\lg(n))$



Motivation

The origin of the name “**B-Tree**” is unknown:

- Balanced, Broad, Bushy, Boeing, Bayer



Definition (Knuth)

- A **B-tree** of *minimum degree* t is a tree that satisfies:
 - Every node has at most $2t$ children
 - Every node, except for the root and the leaves, has at least t children
 - The root has at least 2 children (unless it is a leaf)
 - All leaves appear on the same level, and carry no information
 - A non leaf node with k children contains $k-1$ keys

2-3-4 Tree

- A **B-tree** of *minimum degree* **$t=2$** is a tree that satisfies:
 - Every node has at most **4** children
 - Every node, except for the root and the leaves, has at least **2** children
 - The root has at least 2 children (unless it is a leaf)
 - All leaves appear on the same level, and carry no information
 - A non leaf node with k children contains $k-1$ keys


B-Tree Operations

- Search: $O(t \log_t n)$
- Insert: if a node gets too big, we split it into two nodes
- Delete: if a node gets too small, we combine two nodes

Balance is achieved from the **top** of the tree

- since the height is only modified when the root splits or merges

Operation Costs




$$\begin{aligned}
 n &\geq 1 + (t-1) \sum_{i=1}^h 2t^{i-1} \\
 &= 1 + 2(t-1) \left(\frac{t^h - 1}{t-1} \right) \\
 &= 2t^h - 1.
 \end{aligned}$$

$$h \leq \log_t \frac{n+1}{2}$$

Search

- Form a simple path downward from the root of the tree




Search

- **Form a simple path downward from the root of the tree**
 - Recursively, starting at the root
 - Look for the appropriate position in the node
 - **if** the key is found, **return** the key
 - **else**
 - **if** the node is a leaf, **return** NIL
 - **else** continue recursively checking the appropriate child

Search



- Form a simple path downward from the root of the tree





Insertion

- search from the root the proper leaf for insertion
- do insertion
- if the node is full
 - **overflow: redistribution of keys to restore balance**
 - balance is restored by **splitting**, a procedure that moves from the leaf toward the root

Insertion (337)





Insertion (071)





Deletion

- a search proceeds from the root to locate the proper node
- key resides in a leaf
- key resides in a non-leaf node
 - an adjacent key is found and swapped into the vacated position
 - leftmost leaf of the subtree given by the right pointer of the vacated position

Deletion (337)





Deletion (067)





Deletion

- if the node has not enough keys
 - **underflow: redistribution of keys to restore balance,**
 - keys are obtained from a neighbouring leaf
 - if not : concatenation (inverse of splitting)

Deletion (067)



Deletion (067)



Applications

- Databases
- Filesystems
- File indexes



B-Tree Summary

- Balanced Tree designed to work with storage devices
 - Search, Update in time $O(\lg(n))$
- Insert: if a node gets too big, we split it into two nodes
- Delete: if a node gets too small, we combine two nodes

Balance is achieved from the **top** of the tree

- since the height is only modified when the root splits or merges

Spreadsheet

File Home Insert Page Layout Formulas Data Review View Team										
A2		fx 1								
	A	B	C	D	E	F	G	H	I	J
1	Number	GivenName	MiddleInitial	Surname	Gender	StreetAddress	City	State	ZipCode	Country
2	1	Bruce	R	Bloch	male	3151 Ferrell Street	Argyle	MN	56713	US
3	2	Marie	E	Humphreys	female	3062 Bond Street	Woonsocket	RI	2895	US
4	3	Sylvia	H	Carter	female	1481 Lakeland Terrace	Westland	MI	48185	US
5	4	William	E	Bentz	male	3318 Briercliff Road	New York	NY	10011	US
6	5	Shelly	R	Preston	female	3592 Todds Lane	San Antonio	TX	78212	US
7	6	Chad	P	Henry	male	3553 Grant Street	Tyler	TX	75702	US
8	7	David	L	Richardson	male	1289 Metz Lane	Marlton	NJ	8053	US
9	8	Stephen	A	Pond	male	4316 Bridge Avenue	Lafayette	LA	70503	US
10	9	Jenny	P	Thomas	female	2941 Harron Drive	Baltimore	MD	21202	US
11	10	William	V	Fries	male	4300 Tanglewood Road	Jackson	MS	39201	US
12	11	Julio	D	Bessette	male	4177 Lauren Drive	Madison	WI	53718	US
13	12	Jerry	J	Nicholas	male	2722 Elk Street	Irvine	CA	92718	US
14	13	Thomas	A	Hunter	male	4112 Stadium Drive	Franklin	MA	2038	US
15	14	Edmund	C	Chagoya	male	3685 Essex Court	Brattleboro	VT	5301	US
16	15	David	E	Meador	male	1215 Stratford Drive	Kona	HI	96740	US
17	16	Joan	L	Mayfield	female	3137 Pin Oak Drive	Whittier	CA	90603	US
18	17	Maria	H	Gomez	female	1723 Yorkie Lane	Richmond Hill	GA	31324	US
19	18	Gregory	G	Miguel	male	3233 Breezewood Court	Macksville	KS	67557	US
20	19	Gail	L	Griffin	female	2252 Arbutus Drive	Miami	FL	33179	US

What is missing?

DBMS

DBMS

- A Database Management System (DBMS) is a software package designed to store and manage databases
 - Data independence and efficient access.
 - Reduced application development time.
 - Data integrity and security.
 - Uniform data administration.
 - Concurrent access, recovery from crashes.

Data Models


- A *data model* is a collection of concepts for describing data.
- A *schema* is a description of a particular collection of data, using the a given data model.
- The *relational model of data* is the most widely used model today.
 - Main concept: *relation*, basically a table with rows and columns.
 - Every relation has a *schema*, which describes the columns, or fields.

Example Instance of Students Relation

sid	name	login	age	gpa
53666	Jones	jones@cs	18	3.4
53688	Smith	smith@eecs	18	3.2
53650	Smith	smith@math	19	3.8

Levels of Abstraction

- Many views, single conceptual (logical) schema and physical schema.
 - Views describe how users see the data.
 - Conceptual schema defines logical structure
 - Physical schema describes the files and indexes used.



➡ *Schemas are defined using DDL; data is modified/queried using DML.*

Example: University Database

- Conceptual schema:
Students(sid: string, name: string, login: string, age: integer, gpa: real)
Courses(cid: string, cname: string, credits: integer)
Enrolled(sid: string, cid: string, grade: string)
- Physical schema:
 - Relations stored as unordered files.
 - Index on first column of Students.
- External Schema (View):
Course_info(cid: string, enrollment: integer)

Data Independence

- Applications insulated from how data is structured and stored.
- Logical data independence: Protection from changes in *logical* structure of data.
- Physical data independence: Protection from changes in *physical* structure of data.
 - ➡ *One of the most important benefits of using a DBMS!*

Concurrency Control

- Concurrent execution of user programs is essential for good DBMS performance.
 - Because disk accesses are frequent, and relatively slow, it is important to keep the cpu humming by working on several user programs concurrently.
- Interleaving actions of different user programs can lead to inconsistency: e.g., check is cleared while account balance is being computed.
- DBMS ensures such problems don't arise: users can pretend they are using a single-user system.

Transaction: An Execution of a DB Program

- Key concept is transaction, which is an *atomic* sequence of database actions (reads/writes).
- Each transaction, executed completely, must leave the DB in a consistent state if DB is consistent when the transaction begins.
 - Users can specify some simple integrity constraints on the data, and the DBMS will enforce these constraints.
 - Beyond this, the DBMS does not really understand the semantics of the data. (e.g., it does not understand how the interest on a bank account is computed).
 - Thus, ensuring that a transaction (run alone) preserves consistency is ultimately the *user's* responsibility!

Scheduling Concurrent Transactions

- DBMS ensures that execution of $\{T_1, \dots, T_n\}$ is equivalent to some serial execution $T_1' \dots T_n'$.
 - Before reading/writing an object, a transaction requests a lock on the object, and waits till the DBMS gives it the lock. All locks are released at the end of the transaction. (Strict 2PL locking protocol.)
 - **Idea:** If an action of T_i (say, writing X) affects T_j (which perhaps reads X), one of them, say T_i , will obtain the lock on X first and T_j is forced to wait until T_i completes; this effectively orders the transactions.
 - What if T_j already has a lock on Y and T_i later requests a lock on Y ? (Deadlock!) T_i or T_j is aborted and restarted!

Relational Model

Relational Database: Definitions

- ❖ *Relational database*: a set of *relations*
- ❖ *Relation*: made up of 2 parts:
 - *Instance* : a *table*, with rows and columns.
#Rows = *cardinality*, #fields = *degree / arity*.
 - *Schema* : specifies name of relation, plus name and type of each column.
 - ◆ E.G. Students(*sid*: string, *name*: string, *login*: string, *age*: integer, *gpa*: real).
- ❖ Can think of a relation as a *set* of rows or *tuples* (i.e., all rows are distinct).

Example Instance of Students Relation

sid	name	login	age	gpa
53666	Jones	jones@cs	18	3.4
53688	Smith	smith@eecs	18	3.2
53650	Smith	smith@math	19	3.8

- ❖ Cardinality = 3, degree = 5, all rows distinct
- ❖ Do all columns in a relation instance have to be distinct?

Relational Query Languages

- ❖ A major strength of the relational model: supports simple, powerful *querying* of data.
- ❖ Queries can be written intuitively, and the DBMS is responsible for efficient evaluation.
 - The key: precise semantics for relational queries.
 - Allows the optimizer to extensively re-order operations, and still ensure that the answer does not change.

The SQL Query Language

- ❖ Developed by IBM (system R) in the 1970s
- ❖ Need for a standard since it is used by many vendors
- ❖ Standards:
 - SQL-86
 - SQL-89 (minor revision)
 - SQL-92 (major revision, current standard)
 - SQL-99 (major extensions)

The SQL Query Language

- ❖ To find all 18 year old students, we can write:

```
SELECT *  
FROM Students S  
WHERE S.age=18
```

sid	name	login	age	gpa
53666	Jones	jones@cs	18	3.4
53688	Smith	smith@ee	18	3.2

- To find just names and logins, replace the first line:

```
SELECT S.name, S.login
```

Querying Multiple Relations

❖ What does the following query compute?

```
SELECT S.name, E.cid  
FROM Students S, Enrolled E  
WHERE S.sid=E.sid AND E.grade="A"
```

Given the following instance of Enrolled (is this possible if the DBMS ensures referential integrity?):

sid	cid	grade
53831	Carnatic101	C
53831	Reggae203	B
53650	Topology112	A
53666	History105	B

we get:

S.name	E.cid
Smith	Topology112

Primary Key Constraints

- ❖ A set of fields is a *key* for a relation if :
 1. No two distinct tuples can have same values in all key fields, and
 2. This is not true for any subset of the key.
 - Part 2 false? A *superkey*.
 - If there's >1 key for a relation, one of the keys is chosen (by DBA) to be the *primary key*.
- ❖ E.g., *sid* is a key for Students. (What about *name*?) The set {*sid*, *gpa*} is a superkey.

Foreign Keys, Referential Integrity

- ❖ Foreign key : Set of fields in one relation that is used to `refer' to a tuple in another relation. (Must correspond to primary key of the second relation.) Like a `logical pointer'.
- ❖ E.g. *sid* is a foreign key referring to **Students**:
 - Enrolled(*sid*: string, *cid*: string, *grade*: string)
 - If all foreign key constraints are enforced, referential integrity is achieved, i.e., no dangling references.
 - Can you name a data model w/o referential integrity?
 - ◆ Links in HTML!

Relational Algebra

Relational Query Languages

- ❖ Query languages: Allow manipulation and **retrieval of data** from a database.
- ❖ Relational model supports simple, powerful QLs:
 - Strong formal foundation based on logic.
 - Allows for much optimization.
- ❖ Query Languages **!=** programming languages!
 - QLs not expected to be “Turing complete”.
 - QLs not intended to be used for complex calculations.
 - QLs support easy, efficient access to large data sets.

Formal Relational Query Languages

-Two mathematical Query Languages form the basis for “real” languages (e.g. SQL), and for implementation:

- ① Relational Algebra: More operational, very useful for representing execution plans.
- ② Relational Calculus: Lets users describe what they want, rather than how to compute it.
(Non-operational, declarative.)

➡ *Understanding Algebra & Calculus is key to*
➡ *understanding SQL, query processing!*

Preliminaries

- ❖ A query is applied to *relation instances*, and the result of a query is also a relation instance.
 - *Schemas of input* relations for a query are *fixed* (but query will run regardless of instance!)
 - The *schema for the result* of a given query is also *fixed*! Determined by definition of query language constructs.
- ❖ Positional vs. named-field notation:
 - Positional notation easier for formal definitions, named-field notation more readable.
 - Both used in SQL

Example Instances

- ❖ “Sailors” and “Reserves” relations for our examples.
- ❖ We’ll use positional or named field notation, assume that names of fields in query results are ‘inherited’ from names of fields in query input relations.

Reserves

R1

<u>sid</u>	<u>bid</u>	<u>day</u>
22	101	10/10/96
58	103	11/12/96

Sailors

S1

<u>sid</u>	sname	rating	age
22	dustin	7	45.0
31	lubber	8	55.5
58	rusty	10	35.0

S2

<u>sid</u>	sname	rating	age
28	yuppy	9	35.0
31	lubber	8	55.5
44	guppy	5	35.0
58	rusty	10	35.0

Relational Algebra

❖ Basic operations:

- Selection (σ) Selects a subset of rows from relation.
- Projection (π) Deletes unwanted columns from relation.
- Cross-product (\times) Allows us to combine two relations.
- Set-difference ($-$) Tuples in reln. 1, but not in reln. 2.
- Union (\cup) Tuples in reln. 1 and in reln. 2.

❖ Additional operations:

- Intersection, join, division, renaming: Not essential, but (very!) useful.

❖ Since each operation returns a relation, **operations can be composed!** (Algebra is “closed”.)

Projection

- ❖ Deletes attributes that are not in *projection list*.
- ❖ *Schema* of result contains exactly the fields in the projection list, with the same names that they had in the (only) input relation.
- ❖ Projection operator has to eliminate *duplicates*! (Why??)
 - Note: real systems typically don't do duplicate elimination unless the user explicitly asks for it. (Why not?)

sname	rating
yuppy	9
lubber	8
guppy	5
rusty	10

$\pi_{sname, rating}(S2)$

age
35.0
55.5

$\pi_{age}(S2)$

Selection

sid	sname	rating	age
28	yuppy	9	35.0
58	rusty	10	35.0

- ❖ Selects rows that satisfy *selection condition*.
- ❖ No duplicates in result! (Why?)
- ❖ *Schema* of result identical to schema of (only) input relation.
- ❖ *Result* relation can be the *input* for another relational algebra operation! (Operator composition.)

$$\sigma_{rating > 8}(S2)$$

sname	rating
yuppy	9
rusty	10

$$\pi_{sname, rating}(\sigma_{rating > 8}(S2))$$

Union, Intersection, Set-Difference

- ❖ All of these operations take two input relations, which must be union-compatible:
 - Same number of fields.
 - ‘Corresponding’ fields have the same type.
- ❖ What is the *schema* of result?

sid	sname	rating	age
22	dustin	7	45.0

$S1 - S2$

sid	sname	rating	age
22	dustin	7	45.0
31	lubber	8	55.5
58	rusty	10	35.0
44	guppy	5	35.0
28	yuppy	9	35.0

$S1 \cup S2$

sid	sname	rating	age
31	lubber	8	55.5
58	rusty	10	35.0

$S1 \cap S2$

Cross-Product

- ❖ Each row of S1 is paired with each row of R1.
- ❖ *Result schema* has one field per field of S1 and R1, with field names 'inherited' if possible.
 - *Conflict*: Both S1 and R1 have a field called *sid*.

(sid)	sname	rating	age	(sid)	bid	day
22	dustin	7	45.0	22	101	10/10/96
22	dustin	7	45.0	58	103	11/12/96
31	lubber	8	55.5	22	101	10/10/96
31	lubber	8	55.5	58	103	11/12/96
58	rusty	10	35.0	22	101	10/10/96
58	rusty	10	35.0	58	103	11/12/96

➡ Renaming operator: $\rho (C(1 \rightarrow sid1, 5 \rightarrow sid2), S1 \times R1)$

Joins

❖ Condition Join:

$$R \bowtie_c S = \sigma_c (R \times S)$$

(sid)	sname	rating	age	(sid)	bid	day
22	dustin	7	45.0	58	103	11/12/96
31	lubber	8	55.5	58	103	11/12/96

$$S1 \bowtie_{S1.sid < R1.sid} R1$$

- ❖ *Result schema* same as that of cross-product.
- ❖ Fewer tuples than cross-product, might be able to compute more efficiently
- ❖ Sometimes called a *theta-join*.

Joins

- ❖ Equi-Join: A special case of condition join where the condition c contains only *equalities*.

sid	sname	rating	age	bid	day
22	dustin	7	45.0	101	10/10/96
58	rusty	10	35.0	103	11/12/96

$$S1 \bowtie_{sid} R1$$

- ❖ Result schema similar to cross-product, but only one copy of fields for which equality is specified.
- ❖ Natural Join: Equijoin on *all* common fields.

Division

- ❖ Not supported as a primitive operator, but useful for expressing queries like:
Find sailors who have reserved all boats.
- ❖ Let A have 2 fields, x and y ; B have only field y :
 - $A/B = \{ \langle x \rangle \mid \exists \langle x, y \rangle \in A \ \forall \langle y \rangle \in B \}$
 - i.e., **A/B contains all x tuples (sailors) such that for every y tuple (boat) in B , there is an xy tuple in A .**
 - Or: If the set of y values (boats) associated with an x value (sailor) in A contains all y values in B , the x value is in A/B .
- ❖ In general, x and y can be any lists of fields; y is the list of fields in B , and $x \cup y$ is the list of fields of A .

Examples of Division A/B

sno	pno
s1	p1
s1	p2
s1	p3
s1	p4
s2	p1
s2	p2
s3	p2
s4	p2
s4	p4

A

pno
p2

$B1$

sno
s1
s2
s3
s4

$A/B1$

pno
p2
p4

$B2$

sno
s1
s4

$A/B2$

pno
p1
p2
p4

$B3$

sno
s1

$A/B3$

Expressing A/B Using Basic Operators

- ❖ Division is not essential op; just a useful shorthand.
 - (Also true of joins, but joins are so common that systems implement joins specially.)
- ❖ *Idea:* For A/B , compute all x values that are not 'disqualified' by some y value in B .
 - x value is *disqualified* if by attaching y value from B , we obtain an xy tuple that is not in A .

Disqualified x values: $\pi_x ((\pi_x(A) \times B) - A)$

A/B : $\pi_x(A) -$ all disqualified tuples

Exercises

- Find names of sailors who've reserved boat #103
- Find names of sailors who've reserved a red boat
- Find sailors who've reserved a red or a green boat
- Find the names of sailors who've reserved all boats

Find names of sailors who've reserved boat #103

❖ Solution 1: $\pi_{sname}((\sigma_{bid=103} Reserves) \bowtie Sailors)$

❖ Solution 2: $\rho(Temp1, \sigma_{bid=103} Reserves)$

$\rho(Temp2, Temp1 \bowtie Sailors)$

$\pi_{sname}(Temp2)$

❖ Solution 3: $\pi_{sname}(\sigma_{bid=103}(Reserves \bowtie Sailors))$

Find names of sailors who've reserved a red boat

- ❖ Information about boat color only available in Boats; so need an extra join:

$$\pi_{sname}((\sigma_{color='red'} Boats) \bowtie Reserves \bowtie Sailors)$$

- ❖ A more efficient solution:

$$\pi_{sname}(\pi_{sid}((\pi_{bid} \sigma_{color='red'} Boats) \bowtie Res) \bowtie Sailors)$$

➡ A query optimizer can find this given the first solution!

Find sailors who've reserved a red or a green boat

- ❖ Can identify all red or green boats, then find sailors who've reserved one of these boats:

ρ (*Tempboats*, ($\sigma_{color='red' \vee color='green'} Boats$))

$\pi_{sname}(Tempboats \bowtie Reserves \bowtie Sailors)$

- ❖ Can also define Tempboats using union! (How?)
- ❖ What happens if \vee is replaced by \wedge in this query?

Find sailors who've reserved a red and a green boat

- ❖ Previous approach won't work! Must identify sailors who've reserved red boats, sailors who've reserved green boats, then find the intersection (note that *sid* is a key for Sailors):

$\rho (Tempred, \pi_{sid}((\sigma_{color='red'} Boats) \bowtie Reserves))$

$\rho (Tempgreen, \pi_{sid}((\sigma_{color='green'} Boats) \bowtie Reserves))$

$\pi_{sname}((Tempred \cap Tempgreen) \bowtie Sailors)$

Find the names of sailors who've reserved all boats

- ❖ Uses division; schemas of the input relations to / must be carefully chosen:

$$\rho \text{ (} Temp\text{sids, } (\pi_{sid, bid} Reserves) / (\pi_{bid} Boats) \text{)}$$

$$\pi_{sname} (Temp\text{sids} \bowtie Sailors)$$

- ❖ To find sailors who've reserved all 'Interlake' boats:

$$\dots / \pi_{bid} (\sigma_{bname='Interlake'} Boats)$$

Summary

- ❖ The relational model has rigorously defined query languages that are simple and powerful.
- ❖ Relational algebra is more operational; useful as internal representation for query evaluation plans.
- ❖ Several ways of expressing a given query; a query optimizer should choose the most efficient version.