

NINGBO YI PIAN HONG FASTENER CO.,LTD

TEST CERTIFICATE

Customer:ALPHA FASTENER JOINT STOCK COMPANY

Surface Finish:Green PTFE/Blue Xylan

Dimensions Inspection:(mm Measurement BY Millimeters)

Test items	Requirement			Test results
Xylan 1070 Green color	25-40um			26-35um
Coating hardness	(ASTM D3363)			5H
Pre-processing before presentation	DIN EN ISO 8501-1			ZINC PLATED
Surface drying time	≤220 (drying temperature) 30 minutes (GB/T 1728)			30 minutes
Actual drying time	≤240 (drying temperature) 45 minutes(GB/T 1728)			45minutes
Adhesion/MPa	≥5B(ASTM D3359-B)			5B
Dielectric strength	500-1200V (GB/2681-2023)			1000V
Friction coefficient	0.08-0.12 (ASTMG99-17)			0.1
Firmware testing	After the reagent is dropped onto the product surface and left for 2 minutes, the white cloth is wiped 30 times. There is no significant color fading.			Pass
Salt spray testing	1000H	1500H	2500H	1000H
	The single-directional corrosion in the scratched area shall not exceed 2.0 mm; The non-scraped area shall not blister, rust, crack or peel off.			

TEST RESULT : PASSED

Q A MANAGER	QA			DATE
LISA YANG	NIKI ZHANG			2025/12/30

宁波一片红紧固件有限公司
NINGBO YI PIAN HONG FASTENER CO., LTD

王君