





Basic JSP Tutorial

@ JSP - Home

ISP - Overview

@ JSP - Environment Setup

@ JSP - Architecture

@ JSP - Lifecycle

O JSP - Syntax

JSP - Directives

JSP - Actions

JSP - Implicit Objects

@ JSP - Client Request

@ JSP - Server Response

@ JSP - Http Status Codes

@ JSP - Form Processing

@ JSP - Writing Filters

@ JSP - Cookies Handling

@ JSP - Session Tracking

JSP - File Uploading

@ JSP - Handling Date

@ JSP - Page Redirect

@ JSP - Hits Counter

@ JSP - Auto Refresh

@ JSP - Sending Email

Advanced JSP Tutorials

JSTL - fn:contains() Function

Advertisements

The **fn:contains()** function determines whether an input string contains a specified substring.

Syntax

The fn:contains() function has the following syntax -

boolean contains(java.lang.String, java.lang.String)

Example

Following example explains the functionality of fn:contains() function –

You will receive the following result -

Found test string

● Previous Page

₽ Print

Advertisements

Next Page 🕣









□ JSP - Standard Tag Library JSP - Database Access

■ JSP - Expression Language ■ JSP - Exception Handling

■ JSP - Internationalization

JSP Useful Resources

 JSP - Quick Guide @ JSP - Useful Resources JSP - Discussion

Selected Reading UPSC IAS Exams Notes Developer's Best Practices Questions and Answers Effective Resume Writing HR Interview Questions Computer Glossary Who is Who

@ JSP - XML Data 🛮 JSP - Java Beans JSP - Custom Tags

■ JSP - Debugging @ JSP - Security



