


Related 3 Answers active oldest 3779 How do I check if an array includes a value in JavaScript? Observable.from Documentation: For arrays and iterables, all contained values will be emitted 2331 How can I convert a string to boolean in as a sequence! So your items will always be emitted as T and not T[] JavaScript? For Observable<T[]> do either of the following: 2895 How to append something to an array? 2711 How to insert an item into an array at a \$sub = new Subject<Array<T>>(); specific index (JavaScript)? this.Player = \$sub.asObservable(); 2539 Sort array of objects by string property OR 2944 Loop through an array in JavaScript Home this.Player = of(array); 2583 How to check if an object is an array? PUBLIC OR 7664 How do I remove a particular element from Stack Overflow an array in JavaScript? Tags Observable.create((observer) => {observer.next(array)}) 4453 For-each over an array in JavaScript? Users share improve this answer edited Jul 15 at 3:29 answered Jul 15 at 3:17 1293 What is the difference between Promises Jobs and Observables? Ruraloville 136 • 2 **Hot Network Questions** TEAMS What's this? First 25 Users Free In the first suggestion where do I pass my array? Or in the second one where can I assign the value to my Minimum food on the Sabbath variable Player? - Ramzan Dieze Jul 15 at 3:35 Can socialism and capitalism coexist in the same Take array as param for convert function and add \$sub.next(array) for first and nothing for second. It should work. Also use return and types for your function instead of assigning to var as described in Sidd's answer Why did a gate officer and exit immigration officer below. That would make it much more cleaner - Ruraloville Jul 15 at 3:39 try to peel my visa sticker? Can I ask why you have used type Subject in the first suggestion? - Ramzan Dieze Jul 15 at 3:49 Mhy only sine waves? I thought you would want to reemit the array at same later stage also so then you could just use the same Temporary queue to prevent duplication subject ref and call next. But if you want to use a converter func then of would make more sense - Ruraloville Jul 15 at 4:04 How to test whether a correlation is equal to 1? Are you importing it from the rxis library? – Ruraloville Jul 15 at 5:40 How to participate in group conversations as an outsider? show 3 more comments Controlling a robot blindfolded on a 9x9 grid Am I overreacting or seeing things where they don't exist? Use of operator instead of from Mhy does the takeoff N1 limit start to decrease below 30°C OAT? import { of } from 'rxjs'; ✓ Voltage levels of Microcontroller Oscillator Pins Harmonic sums and elementary number theory player: Observable<T[]>; Visual Studio Code PHP Intelephense Keep convert(){ Showing Not Necessary Error let tempArr:T[] = Object.values(data) as T[]; Home How could pirates reasonably transport dinosaurs let Obsobj = of(tempArr); in captivity, some of them enormous, across this.Player = Obsobj; PUBLIC A Should a soda bottle be stored horizontally or Stack Overflow vertically? share improve this answer answered Jul 15 at 3:08 Tags Is it possible for a moon to have a higher gravity than the planet it is attached to? 4.332 • 8 • 17 • 28 Users How cold does it have to be to freeze a waterfall Jobs Why is the 'anti' in 'anti-semitism'? I tried but it didn't have the source inside the object, which is needed to display. - Ramzan Dieze Jul 15 at 3:36 In OOP, 'protected' keyword is not required?



This isn't how generics work.



You will have to refactor your code in order to make it work.

Ideally your convert method should expect a generic type T

Something like this:

```
convert<T>(array: Array<T>): Observable<Array<T>> {
  return of(array);
}
```

And when you call convert, you call it like this:

import { Component } from '@angular/core';

```
this.convert<User>([{ firstName: `John`, lastName: `Doe` }])
  .subscribe((userArray: Array<User>) => console.log(userArray));
```

When you do this, you are telling your convert function that you want the Type  $\tau$  to be a user type.

Here's a Complete working Example:

```
import { Observable, of } from 'rxjs';
interface User {
    firstName: string;
    lastName: string;
}

@Component({
    selector: 'my-app',
    templateUrl: './app.component.html',
    styleUrls: ['./app.component.css']
})
export class AppComponent {
    player: Observable<Array<User>>;

    ngOnInit() {
        this.convert<User>([{ firstName: `John`, lastName: `Doe` }])
        .subscribe((userArray: Array<User>) => console.log(userArray));
```

convert<T>(array: Array<T>): Observable<Array<T>> {

share improve this answer

return of(array);

answered Jul 15 at 3:15

SiddAjmera

22.8k • 4 • 17 • 52

add a commer

Home PUBLIC

Stack Overflow

Tags

Users Jobs

TEAMS What's this?

First 25 Users Free

Your Answer

B I ∅ 66 {} ■ ほほ蓋壷 ちゃ

- Aces, twos, threes, and fours in a row
- How large should a hole be for a bolt to go through?
- How to set up a "Forced choice" for players in a game?
- Large (70) stellar mass black hole disrupts astrophysics?
- When is NHST appropriate in business?
- **N** Question feed

