



## DATABASES

[SQL](#)[Oracle / PLSQL](#)[SQL Server](#)[MySQL](#)[MariaDB](#)[PostgreSQL](#)[SQLite](#)

## MS OFFICE

[Excel](#)[Access](#)[Word](#)

## WEB DEVELOPMENT

[HTML](#)[CSS](#)[JavaScript](#)[Color Picker](#)

## PROGRAMMING

[C Language](#)

## MORE

[ASCII Table](#)[Unicode](#)[Linux](#)[UNIX](#)[Techie Humor](#)

Advertisement



## Oracle / PLSQL: || Operator

This Oracle tutorial explains how to use the Oracle/PLSQL || concatenate operator with syntax and examples.

### Description

The Oracle/PLSQL || operator allows you to concatenate 2 or more strings together.

### Syntax

The syntax for the || operator in Oracle/PLSQL is:

```
string1 || string2 [ || string_n ]
```

### Parameters or Arguments

**string1**

The first string to concatenate.

**string2**

The second string to concatenate.

**string\_n**

Optional. The nth string to concatenate.

### Returns

The || operator returns a string value.

### Applies To

The || operator can be used in the following versions of Oracle/PLSQL:

- Oracle 12c, Oracle 11g, Oracle 10g, Oracle 9i, Oracle 8i

Filter items

[▶ Oracle Basics](#)[▶ Oracle Advanced](#)[▶ Oracle Cursors](#)[▶ Oracle Exception Handling](#)[▶ Oracle Foreign Keys](#)[▶ Oracle Loops/Conditionals](#)[▶ Oracle Transactions](#)[▶ Oracle Triggers](#)[▼ String/Char Functions](#)[ASCII](#)[ASCIISTR](#)[CHR](#)[COMPOSE](#)[CONCAT](#)[Concat with ||](#)[CONVERT](#)[DECOMPOSE](#)[DUMP](#)[INITCAP](#)[INSTR](#)[INSTR2](#)[INSTR4](#)[INSTRB](#)[INSTRC](#)[LENGTH](#)[LENGTH2](#)[LENGTH4](#)[LENGTHB](#)[LENGTHC](#)[LOWER](#)[LPAD](#)[LTRIM](#)[NCHR](#)[REGEXP\\_INSTR](#)[REGEXP\\_REPLACE](#)

## Example

Let's look at some concatenation examples and explore how to use the `||` operator in Oracle/PLSQL.

For example:

```
'Tech on' || ' the Net'  
Result: 'Tech on the Net'  
  
'a' || 'b' || 'c' || 'd'  
Result: 'abcd'
```

## Concatenate Space Characters

When you are concatenating values together, you might want to add space characters to separate your concatenated values. Otherwise, you might get a long string with the concatenated values running together. This makes it very difficult to read the results.

Let's look at an easy example.

We can concatenate a space character using the `||` operator.

For example:

```
SELECT 'Dave' || ' ' || 'Anderson'  
FROM dual;  
Result: 'Dave Anderson'
```

In this example, we have used the `||` operator to add a space character between the values *Dave* and *Anderson*. This will prevent our values from being squished together.

Instead our result would appear as follows:

```
'Dave Anderson'
```

You would more commonly use the `||` operator to concatenate a space character when you are concatenating multiple fields together.

For example:

```
SELECT first_name || ' ' || last_name AS customer_name  
FROM customers;
```

This example would return a result set with one column that consisted of the *first\_name* and *last\_name* fields (separated by a space) from the *customers* table. The column in the result set would be *aliased* as *customer\_name*.

## Concatenate Single Quotes

Since the `||` operator will concatenate string values that are enclosed in single quotes, it isn't straight forward how to add a single quote character within the result of the concatenated string.

Let's look at a fairly easy example that shows how to add a single quote to the resulting string using the `||` operator.

For example:

```
SELECT 'Let''s' || ' learn Oracle'
```

REGEXP_REPLACE
REGEXP_SUBSTR
REPLACE
RPAD
RTRIM
SOUNDEX
SUBSTR
TRANSLATE
TRIM
UPPER
VSIZE

► **Numeric/Math Functions**

► **Date/Time Functions**

► **Conversion Functions**

► **Analytic Functions**



► **Advanced Functions**


```
FROM dual;  
Result: 'Let's learn Oracle'
```

Since our string values are enclosed in single quotes, we use 2 additional single quotes within the surrounding quotes to represent a single quotation mark in the resulting concatenated string.

If you wanted to separate out the single quote from the other string values, you could also rewrite this query as follows:

```
SELECT 'Let' || ''' || 's' || ' learn Oracle'  
FROM dual;  
Result: 'Let's learn Oracle'
```

Share on  



[Back to top](#)

[Home](#) | [About Us](#) | [Contact Us](#) | [Testimonials](#) | [Donate](#)

While using this site, you agree to have read and accepted our [Terms of Service](#) and [Privacy Policy](#).

We use advertisements to support this website and fund the development of new content.

Copyright © 2003-2019 TechOnTheNet.com. All rights reserved.