

Sets the `valuesAdjusting` property, which indicates whether or not upcoming selection changes should be considered part of a single change. The value of this property is used to initialize the `valuesAdjusting` property of the `ListSelectionEvents` that are generated.

For example, if the selection is being updated in response to a user drag, this property can be set to `true` when the drag is initiated and set to `false` when the drag is finished. During the drag, listeners receive events with a `valuesAdjusting` property set to `true`. At the end of the drag, when the change is finalized, listeners receive an event with the value set to `false`. Listeners can use this pattern if they wish to update only when a change has been finalized.

Setting this property to `true` begins a series of changes that is to be considered part of a single change. When the property is changed back to `false`, an event is sent out characterizing the entire selection change (if there was one), with the event's `valuesAdjusting` property set to `false`.



Đặt thuộc tính `valuesAdjusting`, cho biết liệu các thay đổi lựa chọn sắp tới có được coi là một phần của một thay đổi hay không. Giá trị của thuộc tính này được sử dụng để khởi tạo thuộc tính `valuesAdjusting` của `ListSelectionEvents` được tạo.

Ví dụ: nếu lựa chọn đang được cập nhật để đáp ứng với kéo của người dùng, thuộc tính này có thể được đặt thành `true` khi kéo được bắt đầu và được đặt thành `false` khi quá trình kéo kết thúc. Trong quá trình kéo, người nghe nhận được các sự kiện với thuộc tính `valuesAdjusting` được đặt thành `true`. Khi kết thúc kéo, khi thay đổi được hoàn thành, người nghe sẽ nhận được một sự kiện với giá trị được đặt thành `false`. Người nghe có thể sử dụng mẫu này nếu họ chỉ muốn cập nhật khi một thay đổi đã được hoàn tất.

Đặt thuộc tính này thành `true` bắt đầu một loạt các thay đổi được coi là một phần của một thay đổi. Khi thuộc tính được thay đổi thành `false`, một sự kiện được gửi đi đặc trưng cho toàn bộ thay đổi lựa chọn (nếu có), với thuộc tính `valuesAdjusting` của sự kiện được đặt thành `false`.



1028/5000

