




UNIVERSITY OF SCIENCE
HO CHI MINH CITY

CTT534 – Thiết Kế Giao Diện
HK II 2013 – 2014


UI Architectures and Development Tools

Some slides adapted from materials of MIT
CS Course 6.813/6.831

Outline

- 
- Architectures and design patterns for UIs
 - UI development tools

Read-evaluation architecture



Flowchart

```
repeat  
  read-event (myevent)  
  case myevent.type  
    type_1:  
      do type_1 processing  
    type_2:  
      do type_2 processing  
    ...  
    type_n:  
      do type_n processing  
  end case  
end repeat
```

Pseudo-code

- The application has complete control over the event processing
- Programmer must execute this control over every event that the client will receive
 - very cumbersome task


Separating UI from application

- One aim of a UI architecture is to **separate the interface from the application**
- Provides
 - ❑ Portability
 - ❑ Reuse
 - ❑ Multiple Interfaces
 - ❑ Customization
 - ❑ Maintainability
 - ❑ Cost savings

Notification-based architecture

- Example

- A simple interface for a “Save” and “Quit” operation




Notification-based architecture (cont'd)

```
void main(String[] args) {  
    Menu menu = new Menu();  
    menu.setOption("Save");  
    menu.setOption("Quit");  
    menu.setAction("Save", mySave)  
    menu.setAction("Quit", myQuit)  
    ...  
}
```

```
int mySave(Event e) {  
    // save the current file  
}
```

```
int myQuit(Event e) {  
    // close down  
}
```



Notification-based architecture (cont'd)

- Main control loop for the event processing is outside the application
- A centralized notifier
 - receives events from the windows system
 - filters events to the application program
- The control flow is **not** controlled by application programmer


Model-View-Controller (MVC)

View handles output

- gets data from the model to display it
- listens for model changes and updates display

Controller handles input

- listens for input events on the view
- calls mutators on model or view




Model maintains application state

- implements state-changing behavior
- sends change events to views

MVC example: textbox

TextField is a Component that can be added to a view tree

KeyListener is a listener for keyboard events



Document represents a mutable string of characters

MVC: advantages

- Separation of concerns
 - Model: data
 - View: output
 - Controller: input
- Supporting
 - Reuse
 - Reuse of models and views
 - Portability
 - Multiple interfaces
 - Maintainability
 - Changes in view can be done with minimal effects on model

Hard to separate View and Controller

- Controller often needs output
 - ❑ View must provide **affordances** for controller
 - e.g., button border and/or icon
 - ❑ View must provide feedback about controller state
 - e.g., depressed button
- State shared between controller and view
 - ❑ Must be displayed by the view
 - ❑ Must be updated and used by the controller
 - ❑ Example
 - Checkbox: who manages it when it's checked and unchecked?


Widget: tightly coupled view and controller

- The MVC idea has largely been replaced by the MV idea
- A widget is a reusable view object that manages both its input and output
 - Also called
 - Components in Java or Flex
 - Controls in Windows
 - Example
 - Menubar
 - Button
 - Editbox

Presentation-Abstraction-Control (PAC)

- A hierarchical structure of agents, each consisting of a triad of Presentation (View), Abstraction (Model), and Control
- Somewhat similar to MVC, but...
 - Completely insulates the Presentation (View in MVC) and the Abstraction
 - provides the option to separately multithread the model and view
 - the user interface (presentation) can be shown before the abstraction has fully initialized

Presentation-Abstraction-Control (PAC)



Outline

- Architectures and design patterns for UIs
- UI development tools

Layers of UI development tools


- Layers of development tools can be broadly categorized into
 - Windowing systems
 - Interface Development Toolkits (IDT)
 - User Interface Management Systems (UIMS)

Windowing systems


■ Elements

- ❑ Device independence
 - Abstract terminal device drivers
 - Image models for output and (partially) input
 - ❑ pixels
 - ❑ PostScript (MacOS X, NextStep)
 - ❑ Graphical Kernel System (GKS)
- ❑ Multiple application control
 - Simultaneous user tasks
 - Supports independent processes
 - Isolation of individual applications


Architectures of windowing system



The Client-Server architecture



X Windows architecture




UI development in windowing systems

- UI development tools use **window managers** as the foundation upon which a user interface can be built
 - A window manager allows the user to display, alter, and interact with more than one window at a time
 - The window manager's primary responsibility is to keep track of all aspects of each of the windows being displayed

Example: Android

- Google mobile platform
- A software stack for mobile devices
 - OS, middleware, tools, apps
- Core applications
 - email, browser, maps, SMS
- Application Framework
 - Apps and GUI builder
- Linux kernel
- Java programming language




Interface Development Toolkits (IDT)

■ IDT

- Provides an interactive editor to layout the interface
- May provide limited dialogue definition
- Produces code that represents layout and dialogue (if any)

■ Object interaction example

- Input and output are linked



Interface Development Toolkits (IDT)


■ Advantages

- ❑ Programming with interaction objects (or techniques, widgets, gadgets)
- ❑ Promote consistency and generalizability
- ❑ Support similar look and feel
- ❑ Similar to object-oriented programming

Interface Development Toolkits (IDT)



Motif for X-window system



MFC

MFC

- A library that wraps portions of the Windows API in C++ classes
- Classes are defined for many of the handle-managed Windows objects with predefined windows and controls
- The IDT consists of a software framework used by software developers
 - To promote a standard structure for applications
 - Much simpler to create automatic GUI creation tools when using a standard framework
 - Usually use object-oriented programming (OOP) techniques to implement frameworks


MFC (cont'd)

- When using the **Win32 API**, you will need to

- ❑ Create your core program
- ❑ Create the structures for window and button
- ❑ Initialize all the members for the structures
- ❑ Create callback methods to handle events

→ Programmer has to manage over the entire control and event processing

- ❑ very cumbersome task



MFC (cont'd)

- With MFC, this would be easier
 - Two objects in this program
 - One being the Window object
 - Other being the Application object itself

- HelloWorldWindow :

```
public CFrameWnd {...}
```



- HelloWorldApplication :

```
public CWinApp {...}
```

Choosing right tools for projects

- Tools can offer large savings in development effort
 - Faster prototyping and development time
 - Less training needed to use tools than program systems
- Different tools need varying levels of expertise
 - Higher level tools need less training
 - Lower level tools offer more control and customization
- Specialized tool exists
 - Tools exist to support specific types of user interfaces
 - Tools available to assist in evaluation, benchmarking, testing

Choosing right tools for projects (cont'd)

- Tools evaluation
 - Using table with tool functionality vs. tool usability

FIGURE 5.
A page from the evaluation form, as completed by an evaluator participant for Demo

USABILITY →

FUNCTIONALITY ↓


FORMS	Ease of Using Tool to Produce This Function				Specification/Implementation Technique Used by Tool to Produce This Function					
	Not possible with this tool	☹	☺	☺	Programmed language	Specialized dialogue language	BLIF	Regular expressions	Other (Specify: _____)	Other (Specify: _____)
Typed (non-enumerated) input				X				X		
Formatted fields		X						X		
Toggled (enumerated) input			X							X
Default field values				X						X
Navigation within form										
Arrow keys				X				X		
Picking with mouse	X									
Tab key				X				X		
Space bar				X				X		
Bidirectional				X				X		
Wrap-around	X									
Other (Specify: _____)										
Single-page forms			X							X
Multi-page forms			X							X
Other (Specify: _____)										
TOTALS										

(from D. Hix and R. Schulman, CACM, pp.79, March 1991/Vo1.34, No.3)

Common tools

Flash (Adobe)

- Shockwave Flash and Macromedia Flash
- Supports vector/raster graphics animations, bidirectional
- video/audio streams
- Contains scripting language (ActionScript)
- A browser plug-in, Flash player
- Good for concept prototyping



Common tools (cont'd)

Java toolkits

■ Java toolkit – AWT (Abstract Window Toolkit)

- ❑ an Abstract Window Toolkit, part of the Java Foundation Classes (JFC)
- ❑ Standard API for providing GUIs for Java programs
- ❑ Notification based architecture
- ❑ AWT 1.0 – needs to subclass basic widgets
- ❑ AWT 1.1 and beyond – callback objects


■ Swing toolkit

- ❑ built on top of AWT – higher level features
- ❑ provide a more sophisticated set of GUI components than AWT
- ❑ uses MVC architecture

Common tools (cont'd)

Windows .NET


- Windows GUI builder
 - integral components
- Form-Control pattern
- Element drag-and-drop
- Windows themes support
- OO programming environment
- Visual Studio tools



Common tools (cont'd)

Apple Cocoa

- Mac OS-X GUI builder
- Xcode & Interface Builder
- MVC architecture
 - Cocoa bindings to reduce dependencies between models, views and controllers
- Objective-C, also supports Java, Python, Perl



Common tools (cont'd)

Ruby on Rails


- An open-source web framework
- Good for developing database backed web applications
- Convention over configuration
- MVC pattern
 - ❑ MySQL DB (Model)
 - ❑ Browser-based (View)
 - ❑ Ruby (Controller)

<http://www.rubyonrails.org/>

Common tools (cont'd)

Android

- Google mobile platform
- A software stack for mobile devices
 - OS, middleware, tools, apps
- Core applications
 - email, browser, maps, SMS
- Application Framework
 - Apps and GUI builder
- Linux kernel
- Java programming language



Common tools (cont'd)

S60/ Symbian Platform

- SF platform for Symbian
- OS based mobile phone
- Nokia, Samsung, LG, Lenovo
- Includes standard apps and GUI builder
- Structured MVC pattern
- Supports Java, Symbian C++, Python



Tool resources on the Internet

- A collection of UI tools (no longer maintaining)
 - ❑ <http://www.cs.cmu.edu/afs/cs/user/bam/www/toolnames.html>
- 20 useful tools for web development
 - ❑ http://sixrevisions.com/tools/20_web_development_tools/
- 24 usability testing tools
 - ❑ <http://www.usefulusability.com/24-usability-testing-tools/>

Tool terminologies

- Presentation – that part of the software that displays objects
 - gets inputs from user and modifies screens
- Dialogue – describes the dynamic behavior of the interface
 - what happens when button is pressed
 - has code to determine next objects to display or modify
- Lay out – describes what the visual part will look like
 - contains information on color, size, etc.
 - does not describe any dynamic behavior
- Dialogue/Domain Interface
 - exchanges data between application and dialogue
 - causes application and interface to be independent
- Domain – the core of the application
 - performs non-interface calculations
 - should have no knowledge of how data is displayed

Tool terminologies (cont'd)

- User Interface Management System (UIMS)
 - Provides mechanism for separating the user interface & application
 - Contains language for defining dialogue interface
- Interface Design Tool (IDT)
 - Provides an interactive editor to layout the interface
 - May provide limited dialogue definition
 - Produces code that represents layout and dialogue (if any)
- Specialized Languages
 - High level languages that abstracts away windowing system
- Layout Languages
 - Languages used to define position and attribute of interface objects
- Virtual Toolkits
 - Toolkits that are look and feel independent
 - Allows application to be developed once & moved between platforms
- Toolkits
 - Provide objects of user interface that define look and feel

UI Hall of Fame or Shame

- Model dialog

