
Build plan: from today's code to the demo

Written 2026-10-24, about 30 hours before we present. The spec is REALTIME_PIPELINE.md; this file says what is left, in what order, and what we drop if we run late. Every claim is tagged: **[ran]** checked by running something, **[code]** read in the code, **[assumed]** not checked. "ASK" marks what only a person can answer.

The plan on one page

The middle of the pipeline did not exist on Oct 24: nothing produced `dec.*` or `voice.say`, and nothing put `emg.raw` on the bus [ran]. Both ends work on their own: the camera reader (`lipread/`, merged in #11) and the call (`call/`: Twilio, Ink, Sonic, 23 tests) [ran]. So the first goal is one path through the middle, camera first, EMG joining through its own reader process:



Critical path: **bus → decoder v1 → first end-to-end call → replay of sessions 1 and 2 → lock model fit → session 3 metrics → rehearsal.** EMG joins the decoder only if a 4-channel SVR-1 checkpoint helps on replay; the demo does not wait for it.

When	Milestone	Done when
T-30h to T-24h	Shared bus (`bus/`), decoder + locking v1, logger + replay, `emg.raw` publisher, Claude service on the bus (done in code, this PR)	Unit tests pass with fake publishers; a logged fake session replays (done)
T-24h to T-18h	First live call on the laptop: camera → decoder → Claude → Sonic → Twilio	A teammate as the judge hears 5 mouthed sentences; latency in the log
T-18h to T-12h	Sleep in shifts. Replay sessions 1 and 2 through the decoder; fit lock weights and threshold	WER and mouth-to-lock on sessions 1 and 2 beat the hand-set weights
T-12h to T-8h	EMG joins, only if SVR-1 4-ch is ready and helps on replay; dashboard on real topics	WER with EMG ≤ without it on sessions 1 and 2
T-8h	**Code freeze.** Record session 3 in demo conditions, on battery	Session 3 logged; never trained on
T-8h to T-4h	Metrics on session 3; failure drills; README setup steps	The numbers table below filled in
T-4h to T-0	Rehearse the 2-minute call 3 times; charge with the Uno unplugged	3 clean runs in a row

Cut line. If behind at T-12h: drop EMG from the decoder (the fallback CLAUDE.md protects) and the dashboard's EMG traces. At T-6h: drop the learned lock model (keep the hand-set weights) and pace/effort. At T-2h: drop live Claude repairs (predictions only) and emotion. Never cut: camera → decoder → voice into the call, "Please repeat", logging.

Owners. Austin: decoder and locking sign-off, lock model fit, SVR-1, session 3. Evan: camera reader on the laptop, `laptop_check.sh` on battery. Frank: call, voice clone, dashboard on real topics. Thai: rig publisher, Claude service, prompt tuning on replayed logs. Agents write code against the contract below; one integrator (Austin) merges.

Where the code stands (Oct 24)

Part	Status	Evidence
Rig reader, `rig/filters.py`	works on the rig, untested here	`rig/reader.py`, `rig/filters.py:15` [code]
`emg.raw` on the bus	built: `rig/publish.py`; tested on fake chunks, not yet on the rig	`tests/test_rig_publish.py` [ran]
SVR-1 preprocessing	causal since #13 (`rig/filters.py` in order); `filtfilt` is left only in the `gaddy` baseline path	`svr/preprocess.py` [code]
SVR-1 on 4 channels	pretrained `SVR1_4ch` (Berkeley, epoch 107): WER 78.1 % greedy, homophene-10 72.3 %, phrase ID 96.0 %; not yet fine-tuned on Austin (recordings are on his laptop)	`checkpoints/NIGHT_REPORT.md` [ran]
Live EMG reader	built: `svr/serve.py` (`emg.read`, gap fill, reset on a pulled Uno, channel quality, calibration), `fusion/emg.py` (word support, look-alike settling, pace/effort); `SVR1_4ch` reads in 11 to 15 ms (2 to 8 s window) on the 5090, 160 ms on CPU, so it needs the GPU	`tests/test_svr_serve.py`, `tests/test_fusion_emg.py`, `svr.infer --bench` [ran]
`svr/infer.py`	built: replays recordings through the live reader into a buslog log for `fusion.evaluate --decode --emg`	`tests/test_infer.py` [ran]
Camera reader	merged (#11, `lipread/`); laptop numbers missing	`tests/lipread` [ran]
Final pass (beam + LM)	about 1.1 s for a 7.7 s clip on the 5090, even at beam 3	`live/MEASURED.md` [ran]
Fusion decoder, locking v1 (camera only, EMG hook)	built: `fusion/`; 0.3 ms per pass on a 200-frame tick; end to end over real processes with a fake camera	`tests/test_fusion.py` [ran]
Claude service	built on the shared bus; tested with a fake client, not yet against the live API	`tests/smoke_claude_service.py` [ran]
Call: Twilio, Ink, Sonic	works with fakes; outside git	`tests/call` 23 passed [ran]
Dashboard	prototype on sample data; outside git	`demo/dashboard/README.md` [code]

Part	Status	Evidence
Logger, replay, offline scorer	built: `buslog/`, `fusion/evaluate.py`	`tests/test_buslog.py`, `tests/test_evaluate.py` [ran]
Recorder	merged to main with the delivery styles (#10)	`git log origin/main` [ran]

`call/`, `tests/call/` and `demo/dashboard/` are now in the repo (keys and voice recordings stay out), on the TCP ports and bus v2; `voice.say` effort maps to Sonic volume as 1.0 = normal. `scripts/run_pipeline.py` starts everything. Still outside: `scripts/setup_envs.sh` (it builds venv-live from a lock file that isn't in the repo).

The EMG checkpoint, and when it joins. Fine-tune `W_svr1` from `SVR1_4ch` (better than `SVR1_4ch_artic` at look-alikes, which is EMG's job here) on sessions 1 and 2 on the 5090: `python -m svr.finetune --name W_svr1 --init-from $RECLAIM_WORKDIR/checkpoints/SVR1_4ch/model.pt`. It joins the demo only if session 3's judge top-1 is clearly above chance **and** `fusion.evaluate --decode --emg` (from `svr.infer`) gives WER with EMG ≤ without, on sessions 1 to 3; otherwise run `fusion.run --no-emg`. This gate matters: an end-to-end run with a random model showed bad EMG flipping look-alikes ("please" → "place"), because a lexicon look-alike is always camera-tied, so EMG decides it [ran].

The hard problems, decided

Each quotes the spec where it decides, and proposes where it is silent. Proposals need the owner's sign-off.

1. **Joint search over two models with different units.** The spec: camera and EMG grade every draft as it grows (REALTIME_PIPELINE.md, "The fusion decoder"). Proposal (Austin): v1 decodes camera greedy CTC into words and scores each word, not each piece. EMG joins at the word level: for each word span (camera frame times → EMG frames on the shared clock), SVR-1 scores the word and its look-alikes with its letter CTC over that span. This avoids aligning SentencePiece at 25 fps with letters at 86 fps inside one beam. Risk: a word the camera never proposed can only enter as a look-alike or a Claude prediction.
2. **Stable words across passes.** The spec is silent. v1: align each pass's words to the previous pass (difflib) and count unchanged passes; locked words are a pinned prefix that later passes cannot rewrite.
3. **Word finished, sentence ended.** The spec: the decoder moved on, the lips pause or the muscles go quiet; a sentence ends after about 0.5 s still. The camera reader already ends a segment after 0.5 s without mouthing and caps at 8 s with a 2 s overlap (`live/bus_schema.md`), so v1 uses segment end, and EMG quiet later.
4. **Lock model data.** The spec: every word on every pass is an example. Replaying a session through the decoder regenerates every pass's ingredients, so the logger only needs the inputs (`cam.*`, `emg.raw`, `partner.text`) and the prompt shown. The recorder stores each clip's video with per-frame `bus.now()` (`time.perf_counter()`) stamps (`recorder/README.md`), and the camera reader already replays a recorded clip on its own

clock (`lipread.run --replay CLIP --recorder-clock`, which keeps the recording's capture times) [code]. So a session becomes training data by running the camera reader over each clip into the logger, then replaying that log through the decoder and scoring `dec.lock` against the manifest's prompt (`fusion/evaluate.py`).

5. **Claude timing.** The spec: 0.3 s repair window; later repairs fix captions only. Claude Opus at low effort may take longer than 0.3 s; measure p50/p95 on the first live call. If p95 > 0.3 s, repairs become captions-only fixes and the window stays 0.3 s (voice speed comes first).
6. **GPU and battery.** Every number in the "Delays" table is an estimate until measured on the RTX 5060 on battery. Evan runs `python -m lipread.bench.laptop_check` and `python -m lipread.bench.tick_bench` on battery first thing, and Austin `python -m svr.infer --ckpt ... --bench` alongside (SVR-1 shares the GPU).
7. **One clock.** Everything is `bus.now()` (`time.perf_counter()`, precise on Windows) on the laptop: camera `frame_t`, EMG `t0` per batch, and the logger's receive time. Drift check: the replay compares `t_pub` with receive time.
8. **Phone, emotion, limits.** Twilio and Sonic both use μ-law 8 kHz, so there is no conversion (`call/README.md`). Frank found that Sonic ignores `generation_config` changes inside a context but honours inline `<speed>/<volume>/<emotion>` tags; Cartesia's build rule asks for `generation_config`, so use it per sentence and the tags only per word. ASK Frank: does the face's label set match Cartesia's emotions? Claude spend over rehearsals: ASK Thai to check the rate limit tier.

Interface contract (frozen for the agents)

- One bus package, `bus/`: ZeroMQ PUB/SUB on the loopback, msgpack, numpy as `{'nd': 1, dtype, shape, data}`, plus `v`, `seq`, `t_pub`. `bus` itself is the camera's (`bus/schema.md`); `bus.team` carries every other topic on the same wire format and checks `cam.*` with `bus.validate`.
- One TCP port per producer, each overridable by `RECLAIM_<NAME>_PUB`: `emg` 5555, `cam` 5556, `dec` 5557, `claude` 5558, `call` 5559, `svr` 5560 (topics in the Interfaces table of TEAM_TASKS_AND_INTERFACES.md).
- `voice.say` `pace` and `effort` are relative to normal: 1.0 is Austin's usual rate and effort; from EMG when a fresh `emg.read` exists, 1.0 otherwise.
- Tests use `inproc://`, a free loopback port or a temporary folder, never the real endpoints.

Numbers to show (Anthropic track)

Metric	From
WER on session 3: camera, camera + EMG, camera + EMG + Claude	replay of session 3 with each reader on or off, vs the prompts
Mouth-to-lock, mouth-to-audio	`cam.tick` frame times → `dec.lock` → `voice.say` → `timing.call`

Metric	From
Please-repeat rate	`dec.repeat` per sentence
First-try understanding	rehearsal calls: did the judge answer without asking again (by hand)

Failure drills (before rehearsal)

Pull the Uno: captions go on from the camera. Cover the mouth: "Please repeat", no guess. Turn off Wi-Fi to Claude: the voice keeps flowing, no repairs. Kill the Sonic stream: the call service reconnects or speaks whole sentences.

Sponsor checks

- Anthropic: show raw and fixed text side by side; the 4 metrics above; quote a laryngectomee or speech therapist (ASK: who has talked to one?); mention Claude Code built it.
- Cartesia: Sonic 3.6, Instant Voice Clone with consent, Ink for the judge, `generation_config`, no Line SDK; README setup steps (missing); no keys committed.

Pre-demo checklist

Battery full, charger unplugged with the Uno connected; signal check on all 4 channels; 1-minute calibration; `ANTHROPIC_API_KEY`, Cartesia and Twilio keys in the environment; Twilio number and tunnel up; logger running.