
Consistent but Blind? Image Removal Misranks Image Reliance in Medical Vision-Language Models

Tri Thai Huu
VinUniversity, Hanoi, Vietnam
thaitri2005@gmail.com

Code and data: https://github.com/thaitri2005/Medvlm-Image-Reliance


(a) "Is there spinal cord in this picture?" (SLAKE CT, gold: yes)



	with image	2 paraphrases	image removed	quadrant (removed)
MedGemma-4B	yes	yes, yes	yes	Dangerous
Gemma-3-4B	yes	yes, yes	"Please provide the picture."	Ideal

Gemma-3 asks for the image; its forced yes/no choice is "no", so the probe counts it as image-reliant.

(b) "Does the picture contain heart?" (SLAKE CT, gold: yes)



	with image	2 paraphrases	image removed	wrong image	quadrant (removed)	quadrant (wrong)
MedGemma-4B	yes	yes, yes	yes	no	Dangerous	Ideal
Gemma-3-4B	yes	yes, yes	no*	yes	Ideal	Dangerous

** only 51% of first-token probability on yes/no. Same question, opposite verdicts from the two probes.*

Figure 1. **Two real questions, two models, two probes.** (a) Without the image, medically tuned MedGemma-4B still answers, and the consistent-but-dangerous taxonomy calls the answer DANGEROUS; its general-purpose twin Gemma-3-4B asks for the image, and its forced yes/no choice is scored as image-reliant (IDEAL). (b) On the same question, removing the image and showing a wrong image (whose correct answer is *no*) give opposite verdicts for both models; MedGemma follows the image when one is present. Real model outputs; SLAKE CT images (CC-BY-4.0) [13].

Abstract

The consistent-but-dangerous taxonomy flags a medical vision-language model (VLM) answer as DANGEROUS *when it is stable under paraphrase and unchanged when the image is removed. We ask whether this image-removal test can rank models by how much they use the image. On a matched pair, MedGemma-4B and its general-purpose twin Gemma-3-4B, we pose 3,365 questions over 907 CT, MRI, X-ray and pathology images under five probes, with pre-registered endpoints and three probes registered before they were run. Image removal ranks MedGemma as the less image-reliant model: its* DANGEROUS *share is 13.7 points higher [10.0, 17.5]. All three probes that keep an image in the input rank it as more reliant: MedGemma changes its answer more often when the image is swapped (+5 points), blacked out (+20), or replaced by one on which the same question has the opposite answer (73% vs. 25%, +48). Two confounds explain the reversal. Forced to answer yes or no without an image, Gemma-3 would rather ask for the image on 29% of questions, and its forced answers there are unrelated to its answers with the image; allowed to say "unknown", both models decline on at least 93%. And MedGemma's blind answers are informative, so they match its image answers wherever image and prior agree: its excess* DANGEROUS *answers are all correct. The* DANGER-

OUS *share also rests on a chance floor of 36–42% on yes/no questions, and image reliance does not flag wrong answers (AUROC 0.51). Image-removal results should be checked with in-format probes before they are read as a model ignoring the image.*

1. Introduction

A model that answers a question about an image without using the image is not doing visual question answering, however accurate it is. In general-domain VQA this concern produced balanced benchmarks and prior-robust splits [1, 8]. Medical VQA is still mostly evaluated by accuracy, where it matters more: a correct answer reached from language priors will be wrong on exactly the patients whose images are unusual.

Accuracy cannot separate *seeing* from *guessing well*, and consistency under rephrasing cannot either: a model that ignores the image is often *more* consistent, because nothing visual perturbs it [20]. Sadanandan and Behzadan [19] therefore crossed the two per sample. *Consistent* means the answer is stable under paraphrase; *image-reliant* means it changes when the image is removed. This gives four quadrants: IDEAL (consistent, reliant), FRAGILE, DANGEROUS (consistent but unchanged without the image) and WORST. On chest X-rays they found that fine-tuning for consistency moves most answers into DANGEROUS.

A taxonomy like this invites comparisons between models, and a comparison is only as good as the probe behind it. Removing the image changes the input format: a model asked about an image that is not there may refuse, answer from priors, or guess, and none of these is the same as ignoring an image that is present. We therefore ask whether image removal ranks two models the same way as probes that keep an image in the input. We audit MedGemma-4B [21], a small open medical VLM, against Gemma-3-4B [7], which has the same architecture and size but a general-purpose post-training, on CT, MRI, X-ray and pathology questions from three public benchmarks. The design, endpoints and exclusions were frozen before the main run; three further probes were registered after it and before they were run.

Figure 2 summarizes the answer. Image removal says MedGemma uses the image less than Gemma-3. A wrong image, a black image and an image on which the same question has the opposite answer all say it uses the image more. We trace the disagreement to two properties of image removal: it turns refusals into scored answers, and it cannot distinguish a model that ignores the image from one whose prior agrees with it.

Contributions.




Figure 2. **The probes rank the two models in opposite directions.** Share of yes/no answers that change when the image is altered, by probe (95% CIs clustered by image; right: MedGemma − Gemma-3 in points). A model that uses the image should change its answer when the image changes. Only image removal, the probe that defines the taxonomy, ranks Gemma-3 as the more image-reliant model.

- A side-by-side comparison of four reliance probes on the same questions and an architecture-matched model pair, showing that image removal ranks the pair opposite to three in-format probes. Each probe has precedent [15, 19, 23]; to our knowledge their rankings of models have not been compared.
- Two confounds that explain the reversal, each with direct evidence: refusal under a forced yes/no format, and agreement between a model's prior and the image.
- Two corrections to the DANGEROUS share: its chance floor on yes/no questions (with Cohen's κ), and a paired split into correct and wrong DANGEROUS answers.
- A pre-registered, open pipeline across three datasets and four modalities, with a paraphrase set screened pair by pair for equivalence and a finding that bf16 batching perturbs log-probabilities by up to 1 nat.

2. Related Work

Language priors in VQA. Balanced pairs [8] and changing-prior splits [1] showed that general VQA models exploit answer priors; text-only baselines are the medical analogue.

Does a medical VLM use the image? PSF-Med [20] measured paraphrase flip rates across medical VLMs on chest X-rays and noted that low flip rates often come with high text-only agreement. The quadrant taxonomy [19] defines reliance by image removal and corroborates it with

a KL-divergence score, a black image and random image swaps; on their models these checks agreed with image removal. Zafar *et al*. [23] build blank, pixel-shuffled, absent and CLIP-retrieved hard-negative images to define reliance metrics and train a model against them. Lotfinia *et al*. [15] swap and occlude chest radiographs and find that model class (medical or general) does not predict image use; a question-only medical model scores close to multimodal ones. Pathology VLMs reach high accuracy without the image [25], and attention-based studies find that medical MLLMs often attend to irrelevant regions [14]. Grounding inputs can even hurt closed-ended accuracy [3]; HEAL-MedVQA [16] and MedHEval [2] benchmark localization and hallucination. These works use one probe or treat several as interchangeable; we compare the conclusions they reach about the same pair of models.

Answering without the evidence. MedVIGIL [11] tests whether models refuse when visual evidence is broken, and Vohra [22] finds that frontier VLMs confabulate diagnoses for images that were never attached. We find the converse for two small open models (they decline almost always when allowed to) and show what this does to a reliance probe that forces an answer.

Selective prediction. Ranking answers by a score and abstaining on the lowest is evaluated by AUROC and risk–coverage [6]; we use it to ask whether reliance flags errors.

3. Method

3.1. Data

SLAKE [13] (English; CT, MRI, X-ray; 2,114 questions from test and validation, the only dataset with modality labels; validation is added so each modality has 53–82 images). **VQA-RAD** [12] (radiology, clinician-written; all 451 test questions, from the original release). **PathVQA** [9] (pathology, generated from textbook captions; 600 yes/no and 200 open test questions sampled with a fixed seed). A question is yes/no if its gold answer is *yes* or *no*. The **primary analysis set** is the 1,206 yes/no *test* questions on 670 images. Sampling, partner images and image hashes are fixed in committed manifests (SHA-1 seeded), so every run sees identical inputs.

3.2. Models

MedGemma-4B (`google/medgemma-4b-it`) is an open medical VLM whose SigLIP-style encoder [24] and language model were further trained on medical data; its model card lists SLAKE (split unstated) but not VQA-RAD or PathVQA among training sources. **Gemma-3-4B** (`google/gemma-3-4b-it`) shares its architecture and size. The two differ in their whole post-training, not only in medical data, so we compare *checkpoints* and do not attribute differences to medical data alone. Both run unquantized in bf16 on one 16 GB GPU (quantization would perturb the probabilities we audit) and receive byte-identical prompts: a fixed system line, the question, and "Answer with only 'yes' or 'no'." or "Answer with a single word or short phrase."

3.3. Probes

Every question is posed with its image (**orig**) and with screened paraphrases (**para**$_k$, original image; Sec. 3.5). Reliance is probed five ways, each differing from *orig* only in the image or the instruction:

- **Image removed** (*noimg*): image tokens omitted, text identical; the reference probe of the taxonomy [19].
- **Wrong image** (*shuf*): another image from the same dataset and modality, chosen by a hash of the question ID.
- **R1, black image**: a black image in the image slot, in format but without content.
- **R2, "unknown" allowed**: image removed, and the instruction adds "If this cannot be determined without seeing the image, answer 'unknown'."
- **R3, opposite-answer image**: another image of the same dataset and modality on which the *same* question has the opposite gold answer. A model that uses the image must change its answer. Partners exist for 367 SLAKE yes/no questions (130 images), whose templated questions recur across images.

The first two belong to the pre-registered main run. R1–R3 were registered after it, with directional hypotheses (H6: MedGemma's answers survive a black image more; H7: with "unknown" allowed MedGemma still declines less; H8: MedGemma follows opposite-answer images more), and run afterwards.

3.4. Measures

Yes/no answers come from one forward pass: $P(\text{yes}) = \sigma(\text{LSE}_{t\in Y}\,\ell_t - \text{LSE}_{t\in N}\,\ell_t)$ over the single-token variants of *yes* and *no*; the first-token mass $m = P(Y) + P(N)$ is logged as a format check. **Open answers** use greedy decoding and token-F1 $\geq$ 0.5 after normalization, with an opposite-term guard (left/right, upper/lower, *etc*. never match). **Consistent**: the answer on the first two valid paraphrases equals the *orig* answer. **Reliant** under a probe: the probe answer differs from *orig*. The **quadrant** follows from (consistent, reliant). **Refusal**: $m < 0.5$, *i.e*. most first-token mass is on neither *yes* nor *no*; free generation confirms these are requests for the image (Fig. 1a). **Image PMI** of an answer $\hat{y}$ is $\log p(\hat{y} \mid I, q) - \log p(\hat{y} \mid \varnothing, q)$. **Chance correction**: Cohen's κ [4] between *orig* and probe answers; the *chance floor* of the DANGEROUS share is $P(\text{consistent}) \cdot p_e$, where p_e is the agreement expected from the two answer

distributions alone.

3.5. Paraphrase construction and screening

Paraphrase consistency is meaningful only if a paraphrase cannot change the correct answer. Candidates come from Qwen2.5-3B-Instruct [18] (greedy; five styles) and from two deterministic templates that copy every content word ("Is there X?"→"Is X present?"). A rule validator rejects changes to laterality, negation and absence words, quantities, antonyms, imaging planes, question form, answer leakage, near-copies and length. Two audit rounds accepted 81% and 83%, below the pre-specified 85%, so we tightened the rules, excluded a "plain language" style, and **judged every unique rule-valid (question, paraphrase) pair**, 4,890 in total, against a written rubric (Appendix A). The judge was an LLM (Claude); see Sec. 6. 1,208 pairs were rejected, each with a recorded reason (*e.g.* *mass→lesion*, *is enlarged→can be enlarged*), and unjudged pairs are rejected by construction. 84% of the primary-set questions retain at least two valid paraphrases; quadrant analyses use those (1,012 questions, 600 images).

3.6. Statistics and pre-registration

Hypotheses, endpoints, tests and exclusions were frozen before the main run [17]; every later change is listed in Appendix B, and post-hoc analyses are labeled as such. Several questions share an image, so all intervals are percentile 95% CIs from a cluster bootstrap over images [5] ($B = 2000$) with two-sided bootstrap p-values. Endpoints (Tab. 2): **P1a–c** blind accuracy minus the majority-answer prior per dataset and **P2** AUROC(image PMI) − AUROC(confidence), one Holm family [10]; **P3** the paired difference in DANGEROUS share, MedGemma − Gemma-3; and **H6–H8**, a second Holm family. A finding is called robust only if its sign holds across a grid of F1 thresholds (0.3/0.5/0.8), paraphrase counts (1/2/3) and "strong" flips.

4. Results

Both runs completed (18,896 calls per model, plus 3,535 per model for R1–R3). Our pipeline reproduces MedGemma's published SLAKE score (token-F1 70.2 [67.5, 72.7] *vs.* 72.3 on the model card; Gemma-3: 45.1 *vs.* 40.2), and the yes/no format mass with the image is ≥ 0.997 in every dataset. MedGemma is the more accurate model with the image (Tab. 1), by 18 points on SLAKE and 25 on VQA-RAD yes/no.

4.1. The reference probe: MedGemma looks more consistent but blind

Under image removal MedGemma's DANGEROUS share is 50.6/46.8/56.5% (PathVQA/SLAKE/VQA-RAD) against 43.2/28.1/31.0% for Gemma-3 (Fig. 3, left). The paired difference, **P3** $= +13.7$ **points** [10.0, 17.5] ($p < 0.001$; 1,012 questions, 600 images), is positive in every dataset (PathVQA +7.5 [2.6, 12.3], SLAKE +18.6 [12.2, 24.9], VQA-RAD +25.6 [14.7, 36.5]) and in every cell of the sensitivity grid. MedGemma is also the more consistent model (paraphrase flip rate 6.8% *vs.* 13.6% on SLAKE). Read at face value, the medical checkpoint is more often stable, confident and blind.

4.2. In-format probes reverse the ranking

Figure 2 places all four probes on one scale, the share of answers that change. Image removal is the only one under which Gemma-3 changes more (-6.1 [-9.5, -2.7] points). The three in-format probes all say the opposite.

Opposite-answer image (R3). This is the most direct test: the question is unchanged and the image now calls for the other answer. MedGemma follows the image on 72.8% [68.1, 77.0] of swaps and Gemma-3 on 24.8% [20.4, 29.3] (H8, +48.0 points), so MedGemma is right on the new image 86% of the time and Gemma-3 61%. The gap holds for CT (75 *vs.* 26%), MRI (57 *vs.* 26%) and X-ray (81 *vs.* 8%; Fig. 4) and when 40 PathVQA and VQA-RAD swaps are added (69.8 *vs.* 24.8%, exploratory).

Black image (R1). H6 predicted that MedGemma's answers would survive a black image more often; it failed in the opposite direction. Gemma-3 keeps the answer it gave with the real image on 72.9% of questions, MedGemma on 52.6%; chance-corrected, $\kappa = 0.33$ [0.28, 0.39] *vs.* 0.11 [0.06, 0.17]. Under this probe Gemma-3 is the more DANGEROUS model by 14.0 points [9.4, 18.6]. The answers show why: on a black image MedGemma's yes-rate drops from 58% to 28% (it reads an empty image as absent findings), while Gemma-3's rises from 64% to 84%, tracking the question rather than the image.

Wrong image. A random image of the same modality changes MedGemma's answer more often (+5.1 points [1.7, 8.5]); the DANGEROUS share under this probe does not differ (-0.7 [-4.4, 3.2]). It is the weakest probe, because a random partner often has the same correct answer: where the partner image carries the same question, *all 23* chest X-ray partners had the same answer (CT 58%, MRI 60%). This explains why the modality ordering of the DANGEROUS share reverses between probes (Fig. 5): X-ray is the least DANGEROUS modality under image removal (33.1%) and the most under a wrong image (75.4%). The two probes agree poorly (κ between their reliance labels -0.11 to 0.23).

4.3. Why image removal misranks

Refusal. The pre-registered format check ($m \geq 0.9$) failed in exactly one condition, image removed. Free gen-

Table 1. Accuracy (%) on test questions. Yes/no: with the image, without it ("none"), with a wrong image, against the majority-answer prior. Open: token-F1 ≥ 0.5 with the image. CIs are in the repository.

		MedGemma-4B (yes/no)			Gemma-3-4B (yes/no)			Open, with image	
Dataset	Prior	image	none	wrong	image	none	wrong	MedGemma	Gemma-3
PathVQA (pathology)	52.2	65.5	57.2	51.0	63.2	53.5	46.7	10.5	4.0
SLAKE (CT/MRI/X-ray)	50.7	**86.5**	47.6	67.0	68.7	47.6	62.3	66.7	37.1
VQA-RAD (radiology)	53.0	**81.3**	60.6	70.5	56.2	55.4	60.2	46.0	33.5




Figure 3. Quadrant composition of yes/no answers (test). Left: reliance probed by removing the image (the reference definition). Right: by a wrong image of the same modality. Shares are raw; on yes/no questions they include chance agreement (Sec. 4.4) and correct answers (Sec. 4.3).

Table 2. Confirmatory tests. P1–P2 concern MedGemma (P2 on the model's own answer, Appendix B); P3 and H6–H8 are paired differences, MedGemma − Gemma-3 (points, or κ for H6). 95% CIs clustered by image.

	Test	Estimate	Outcome
Frozen before the main run			
P1a	blind − prior, PathVQA	$+5.0\,[0.9, 8.8]$	p_{Holm}=.042
P1b	SLAKE	$-3.1\,[-7.8, 1.8]$	n.s.
P1c	VQA-RAD	$+7.6\,[0.4, 14.5]$	p_{Holm}=.072
P2	AUROC: PMI − conf.	$-0.20\,[-0.25, -0.15]$	worse
P3	DANGEROUS, image removed	$+13.7\,[10.0, 17.5]$	$p<.001$
Registered after the main run, before the probes			
H6	κ(image, black) > 0	$-0.22\,[-0.30, -0.14]$	reversed
H7	declines, "unknown" < 0	$-6.7\,[-8.2, -5.3]$	supported
H8	follows opp. image > 0	$+48.0\,[41.9, 53.8]$	supported

eration explains it: "*Please provide the picture. I need to see the image to determine if there is a spinal cord present*" (Gemma-3). Gemma-3 would rather refuse on 354 of the 1,206 questions and MedGemma on 219 (Fig. 6; 14/41/50% *vs.* 10/26/27% by dataset). On those questions the forced answer is mostly *no* and unrelated to the model's answer with the image ($\kappa = -0.01$ for Gemma-3, 0.04 for MedGemma), so 53–55% of them count as "image-reliant".




Figure 4. Probe R3: share of answers that change when the image is replaced by one on which the same question has the opposite correct answer (SLAKE yes/no, test+validation; 95% CIs by image).

Allowed to say "unknown" (R2), MedGemma declines on 93.0% and Gemma-3 on 99.7%. H7's direction holds (-6.7 points) and MedGemma keeps a small tendency to answer blind, concentrated in PathVQA (12% answered), but most




Figure 5. DANGEROUS share by modality (SLAKE yes/no, test and validation pooled as pre-specified; 95% CIs by image). The modality ordering reverses between probes.




Figure 6. Share of yes/no questions on which the model declines to answer when the image is removed ($m < 0.5$; 95% CIs by image). Top: the main run's instruction ("Answer with only yes or no"). Bottom: probe R2, whose instruction allows "unknown".

of the forced-format difference of 11.2 points disappears.

Agreement between prior and image. Refusal is not the whole story: on the 436 questions where both models answer without the image ($m \geq 0.9$), P3 is still +8.0 [2.9, 13.3]. Here MedGemma's blind answers are informative. It beats the majority-answer prior on PathVQA (P1a, +5.0; +11.9 [7.1, 16.6] among questions it answers), and its no-image answers agree with its image answers beyond chance ($\kappa = 0.21$ *vs.* 0.11 for Gemma-3, each




Figure 7. The MedGemma − Gemma-3 difference in DANGEROUS share under each probe and subset, and split by whether the DANGEROUS answer is correct (paired; 95% CIs by image).

on the questions it answers). A model that looks at the image and whose prior predicts what the image shows gives the same answer with and without it, and image removal scores that as blind. The correctness split shows that this is what MedGemma's excess consists of (Fig. 7, bottom): DANGEROUS-and-correct is 39.2% *vs.* 25.1% (+14.1 [11.1, 17.1]), while DANGEROUS-and-wrong, the cell that would mislead a user, is 11.3% *vs.* 11.7% (−0.4 [−2.7, 2.0]). R3 removes this case by construction, and there MedGemma follows the image. The P1 margin also argues against memorization: it appears on PathVQA and VQA-RAD, which the model card does not list as training data, and not on SLAKE, which it does.

4.4. The chance floor

An answer counts as image-independent whenever the no-image answer equals the with-image answer, which on yes/no questions happens often by chance. On the P3 set MedGemma's answers are unchanged without the image 58.6% of the time against 49.1% expected from its answer distributions alone (Gemma-3: 49.7% *vs.* 45.7%). Combined with consistency this gives a **chance floor of 41.5% (MedGemma) and 35.8% (Gemma-3)**, against observed DANGEROUS shares of 50.5% and 36.8%. About 6 of the 13.7 points of P3 are the difference in floors, partly because MedGemma is more consistent (84.5% *vs.* 78.4%), a desirable property the metric counts against it. Corrected for chance the image-removal effect remains, $\Delta\kappa = +0.112$ [0.044, 0.180], but it is the size of a consistency difference, not of a model that ignores images.

4.5. Does image reliance flag wrong answers?

If image-independent answers were the unreliable ones, image reliance could serve as a warning signal. Ranking each yes/no answer by its image PMI separates



Figure 8. AUROC for ranking correct above incorrect yes/no answers (test, 95% CIs): the model's confidence *vs*. label-free image reliance under each probe.

correct from incorrect answers at chance (Fig. 8; AUROC **0.513** [0.473, 0.552] for MedGemma, 0.532 for Gemma-3), while the model's own confidence reaches 0.709 and 0.603 (P2: better by 0.197 [0.145, 0.250] and 0.071 [0.026, 0.116]). The wrong-image variant is no better (0.524, 0.536). Whether a model leaned on the image does not tell us whether it was right.

5. Discussion

What image removal measures. Removing the image asks a model a question about an image that is not there. Its answer depends on whether it will answer at all and on how good its priors are, and only then on whether it would have used the image. In our pair these two factors point the same way: the general checkpoint refuses more and has weaker priors, so it looks more image-reliant, while every probe that keeps an image in the input finds the medical checkpoint more reliant, by up to 48 points. The original study's corroborating checks (black image, random swaps) agreed with image removal on its chest X-ray models [19]; on our models and data they do not. Agreement between probes therefore has to be checked for each comparison rather than assumed, and a DANGEROUS share is underspecified without its probe.

Where the residual risk is. MedGemma's extra DANGEROUS answers are correct, and the stable, image-independent and wrong cell is the same for both models. The remaining concern is that MedGemma's errors, fewer overall (25.7% *vs*. 37.6%), are more often of this kind (44% *vs*. 31%, +12.9 [6.0, 19.9]), so a consistency or reliance check would miss them. It also answers without an image on 7% of questions even when allowed to decline.

Recommendations for reliance audits. (1) Probe reliance in format, ideally with an image that calls for a different answer, and report agreement between probes. (2) Report the DANGEROUS share with its chance floor or as κ; on balanced yes/no data a model whose blind answers are pure noise is about 50% "not reliant". (3) Split DANGEROUS by correctness. (4) Allow abstention, and treat declining without an image as desirable rather than as a format failure.

6. Limitations

One model pair shows that image removal *can* misrank models, not how often it does; more pairs are needed, and the two checkpoints differ in their whole post-training, not only in medical data. The probes were registered after the main results were known (before running them), and one of three predictions failed. R3 is limited to SLAKE, where questions recur across images. SLAKE is in MedGemma's training data (split unstated). Refusal is inferred from first-token mass and confirmed on a sample by free generation, not annotated per question. Paraphrase equivalence was judged by an LLM and **was not validated by human raters**; this is the main limitation of the consistency measure, and an LLM judge may share blind spots with the paraphraser. PathVQA questions are auto-generated and often ungrammatical. The correctness split, the chance correction and the refusal split were added after seeing the results. All 330 pilot questions used to tune the design are inside the evaluation set; excluding them leaves every conclusion unchanged (P1a +6.3 [2.4, 10.6], P3 +12.9 [8.9, 17.1]). Benchmark VQA is not clinical use, and nothing here is a clinical claim.

7. Implementation Details

Pipeline. A Python package (`medvlm`) with a command-line interface: `prepare` (download, deterministic sampling, SHA-checked images), `paraphrase` (generation plus rule and judgment validation, fail-closed), `pipeline` (resumable inference in parts with checkpoint analysis), `probes` (R1–R3), `analyze`, `compare` and `posthoc` (all tables and figures here). Configs layer base, profile, model and hardware settings. Each job is one (question, condition) pair keyed by ID, so interrupted runs resume without recomputation, and every run records its config, commit and library versions.

Inference. PyTorch 2.11 and Hugging Face Transformers 5.19, bf16, SDPA attention, one RTX 4080 SUPER (16 GB). A full run is 18,896 calls per model at 0.23 s per call (about 75 minutes, 8.2 GB peak). During pre-flight we found that in bf16 the *batch size* changes teacher-forced log-probabilities by up to 1.09 nats (median 0.17) even with identical, unpadded inputs, while $P(\text{yes})$ changes by at most 0.008. An fp32 output head did not remove it, so the cause is inside the network. All runs therefore use batch size

1, which costs about 1.5× throughput. A regression check reproduced the T4 pilot on the new GPU (98.5% identical answers, mean $|\Delta P(\text{yes})| = 0.004$).

Testing. 96 unit tests and 7 real-model tests cover, among others, scoring edge cases, paraphrase rules (including each failure class found in the audit), batching equivalence, crash-safe resume, the coverage of the clustered bootstrap (by simulation), the test-split restriction of P3, chance agreement of κ, and the construction of opposite-answer partners.

8. Conclusion

Is a small medical VLM consistent but blind? By the image-removal test it looks that way, more than its general-purpose twin. By every test that keeps an image in the input it is the opposite: the medical checkpoint follows the image more, by up to 48 points. Image removal measures whether a model answers without an image and whether its priors agree with the image, and both differ between the two checkpoints. Reliance audits that compare models need informat probes, chance correction and a correctness split.

References

[1] Aishwarya Agrawal, Dhruv Batra, Devi Parikh, and Aniruddha Kembhavi. Don't just assume; look and answer: Overcoming priors for visual question answering. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2018. 2

[2] Aofei Chang, Le Huang, Parminder Bhatia, Taha Kass-Hout, Fenglong Ma, and Cao Xiao. MedHEval: Benchmarking hallucinations and mitigation strategies in medical large vision-language models. *arXiv preprint arXiv:2503.02157*, 2025. 3

[3] Xupeng Chen, Binbin Shi, Chenqian Le, Qifu Yin, Lang Lin, Haowei Ni, Ran Gong, and Panfeng Li. Why does grounding hurt medical VQA? benchmarking, diagnosis, and fine-tuning of vision-language models. *arXiv preprint arXiv:2604.27720*, 2026. 3

[4] Jacob Cohen. A coefficient of agreement for nominal scales. *Educational and Psychological Measurement*, 20(1):37–46, 1960. 3

[5] Christopher A. Field and Alan H. Welsh. Bootstrapping clustered data. *Journal of the Royal Statistical Society: Series B*, 69(3):369–390, 2007. 4

[6] Yonatan Geifman and Ran El-Yaniv. Selective classification for deep neural networks. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2017. 3

[7] Gemma Team. Gemma 3 technical report. *arXiv preprint arXiv:2503.19786*, 2025. 2

[8] Yash Goyal, Tejas Khot, Douglas Summers-Stay, Dhruv Batra, and Devi Parikh. Making the V in VQA matter: Elevating the role of image understanding in visual question answering. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2017. 2

[9] Xuehai He, Yichen Zhang, Luntian Mou, Eric Xing, and Pengtao Xie. PathVQA: 30000+ questions for medical visual question answering. *arXiv preprint arXiv:2003.10286*, 2020. 3

[10] Sture Holm. A simple sequentially rejective multiple test procedure. *Scandinavian Journal of Statistics*, 6(2):65–70, 1979. 4

[11] Hanqi Jiang, Junhao Chen, Mingyu Kang, Hyeokjae Kwon, Yi Pan, Lifeng Chen, Weihang You, Haozhen Gong, Ruiyu Yan, Jinglei Lv, Lin Zhao, Hui Ren, Quanzheng Li, Tianming Liu, and Xiang Li. MedVIGIL: Evaluating trustworthy medical VLMs under broken visual evidence. *arXiv preprint arXiv:2605.07919*, 2026. 3

[12] Jason J. Lau, Soumya Gayen, Asma Ben Abacha, and Dina Demner-Fushman. A dataset of clinically generated visual questions and answers about radiology images. *Scientific Data*, 5:180251, 2018. 3

[13] Bo Liu, Li-Ming Zhan, Li Xu, Lin Ma, Yan Yang, and Xiao-Ming Wu. SLAKE: A semantically-labeled knowledge-enhanced dataset for medical visual question answering. In *IEEE International Symposium on Biomedical Imaging (ISBI)*, 2021. 1, 3

[14] Guimeng Liu, Tianze Yu, Somayeh Ebrahimkhani, Lin Zhi Zheng Shawn, Kok Pin Ng, and Ngai-Man Cheung. How do medical MLLMs fail? A study on visual grounding in medical images. In *International Conference on Learning Representations (ICLR)*, 2026. 3

[15] Mahshad Lotfinia, Sebastian Ziegelmayer, Lisa Adams, Tri-Thien Nguyen, Daniel Truhn, Andreas Maier, and Soroosh Tayebi Arasteh. Vision-language models for chest radiography do not always need the image. *arXiv preprint arXiv:2606.17710*, 2026. 2, 3

[16] Dung Nguyen, Minh Khoi Ho, Huy Ta, Thanh Tam Nguyen, Qi Chen, Kumar Rav, Quy Duong Dang, Satwik Ramchandre, Son Lam Phung, Zhibin Liao, Minh-Son To, Johan Verjans, Phi Le Nguyen, and Vu Minh Hieu Phan. Localizing before answering: A hallucination evaluation benchmark for grounded medical multimodal LLMs. In *International Joint Conference on Artificial Intelligence (IJCAI)*, 2025. arXiv:2505.00744. 3

[17] Brian A. Nosek, Charles R. Ebersole, Alexander C. DeHaven, and David T. Mellor. The preregistration revolution. *Proceedings of the National Academy of Sciences*, 115(11): 2600–2606, 2018. 4

[18] Qwen Team. Qwen2.5 technical report. *arXiv preprint arXiv:2412.15115*, 2024. 4

[19] Binesh Sadanandan and Vahid Behzadan. Consistent but dangerous: Per-sample safety classification reveals false reliability in medical vision-language models. In *CVPR Workshop on Medical Reasoning with Vision Language Foundation Models*, 2026. arXiv:2603.20985. 2, 3, 7

[20] Binesh Sadanandan and Vahid Behzadan. PSF-Med: Measuring and explaining paraphrase sensitivity in medical vision language models. *arXiv preprint arXiv:2602.21428*, 2026. 2

[21] Andrew Sellergren, Sahar Kazemzadeh, Tiam Jaroensri, Atilla Kiraly, Madeleine Traverse, et al. MedGemma technical report. *arXiv preprint arXiv:2507.05201*, 2025. 2

[22] Siddharth Vohra. Hearsay: Vision-language medical diagnoses without an image. *arXiv preprint arXiv:2607.26886*, 2026. 3

[23] Anas Zafar, Leema Krishna Murali, Siddhant Bharadwaj, Ashish Vashist, and Jia Wu. Do medical vision language models actually see? A counterfactual grounding framework and hard-negative contrastive training for visually-reliant medical VLMs. *arXiv preprint arXiv:2607.03647*, 2026. 2, 3

[24] Xiaohua Zhai, Basil Mustafa, Alexander Kolesnikov, and Lucas Beyer. Sigmoid loss for language image pre-training. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, 2023. 3

[25] Chengyang Zhang et al. Do pathology vision-language models truly see pathology? *arXiv preprint arXiv:2607.21065*, 2026. 3

A. Paraphrase equivalence rubric

A pair is **accepted** only if it asks exactly the same thing, so the correct answer cannot differ. Allowed: perception framing ("can X be seen", "is X visible", "can X be seen to be enlarged"), exact synonyms (clavicle/collarbone, encephalon/brain, intravenous contrast/dye), reordering. **Rejected**: a fact turned into a possibility or capability ("Is the heart enlarged?"→"Can the heart be enlarged?"); a broadened or narrowed term (mass→lesion, organs→structures, digestive system→GI tract, skull fracture→cranial injury); a changed scope or presupposition ("Do the organs exist in X"→"Are there organs in X"); added qualifiers, findings or modality ("bilaterally", "on imaging studies", "radiograph"); a reversed or changed relation ("does A show B"→"is A associated with B", "mass lateral to X"→"X lateral to mass"); antonyms (healthy↔unhealthy, coronal→transverse); two questions in one; malformed text. Rejections by class: relation 447, term 364, modal 106, added content 102, organ→structure 47, generic collapse 30, polarity 19, scope 9 (plus template-pass rejections).

B. Deviations from the pre-registration

Every change made after the analysis plan was frozen, with its reason.

Change	Reason and effect
Batch size 1 for all runs	bf16 batching shifts teacher-forced log-probabilities by up to 1.09 nats; decided before the main run.
Validator v2/v3, *plain* style excluded, full equivalence screen, template styles	Audit acceptance below the pre-specified 85% line; before the main run.
Format stop-the-line rule triggered (image removed only)	Model behavior (refusal), not a pipeline error; forced-choice $P(\text{yes})$ kept, refusal reported, P1/P3 re-estimated without refusals.
P2 computed on the model's answer $\hat{y}$	The registered formula used the gold answer, which is unavailable at deployment and predicts correctness by construction.
P3 restricted to the test split	An analysis bug had pooled the validation split; fixed to the registered set.
Chance correction, correctness split, refusal split, answer-change comparison across probes	Added after the run; descriptive, reported next to the registered estimates.
Robustness probes R1–R3	Registered after the main run, before running them (PLAN.md §15); R3 restricted to SLAKE as registered (the run also covered 40 other swaps, reported as exploratory).