

Name:Prithviraj Thakur

PRN:202501040026

PRACTICAL: 02

2.1.1. List operations

08:32

Write a Python program that implements a menu-driven interface for managing a list of integers. The program should have the following menu options:

1. Add
2. Remove
3. Display
4. Quit

The program should repeatedly prompt the user to enter a choice from the menu.

Depending on the choice selected, the program should perform the following actions:

- Add: Prompts the user to enter an integer and add it to the integer list. If the input is not a valid integer, display "Invalid input".
- Remove: Prompts the user to enter an integer to remove from the list. If the integer is found in the list, remove it; otherwise, display "Element not found". If the list is empty, display "List is empty".
- Display: Displays the current list of integers. If the list is empty, display "List is empty".
- Quit: Exits the program.
- The program should handle invalid menu choices by displaying "Invalid choice". Ensure that the program continues to prompt the user until they choose to quit (option 4).

```
# listOps.py
```

```
int_list = []
```

```
while True:
```

```
    print("1. Add")
```

```
    print("2. Remove")
```

```
    print("3. Display")
```

```
    print("4. Quit")
```

```
    choice = input("Enter choice: ")
```

```
    if choice == '1': # Add
```

```
        value = input("Integer: ")
```

```
        try:
```

```
            num = int(value)
```

```
            int_list.append(num)
```

```
            print("List after adding:", int_list)
```

```
        except ValueError:
```

```
            print("Invalid input")
```

```
    elif choice == '2': # Remove
```

```
        if not int_list:
```

```
            print("List is empty")
```

```
        else:
```

```
value = input("Integer: ")

try:
    num = int(value)
    if num in int_list:
        int_list.remove(num)
        print("List after removing:", int_list)
    else:
        print("Element not found")
except ValueError:
    print("Invalid input")

elif choice == '3': # Display
    if not int_list:
        print("List is empty")
    else:
        print(int_list)

elif choice == '4': # Quit
    break

else:
    print("Invalid choice")
```


Explorer

Average time

0.072 s

71.67 ms

Maximum time

0.089 s

89.00 ms

2 out of 2 shown test case(s) passed

1 out of 1 hidden test case(s) passed

Debugger

Integer: 11	Integer: 11
List after removing: [25]	List after removing: [25]
1. Add	1. Add
2. Remove	2. Remove
3. Display	3. Display
4. Quit	4. Quit
Enter choice: 2	Enter choice: 2
Integer: 25	Integer: 25
List after removing: []	List after removing: []
1. Add	1. Add
2. Remove	2. Remove
3. Display	3. Display
4. Quit	4. Quit
Enter choice: 3	Enter choice: 3
List is empty	List is empty
1. Add	1. Add
2. Remove	2. Remove
3. Display	3. Display
4. Quit	4. Quit
Enter choice: 2	Enter choice: 2
List is empty	List is empty
1. Add	1. Add
2. Remove	2. Remove
3. Display	3. Display
4. Quit	4. Quit
Enter choice: 8	Enter choice: 8
Invalid choice	Invalid choice
1. Add	1. Add
2. Remove	2. Remove

< Prev

Reset

Submit

Next >

List is empty	List is empty
1. Add	1. Add
2. Remove	2. Remove
3. Display	3. Display
4. Quit	4. Quit
Enter choice: 8	Enter choice: 8
Invalid choice	Invalid choice
1. Add	1. Add
2. Remove	2. Remove
3. Display	3. Display
4. Quit	4. Quit
Enter choice: 4	Enter choice: 4

< Prev

Reset

Submit

Next >

2.1.2. Dictionary Operations

07:23

Write a Python program to perform insertion, update, deletion, and traversal operations on a dictionary. An initial dictionary containing 10 predefined records is already given in the program.

Operations to be Performed:

1. Insertion – Insert a new key-value pair into the dictionary using user input.
2. Update – Update the value of an existing key using user input.
3. Deletion – Delete a specified key from the dictionary using user input.
4. Traversal – Traverse the final dictionary and display all key-value pairs.

Input and Output Format:

1. Read an integer representing the key to be inserted and a string representing its value. Insert this new key-value pair into the dictionary and display the dictionary after insertion.
2. Read an integer representing the key to be updated and a string representing the new value. Update the value of the specified key (only if it exists) and display the dictionary after the update.
3. Read an integer representing the key to be deleted. Delete the specified key from the dictionary (only if it exists) and display the dictionary after deletion.
4. Finally, traverse the dictionary and display all key-value pairs.

The program should also display the original dictionary before performing any operations. Each output should be printed with appropriate messages.

Note:

- All operations must be performed using dictionary methods.
- Perform deletion only if possible; leave the dictionary unchanged.
- Refer to the visible test cases for better understanding and strictly match with the input/outputs.

Initial dictionary with 10 predefined records

student = {

1: "Amit",

2: "Riya",

3: "Kiran",

4: "Neha",

5: "Arjun",

6: "Pooja",

```
7: "Rahul",  
8: "Sneha",  
9: "Vikram",  
10: "Anjali"  
}
```

```
#Display original dictionary  
print("Original Dictionary:", student)
```

```
# Insertion  
key = int(input())  
value = input()  
student[key] = value  
print("After Insertion:", student)
```

```
# Update  
upd_key = int(input())  
upd_value = input()  
if upd_key in student:  
    student[upd_key] = upd_value  
print("After Update:", student)
```

```
# Deletion  
del_key = int(input())  
if del_key in student:  
    student.pop(del_key)  
print("After Deletion:", student)
```

Traversal

```
print("Traversing Dictionary:")
```

```
for k, v in student.items():
```

```
    print(k, ":", v)
```

The screenshot shows a coding platform interface. At the top, there's a status bar indicating '2 out of 2 shown test case(s) passed' and '2 out of 2 hidden test case(s) passed'. Below this, the 'Expected output' and 'Actual output' are compared. The 'Expected output' shows the original dictionary, followed by an insertion of 'Suresh' at index 11, an update of 'Arjun' to 'Karthik' at index 3, and a deletion of 'Suresh' at index 11. The 'Actual output' shows the same sequence of operations. At the bottom, there's a 'Terminal' tab showing the output of the program, which is a list of key-value pairs from the dictionary: 1:-Amit, 2:-Riya, 3:-Karthik, 4:-Neha, 5:-Arjun, 6:-Pooja, 7:-Rahul, 8:-Sneha, 9:-Vikram, 10:-Anjali, 11:-Suresh.

2.2.1. Linear search Technique

04:45

Write a program to check whether the given element is present or not in the array of elements using linear search.

Input format:

- The first line of input contains the array of integers which are separated by space
- The last line of input contains the key element to be searched

Output format:

- If the element is found, print the index.
- If the element is not found, print Not found.

Sample Test Case:

Input:

1 2 3 4 3 5 6

3

Output:

2

```
# Read input array
```

```
arr = list(map(int, input().split()))
```

```
# Read key element
```

```
key = int(input())
```

```
# Linear search
```

```
found = False
```

```
for i in range(len(arr)):
```

```
    if arr[i] == key:
```

```
print(i)

found = True

break
```

If not found

if not found:

```
print("Not found")
```

The screenshot displays a code execution environment with the following details:

- Performance Metrics:**
 - Average time: 0.010 s (9.75 ms)
 - Maximum time: 0.012 s (12.00 ms)
- Test Results:**
 - 2 out of 2 shown test case(s) passed
 - 2 out of 2 hidden test case(s) passed
- Test Case 1 (10 ms):**
 - Expected output:** 1 2 3 4 3 5 6, 3, 2
 - Actual output:** 1 2 3 4 3 5 6, 3, 2
- Test Case 2 (12 ms):** (Status: Passed)

2.2.2. Captain of the Team

01:32

You are provided with the heights of 11 cricket players (in centimeters). Your task is to identify the tallest player, who will be selected as the captain of the team.

Input Format:

The first line of input will contain 11 integers, each representing the height of a player (in centimeters), each separated by a space.

Output Format

The output should be the height (in centimeters) of the tallest player.

```
# Read heights of 11 players  
heights = list(map(int, input().split()))
```

```
# Find the tallest player  
tallest = max(heights)
```

```
# Output the tallest height  
print(tallest)
```

The screenshot displays a coding platform's test results interface. At the top, performance metrics are shown: Average time is 0.005 s (5.33 ms) and Maximum time is 0.006 s (6.00 ms). Test results indicate that 1 out of 1 shown test case(s) passed and 2 out of 2 hidden test case(s) passed. Below this, 'Test case 1' is expanded, showing a 'Debug' button and a list icon. The 'Expected output' and 'Actual output' sections both display the sequence of numbers: 171 169 185 156 174 191 186 190 187 172 160, followed by the value 191 on a new line. At the bottom, there are tabs for 'Terminal' and 'Test cases', and a navigation bar with buttons for '< Prev', 'Reset', 'Submit', and 'Next >'.