

Name:Prithviraj Thakur

PRN:202501040026

PRACTICAL: 05

5.1.1. Stacked Plot

20:50

Create a stacked area plot to visualize the temperature variations for three different cities (City A, City B, and City C) across the months of the year. The temperature data is provided for each city in the editor.

Your task is to:

- Create a stacked area plot using the data.
- Label the x-axis as "Month", the y-axis as "Temperature", and provide the title "Temperature Variation" for the plot.
- Display the plot showing the temperature variation for each city throughout the months of the year.

```
import matplotlib.pyplot as plt
```

```
import pandas as pd
```

```
#Data for Months and Temperature for three cities
```

```
data = {
```

```
    'Month': ['January', 'February', 'March', 'April', 'May', 'June', 'July', 'August', 'September', 'October',  
             'November', 'December'],
```

```
    'City_A_Temperature': [5, 7, 10, 13, 17, 20, 22, 21, 18, 12, 8, 6],
```

```

'City_B_Temperature': [2, 3, 5, 6, 10, 14, 16, 17, 12, 9, 5, 3],
'City_C_Temperature': [3, 4, 6, 8, 9, 12, 15, 14, 10, 7, 4, 2]
}

# Write your code...

df = pd.DataFrame(data)

plt.stackplot(df['Month'],df['City_A_Temperature'],df['City_B_Temperature'],df['City_C_Temperature'])

plt.xlabel('Month')

plt.ylabel('Temperature')

plt.title('Temperature Variation')

plt.show()

```



5.2.1. Titanic Dataset

16:35

Write a Python program to analyze and visualize data from the Titanic dataset based on the following instructions:

Dataset Information:

The dataset is stored in a CSV file named `titanic.csv` and has been loaded using the pandas library. It contains the following columns:

- `Pclass`: Passenger class (1 = First, 2 = Second, 3 = Third).
- `Gender`: Gender of the passenger (male/female).
- `Age`: Age of the passenger.
- `Survived`: Survival status (0 = Did not survive, 1 = Survived).
- `Fare`: Ticket fare paid by the passenger.

Visualization:

To represent these trends, you will create 5 visualizations using Matplotlib. The visualizations should be arranged in a 3x2 grid (3 rows and 2 columns).

Visualization Details:

Write the code to create a series of visualizations as follows:

Bar Plot (Pclass Distribution):

- Create a bar plot to show the distribution of passengers across the different passenger classes (`Pclass`).
- Use the color `skyblue` for the bars.
- Title the plot as **"Passenger Class Distribution"**.
- Label the x-axis as **"Pclass"** and the y-axis as **"Count"**.

Pie Chart (Gender Distribution):

- Create a pie chart to display the distribution of male and female passengers.
- Use `lightblue` for males and `lightcoral` for females.
- Include percentages on the slices (use `autopct='%1.1f%%'`).
- Title the plot as **"Gender Distribution"**.

Histogram (Age Distribution):

- Create a histogram to visualize the distribution of passengers' ages.
- Use `lightgreen` for the bars with black edges (`edgecolor = 'black'`).
- Set the number of bins to **8** for the histogram.

- Title the plot as **"Age Distribution"**.
- Label the x-axis as **"Age"** and the y-axis as **"Frequency"**.

Bar Plot (Survival Count):

- Create a bar plot to show the count of passengers who survived and those who did not, based on the Survived column.
- Use the colors lightblue for survivors (1) and lightcoral for non-survivors (0).
- Title the plot as **"Survival Count"**.
- Label the x-axis as **"Survived (0 = No, 1 = Yes)"** and the y-axis as **"Count"**.

Scatter Plot (Fare vs Age):

- Create a scatter plot to visualize the relationship between the Fare and Age of passengers.
- Use orange for the data points.
- Title the plot as **"Fare vs Age"**.
- Label the x-axis as **"Age"** and the y-axis as **"Fare"**.

Note: Refer to the displayed plot in the sample test cases for better understanding.

```
import pandas as pd
```

```
import matplotlib.pyplot as plt
```

```
#Load the Titanic dataset from the CSV file
```

```
df=pd.read_csv('titanic.csv')
```

```
#Setup the figure for 5 subplots
```

```
fig,axes = plt.subplots(3, 2, figsize=(12, 12))
```

```
# write the code..
```

```
axes[0,0].bar(df['Pclass'].value_counts().index,df['Pclass'].value_counts(),color='skyblue')
```

```
axes[0,0].set_title('Passenger Class Distribution')
```

```
axes[0,0].set_xlabel('Pclass')
```


```
axes[0,0].set_ylabel('Count')
```

```
gender_counts=df['Gender'].value_counts()
```

```

axes[0,1].pie(gender_counts,labels=gender_counts.index,colors=['lightblue','lightcoral'])
axes[0,1].set_title('Gender Distribution')
axes[1,0].hist(df['Age'].dropna(),bins=8,color='lightgreen',edgecolor='black')
axes[1,0].set_title('Age Distribution')
axes[1,0].set_xlabel('Age')
axes[1,0].set_ylabel('Frequency')
survival_counts=df['Survived'].value_counts()
axes[1,1].bar(survival_counts.index,survival_counts,color=['lightblue','lightcoral'])
axes[1,1].set_title('Survival Count')
axes[1,1].set_xlabel('Survived (0 = No, 1 = Yes)')
axes[1,1].set_ylabel('Count')
axes[2,0].scatter(df['Age'],df['Fare'],color='orange')
axes[2,0].set_title('Fare vs Age')
axes[2,0].set_xlabel('Age')
axes[2,0].set_ylabel('Fare')
axes[2,1].plot()
axes[2,1].set_xlim(0,1)
axes[2,1].set_ylim(0,1)
plt.tight_layout()
plt.show()

```



5.2.2. Histogram of passenger information of Titanic

01:19

Write a Python code to plot a histogram for the distribution of the 'Age' column from the Titanic dataset. The histogram should display the frequency of different age ranges with the following specifications:

1. Use **30 bins** for the histogram.
2. Set the **edge color** of the bars to **black** (k).
3. Label the x-axis as '**Age**' and the y-axis as '**Frequency**'.
4. Add the title "**Age Distribution**" to the histogram.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket

Sample Data:

PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked

```
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C
3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S
5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S
6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q
7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S
8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S
9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S
10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C
```

Note: Refer to the visible test case for better reference.

```
import pandas as pd
```

```
import matplotlib.pyplot as plt
```

```
#Load the Titanic dataset
```

```
data = pd.read_csv('Titanic-Dataset.csv')
```

```
#Data Cleaning
```

```
data['Age'].fillna(data['Age'].median(), inplace=True)
```

```
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
```

```
data.drop('Cabin', axis=1, inplace=True)
```

```
#Convert categorical features to numeric
```

```
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
```

```
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
```

```
# Write your code here for Histogram
```


```
plt.hist(data['Age'], bins=30, edgecolor='k')
```

```
plt.xlabel('Age')
```

```
plt.ylabel('Frequency')
```

```
plt.title('Age Distribution')
```

plt.show()



5.2.3. Bar plot of survival rate of passengers

15:39

Write a Python code to plot a bar chart that shows the count of passengers who survived and did not survive in the Titanic dataset. The chart should display the following specifications:

1. Use the '**Survived**' column to show the count of survivors (0 = Did not survive, 1 = Survived).
2. Set the chart type to '**bar**'.
3. Add the title "**Survival Count**" to the chart.
4. Label the x-axis as '**Survived**' and the y-axis as '**Count**'.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket

Sample Data:

PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked

1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S

2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C

3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S

4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S

5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S
6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q
7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S
8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S
9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S
10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C

Note: Refer to the visible test case for better reference.

```
import pandas as pd
```

```
import matplotlib.pyplot as plt
```

```
#Load the Titanic dataset
```

```
data = pd.read_csv('Titanic-Dataset.csv')
```

```
#Data Cleaning
```

```
data['Age'].fillna(data['Age'].median(), inplace=True)
```

```
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
```

```
data.drop('Cabin', axis=1, inplace=True)
```

```
#Convert categorical features to numeric
```

```
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
```

```
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
```

```
# Write your code here for Bar Plot for Survival Rate
```

```
survival_counts=data['Survived'].value_counts().sort_index()
```

```
plt.figure()
```

```
survival_counts.plot(kind='bar')
```

```
plt.title('Survival Count')
```

```
plt.xlabel('Survived')
```

```
plt.ylabel('Count')
```

```
plt.show()
```



5.2.4. Bar Plot for Survival by Gender

01:21

Write a Python code to plot a stacked bar chart that shows the count of passengers who survived and did not survive, grouped by gender, in the Titanic dataset. The chart should display the following specifications:

1. Group the data by the '**Sex**' column, then use the **value_counts()** function to count the occurrences of survivors (0 = Did not survive, 1 = Survived) for each gender.
2. Use a **stacked bar chart** to display the survival counts.
3. Add the title "**Survival by Gender**" to the chart.
4. Label the x-axis as '**Gender**' and the y-axis as '**Count**'.
5. The legend should indicate '**Not Survived**' and '**Survived**'.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket

Sample Data:

PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked

1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C
3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S
5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S
6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q
7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S
8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S
9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S
10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C

Note: Refer to the visible test case for better reference.

```
import pandas as pd

import matplotlib.pyplot as plt

#Load the Titanic dataset
data = pd.read_csv('Titanic-Dataset.csv')

#Data Cleaning
data['Age'].fillna(data['Age'].median(), inplace=True)
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
data.drop('Cabin', axis=1, inplace=True)


#Convert categorical features to numeric
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)

# Write your code here for Bar Plot for Survival by Gender
counts = data.groupby('Sex')['Survived'].value_counts().unstack()

counts.plot(kind='bar', stacked=True)

plt.title("Survival by Gender")
plt.xlabel("Gender")
plt.ylabel("Count")
plt.legend(["Not Survived", "Survived"])
```

plt.show()



5.2.5. Bar Plot for Survival by Pclass

01:17

Write a Python code to plot a stacked bar chart that shows the count of passengers who survived and did not survive, grouped by passenger class (**Pclass**), in the Titanic dataset. The chart should display the following specifications:

1. Group the data by the **Pclass** column and count the number of survivors (0 = Did not survive, 1 = Survived) for each class using **value_counts()**.
2. Use a **stacked bar chart** to display the survival counts.
3. Add the title "**Survival by Pclass**" to the chart.
4. Label the x-axis as '**Pclass**' and the y-axis as '**Count**'.
5. The legend should indicate '**Not Survived**' and '**Survived**'.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch

Sample Data:

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked
1	0	3	"Braund, Mr. Owen Harris"	male	22	1	0	A/5 21171	7.25		S
2	1	1	"Cumings, Mrs. John Bradley (Florence Briggs Thayer)"	female	38	1	0	PC 17599	71.2833	C85	C
3	1	3	"Heikkinen, Miss. Laina"	female	26	0	0	STON/O2. 3101282	7.925		S
4	1	1	"Futrelle, Mrs. Jacques Heath (Lily May Peel)"	female	35	1	0	113803	53.1	C123	S
5	0	3	"Allen, Mr. William Henry"	male	35	0	0	373450	8.05		S
6	0	3	"Moran, Mr. James"	male		0	0	330877	8.4583		Q
7	0	1	"McCarthy, Mr. Timothy J"	male	54	0	0	17463	51.8625	E46	S
8	0	3	"Palsson, Master. Gosta Leonard"	male	2	3	1	349909	21.075		S
9	1	3	"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)"	female	27	0	2	347742	11.1333		S
10	1	2	"Nasser, Mrs. Nicholas (Adele Achem)"	female	14	1	0	237736	30.0708		C

Note:

- Refer to the visible test case for better reference.
- Ensure you use the **groupby()** function with **value_counts()** to count the survivors and non-survivors for each **Pclass**.
- Do **not** manually use **size()** or **unstack()** without **value_counts()**. Use the **value_counts()** method for counting survival status directly.

```
import pandas as pd
```

```
import matplotlib.pyplot as plt
```

```
#Load the Titanic dataset
```

```
data = pd.read_csv('Titanic-Dataset.csv')
```

```
#Data Cleaning
```

```
data['Age'].fillna(data['Age'].median(), inplace=True)
```

```
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
```

```
data.drop('Cabin', axis=1, inplace=True)
```

```
# Convert categorical features to numeric
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})

data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)


# Write your code here for Bar Plot for Survival by Pclass

counts = data.groupby('Pclass')['Survived'].value_counts().unstack()

counts.plot(kind='bar', stacked=True)

plt.title("Survival by Pclass")
plt.xlabel("Pclass")
plt.ylabel("Count")
plt.legend(["Not Survived", "Survived"])

plt.show()
```



5.2.6. Bar Plot for Survival by Embarked

04:55

Write a Python code to plot a stacked bar chart showing the survival count for passengers based on their embarkation location in the Titanic dataset.

The chart should display the following specifications:

1. Use the **Embarked** column to determine the embarkation location. After converting this column into dummy variables (using `pd.get_dummies()`), plot the survival count based on the **Embarked_Q** column (representing passengers who embarked from Queenstown) in relation to survival.
2. Set the chart type to 'bar' and make it stacked.
3. Add the title "**Survival by Embarked** " to the chart.
- 4.
5. Label the x-axis as '**Embarked**' and the y-axis as '**Count**'.

Include a legend to distinguish between survivors and non-survivors (label the legend as '**Survived**' and '**Not Survived**').

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch

Sample Data:

PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked

1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S
 2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C
 3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S
 4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S
 5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S
 6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q
 7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S
 8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S
 9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S
 10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C

Note: Refer to the visible test case for better reference.

```
import pandas as pd
import matplotlib.pyplot as plt

#Load the Titanic dataset
data = pd.read_csv('Titanic-Dataset.csv')

#Data Cleaning
data['Age'].fillna(data['Age'].median(), inplace=True)
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
data.drop('Cabin', axis=1, inplace=True)

#Convert categorical features to numeric
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
```

```
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
```

#Write your code here for Bar Plot for Survival by Embarked

```
grouped = pd.crosstab(data['Embarked_Q'],data['Survived'])
```

```
grouped.plot(kind='bar',stacked=True)
```


```
plt.xlabel('Embarked')
```

```
plt.ylabel('Count')
```

```
plt.title('Survival by Embarked')
```

```
plt.legend(['Not Survived','Survived'])
```

```
plt.show()
```



5.2.7. Box plot for Age Distribution

00:56

Write a Python code to plot a boxplot that shows the distribution of the 'Age' column from the Titanic dataset across different passenger classes. The boxplot should display the following specifications:

1. Use the **Pclass** column to group the data for the boxplot.
2. Set the title of the plot to **"Age by Pclass"**.
3. Remove the default subtitle with **plt.suptitle("")**.

4. Label the x-axis as '**Pclass**' and the y-axis as '**Age**'.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch

Sample Data:

PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked

1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C
3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S
5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S
6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q
7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S
8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S
9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S
10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C

Note: Refer to the visible test case for better reference.

```
import pandas as pd
```

```
import matplotlib.pyplot as plt
```

```
# Load the Titanic dataset

data = pd.read_csv('Titanic-Dataset.csv')


#Data Cleaning

data['Age'].fillna(data['Age'].median(), inplace=True)

data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)

data.drop('Cabin', axis=1, inplace=True)


#Convert categorical features to numeric

data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})

data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)

# Boxplot of Age grouped by Pclass

data.boxplot(column='Age', by='Pclass')


#Remove default subtitle

plt.suptitle("")


#Set title and axis labels


plt.title("Age by Pclass")

plt.xlabel("Pclass")

plt.ylabel("Age")


#Show plot
```

plt.show()



5.2.8. Box Plot for Age by Survived

00:47

Write a Python code to plot a boxplot that shows the distribution of the 'Age' column from the Titanic dataset based on whether passengers survived or not. The boxplot should display the following specifications:

1. Use the **Survived** column to group the data for the boxplot (0 = Did not survive, 1 = Survived).
2. Set the title of the plot to **"Age by Survival"**.
3. Remove the default subtitle with **plt.suptitle("")**.
4. Label the x-axis as **'Survived'** and the y-axis as **'Age'**.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch

Sample Data:

PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked

1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S

2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C

3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S
5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S
6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q
7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S
8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S
9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S
10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C

Note: Refer to the visible test case for better reference.

```
import pandas as pd
```

```
import matplotlib.pyplot as plt
```

```
#Load the Titanic dataset
```

```
data = pd.read_csv('Titanic-Dataset.csv')
```

```
#Data Cleaning
```

```
data['Age'].fillna(data['Age'].median(), inplace=True)
```

```
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
```

```
data.drop('Cabin', axis=1, inplace=True)
```

```
#Convert categorical features to numeric
```

```
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
```

```
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
```

```
# Boxplot of Age grouped by Survived
```

```
data.boxplot(column='Age', by='Survived')
```

```
#Remove default subtitle
```

```
plt.suptitle("")
```

```
#Set title and axis labels


plt.title("Age by Survival")

plt.xlabel("Survived")

plt.ylabel("Age")
```

```
#Show plot
```

```
plt.show()
```



5.2.9. Box Plot for Fare by Pclass

01:13

Write a Python code to plot a boxplot that shows the distribution of the 'Fare' column from the Titanic dataset based on the passenger class (Pclass). The boxplot should display the following specifications:

1. Use the **Pclass** column to group the data for the boxplot.

2. Set the title of the plot to **"Fare by Pclass"**.
3. Remove the default subtitle with **plt.suptitle('')**.
4. Label the x-axis as **'Pclass'** and the y-axis as **'Fare'**.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch

Sample Data:

PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked

1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S

2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C

3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S

4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S

5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S

6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q

7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S

8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S

9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S

10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C

Note: Refer to the visible test case for better reference.

```
import pandas as pd
import matplotlib.pyplot as plt

#Load the Titanic dataset
data = pd.read_csv('Titanic-Dataset.csv')

#Data Cleaning
data['Age'].fillna(data['Age'].median(), inplace=True)
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
data.drop('Cabin', axis=1, inplace=True)

#Convert categorical features to numeric
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)

# Boxplot of Fare grouped by Pclass
```

```
data.boxplot(column='Fare', by='Pclass')
```

```
#Remove default subtitle
```

```
plt.suptitle("")
```

```
#Set title and axis labels
```


```
plt.title("Fare by Pclass")
```

```
plt.xlabel("Pclass")
```

```
plt.ylabel("Fare")
```

```
#Show plot
```

```
plt.show()
```



5.2.10. Scatter Plot for Age vs. Fare

05:23

Write a Python code to plot a scatter plot showing the relationship between the 'Age' and 'Fare' columns in the Titanic dataset. The scatter plot should display the following specifications:

1. Use the **Age** column for the x-axis and the **Fare** column for the y-axis.

2. Set the title of the plot to "**Age vs. Fare**".
3. Label the x-axis as '**Age**' and the y-axis as '**Fare**'.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch

Sample Data:

PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked

1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C
3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S
5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S
6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q
7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S
8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S
9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S
10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C

Note: Refer to the visible test case for better reference.

```
import pandas as pd
```

```
import matplotlib.pyplot as plt
```

```
#Load the Titanic dataset
```

```
data = pd.read_csv('Titanic-Dataset.csv')
```

#Data Cleaning

```
data['Age'].fillna(data['Age'].median(), inplace=True)
```

```
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
```

```
data.drop('Cabin', axis=1, inplace=True)
```

#Convert categorical features to numeric

```
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
```

```
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
```

#Write your code here for Box Plot for Fare by Pclass

```
plt.scatter(data['Age'], data['Fare'])
```

```
plt.title('Age vs. Fare')
```

```
plt.xlabel('Age')
```

```
plt.ylabel('Fare')
```

```
plt.show()
```



5.2.11. Scatter Plot for Age vs. Fare by Survived

28:21

Write a Python code to plot a scatter plot showing the relationship between the 'Age' and 'Fare' columns in the Titanic dataset, with points color-coded by survival status. The scatter plot should display the following specifications:

1. Use the Age column for the x-axis and the Fare column for the y-axis.
2. Color the points based on the Survived column: Red for passengers who did not survive (Survived = 0). Blue for passengers who survived (Survived = 1).
3. Set the title of the plot to "Age vs. Fare by Survival".
4. Label the x-axis as 'Age' and the y-axis as 'Fare'.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked
-------------	----------	--------	------	-----	-----	-------	-------	--------	------	-------	----------

Sample Data:

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked
1	0	3	"Braund, Mr. Owen Harris"	male	22	1	0	A/5 21171	7.25		S
2	1	1	"Cumings, Mrs. John Bradley (Florence Briggs Thayer)"	female	38	1	0	PC 17599	71.2833	C85	C
3	1	3	"Heikkinen, Miss. Laina"	female	26	0	0	STON/O2. 3101282	7.925		S
4	1	1	"Futrelle, Mrs. Jacques Heath (Lily May Peel)"	female	35	1	0	113803	53.1	C123	S
5	0	3	"Allen, Mr. William Henry"	male	35	0	0	373450	8.05		S
6	0	3	"Moran, Mr. James"	male		0	0	330877	8.4583		Q
7	0	1	"McCarthy, Mr. Timothy J"	male	54	0	0	17463	51.8625	E46	S
8	0	3	"Palsson, Master. Gosta Leonard"	male	2	3	1	349909	21.075		S
9	1	3	"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)"	female	27	0	2	347742	11.1333		S
10	1	2	"Nasser, Mrs. Nicholas (Adele Achem)"	female	14	1	0	237736	30.0708		C

Note: Refer to the visible test case for better reference.