

Manuscript Number: SCICO-D-19-00025R1

Title: Certified Virtual Machine Based Regular Expression Parsing

Article Type: VSI: SBLP 2018

Keywords: Regular Expressions; Virtual Machines; Parsing

Corresponding Author: Mr. Rodrigo Geraldo Ribeiro, Ph.D.

Corresponding Author's Institution: Universidade Federal de Ouro Preto

First Author: Elton Cardoso

Order of Authors: Elton Cardoso; Thales Delfino; Rodrigo Geraldo Ribeiro, Ph.D.; Andre R Du Bois, Ph.D.; Leonardo Reis, Ph.D.

Manuscript Region of Origin: BRAZIL

Abstract: Regular expressions (REs) are pervasive in computing. We use REs in text editors, string search tools (like GNU-Grep) and lexical analysers generators. Most of these tools rely on converting REs to their corresponding finite state machines or use REs derivatives for directly parse an input string. In this work, we investigate the suitability of another approach: instead of using derivatives or generating a finite state machine for a given RE, we developed a virtual machine (VM) for parsing regular languages, in such a way that a RE is merely a program executed by the VM over the input string. We show that the proposed semantics is sound w.r.t. a standard inductive semantics for RE and that the evidence produced by it denotes a valid parsing result. All of our results are formalized in Coq proof assistant and from it we extract a certified algorithm which we use to build a RE parsing tool using Haskell programming language. Experiments comparing the efficiency of our algorithm with other approaches implemented using Haskell are reported.

Reviewer #1:

The paper is relatively easy to read, despite some parts that may be heavy for those not familiar with Coq. In general, it's only critical issue is that the "grand finale" is missing: the description of the interpreter itself. On page 32 the paper gives the specification of 'interp', but there are no clues about how it is implemented.

Response: In the paper's first version, we avoid giving details about the interpreter's implementation mainly because it is built using tactics (a common pattern when programming with dependent types in Coq) which would difficult the high-level comprehension of our formalization.

We have improved the explanation of our semantics interpreter by showing some parts of its tactic definition.

The paper later does some benchmarks over this implementation, which is weird to read without knowing what it is benchmarking. The paper says the implementation is based on a virtual machine, but how is this VM? What instructions does it have, what is its internal state, etc.? Does it do backtracking? When and how?

Response: In the introduction, we mention that our view of a VM is the one commonly used by machines for lambda-calculi, like the SECD and Krivine machines. We inspire our semantics for RE parsing on such machines for lambda-calculus.

Essentially, our VM sees a RE as a program executed over the input string, and it backtracks as expected by a greedy RE parser strategy. As suggested by Reviewer #3, we changed our semantics definition in order to produce bit-coded parse trees following the greedy disambiguation strategy.

As a minor issue, the paper sometimes gives too much details for some parts of the code that seems mostly bureaucratic. (The removal of these parts will give lots of space for the missing description of the VM.) Some examples:

- Function 'in_regex_p'. As the paper explains, this is a translation to Coq of the rules in Figure 5. It adds nothing to the reader.

- Function 'is_code_of': Another mostly "bureaucratic" function. It is important to have its signature and a brief description, but the code itself adds little to the text.

- Function 'is_tree_of': The same.

Response: We try to limit Coq code presentations to things that the reader could readily understand without a deeper comprehension of how to formalize stuff using Coq proof assistant. This was the main motivation for showing all these simple definitions.

Follows some other details about the text:

- The parse tree in Example 1 has some "poetic license" against the given grammar regarding lists. (Lists are made of several nodes, each with two children, ending with an end-of-list node.) This is the cause of some bits in bit code given later (on Line 265) not appearing in the tree.

Response: We have improved our figure to include all bit separators. Thanks!

- Function 'code', ~line 250: it would be useful to give its type. (In general, types are more important than bodies.)

Response: Ok, it is fixed. Thanks!

- Line 269: "Remaining three digits" -> "The remaining three digits"

Response: Ok, it is fixed. Thanks!

- Line 314: "where 'e' is current RE" -> "where 'e' is the current RE" (In general, there are several places where the article "the" seems to be missing.)

Response: Ok, it is fixed. Thanks!

- Figure 5, rule ConsVM: I think the precondition ' $s_{\{p1\}} \neq \epsilon$ ' is not needed. The text highlights that the original RE is unproblematic; therefore, the body of a Kleene star cannot match the empty string.

Response: Ok, it is fixed. Thanks!

- Line 320: "Rules LeftVM and RightVM specifies" -> "specify"

Response: Ok, it is fixed. Thanks!

- Line 348: "in type theory-based" -> "in type-theory based" (or "in type-theory--based")

Response: Ok, it is fixed. Thanks!

- Line 366: "which provide" -> "which provides"

Response: Ok, it is fixed. Thanks!

- In would help to explain why we need 'invalid_code' (to define 'decode' later).

Response: In order to define function decode using a dependent type, we need to consider both successful and failure situations. Type nocode_for denotes a proof that a given bit sequence is not a valid code for a specific regular expression. Notice that nocode_for denotes a proof that a full bit list is not valid. However, another possibility is that just a prefix of the input list could be parsed as a code for the RE, and it leaves a remaining non-empty bit sequence without parsing, which is another possibility of a decoding error. We use type invalid_code to combine these two kinds of errors.

- Line 467: "The completeness express" -> "The completeness expresses"

Response: Ok, it is fixed. Thanks!

- Line 499: in the description of the set up for the experiments, it seems important to specify which version of Haskell was used.

Response: Ok, fixed. Thanks!

- Line 518: "Such RE pose a challenge" -> "poses".

Response: Ok, it is fixed. Thanks!

- Line 526: Why/how does the presented VM have linear performance on those problematic inputs? (A benchmark where we cannot understand its results is not very helpful.)

Response: We improve our evaluation section introducing an analytical model of our parsing VM semantics. Basically, the model shows that the semantics exhibits a performance of the order $O(n)$. A proof sketch of this property is included in an appendix.

- Last line: What is the difficulty of knowing the time complexity of the proposed algorithm? (Why is it future work?) It seems important some discussion about the complexity (which, of course, demands a discussion of the algorithm itself).

Response: As we have answered in the previous question, we introduced an analytical model that is used to formally justify the linear time performance of our semantics.

Reviewer #2:

The paper develops and formalizes a virtual machine for parsing regular languages. The specification of the virtual machine is given in terms of a big-step semantics which produces a bit-code representation of parse trees. The machine is proved correct wrt the membership semantics of regular expressions. The formalization of the virtual machine and its ecosystem (associated definitions and properties) is performed in Coq. Finally, a Haskell implementation of the VM-based interpreter is obtained from the formalization by using Coq's program extraction mechanism; experimental results are presented for that implementation.

In comparison with the original paper published at SBLP'18, the present paper presents several improvements and differences.

The paper is interesting, in general well-written, and presents a good account of related work. The contribution of the paper is much stronger than that of the SBLP'18 paper as it presents the complete formalization of the big-step semantics for the VM and its proof of correctness. I have some comments and suggestions that I present as part of the specific comments below.

Regarding the structure of the paper, I would move the section 2 on Coq to an appendix and give more importance and space to the results associated with the VM.

Response: We moved the Coq introductory section to an appendix.

Specific comments:

- page 10

l.44-45 maybe (fun x => P) instead of maybe P

Response: Keeping P is correct since, in maybe type definition, we have defined maybe's type parameter as $A \rightarrow \text{Prop}$, so there is no need to add an anonymous function to introduce an element of type A.

l.46 extra curly braces missing in $\{x|P\}$, correct is $\{\{x|P\}\}$

l.46 [n] is actually [n]

Response: We have changed our specification, and now, our Coq code does not use the maybe type. Now, instead of using the refine tactic to give the computational content of a dependently typed function, we are constructing everything using Coq tactics.

- page 11

I.45 (Figure ??) is (Figure 1)

Response: We have changed our specification, and now, our Coq code does not use the maybe type. Now, instead of using the refine tactic to give the computational content of a dependently typed function, we are constructing everything using Coq tactics.

- page 13

I.10 RE -> REs

Response: Ok, it is fixed. Thanks!

- page 14

I.48-49 add a reference to Fig. 4

Response: We have added a reference to Fig. 4. Thanks!

- page 15

The bit-code generation does not need to be driven by an input RE. Like flatten, function code can produce its output string (a bit-code) without looking at the type (RE) of the input tree. Defining the way it is defined gives the impression that code is actually taking proofs of the parse tree typing relation ($| - t : e$) as input. The relationship between parse trees and the corresponding bit-codes is clearly stated in Thm 3 (page 17) and there you take as hypothesis that $| - t : e$.

Response: We keep RE on the input of function code to follow Heinglein et al. original formulation of coding / decoding of RE parsing trees. We introduce the following sentence to clarify this:

While coding a parse tree does not depend on its underlying RE, we keep it on the code function to follow the original definition of Heinglein et al.

- page 16

I.9-14 The explanation about the bit-code of Example 2 at the beginning of the page does not clarify much; rewrite it or simply drop it.

We have improved the explanation of this example and the drawing of its bit-annotated parse tree. Thanks!

I.44 approach _to_

I.47 _an_ equivalent

Response: Ok, it is fixed. Thanks!

- page 18

l.32 obeys -> obey

Response: Ok, it is fixed. Thanks!

- page 20

It would be nice if you can motivate somewhere the need for introducing a VM, compared with other approaches like eg. parsing functions for REs.

l.16-18 may produce as a side effect -> produces as result

Response: Ok, it is fixed. Thanks!

Fig. 5: you should mention that the semantics is non-deterministic.

Response: We have fixed our semantics in order to follow the greedy disambiguation strategy. Now our semantics is deterministic.

==> is it necessary the precondition $s_{\{p_1\}} \neq \epsilon$ in rule ConsVM? Putting the precondition that the RE is unproblematic (as it is done in the formalization of the interpreter in Coq) it is not necessary to check within the rule that the string $s_{\{p_1\}}$ is non-empty.

Response: You are right. We change rule ConsVM dropping the precondition that $s_{\{p_1\}} \neq \epsilon$. Thanks!

l.46-47 semantics rules -> semantic rule

Response: Ok, it is fixed. Thanks!

- page 21

l.12 for the $_RE_e_1\ e_2$

Response: Ok, it is fixed. Thanks!

I.14-15 You say that "rules NilVM and ConsVM deal with unproblematic Kleene star REs". As far as I see only ConsVM deals with unproblematic Kleene stars, I don't see how NilVM does. ConsVM properly works when the Kleene star is unproblematic because of the condition $s_{\{p_1\}} \leq \epsilon$. Perhaps it would be better if you simply define the big-step semantics assuming that the RE is unproblematic. That way it would be unnecessary to check that property in ConsVM. At the end you want that condition to hold on the RE when parsing a string. In fact, you do that in the formalization of the interpreter in Coq: you first convert the RE to an unproblematic one and then you run the VM on the input string. Therefore you are always executing your semantics on an unproblematic RE. Of course, adding that precondition on the RE surely would require to add it in all properties involving the big-step semantics of the VM (eg. Thms 5, 6 and 7).

Response: We follow your recommendation, and now we assume that our semantics deal only with non-problematic expressions. In our interpreter definition, we convert any regular expression into an equivalent non-problematic one.

Thms 4, 5 and 6 state the main properties of your semantics. Being a journal paper I would assign more space for those properties and show, at least, proof sketches. That may appear in an appendix.

Response: We have added an appendix containing the proofs sketches of the main paper properties.

- page 22

I.31-32 You need to mention that $(\$ c)$ denotes $\text{Chr } c$. I assume that $\text{String } c$ means " c "; for readability, I would directly write " c " in the paper.

Response: Ok, it is fixed. Thanks!

I.51-55 The where clause and the sentence just after speak about the same. Use one for or the other. In case of using explanations about notation it is better that they appear before the the Inductive definitions seem more readable and

I.42-43 why the condition $s \neq \text{""}$ in `InStarRight`?

Response: This condition is not necessary. We removed it.

- page 23

I.31 its -> the

I.53 its types -> their types

I.54-55 has its -> satisfies the

Response: Ok, it is fixed. Thanks!

- page 26

I.27 `_an_` input

I.31-32 `_an_` unproblematic

I.42-43

`_Function_` `unprob_rec`'s

`return_ed_` RE

I.44 accepts -> accept

Response: Ok, it is fixed. Thanks!

- page 27

I.53-54 Function `flatten` `_(shown in page 13)_`

Response: Ok, it is fixed. Thanks!

- page 28

Be careful that the name "code" is used for the function defined in page 15, but also as a type synonym for list bit (Definition on line 13). It is better to name that function as "encode" from the beginning (when it is introduced in page 15), since that is its name in the Coq formalization.

Response: Ok, we have changed all references to function name "code" to "encode".

Thanks!

- page 29
l.12-13 code -> encode
l.53-54 empty set RE, ##0 -> empty RE #0.

Response: Ok, it is fixed. Thanks!

- page 30
l.24 code -> encode

Response: Ok, it is fixed. Thanks!

In the existential, `invalid_code` should say that the tree `t` is of type `e`.

Response: It is not necessary to include such a condition because of the theorem "decode_sound", which states that the produced tree is well-typed.

l.35 code -> encode

Response: Ok, it is fixed. Thanks!

- page 31
l.34-37 Write the explanation about notation before the definition of `in_regex_p`.

The definition of `in_regex_p` does not follow completely the semantics in Fig 5 because it does not consider the production of bit-codes. You should comment why you are not considering the production of bit-codes as part of `in_regex_p`. In principle, I would have considered their production for the definition of the interpreter (`interp`).

Response: As requested by Reviewer #3, we have changed our semantics in order to consider the greedy disambiguation strategy and also include the bit-codes as a result of our semantics.

Mention that the Theorems `in_regex_p_complete` and `in_regex_p_sound` correspond to the Thms 6 and 5, respectively.

Response: We have added the corresponding references. Thanks!

I.52-54

express_es_

an string -> a string

Response: Ok, it is fixed. Thanks!

- page 32

I.29 _an_obvious

Response: Ok, it is fixed. Thanks!

In the interpreter, how you deal with the fact that the semantics of the VM is non-deterministic?

Response: We have changed our semantics definition, and now it is deterministic.

- page 34

Figure 7: input size thousands of _"ab"s_

Ok, fixed. Thanks!

I.27-29 You present the experiment by saying that you parse strings of the form a^n . Why not simply saying, as in the previous experiment, strings of a's? The RE in this case should be $(a+\epsilon)^*a^*$.

Ok, fixed. Thanks!

I.34 is preented below -> are presented in Figures 8 and 9.

Response: Ok, it is fixed. Thanks!

- page 35

I would eliminate footnote 6.

Ok, we have removed it. Thanks!

- page 36

I would eliminate completely all Haskell code of this page. It seems unnecessary to show it.

You can give a rough idea of how you generate REs and strings for that RE without showing the code.

We believe that the generation algorithm is an important component of how our experiments are executed. This is the main reason that we keep the Haskell code of random test case generation algorithm.

- page 37

l.14-15 "to" appears twice

Response: Ok, it is fixed. Thanks!

Reviewer #3:

The notion of equivalence of REs is defined as being language equivalence.

Thus statements about turning, for example, a problematic regex into an equivalent non-problematic one, is not that interesting. A more interesting research question would be to consider what happens when

(the infinitely many) parse trees of a problematic regex and given input string are considered and compared to those obtained by the non-problematic regex obtained via the construction of Medeiros (or related constructions).

Response: The research question of what is the computational content (on parse trees) of Medeiros et. al. construction on problematic REs is left for future work. We intend to characterize Medeiros et al. construction in terms of the coinductive axiomatization of Heinglein and its co-workers in "Regular expression containment: coinductive axiomatization and computational interpretation".

In my opinion, the proposed approach should be extended in order to handle Greedy and/or Posix regex matching. In short, considering all parse trees (or bit-codes) when an input string is matched by a non-problematic regular expression, is too close to classical formal language theory that is well understood. Regular expression matching becomes interesting when disambiguation policies (such as Greedy or Posix) is used to associate at most one parse tree (or bit-code) with a given RE and input string.

Response: We have modified our formalization to follow the greedy disambiguation strategy. Now our semantics is deterministic: given a regular expression e and a string s it outputs only one bit-coded parse tree or no parse is possible.

Alternatively (or in addition), research in line with the following statement on p39 will improve novelty: "In many cases, the goal of a RE is not only to match a given text, but also to extract information from it."

Response: The main novelty of Radanne paper is to use a GADT to provide a type-safe interface for RE parsing. While our extracted Haskell code does not use GADTs, we have proved that our algorithm is correct, which includes proofs that its parsing / unparsing behavior is correct.

Providing a similar GADT-based interface that encapsulates the verified extracted code is a simple task, but not related with our main work objective: formalizing an operational semantics for RE parsing and use it to build a tool with a reasonable performance.

- An operational semantics for a virtual machine for regular expression parsing. Our proposed semantics follows the greedy disambiguation strategy.
- The semantics produces, as evidence, correct bit-coded parse trees.
- A correct algorithm to convert problematic regular expressions into non-problematic.
- Certified interpreter for the semantics in Coq proof assistant.

Certified Virtual Machine Based Regular Expression Parsing

Elton Cardoso

Departamento de Computação e Sistemas - DECSI, Universidade Federal de Ouro Preto

Thales Delfino, Rodrigo Ribeiro

Programa de Pós-Graduação em Ciência da Computação - PPGCC, Universidade Federal de Ouro Preto

André Rauber Du Bois

Programa de Pós-Graduação em Computação - PPGC, Universidade Federal de Pelotas

Leonardo Reis

Departamento de Computação, Universidade Federal de Juiz de Fora

Abstract

Regular expressions (REs) are pervasive in computing. We use REs in text editors, string search tools (like GNU-Grep) and lexical analysers generators. Most of these tools rely on converting REs to their corresponding finite state machines or use REs derivatives for directly parse an input string. In this work, we investigate the suitability of another approach: instead of using derivatives or generating a finite state machine for a given RE, we developed a virtual machine (VM) for parsing regular languages, in such a way that a RE is merely a program executed by the VM over the input string. We show that the proposed semantics is sound w.r.t. a standard inductive semantics for RE and that the evidence produced by it denotes a valid parsing result. All of our results are formalized in Coq proof assistant and from it we extract a certified algorithm which we use to build a RE parsing tool using Haskell programming language. Experiments comparing the efficiency of our algorithm with other approaches implemented using Haskell are reported.

Keywords: Regular Expressions, Virtual Machines, Parsing

1. Introduction

We name parsing the process of analyzing if a sequence of symbols matches a given set of rules. Such rules are usually specified in a formal notation, like a grammar. If a string can be obtained from those rules, we have success: we can build some evidence that the input is in the language described by the underlying formalism. Otherwise, we have a failure: no such evidence exists.

In this work, we focus on the parsing problem for regular expressions (REs), which are an algebraic and compact way of defining regular languages (RLs), i.e., languages that can be recognized by (non-)deterministic finite automata and equivalent formalisms. REs are widely used in string search tools, lexical analyser generators and XML schema languages [1]. Since RE parsing is pervasive in computing, its correctness is crucial. Nowadays, with the recent development of languages with dependent types and proof assistants it has become possible to represent algorithmic properties as program types which are verified by the compiler. The usage of proof assistants to verify RE parsing / matching algorithms were the subject of study of several recent research works (e.g. [2, 3, 4, 5]).

Approaches for RE parsing can use representations of finite state machines (e.g. [2]), derivatives (e.g. [3, 6, 4]) or the so-called pointed RE's or its variants [5, 7]. Another approach for parsing is based on the so-called parsing machines, which dates back to 70's with Knuth's work on top-down syntax analysis for context-free languages [8]. Recently, some works have tried to revive the use of such machines for parsing: Cox [9] defined a VM for which a RE can be seen as "high-level programs" that can be compiled to a sequence of such VM instructions and Lua library LPEG [10] defines a VM whose instruction set can be used to compile Parser Expressions Grammars (PEGs) [11]. Such renewed research interest is motivated by the fact that is possible to include new features by just adding and implementing new machine instructions.

Cox’s work on VM-based RE parsing has problems. First, it is poorly specified: both the VM semantics and the RE compilation process are described only informally and no correctness guarantee is even mentioned. Second, it does not provide an evidence for matching, which could be used to characterize a disambiguation strategy, like Greedy [1] and POSIX [12]. To the best of our knowledge, no previous work has formally defined a VM for RE parsing that produces evidence (parse trees) for successful matches. The objective of this work is to give a first step in filling this gap. More specifically, we are interested in formally specify and prove the correctness of a VM based semantics for RE parsing which produces bit-codes as a memory efficient representation of parse-trees. As pointed by [13], bit-codes are useful because they are not only smaller than the parse tree, but also smaller than the string being parsed and they can be combined with methods for text compression. We would like to emphasize that, unlike Cox’s work, which develops its VM using a instruction set like syntax and semantics, we use, as inspiration, virtual machines for the λ -calculus, like the SECD and Krivine machines [14, 15].

One important issue regarding RE parsing is how to deal with the so-called problematic RE¹[1]. In order to avoid the well-known issues with problematic RE, we use a transformation proposed by Medeiros et. al. [16] which turns a problematic RE into an equivalent non-problematic one. We prove that this algorithm indeed produce equivalent REs using Coq proof assistant.

Our contributions are:

- We present a big step semantics for a greedy RE parsing VM which produces bit-codes as parsing evidence.
- We develop a certified implementation of an algorithm that converts a problematic RE into a non-problematic one.
- We prove that the bit-codes produced by our VM are valid parsing evi-

¹We say that a RE e is problematic if there’s exists e_1 s.t. $e = e_1^*$ and e_1 accepts the empty string.

dence.

- We extract from our formalization a certified algorithm in Haskell and use it to build a RE parsing tool. We compare its performance against well known Haskell library for RE parsing.

This paper describes the continuation of the RE VM-based parsing research which we previously reported on a paper published on SBLP 2018 [17]. The current work improves our previous results mainly by: 1) using a big-step operational semantics which deals correctly with problematic REs, unlike our previous small-step semantics. We simply transform problematic REs into equivalent non-problematic ones before starting their execution by our semantics; 2) we proved that the proposed semantics is deterministic by following the greedy disambiguation strategy; 3) all results of this paper are completely mechanized using Coq proof assistant. Our previous work used property-based testing in order to provide an evidence for the correctness of the small-step semantics.

The rest of this paper is organized as follows. Section 2 presents some background concepts on RE and its parsing problem. Our operational semantics for RE parsing and its theoretical properties are described in Section 3. Our Coq formalization is described in Section 4. Section 5 presents some experimental results regarding the tool produced using the verified algorithm and Section 6 discuss related works. Finally, Section 7 concludes and presents some directions for future work.

While all the code on which this paper is based has been developed in Coq, we adopt a “lighter” syntax when presenting its code fragments. We chose this presentation style in order to improve readability, because functions that use dependently typed pattern matching require a high number of type annotations, which would deviate from our objective of providing an easily understandable formalization. A brief introduction to Coq proof assistant can be found on [Appendix A](#) and proof sketches of the main paper results are presented on [Appendix B](#).

Coq formalization. All source code produced, including the source of this article, instructions on how to build it and replicate the reported experiments are available on-line [18].

2. Background

2.1. Regular expressions: syntax and semantics

REs are defined with respect to a given alphabet. Formally, the following context-free grammar defines RE syntax:

$$e ::= \emptyset \mid \epsilon \mid a \mid ee \mid e + e \mid e^*$$

Meta-variable e will denote an arbitrary RE and a an arbitrary alphabet symbol. As usual, all meta-variables can appear primed or subscripted. In our Coq formalization, we represent alphabet symbols using type `ascii`. We let concatenation of RE, strings and lists by juxtaposition. Notation $|s|$ denotes the size of a string s . Given a RE, we let its `size` be defined by the following function:

$$\begin{aligned} \text{size}(\emptyset) &= 0 \\ \text{size}(\epsilon) &= 1 \\ \text{size}(a) &= 2 \\ \text{size}(e_1 + e_2) &= 1 + \text{size}(e_1) + \text{size}(e_2) \\ \text{size}(e_1 e_2) &= 1 + \text{size}(e_1) + \text{size}(e_2) \\ \text{size}(e^*) &= 1 + \text{size}(e) \end{aligned}$$

Given a pair (e, s) , formed by a RE expression e and a string s , we define its complexity as $(\text{size}(e), |s|)$.

Following common practice [4, 3, 19], we adopt an inductive characterization of RE membership semantics. We let judgment $s \in \llbracket e \rrbracket$ denote that string s is in the language denoted by RE e (Figure 1).

Rule *Eps* states that the empty string (denoted by the ϵ) is in the language of RE ϵ . For any single character a , the singleton string `a` is in the language

$$\begin{array}{c}
\frac{}{\epsilon \in \llbracket \epsilon \rrbracket} \{Eps\} \qquad \frac{a \in \Sigma}{a \in \llbracket a \rrbracket} \{Chr\} \\
\\
\frac{s \in \llbracket e \rrbracket}{s \in \llbracket e + e' \rrbracket} \{Left\} \qquad \frac{s' \in \llbracket e' \rrbracket}{s' \in \llbracket e + e' \rrbracket} \{Right\} \\
\\
\frac{}{\epsilon \in \llbracket e^* \rrbracket} \{StarBase\} \qquad \frac{s \in \llbracket e \rrbracket \quad s' \in \llbracket e^* \rrbracket}{ss' \in \llbracket e^* \rrbracket} \{StarRec\} \\
\\
\frac{s \in \llbracket e \rrbracket \quad s' \in \llbracket e' \rrbracket}{ss' \in \llbracket ee' \rrbracket} \{Cat\}
\end{array}$$

Figure 1: RE inductive semantics.

of RE a . Given membership proofs for REs e and e' , $s \in \llbracket e \rrbracket$ and $s' \in \llbracket e' \rrbracket$, rule *Cat* can be used to build a proof for the concatenation of these REs. Rule *Left* (*Right*) creates a membership proof for $e + e'$ from a proof for e (e'). Semantics for Kleene star is built using the following well known equivalence of REs: $e^* = \epsilon + e e^*$.

We say that two REs are equivalent, written $e \approx e'$, if the following holds:

$$\forall s. s \in \Sigma^* \rightarrow s \in \llbracket e \rrbracket \leftrightarrow s \in \llbracket e' \rrbracket$$

2.2. RE parsing and bit-coded parse trees

One way to represent parsing evidence is to build a tree that denotes a RE membership proof. Following Frisch et. al. and Nielsen et. al. [13, 1], we let parse trees be terms whose type is its underlying RE. The following context-free grammar defines the syntax of parse trees, where we use a Haskell-like syntax for lists.

Term $()$ denotes the parse tree for ϵ and a the tree for a single character RE. Constructor `inl` (`inr`) tags parse trees for the left (right) operand in a union RE. A parse tree for the concatenation $e e'$ is a pair formed by a tree for e and another for e' . A parse tree for e^* is a list of trees for RE e . Such relationship

$$t \rightarrow () \mid a \mid \mathbf{inl} \ t \mid \mathbf{inr} \ t \mid \langle t, t \rangle \mid [] \mid t : ts$$

Figure 2: Parse trees for REs.

between trees and REs is formalized by typing judgment $\vdash t : e$, which specifies that t is a parse tree for the RE e . The typing judgment is defined in Figure 3.

$$\begin{array}{c}
\overline{\vdash () : \epsilon} \qquad \overline{\vdash a : a} \\
\\
\frac{\vdash t : e}{\vdash \mathbf{inl} \ t : e + e'} \qquad \frac{\vdash t : e'}{\vdash \mathbf{inr} \ t : e + e'} \\
\\
\frac{\vdash t_1 : e_1 \quad \vdash t_2 : e_2}{\vdash \langle t_1, t_2 \rangle : e_1 e_2} \qquad \overline{\vdash [] : e^*} \\
\\
\frac{\vdash t : e \quad \vdash ts : e^*}{\vdash t : ts : e^*}
\end{array}$$

Figure 3: Parse tree typing relation.

For any parse tree t , we can produce its parsed string using function `flatten`, which is defined below:


¹²⁵ **Example 1.** Consider the RE $((ab)+c)^*$ and the string $abcab$, which is accepted by that RE. Here is shown the string's corresponding parse tree:

```

10  flatten()      =  ε
11  flatten a      =  a
12
13  flatten(inl t)  =  flatten t
14
15  flatten(inr t)  =  flatten t
16
17  flatten⟨t1, t2⟩ =  (flatten t1)(flatten t2)
18
19  flatten[]       =  ε
20
21  flatten(t : ts) =  (flatten t)(flatten ts)

```

Figure 4: Function for parse tree flattening.



The next theorems relates parse trees and RE semantics. The first one can be proved by an easy induction on the RE semantics derivation and the second
130 by induction on the derivation of $\vdash t : e$.

Theorem 1. For all s and e , if $s \in \llbracket e \rrbracket$ then exists a tree t such that $\text{flatten } t = s$ and $\vdash t : e$.

Theorem 2. If $\vdash t : e$ then $(\text{flatten } t) \in \llbracket e \rrbracket$.

Nielsen et. al. [13] proposed the use of bit-marks to register which branch
135 was chosen in a parse tree for union operator, $+$, and to delimit different matches done by Kleene star expression. Evidently, not all bit sequences correspond to valid parse trees. Ribeiro et. al. [3] showed an inductively defined relation

between valid bit-codes and RE, accordingly to the encoding proposed by [13].

We let the judgement $bs \triangleright e$ denote that the sequence of bits bs corresponds to a
 140 parse-tree for RE e . The bit-code typing relation is presented as an inductively
 defined judgement in Figure 5.

$$\begin{array}{c}
 \overline{[] \triangleright \epsilon} \qquad \overline{[] \triangleright a} \qquad \frac{bs \triangleright e}{0_b bs \triangleright e + e'} \\
 \\
 \frac{bs \triangleright e'}{1_b bs \triangleright e + e'} \quad \frac{bs \triangleright e \quad bs' \triangleright e'}{bs bs' \triangleright ee'} \quad \overline{1_b \triangleright e^*} \\
 \\
 \frac{bs \triangleright e \quad bss \triangleright e^*}{0_b (bs bss) \triangleright e^*}
 \end{array}$$

Figure 5: Typing relation for bit-codes.

The empty string and single character RE are both represented by empty
 bit lists. Codes for RE $e e'$ are built by concatenating codes of e and e' . In RE
 union operator, $+$, the bit 0_b marks that the parse tree for $e + e'$ is built from
 145 e 's and bit 1_b that it is built from e' 's. For the Kleene star, we use bit 1_b to
 denote the parse tree for the empty string and bit 0_b to begin matchings of e in
 a parse tree for e^* .

The relation between a bit-code and its underlying parse tree can be defined
 using functions **encode** and **decode**, which generates a code for an input parse
 150 tree and builds a tree from a bit sequence, respectively.

$$\begin{array}{ll}
 \text{encode}(() : \epsilon) & = [] \\
 \text{encode}(a : a) & = [] \\
 \text{encode}(\text{inl } t : e_1 + e_2) & = 0_b \text{encode}(t : e_1) \\
 \text{encode}(\text{inr } t : e_1 + e_2) & = 1_b \text{encode}(t : e_2) \\
 \text{encode}(\langle t_1, t_2 \rangle : e_1 e_2) & = \text{encode}(t_1 : e_1) \text{encode}(t_2 : e_2) \\
 \text{encode}([] : e^*) & = 1_b \\
 \text{encode}((t : ts) : e^*) & = 0_b \text{encode}(t : e) \text{encode}(ts : e^*)
 \end{array}$$

Function `encode` has an immediate definition by recursion on the structure of a parse tree. While coding a parse tree does not depend on its underlying RE, we keep it on the `encode` function to follow its original definition [13]. In the definition of function `decode`, we use an auxiliary function, `decode1`, which

155 threads the remaining bits in recursive calls.

```

decode1(bs : ε)      =  ((), bs)
decode1(bs : a)      =  (a, bs)
decode1(0b bs : e1 + e2) =  let (t, bs1) = decode1(bs : e1)
                                in (inl t, bs1)
decode1(1b bs : e1 + e2) =  let (t, bs2) = decode1(bs : e2)
                                in (inr t, bs2)
decode1(bs : e1 e2)    =  let (t1, bs1) = decode1(bs : e1)
                                (t2, bs2) = decode1(bs1 : e2)
                                in ((t1, t2), bs2)
decode1(1b bs : e*)    =  ([], bs)
decode1(0b bs : e*)    =  let (t, bs1) = decode1(bs : e)
                                (ts, bs2) = decode1(bs1 : e*)
                                in ((t : ts), bs2)

decode(bs : e)        =  let (t, bs1) = decode1(bs : e)
                                in if bs1 = [] then t else error


```

For single character and empty string REs, its decoding consists in just building the tree and leaving the input bit-coded untouched. We build a left tree (using `inl`) for $e + e'$ if the code starts with bit 0_b . A parse tree using constructor `inr` is built whenever we find bit 1_b for a union RE. Building a

160 tree for concatenation is done by sequencing the processing of codes for left component of concatenation and starting the processing of right component with the remaining bits from the processing of the left RE. Parsing the code for a Kleene star e^* consists in consuming a 0_b , which marks the beginning of the code for a match for e , followed for the code for a tree for e itself. We finish a

list of matchings using a bit 1_b .

Example 2. We present again the same RE and string we showed in Example 1, denoted by $((ab) + c)^*$ and $ab cab$, respectively. Note that the parse tree is also the same. However, this time we decorate trees with its bit codes. Bits introduced as parse tree separators of the Kleene star were put as childs of the tree's root. The first tree is built by the left operand of choice. Then it is marked by the bit 0_b . Second tree is built by choice's right operand and then is marked by bit 1_b . Last parse tree is again processed by the left alternative of choice and then is represented by the bit 0_b . Finally, we finish the code using the bit 1_b , which ends the matching list build by the Kleene star operator.



The relation between codes and its correspondent parse trees is specified in the next theorem.

Theorem 3. Let t be a parse tree such that $\vdash t : e$, for some RE e . Then $(\text{encode } t e) \triangleright e$ and $\text{decode}(\text{encode } t e) : e = t$.

2.3. Dealing with problematic REs

A known problem in RE parsing is how to deal with the so-called problematic REs. A naive approach to parsing problematic REs can make the algorithm loop [1]. Medeiros et al. [16] present a function which converts a problematic RE into an equivalent non-problematic one.

The conversion function relies on two auxiliar definitions: one for testing if a RE accepts the empty string and another to test if a RE is equivalent to ϵ . We name such functions as **nullable** and **empty**, respectively.

$$\begin{aligned}
\text{nullable}(\emptyset) &= \perp \\
\text{nullable}(\epsilon) &= \top \\
\text{nullable}(a) &= \perp \\
\text{nullable}(e_1 + e_2) &= \text{nullable}(e_1) \vee \text{nullable}(e_2) \\
\text{nullable}(e_1 e_2) &= \text{nullable}(e_1) \wedge \text{nullable}(e_2) \\
\text{nullable}(e^*) &= \top \\
\\
\text{empty}(\emptyset) &= \perp \\
\text{empty}(\epsilon) &= \top \\
\text{empty}(a) &= \perp \\
\text{empty}(e_1 + e_2) &= \text{empty}(e_1) \wedge \text{empty}(e_2) \\
\text{empty}(e_1 e_2) &= \text{empty}(e_1) \wedge \text{empty}(e_2) \\
\text{empty}(e^*) &= \text{empty}(e)
\end{aligned}$$

Functions **nullable** and **empty** obey the following correctness properties.

Lemma 1. $\text{nullable}(e) = \top$ if, and only if, $\epsilon \in \llbracket e \rrbracket$.

Lemma 2. If $\text{empty}(e) = \top$ then $e \approx \epsilon$.

Given these two predicates, Medeiros et.al. [16] define two mutually recursive functions, named **f_{in}** and **f_{out}**. The function **f_{out}** recurses over the structure of an input RE searching for a problematic sub-expression and **f_{in}** rewrites the Kleene star subexpression so that it becomes non-problematic and preserves the language of the original RE. The definition of functions **f_{in}** and **f_{out}** are presented next.

$$\begin{aligned}
f_{\text{out}}(e) &= e, \text{ if } e = \epsilon, e = \emptyset \text{ or } e = a \\
f_{\text{out}}(e_1 + e_2) &= f_{\text{out}}(e_1) + f_{\text{out}}(e_2) \\
f_{\text{out}}(e_1 e_2) &= f_{\text{out}}(e_1) f_{\text{out}}(e_2) \\
f_{\text{out}}(e^*) &= \begin{cases} f_{\text{out}}(e)^* & \text{if } \neg \text{nullable}(e) \\ \epsilon & \text{if } \text{empty}(e) \\ f_{\text{in}}(e)^* & \text{otherwise} \end{cases}
\end{aligned}$$

$$\begin{aligned}
f_{\text{in}}(e_1 e_2) &= f_{\text{in}}(e_1 + e_2) \\
f_{\text{in}}(e_1 + e_2) &= \begin{cases} f_{\text{in}}(e_2) & \text{if } \text{empty}(e_1) \wedge \text{nullable}(e_2) \\ f_{\text{out}}(e_2) & \text{if } \text{empty}(e_1) \wedge \neg \text{nullable}(e_2) \\ f_{\text{in}}(e_1) & \text{if } \text{nullable}(e_1) \wedge \text{empty}(e_2) \\ f_{\text{out}}(e_1) & \text{if } \neg \text{nullable}(e_1) \wedge \text{empty}(e_2) \\ f_{\text{out}}(e_1) + f_{\text{in}}(e_2) & \text{if } \neg \text{nullable}(e_1) \wedge \neg \text{empty}(e_2) \\ f_{\text{in}}(e_1) + f_{\text{out}}(e_2) & \text{if } \neg \text{empty}(e_1) \wedge \neg \text{nullable}(e_2) \\ f_{\text{in}}(e_1) + f_{\text{in}}(e_2) & \text{otherwise} \end{cases} \\
f_{\text{in}}(e^*) &= \begin{cases} f_{\text{in}}(e) & \text{if } \text{nullable}(e) \\ f_{\text{out}}(e) & \text{otherwise} \end{cases}
\end{aligned}$$

The result of applying f_{out} on a RE is producing an equivalent non-problematic one. This fact is expressed by the following theorem.

Theorem 4. If $f_{\text{out}}(e) = e'$ then $e \approx e'$ and e' is a non-problematic RE.

²⁰⁰ This result is proved (informally²) by Medeiros et. al. [16]. In order to formalize this result in Coq, we needed to prove several theorems about RE equivalence. We postpone the discussion on some details of our formalization to Section 4.

²By “informally”, we mean that the result is not mechanized in a proof assistant.

3. Proposed semantics for RE parsing

In this section we present the definition of a big step operational semantics for a greedy RE parsing VM. The state of our VM is a pair formed by the current RE and the string under parsing. Each machine transition produces as a result a bit-coded parse tree and the remaining string to be parsed. We denote our semantics by a judgement of the form $\langle e, s \rangle \rightsquigarrow^n (bs, s_p, s_r)$, where e is the current RE, s is the input string, n a step counter (used in some inductive arguments about the semantics), bs is the produced bit-coded tree, s_p is the parsed prefix of the input string and s_r is the yet to be parsed string. We let notation $\langle e, s \rangle \not\rightsquigarrow^n$ denote the fact that string s cannot be parsed by RE e . The semantics rules are presented in Figure 6.

The meaning of each semantic rule in Figure 6 is as follows. Rule *Emp* says that the empty set RE fails on every input string and rule *Eps* specifies that parsing s using RE ϵ produces an empty list of bits and does not consume any symbol from s . The rule *Chr1* consumes the first symbol of the input string if it matches the input RE and rules *Chr2* and *Chr3* handles the fail cases (different first symbol or empty string).

Rules for star and choice operator encode the greedy disambiguation strategy for RE parsing: first the parse tries the left operand of an alternative (rule *Ch1*) and backtracks to try the right one only if the left fails (rule *Ch2*). Rules for Kleene star follows the interpretation which matches the input as many times as possible (rule *St2*). Parsing input using RE e^* stops when e fails (rule *St1*).

Our proposed semantics enjoy some important properties: 1) it is sound with respect to standard RE inductive semantics; 2) it produces only valid parsing results; 3) the semantics is deterministic and 4) the successful execution of the semantics will consume a prefix of the input string. All these results were proved by induction on the complexity of the pair (e, s) .

Theorem 5 (Soundness). If $\langle e, s \rangle \rightsquigarrow^n (bs, s_p, s_r)$ then $s = s_p s_r$ and $s_p \in \llbracket e \rrbracket$.

Theorem 6 (Parsing result soundness). If $\langle e, s \rangle \rightsquigarrow^n (bs, s_p, s_r)$ then: 1) $bs \triangleright e$; 2) $\text{flatten}(\text{decode}(bs : e)) = s_p$; and 3) $\text{encode}(\text{decode}(bs : e) : e) = bs$.

$$\begin{array}{c}
\overline{\langle \emptyset, s \rangle \not\rightarrow^1} \{Emp\} \qquad \overline{\langle \epsilon, s \rangle \rightsquigarrow^1 ([], \epsilon, s)} \{Eps\} \qquad \overline{\langle a, as \rangle \rightsquigarrow^1 ([], a, s)} \{Chr1\} \\
\\
\frac{a \neq a'}{\langle a, a' s \rangle \not\rightarrow^1} \{Chr2\} \qquad \overline{\langle a, \epsilon \rangle \not\rightarrow^1} \{Chr3\} \qquad \frac{\langle e_1, s \rangle \not\rightarrow^n}{\langle e_1 e_2, s \rangle \not\rightarrow^{1+n}} \{Cat1\} \\
\\
\frac{\langle e_1, s_1 s_2 \rangle \rightsquigarrow^n (bs_1, s_1, s_2) \quad \langle e_2, s_2 \rangle \not\rightarrow^m}{\langle e_1 e_2, s_1 s_2 \rangle \not\rightarrow^{1+n+m}} \{Cat2\} \\
\\
\frac{\langle e_1, s_1 s_2 s_r \rangle \rightsquigarrow^n (bs_1, s_1, s_2 s_r) \quad \langle e_2, s_r \rangle \rightsquigarrow^m (bs_2, s_2, s_r)}{\langle e_1 e_2, s_1 s_2 s_r \rangle \rightsquigarrow^{1+n+m} (bs_1 bs_2, s_1 s_2, s_r)} \{Cat3\} \\
\\
\frac{\langle e_1, s_1 s_r \rangle \rightsquigarrow^n (bs, s_1, s_r)}{\langle e_1 + e_2, s_1 s_r \rangle \rightsquigarrow^{1+n} (0_b bs, s_1, s_r)} \{Ch1\} \\
\\
\frac{\langle e_1, s_2 s_r \rangle \not\rightarrow^n \quad \langle e_2, s_2 s_r \rangle \rightsquigarrow^m (bs, s_2, s_r)}{\langle e_1 + e_2, s_2 s_r \rangle \rightsquigarrow^{1+n+m} (1_b bs, s_2, s_r)} \{Ch2\} \\
\\
\frac{\langle e_1, s \rangle \not\rightarrow^n \quad \langle e_2, s \rangle \not\rightarrow^m}{\langle e_1 + e_2, s \rangle \not\rightarrow^{1+n+m}} \{Ch3\} \\
\\
\frac{\langle e_1, s \rangle \not\rightarrow^n}{\langle e_1^*, s \rangle \rightsquigarrow^{1+n} (1_b, \epsilon, s)} \{St1\} \quad \frac{\langle e_1, s_1 s_2 s_r \rangle \rightsquigarrow^n (bs, s_1, s_2 s_r) \quad \langle e_1^*, s_2 s_r \rangle \rightsquigarrow^m (bss, s_2, s_r)}{\langle e_1^*, s_1 s_2 s_r \rangle \rightsquigarrow^{1+n+m} (0_b bs bs, s_1 s_2, s_r)} \{St2\}
\end{array}$$

Figure 6: Operational semantics for RE parsing.

Theorem 7 (Determinism). If $\langle e, s \rangle \rightsquigarrow^n r$ and $\langle e, s \rangle \rightsquigarrow^m r'$ then $n = m$ and $r = r'$.

Proof sketches of these theorems can be found on [Appendix B](#).

4. Coq formalization

In this section we describe the main design decisions in our formalization. At the end of this section, we discuss how we extract a Haskell implementation from our Coq development.

RE syntax and semantics. Our representation of RE syntax and semantics is as usual in type-theory based proof assistants. We use an inductive type to represent RE syntax and an inductive predicate to denote its semantics.

```
Inductive regex : Set :=
| Empty : regex | Eps : regex | Chr : ascii -> regex
| Cat : regex -> regex -> regex
| Choice : regex -> regex -> regex
| Star : regex -> regex.
```

Type `regex` represents RE syntax and its definition is straightforward. We use some notations to write `regex` values. We let `#0` denote `Empty`, `#1` represents `Eps`. Constructor `Chr` is denoted by `$`, while infix operators `:+:` and `@` denote `Choice` and `Cat`. Finally, `Star e` is written `(e ^*)`. In our code presentation, we let `‘c’` denote `String c ‘‘’`, for readability reasons.

RE semantics is represented by type `in_regex` which has a constructor for each rule of the semantics presented in Figure 1.

```
Inductive in_regex : string -> regex -> Prop :=
| InEps : "" <-< #1
| InChr : forall c, "c" <-< ($ c)
| InLeft
: forall s e e'
```

```

9      , s <- e
10     -> s <- (e :+: e')
11
12 | InStarRight
13   : forall s s' e a s1
14   -> String a s <- e
15   -> s' <- (e ^*)
16   -> s1 = String a s ++ s'
17   -> s1 <- (e ^*)
18
19 ... (** some constructors omitted. *)
20
21 where "s '<->' e" := (in_regex s e).

```

We use notation $s \leftarrow e$ to denote `in_regex s e`.

RE equivalence. Using the previous presented semantics, we can define RE equivalence by coding the standard definition in Coq as:

```

32 Definition regex_equiv (e e' : regex) : Prop :=
33   forall s, s <- e <-> s <- e'.

```

We use notation $e1 === e2$ to denote `regex_equiv e1 e2`. In our formalization, we proved that `regex_equiv` is an equivalence relation, which is necessary to allow the rewriting of such equalities by Coq tactics.

In order to complete our formalization, we needed several results about RE equivalence. Most of them are proved by well-founded induction on the complexity of a pair formed by a RE and a string (defined in Section 2.1). In order to formalize the needed ordering relation, we take advantage of Coq's standard library, which provides several combinators to assemble well-founded relations. As an example, consider the following fact used by Medeiros et. al [16] to prove the correctness of its `fout` function: $(e_1 + e_2)^* \approx (e_1 e_2)^*$, which holds if both e_1 and e_2 accepts the empty string. In our formalization such equivalence is proved by the following theorem proved by well-founded induction.

```

56 Lemma choice_star_cat_star

```



```

9      : forall e1 e2, "" <- e1 -> "" <- e2 ->
10      ((e1 @ e2) ^*) == ((e1 :+: e2) ^*).

```

Several other lemmas about RE equivalence were proved in order to complete the formalization of the problematic RE conversion function. We omit them for brevity.

Converting problematic REs. The first step to certify the algorithm for converting problematic REs into non-problematic ones is to define the predicates for testing whether an input RE is nullable or whether it is equivalent to ϵ . We define such functions using dependently typed programming, i.e. their types provide certificates that the result satisfies the desired correctness property.

The nullability test is represented by function `null`:

```

29 Definition null : forall e, {"" <- e} + {~ "" <- e}.
30
31 refine (fix null e : {"" <- e} + {~ "" <- e} :=
32   match e as e' return e = e' ->
33     {"" <- e'} + {~ "" <- e'} with
34   | #1 => fun Heq => Yes
35   | e1 @ e2 => fun Heq =>
36     match null e1 , null e2 with
37     | Yes , Yes => Yes
38     | _ , _ => No
39   end
40   | e1 :+: e2 => fun Heq => ...
41   | e1 ^* => fun Heq => Yes
42   end (eq_refl e)) ...
43
44 (** some cases and tactics omitted *)

```

Its type specifies that for any RE e either e accepts the empty string (i.e. `"" <- e` holds) or not (`~ "" <- e`). Since such function contains proofs terms, we use tactic `refine` to define its computation content leaving the logical subterms to be filled by tactics. The definition of `null` employs the convoy-

pattern [20], which consists in introducing an equality to allow the refinement

280 of each equation type in dependently typed pattern-matching.

In order to specify the emptiness test predicate, we use an inductive type which characterizes when a RE is equivalent to ϵ .

```

Inductive empty_regex : regex -> Prop :=
| Emp_Eps : empty_regex #1
| Emp_Cat : forall e e', empty_regex e ->
    empty_regex e' ->
    empty_regex (e @ e')
| Emp_Choice : forall e e', empty_regex e ->
    empty_regex e' ->
    empty_regex (e :+: e')
| Emp_Star : forall e, empty_regex e ->
    empty_regex (e ^*).

```

285 The meaning of each constructor of `empty_regex` is as follows: `Emp_Eps` specifies that the empty RE is equivalent to itself. For concatenation, choice and Kleene star, we can only say that they are equivalent to ϵ if all of its subterms are also equivalent to the empty RE.

290 Using the `empty_regex` predicate we can easily prove the following theorems. The first specifies that if `empty_regex e` holds then `e` accepts the empty string and the second says that if `empty_regex e` is provable then `e` is equivalent to the empty string RE.

```

Lemma empty_regex_sem : forall e, empty_regex e -> "" <- e.
Theorem empty_regex_spec : forall e, empty_regex e -> e == #1.

```

The emptiness test function follows the same definition pattern as `null` using the `refine` tactic. We specify its type using `empty_regex` predicate and we omit its definition for brevity.

295 Having defined these two predicates, we can implement the function to convert problematic REs into non-problematic ones. The specification of when a RE is not problematic is given by the following inductive predicate.

```

1
2
3
4
5
6
7
8
9   Inductive unproblematic : regex -> Prop :=
10   | UEmpty : unproblematic #0
11   | UEps   : unproblematic #1
12   | UChr   : forall c, unproblematic ($ c)
13   | UCat   : forall e e', unproblematic e ->
14             unproblematic e' ->
15             unproblematic (e @ e')
16   | UChoice : forall e e', unproblematic e ->
17             unproblematic e' ->
18             unproblematic (e :+: e')
19   | UStar   : forall e, ~ (" <- e) ->
20             unproblematic e ->
21             unproblematic (Star e).
22
23
24
25
26
27
28
29

```

Type `unproblematic` says that empty set, empty string and single characters REs are unproblematic. Concatenation and choice REs are unproblematic if both its subexpression are unproblematic. Finally, a Kleene star is unproblematic if its subexpression is unproblematic and does not accept the empty string. Finally, we specify the problematic RE conversion function with the following type:

```

30
31
32
33
34
35   Definition unprob
36   : forall (e : regex), {e' | e == e' /\ unproblematic e'}.
37
38
39

```

Function `unprob` type says that from an input RE `e` it returns another RE `e'` which is unproblematic and equivalent to `e`. Again, we define `unprob` using `refine` tactic and its definition is just the Coq coding of `fout`. As pointed by Medeiros et. al. [16], most of the work to produce an unproblematic RE is done by function `fin`, which is applied when the inner RE of a Kleene star accepts the empty string and is not equivalent to the empty RE. Function `unprob_rec` implements `fin` function and we specify it with the following type:

```

40
41
42
43
44
45   Definition unprob_rec : forall e, " <- e -> ~ empty_regex e ->
46   {e' | (e ^*) == (e' ^*) /\ ~ " <- e' /\ unproblematic e'}
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65

```

310 `unprob_rec`'s type establishes that the returned RE `e'` is unproblematic, does not accept the empty string and that its Kleene star is equivalent to input REs Kleene star, i.e. $(e \ ^*) == (e' \ ^*)$.

Parse trees and bit-code representation. In our formalization, we use the following inductive type to represent parse trees:

```
Inductive tree : Set :=
| TUnit   : tree | TChr   : ascii -> tree
| TCat    : tree -> tree -> tree
| TLeft   : tree -> tree | TRight : tree -> tree
| TNil    : tree | TCons   : tree -> tree -> tree.
```

315 Constructor `TUnit` denotes a parse tree for the empty string RE, `TChr` the tree for a single symbol RE and `TCat` the tree for the concatenation of two REs. `TLeft` and `TRight` denote trees for the choice operator. Constructors `TCons` and `TNil` can be used to form a list of trees for a Kleene star RE.

320 The parse tree typing judgement is coded as the following inductive predicate, in which each constructor has a correspondent rule in Figure 3.

```
Inductive is_tree_of : tree -> regex -> Prop :=
| ITChr   : forall c, (TChr c) :> ($ c)
| ITCat   : forall e t e' t',
    t :> e ->
    t' :> e' ->
    (TCat t t') :> (e @ e')
| ITLeft  : forall e t e',
    t :> e ->
    (TLeft t) :> (e :+: e')
| ITCons  : forall e t ts,
    t :> e ->
    ts :> (Star e) ->
    (TCons t ts) :> (Star e)
```

```
where "t'>' e" := (is_tree_of t e).
```

```
(** some code omitted *)
```

Function `flatten` (shown in Figure 4) has a direct encoding as a Coq recursive definition and we omit it for brevity. From `flatten` and tree typing relation definitions, theorems 1 and 2 are easily proved.

Bit coding of parse trees is represented by a list of bits, as follows:

```
Inductive bit : Set := 0 : bit | 1 : bit.
```

```
Definition code := list bit.
```

325 The typing relation for bit-coded parse trees (Figure 5) has an immediate definition as an inductively defined Coq relation.

```
Inductive is_code_of : code -> regex -> Prop :=
```

```
| ICChar : forall c, [] :# ($ c)
```

```
| ICLLeft : forall bs e e'
```

```
, bs :# e ->
```

```
(0 :: bs) :# (e :+: e')
```

```
| ICCat : forall bs bs' e e'
```

```
, bs :# e ->
```

```
bs' :# e' ->
```

```
(bs ++ bs') :# (e @ e')
```

```
| ICCons : forall e bs bss,
```

```
bs :# e ->
```

```
bss :# (e ^*) ->
```

```
(0 :: bs ++ bss) :# (e ^*)
```

```
where "bs' :# e" := (is_code_of bs e).
```

```
(** some code omitted *)
```

As with `flatten`, function `encode` has an immediate Coq definition. The next results about `encode` are proved by a routine inductive proof.

```
Lemma encode_sound
```

```
: forall bs e, bs :# e -> exists t, t :> e /\ encode t = bs.
```

```

1
2
3
4
5
6
7
8
9   Lemma encode_complete
10      : forall t e, t :> e -> (encode t) :# e.
11
12

```

Unlike `encode`, function `decode` has a more elaborate recursive definition, as shown in Section 2.2, since it recurses over the input RE while threading the remaining bits to be parsed into a tree. Since it has a more complicated definition, we use dependent types to combine its definition with its correctness proof. First, we define type `nocode_for` which denotes proofs that some bit list is not a valid bit-coded tree for some RE.

```

22
23   Inductive nocode_for : code -> regex -> Prop :=
24   | NCEmpty : forall bs, nocode_for bs #0
25   | NCChoicenil : forall e e', nocode_for [] (e :+: e')
26   | NCLBase : forall bs e e',
27     nocode_for bs e ->
28     nocode_for (0 :: bs) (e :+: e')
29   | NCRBase : forall bs e e',
30     nocode_for bs e' ->
31     nocode_for (I :: bs) (e :+: e')
32   | NCStarnil : forall e, nocode_for [] (e ^*)
33   | NCStar : forall bs bs1 bs2 e,
34     is_code_of bs1 e ->
35     nocode_for bs2 (e ^*) ->
36     bs = 0 :: bs1 ++ bs2 ->
37     nocode_for bs (e ^*)
38   | NCStar1 : forall bs e,
39     nocode_for bs e ->
40     nocode_for (0 :: bs) (e ^*).
41
42   (** some code omitted *)
43
44

```

Constructor `NCEmpty` specifies that there is no code for the empty RE, `#0`. For choice REs, we have several cases to cover. Constructor `NCChoicenil` specifies that the empty list is not a valid code for any choice RE. Constructor `NCLBase`

(NCRBase) specifies that if a list isn't a valid code for a RE e (e') it cannot be used to form a valid code for $e :: e'$. In order to build a proof that some bit list isn't a valid code for a concatenation RE, we just need to prove that it is not a code for some of its sub-expressions. Finally, for the Kleene star, we have some cases to cover: first, constructor `NCRstarnil` shows that the empty list cannot be a code for any star RE. For non-empty bit-lists, it is just necessary to show that some part of the bit list isn't a code either for e or e^* .

Using predicate `nocode_for` we can define a type for invalid bit-codes:

```
Definition invalid_code bs e :=
  nocode_for bs e /\ exists t b1 bs1, bs = (encode t) ++ (b1 :: bs1).
```

which basically says that a bit list is an invalid code for a RE e when either we can construct a proof of `nocode_for` or we can parse a prefix of it into a valid tree but it leaves a non-empty bit list as a remaining suffix. Using this infrastructure, we can define the decode function with the following type:

```
Definition decode e bs :
  {t | bs = encode t /\ is_tree_of t e} + {invalid_code bs e}.
```

Note that the previous type denotes the correctness property of a decode function: either it returns a valid tree for the input RE that can be converted into the input bit list or a proof that such bit list isn't a valid code for the input RE.

Formalizing the proposed semantics and its interpreter. Our semantics definition consists of the Coq representation of the judgement in Figure 6, which is presented below. We use data-type `ouput` to represent success and failure cases in the semantics.

```
Inductive ouput : Set :=
| Ok      : string -> string -> code -> ouput
| Error   : ouput.
```

Constructor `Ok` stores the parsed prefix, the remaining suffix and the produced bit-code. The constructor `Error` is used to represent a parsing failure.

The semantics rules presented in Figure 6, are encoded as constructors of type `greedy`, which relates the executed RE, the input string, a step counter (value of type `nat`) and the result, of type `output`.

```

Inductive greedy : regex -> string -> nat -> output -> Prop :=
| G_Empty
  : forall s, greedy #0 s 0 Error
| G_Eps
  : forall s, greedy #1 s 1 (Ok "" s [])
| G_ChroK
  : forall a s, greedy ($ a) (String a s) 2 (Ok (String a "") s [])
| G_Choice_0k1
  : forall e1 e2 s s1 r1 bs1 n,
    s = s1 ++ r1 ->
    greedy e1 s n (Ok s1 r1 bs1) ->
    greedy (e1 :+: e2) s (1 + n) (Ok s1 r1 (0 :: bs1))
| G_Choice_0k2
  : forall e1 e2 s s2 r2 bs2 n m,
    s = s2 ++ r2 ->
    greedy e1 s n Error ->
    greedy e2 s m (Ok s2 r2 bs2) ->
    greedy (e1 :+: e2) s (1 + n + m) (Ok s2 r2 (I :: bs2))
| G_Star_Rec
  : forall e1 s s1 r1 bs1 s2 r2 bs2 n m,
    s = s1 ++ r1 ->
    greedy e1 s n (Ok s1 r1 bs1) ->
    r1 = s2 ++ r2 ->
    greedy (Star e1) r1 m (Ok s2 r2 bs2) ->
    greedy (Star e1) s (1 + n + m) (Ok (s1 ++ s2) r2 (0 :: bs1 ++ bs2))
| G_Star_Base
  : forall e1 s n,

```



```

9      greedy e1 s n Error ->
10     greedy (Star e1) s (1 + n) (Ok "" s (I :: [])).
11
12 (** some code omitted *)
13

```

The main results of our semantics are stated below: soundness and determinism. The soundness theorem is proved by induction on the complexity of the pair (e, s) and it is the Coq encoding of Theorem 5.

```

19
20 Theorem greedy_sound
21   : forall e s n s1 r1 bs1,
22     s = s1 ++ r1 ->
23     unproblematic e ->
24     greedy e s n (Ok s1 r1 bs1) ->
25     s1 <== e.
26

```

365 Determinism of our semantics is proved by the next Coq theorem which encodes Theorem 7.

```

33
34 Theorem greedy_deterministic
35   : forall n e s o1, greedy e s n o1 ->
36     forall m o2, greedy e s m o2 -> n = m /\ o1 = o2.
37

```

370 After a proper definition of our semantics, we developed a formalized interpreter for it. First, we need to define a type which ensures its correctness. Type `interp_type` uses type `sumor` to encode the following property: either the interpreter returns a bit list which is a valid parsing evidence for the RE e' which is a equivalent non-problematic RE to the input expression e or either it returns a proof that the parsing process results in a error.

```

49
50 Definition interp_type e s :=
51   {bs : code | exists e', e == e' /\
52     exists n cs rs, greedy e' s n (Ok cs rs bs) /\ bs :# e'} +
53   {exists e' m, e == e' /\ greedy e' s m Error}.
54

```

Building a term with an intricate dependent type such `interp_type` is a hard job. Some Coq extensions try to ease the task of dependently typed programming [21]. In this work, we avoid using such extensions and build our definition using tactics, which can be used to build programs. The code of our semantics interpreter is shown next.

The main interpreter logic is built by well-founded induction on the complexity of the RE and input string. This is done using the following definitions. Type `greedy_interp_type` gives a synonym for the interpreter of our semantics, which basically takes a non-problematic RE and a string and returns a pair formed by the step counter and a value of type `output`, which represents the parsing process result.

```
Definition greedy_interp_type e s :=
  unproblematic e -> {r | greedy e s (fst r) (snd r)}.
```

Next, we define a function which encodes the interpreter logics by allowing recursion only on pairs which are structurally smaller than the input. This style of programming is a way to define function of a complex recursive pattern in a total programming language, like Coq [20]. Function `greedy_interp_F` takes a pair $p = (e, s)$ formed by a RE and a string and a function which allows to recurse on smaller pairs and returns the result of executing the semantics on the input pair p .

```
Definition greedy_interp_F
: forall p, (forall p', input_lt p' p ->
  greedy_interp_type (get_regex p') (get_string p')) ->
  greedy_interp_type (get_regex p) (get_string p).
```

Using function `greedy_interp_F`, we build the interpreter for non-problematic expressions: `greedy_interp`, which is defined using Coq's library well-founded recursion combinator `well_founded_induction` [22].

```
Definition greedy_interp : forall e s, greedy_interp_type e s.
  intros e s Hu.
```

```

1
2
3
4
5
6
7
8
9   change e with (get_regex (mk_input e s)) in *.
10  change s with (get_string (mk_input e s)).
11
12    apply (well_founded_induction
13           wf_input_lt
14           (fun p =>
15             greedy_interp_type (get_regex p) (get_string p))
16           ) ; eauto.
17
18  apply greedy_interp_F.
19
20 Defined.
21
22
23

```

Now that we have an interpreter for non-problematic RE, we just need to combine it with function `unprob` which converts the input RE into a non-problematic equivalent.

```

24
25
26
27
28
29 Definition interp e s : interp_type e s.
30
31   lets Hu : unprob e.
32   destruct Hu as [e' [Heq' Hu']].
33
34

```

Next, we just call function `greedy_interp` which executes a non-problematic RE over the input string and returns a semantics derivation corresponding to the parser execution.

```

35
36
37
38
39
40   assert (Hr : {r : nat * output | greedy e' s (fst r) (snd r)}).
41   apply greedy_interp ; eauto.
42
43

```

We finish the interpreter definition by pattern matching on `greedy_interp` results and applying lemmas which prove that: 1) assert that the input string is the concatenation of the parsed prefix and the remaining suffix (lemma `greedy_prefix`) and the returned bit-coded parse tree is a valid for the RE.

```

44
45
46
47
48
49
50
51   destruct Hr as [[n o] Hr] ; simpl in *.
52   destruct o as [cs rs bs | ].
53
54   -
55
56   left ; exists* bs.
57
58

```

```

1
2
3
4
5
6
7
8
9     exists e' ; splits* ; exists n cs rs ; splits*.
10    assert (s = cs ++ rs) by (eapply greedy_sound ; eauto).
11    eapply greedy_typed ; eauto.
12
13  -
14
15    right ; exists* e' n.
16
17  Defined.
18

```

Extracting a certified implementation. In order to obtain a certified Haskell
405 implementation from our VM-based algorithm, we use Coq support for extrac-
22 tion, which has several pre-defined settings for using data-types and functions
23 of Haskell's Prelude³.

The extracted Haskell code for our VM interpreter has 280 lines. In order
27 to use the algorithm, we build a grep-like command line tool, which is available
28 at project's on-line repository [18].
410

5. Evaluation

In this section we consider the performance of our VM for RE parsing.
36 First, we develop an analytical model of its execution time and then consider
37 its performance against some well-known REs used to test parsing algorithms.

5.1. Analytical model

Given an input non-problematic RE e , we will let $T(e)$ denote the time to
43 execute e over an input string s . We consider that n denote the length of the
44 currently parsed input string. The definition of $T(e)$ is as follows:

³Prelude is the name of the Haskell library automatically loaded in any Haskell module [23].

$$\begin{aligned}
T(\emptyset) &= 1 \\
T(\epsilon) &= 1 \\
T(a) &= 1 \\
T(e_1 + e_2) &= T(e_1) + T(e_2) \\
T(e_1 e_2) &= T(e_1) + T(e_2) \\
T(e_1^*) &= n \times T(e_1)
\end{aligned}$$

Figure 7: Analytical model for VM execution time.

The execution time of the empty set, empty word and a single character RE is constant. The time needed to parse the concatenation or the choice of two RE is just the sum of their times.

Since our formalization deals only with non-problematic RE, each iteration of a Kleene star RE must consume, at least, one character. Since the input string has size n and each match demands $T(e_1)$, total parsing time would be $n \times T(e_1)$.

The model allow us to show that time complexity of the proposed semantics is linear on the size of input string. This property can be proved by structural induction on the executed RE.

Theorem 8. Let e be an arbitrary unproblematic expression and s arbitrary string. The execution time of $\langle e, s \rangle \rightsquigarrow r$ is $O(n)$, where $n = |s|$.

5.2. Experiments

We use the formalized algorithm to build a Haskell tool for RE parsing and compare its performance against the library regex-applicative [24], which is an optimized library for RE matching / parsing for Haskell. The reason for choosing this library is that it allows us to build bit coded parse trees using its applicative interface [25], enabling a more fair comparison with our algorithm. We ran our experiments on a machine with a Intel Core I7 1.7 GHz, 8GB RAM running Mac OS X 10.15.2 using GHC version 8.0.1; the results were collected and the

average of several test runs were computed. In order to allow reproducibility, the on-line repository contains a Haskell program that automates the task of running the experiments to produce the graphs presented next.

Also, we would like to emphasize that the intent of these experiments is not to conclude that the proposed algorithm is more (less) efficient than the chosen library for RE parsing. Our main objective is to show that a fully verified algorithm can have a performance comparable to an optimized library to the same task.

The first experiment consists in parsing strings formed by a's by RE $(a + b + ab)^*$ and the second with strings formed by ab's (examples taken from [12]). The results are presented in Figures 8 and 9.




Figure 8: Results of experiment 1.




Figure 9: Results of experiment 2.

When compared with regex-applicative, our tool exhibits a similar performance in this test: both have a linear performance.

Another experiment considered was to parse strings a^n by the RE $(a + \epsilon)^n a^n$, where a^n denotes $n \geq 0$ copies of a . Such RE poses a challenge to RE parsing algorithms since they need to simulate the traversal of 2^n paths, by backtracking, before finding a match [13]. The results of executing this experiment on increasing values of n is presented in Figure 10.

In this example, our approach has a much better performance than regex-applicative, which exhibits an exponential behaviour (also known as catastrophic backtracking [26]). Such bad behaviour on large REs can be explained by the NFA-based parsing algorithm used by regex-applicative library. Notice that our




Figure 10: Results of experiment 3.




Figure 11: Results of experiment 3 considering only the VM.

VM-based algorithm shows a linear performance on such problematic inputs, as expected by our analytical model.

The last experiment considered is to test how both approaches perform on random generated REs and random accepted strings for them. In order to perform such test, we use Haskell library QuickCheck [27]. The experiment consists in collecting the result of running both semantics on thousands of input pairs formed by a RE and strings. The average of such executions is presented in the Figure 12, which shows that both algorithms exhibit a linear behaviour on random inputs.




Figure 12: Results of experiment 4.

A few words should be written about how we generate random inputs. Gen-

eration of random RE is done by function `sizedRegex` with takes a depth limit to restrict the size of the generated RE. Whenever the input depth limit is less or equal to 1, we can only build a ϵ or a single character RE. The definition of `sizedRegex` uses QuickCheck function `frequency`, which receives a list of pairs formed by a weight and a random generator and produces, as result, a generator which uses such frequency distribution. In `sizedRegex` implementation we give a higher weight to generate characters and equal distributions to build concatenation, union or star.

```
sizedRegex :: Int -> Gen Regex
sizedRegex n
  | n <= 1 = frequency [ (10, return Eps), (90, Chr <$> genChar) ]
  | otherwise = frequency [ (10, return Epsilon), (30, Chr <$> genChar)
    , (20, Cat <$> sizedRegex n2 <*> sizedRegex n2)
    , (20, Choice <$> sizedRegex n2 <*> sizedRegex n2)
    , (20, Star <$> sizedRegex n2)]
    where n2 = div n 2
```

Given an RE e , we can generate a random string s such that $s \in \llbracket e \rrbracket$ using the next definition. We generate strings by choosing randomly between branches of a union or by repeating n times a string s which is accepted by e , whenever we have e^* (function `randomMatches`).

```
randomMatch :: Regex -> Gen String
randomMatch Eps = return ""
randomMatch (Chr c) = return [c]
randomMatch (Cat e e') = liftM2 (++) (randomMatch e)
    (randomMatch e')
randomMatch (Choice e e') = oneof [ randomMatch e, randomMatch e' ]
randomMatch (Star e) = do
  n <- choose (0,3) :: Gen Int
  randomMatches n e
```



```

10 randomMatches :: Int -> Regex -> Gen String
11 randomMatches m e'
12   | m <= 0 = return []
13   | otherwise = liftM2 (++) (randomMatch e')
14                                     (randomMatches (m - 1) e')

```

6. Related works

Ierusalimsky [10] proposed the use of Parsing Expression Grammars (PEGs) as a basis for pattern matching. He argued that pure REs are a weak formalism for pattern-matching tasks: many interesting patterns either are difficult to describe or cannot be described by REs. He also said that the inherent non-determinism of REs does not fit the need to capture specific parts of a match. Following this proposal, he presented LPEG, a pattern-matching tool based on PEGs for the Lua language. He argued that LPEG unifies the ease of use of pattern-matching tools with the full expressive power of PEGs. He also presented a parsing machine that allows an implementation of PEGs for pattern matching. Medeiros et. al. [28] presents informal correctness proofs of LPEG parsing machine. While such proofs represent an important step towards the correctness of LPEG, there is no guarantee that LPEG implementation follows its specification.

Rathnayake and Thielecke [19] formalized a VM implementation for RE matching using operational semantics. Specifically, they derived a series of abstract machines, moving from the abstract definition of matching to realistic machines. First, a continuation is added to the operational semantics to describe what remains to be matched after the current expression. Next, they represented the expression as a data structure using pointers, which enables redundant searches to be eliminated via testing for pointer equality. Although their work has some similarities with ours (a VM-based parsing of REs), they did not present any evidence or proofs that their VM is correct.

Fischer, Huch and Wilke [7] developed a Haskell program for matching REs. Their program is purely functional and it is overloaded over arbitrary semirings, which solves the matching problem and supports other applications like computing leftmost longest matchings or the number of matchings. Their program can also be used for parsing every context-free language by taking advantage of laziness. Their developed program is based on an old technique to turn REs into finite automata, which makes it efficient compared to other similar approaches. One advantage of their implementation over our proposal is that their approach works with context-free languages, not only with REs purely. However, they did not present any correctness proof of their Haskell code.

Cox [9] said that viewing RE matching as executing a special machine makes it possible to add new features just by the inclusion of new machine instructions. He presented two different ways to implement a VM that executes a RE that has been compiled into byte-codes: a recursive and a non-recursive backtracking implementation, both in C programming language. Cox's work on VM-based RE parsing is poorly specified: both the VM semantics and the RE compilation process are described only informally and no correctness guarantees are even mentioned.

Frisch and Cardelli [1] studied the theoretical problem of matching a flat sequence against a type (RE): the result of the process is a structured value of a given type. Their contributions were in noticing that: (1) A disambiguated result of parsing can be presented as a data structure that does not contain ambiguities. (2) There are problematic cases in parsing values of star types that need to be disambiguated. (3) The disambiguation strategy used in XDuce and CDuce (two XML-oriented functional languages) pattern matching can be characterized mathematically by what they call greedy RE matching. (4) There is a linear time algorithm for the greedy matching. Their approach is different since they want to axiomatize abstractly the disambiguation policy, without providing an explicit matching algorithm. They identified three notions of problematic words, REs, and values (which represent the ways to match words), related these three notions, and proposed matching algorithms to deal with the problematic

case.

Ribeiro and Du Bois [3] described the formalization of a RE parsing algorithm that produces a bit representation of its parse tree in the dependently typed language Agda. The algorithm computes bit-codes using Brzozowski derivatives and they proved that the produced codes are equivalent to parse trees ensuring soundness and completeness with respect to an inductive RE semantics. They included the certified algorithm in a tool developed by themselves, named verigrep, for RE-based search in the style of GNU grep. While the authors provided formal proofs, their tool show a bad performance when compared to other approaches to RE parsing.

Nielsen and Henglein [13] showed how to generate a compact bit-coded representation of a parse tree for a given RE efficiently, without explicitly constructing the parse tree first, by simplifying the DFA-based parsing algorithm of Dub and Feeley [29] to emit a bit representation without explicitly materializing the parse tree itself. They also showed that Frisch and Cardellis greedy RE parsing algorithm [1] can be straightforwardly modified to produce bit codings directly. They implemented both solutions as well as a backtracking parser and performed benchmark experiments to measure their performance. They argued that bit codings are interesting in their own right since they are typically not only smaller than the parse tree, but also smaller than the string being parsed and can be combined with other techniques for improved text compression. As others related works, the authors did not present a formal verification of their implementations.

Sulzmann et. al. [12] propose an algorithm for POSIX RE parsing with uses RE derivatives to construct parse trees incrementally to solve both matching and submatching for REs. In order to improve the efficiency of the proposed algorithm, Sulzmann et al. use a bit encoded representation of RE parse trees. Textual proofs of correctness of the proposed algorithm are presented in an appendix. Ausaf et. al. [30] present a Isabelle/HOL formalization of Sulzmann et. al POSIX parsing algorithm. They gave their inductive definition of what a POSIX value is and showed that such a value is unique for a given RE and

1
2
3
4
5
6
7
8
9 a string being matched. We intend, as future work, to use a similar induc-
10 tive definition to characterize the disambiguation strategy followed by our VM
11 semantics.
12
13

14 A recent application of REs was presented by Radanne [31]. In many cases,
15 the goal of a RE is not only to match a given text, but also to extract information
16 from it. With that in mind, the author presented a technique to provide type-
17 safe extraction based on the typed interpretation of REs. That technique relies
18 on two-layer REs in which the upper layer allows to compose and transform
19 data in a well-typed way, while the lower one is composed by untyped REs that
20 can leverage features from a preexisting RE matching engine. Results showed
21 that this technique is faster than other two libraries that perform the same
22 task, despite its lack of efficiency when compared with some full RE parsing
23 algorithms. No formalization was provided in that work.
24
25

26 Radanne and Thiemann [32] pointed that some of the algorithms for RE
27 matching are rather intricate and the natural question that arises is how to
28 test these algorithms. It is not too hard to come up with generators for strings
29 that match a given RE, but on the other hand, the algorithms should reject
30 strings that do not match that RE. So it is equally important to come up with
31 strings that do not match. In other words, a satisfactory solution for testing such
32 matchers would require generating positive as well as negative examples for some
33 language. Thus, the authors presented an algorithm to generate the language
34 of a generalized RE with union, intersection and complement operators. Using
35 this technique, they could generate both positive and negative instance of a RE.
36 They provided two implementations: one in Haskell, which explores different
37 algorithmic improvements, and one in OCaml, which evaluates choices in data
38 structures. Their algorithm lacks of correctness proofs.
39
40

41 Groz and Maneth [33] approached the efficiency of testing and matching of
42 deterministic REs. They presented a linear time algorithm for testing whether
43 a RE is deterministic and an efficient algorithm for matching words against de-
44 terministic REs. It was shown that an input word of length n can be matched
45 against a deterministic RE of length m in time $O(m + n \log \log m)$. If the
46
47
48
49

1
2
3
4
5
6
7
8
9 deterministic RE has bounded depth of alternating union and concatenation
10
11 600 operators, then matching can be performed in time $O(m+n)$. According to the
12 authors, these results extend to REs containing numerical occurrence indicators.
13 The authors presented the concept of deterministic REs and the differences be-
14 tween weak and strong determinism. Their paper contains some proofs, many of
15 them related to algorithmic running time. However, their approach was focused
16
17 on performance over deterministic REs, leaving aside the non-deterministic ones.
18 605
19 We intend to investigate time complexity of algorithm in future works.
20

21 A formal constructive theory of RLs was presented by Doczkal et. al. in [34].
22 They formalized some fundamental results about RLs. For their formalization,
23 they used the Ssreflect extension to Coq, which features an extensive library
24
25 with support for reasoning about finite structures such as finite types and fi-
26 610 nite graphs. They established all of their results in about 1400 lines of Coq,
27 half of which are specifications. Most of their formalization deals with transla-
28 tions between different representations of RLs, including REs, DFAs, minimal
29 DFAs and NFAs. They formalized all these (and other) representations and
30
31 constructed computable conversions between them. Besides other interesting
32 aspects of their work, they proved the decidability of language equivalence for
33 all representations. Unlike our work, Doczkal et. al.'s only concerns about
34 formalizing classical results of RL theory in Coq, without using the formalized
35 615 automata in practical applications, like matching or parsing.
36
37

38 A new technique for constructing a finite deterministic automaton from a
39 620 RE was presented by Asperti et al in [5]. It's based on the idea of marking
40 a suitable set of positions inside the RE, intuitively representing the possible
41 points reached after the processing of an initial prefix of the input string. In
42 other words, the points mark the positions inside the RE which have been
43
44 reached after reading some prefix of the input string, or better positions where
45 625 the processing of the remaining string has to be started. Each pointed expression
46 for a RE e represents a state of the deterministic automaton associated with e ;
47 since there is obviously only a finite number of possible labellings, the number
48 of states of the automaton is finite. The authors argued that Pointed REs join
49
50
51
52
53
54
55
56
57
58

the elegance and the symbolic appealingness of Brzozowski's derivatives with the effectiveness of McNaughton and Yamada's labelling technique, essentially combining the best of the two approaches, allowing a direct, intuitive and easily verifiable construction of the deterministic automaton for e . The authors said that pointed expressions can provide a more compact description for REs than traditional REs. However, the authors do not discuss the usage of pointed REs for parsing or matching.

The concept of prioritized transducers to formalize capturing groups in RE matching was introduced by Berglund and Merwe [35]. Their main goal was to provide an automata-based theoretical foundation for the basic functionality of modern RE matchers (with a focus on the Java RE standard library). Many RE matching libraries perform matching as a form of parsing by using capturing groups, and thus output what subexpression matched which substring. Their approach permits an analysis of matching semantics of a subset of the REs supported in Java. According to the authors, converting REs to what they called as prioritized transducers is a natural generalization of the Thompson construction for REs to NFA.

7. Conclusion

In this work, we presented a big-step operational semantics for a virtual machine for greedy RE parsing. Our semantics produces, as parsing evidence, bit-codes. In order to avoid the well-known problems with problematic REs, we use an algorithm that converts a problematic RE into an equivalent non-problematic one. All theoretical results reported in this paper are integrally verified using Coq proof assistant. From our formalization, we extract a Haskell implementation of our algorithm and used it to build a tool for RE parsing, which has performance comparable to a optimized Haskell library for RE parsing. The complete development is available at [18].

As future work we intend to extend our semantics with some real-world regex features like capture groups and quantifiers, while keeping an easy to

follow formalization and an efficient algorithmic interpreter for it. Other line of
research we intend to pursue is to characterize Medeiros et. al. [16] construction
of non-problematic RE in terms of the coinductive axiomatization of Heinglein
et. al. [36].

Acknowledgements

This work is supported by the CNPq Brazil under grant No.: 426232/2016.

References

- [1] A. Frisch, L. Cardelli, Greedy Regular Expression Matching, ICALP 2004 -
International Colloquium on Automata, Languages and Programming 3142
(2004) 618–629.
- [2] D. Firsov, T. Uustalu, [Certified parsing of regular languages](#), in: Pro-
ceedings of the Third International Conference on Certified Programs and
Proofs - Volume 8307, Springer-Verlag New York, Inc., New York, NY,
USA, 2013, pp. 98–113. [doi:10.1007/978-3-319-03545-1_7](#).
URL http://dx.doi.org/10.1007/978-3-319-03545-1_7
- [3] R. Ribeiro, A. D. Bois, [Certified Bit-Coded Regular Expression Parsing](#),
Proceedings of the 21st Brazilian Symposium on Programming Languages
- SBLP 2017 (2017) 1–8.
URL <http://dl.acm.org/citation.cfm?doid=3125374.3125381>
- [4] R. Lopes, R. Ribeiro, C. Camarão, Certified derivative-based parsing of
regular expressions, in: Programming Languages — Lecture Notes in Com-
puter Science 9889, Springer, 2016, pp. 95–109.
- [5] A. Asperti, C. S. Coen, E. Tassi, [Regular expressions, au point](#), CoRR
abs/1010.2604. [arXiv:1010.2604](#).
URL <http://arxiv.org/abs/1010.2604>

- [6] R. F. P. Lopes, Certified Derivative-based Parsing of Regular Expressions
— Master Thesis.
- [7] S. Fischer, F. Huch, T. Wilke, A play on regular expressions, ACM SIGPLAN Notices 45 (9) (2010) 357. doi:10.1145/1932681.1863594.
- [8] D. E. Knuth, Top-down syntax analysis, Acta Inf. 1 (2) (1971) 79–110.
doi:10.1007/BF00289517.
- URL <http://dx.doi.org/10.1007/BF00289517>
- [9] R. Cox, Regular Expression Matching: the Virtual Machine Approach.
URL <https://swtch.com/{~}rsc/regexp/regexp2.html>
- [10] R. Ierusalimsky, A text patternmatching tool based on parsing expression
grammars, Software - Practice and Experience doi:10.1002/spe.892.
- [11] B. Ford, Parsing expression grammars: A recognition-based syntactic foundation, in: Proceedings of the 31st ACM SIGPLAN-SIGACT Symposium
on Principles of Programming Languages, POPL '04, ACM, New York,
NY, USA, 2004, pp. 111–122. doi:10.1145/964001.964011.
URL <http://doi.acm.org/10.1145/964001.964011>
- [12] M. Sulzmann, K. Z. M. Lu, Posix regular expression parsing with derivatives, in: M. Codish, E. Sumii (Eds.), Functional and Logic Programming,
Springer International Publishing, Cham, 2014, pp. 203–220.
- [13] L. Nielsen, F. Henglein, Bit-coded regular expression parsing, in: A.-H.
Dediu, S. Inenaga, C. Martín-Vide (Eds.), Language and Automata Theory
and Applications, Springer Berlin Heidelberg, Berlin, Heidelberg, 2011, pp.
402–413.
- [14] J.-L. Krivine, A call-by-name lambda-calculus machine, Higher Order Symbol. Comput. 20 (3) (2007) 199–207. doi:10.1007/s10990-007-9018-9.
URL <http://dx.doi.org/10.1007/s10990-007-9018-9>

- [15] P. J. Landin, [The mechanical evaluation of expressions](#), The Computer Journal 6 (4) (1964) 308–320. [arXiv:/oup/backfile/content_public/journal/comjnl/6/4/10.1093/comjnl/6.4.308/2/6-4-308.pdf](#), doi:10.1093/comjnl/6.4.308.
URL <http://dx.doi.org/10.1093/comjnl/6.4.308>
- [16] S. Medeiros, F. Mascarenhas, R. Ierusalimsky, [From regexes to parsing expression grammars](#), Sci. Comput. Program. 93 (2014) 3–18. doi:10.1016/j.scico.2012.11.006.
URL <http://dx.doi.org/10.1016/j.scico.2012.11.006>
- [17] T. A. Delfino, R. Ribeiro, [Towards certified virtual machine-based regular expression parsing](#), in: Proceedings of the XXII Brazilian Symposium on Programming Languages, SBPL '18, ACM, New York, NY, USA, 2018, pp. 67–74. doi:10.1145/3264637.3264646.
URL <http://doi.acm.org/10.1145/3264637.3264646>
- [18] T. Delfino, R. Ribeiro, [Towards certified virtual machine-based regular expression parsing — on-line repository](#), <https://github.com/thalesad/regexvm> (2018).
- [19] A. Rathnayake, H. Thielecke, [Regular Expression Matching and Operational Semantics](#), Electronic Proceedings in Theoretical Computer Science 62 (Sos) (2011) 31–45. [arXiv:1108.3126](#), doi:10.4204/EPTCS.62.3.
URL <http://arxiv.org/abs/1108.3126>
- [20] A. Chlipala, Certified Programming with Dependent Types: A Pragmatic Introduction to the Coq Proof Assistant, The MIT Press, 2013.
- [21] M. Sozeau, Equations: A dependent pattern-matching compiler, in: M. Kaufmann, L. C. Paulson (Eds.), Interactive Theorem Proving, Springer Berlin Heidelberg, Berlin, Heidelberg, 2010, pp. 419–434.
- [22] Y. Bertot, P. Castran, Interactive Theorem Proving and Program Development

opment: Coq'Art The Calculus of Inductive Constructions, 1st Edition,
Springer Publishing Company, Incorporated, 2010.

[23] S. P. Jones (Ed.), [Haskell 98 Language and Libraries: The Revised Report](#),
http://haskell.org/, 2002.

URL <http://haskell.org/definition/haskell98-report.pdf>

[24] R. Cheplyaka, regex-applicative: Regex based parsing with applicative
interface — on-line repository, [http://hackage.haskell.org/package/regex-](http://hackage.haskell.org/package/regex-applicative)
applicative (2018).

[25] C. McBride, R. Paterson, [Applicative programming with effects](#), J. Funct.
Program. 18 (1) (2008) 1–13. doi:10.1017/S0956796807006326.

URL <http://dx.doi.org/10.1017/S0956796807006326>

[26] J. Kiriage, A. Rathnayake, H. Thielecke, Static analysis for regular expres-
sion denial-of-service attacks, in: J. Lopez, X. Huang, R. Sandhu (Eds.),
Network and System Security, Springer Berlin Heidelberg, Berlin, Heidel-
berg, 2013, pp. 135–148.

[27] K. Claessen, J. Hughes, Quickcheck: A lightweight tool for random testing
of haskell programs, in: Proceedings of the Fifth ACM SIGPLAN Inter-
national Conference on Functional Programming, ICFP '00, ACM, New
York, NY, USA, 2000, pp. 268–279.

[28] S. Medeiros, R. Ierusalimschy, [A parsing machine for PEGs](#), Proceedings
of the 2008 symposium on Dynamic languages - DLS '08 (2008) 1–12doi:

[10.1145/1408681.1408683](https://doi.org/10.1145/1408681.1408683).

URL <http://portal.acm.org/citation.cfm?doid=1408681.1408683>

[29] D. Dubé, M. Feeley, [Efficiently building a parse tree from a regular expres-](#)
[sion](#), Acta Inf. 37 (2) (2000) 121–144. doi:10.1007/s002360000037.

URL <http://dx.doi.org/10.1007/s002360000037>

[30] F. Ausaf, R. Dyckhoff, C. Urban, Posix lexing with derivatives of regular
expressions (proof pearl), in: J. C. Blanchette, S. Merz (Eds.), Interactive

- 765 Theorem Proving, Springer International Publishing, Cham, 2016, pp. 69–
86.
- [31] G. Radanne, [Typed parsing and unparsing for untyped regular expression engines](#), in: Proceedings of the 2019 ACM SIGPLAN Workshop on Partial Evaluation and Program Manipulation, PEPM 2019, ACM, New York, NY, USA, 2019, pp. 35–46. [doi:10.1145/3294032.3294082](#).
770 URL <http://doi.acm.org/10.1145/3294032.3294082>
- [32] G. Radanne, P. Thiemann, [Regenerate: A Language Generator for Extended Regular Expressions](#), working paper or preprint (May 2018).
URL <https://hal.archives-ouvertes.fr/hal-01788827>
- 775 [33] B. Groz, S. Maneth, [Efficient testing and matching of deterministic regular expressions](#), Journal of Computer and System Sciences 89 (2017) 372–399. [doi:10.1016/j.jcss.2017.05.013](#).
URL <http://dx.doi.org/10.1016/j.jcss.2017.05.013>
- [34] C. Doczkal, J. O. Kaiser, G. Smolka, A constructive theory of regular languages in Coq, Lecture Notes in Computer Science (including subseries
780 Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics) 8307 LNCS (2013) 82–97. [doi:10.1007/978-3-319-03545-1_6](#).
- [35] M. Berglund, B. V. D. Merwe, [On the semantics of regular expression parsing in the wild](#), Theoretical Computer Science 1 (2016) 1–14. [doi:10.1016/j.tcs.2016.09.006](#).
785 URL <http://dx.doi.org/10.1016/j.tcs.2016.09.006>
- [36] F. Henglein, L. Nielsen, [Regular expression containment: Coinductive axiomatization and computational interpretation](#), SIGPLAN Not. 46 (1) (2011) 385398. [doi:10.1145/1925844.1926429](#).
790 URL <https://doi.org/10.1145/1925844.1926429>
- [37] M. H. Sørensen, P. Urzyczyn, Lectures on the Curry-Howard Isomorphism,

Volume 149 (Studies in Logic and the Foundations of Mathematics), Elsevier Science Inc., New York, NY, USA, 2006.

Appendix A. A tour of Coq proof assistant

Coq is a proof assistant based on the calculus of inductive constructions (CIC) [22], a higher-order typed λ -calculus extended with inductive definitions. Theorem proving in Coq follows the ideas of the so-called “BHK-correspondence”⁴, in which types represent logical formulas, λ -terms represent proofs, and the task of checking if a piece of text is a proof of a given formula corresponds to type-checking (i.e. checking if the term that represents the proof has the type corresponding to the given formula) [37].

Writing a proof term whose type is that of a logical formula can be however a hard task, even for simple propositions. In order to make this task easier, Coq provides *tactics*, which are commands that can be used to help the user in the construction of proof terms.

In this section we provide a brief overview of Coq. We start with a small example, that uses basic features of Coq — types, functions and proof definitions. In this example, we use an inductive type that represents natural numbers in Peano notation. The `nat` type definition includes an annotation, that indicates that it belongs to the `Set` sort⁵. Type `nat` is formed by two data constructors: `0`, that represents the number 0, and `S`, the successor function.

```
Inductive nat : Set :=  
  | 0 : nat  
  | S : nat -> nat.
```

⁴Abbreviation of Brower, Heyting, Kolmogorov, de Bruijn and Martin-Löf Correspondence. This is also known as the Curry-Howard “isomorphism”.

⁵Coq’s type language classifies new inductive (and co-inductive) definitions by using sorts. `Set` is the sort of computational values (programs) and `Prop` is the sort of logical formulas and proofs.

```

10 Fixpoint plus (n m : nat) : nat :=
11     match n with
12     | 0 => m
13     | S n' => S (plus n' m)
14     end.
15
16 Theorem plus0r : forall n, plus n 0 = n.
17 Proof.
18     intros n. induction n.
19     reflexivity.
20     simpl. rewrite -> IHn. reflexivity.
21 Qed.

```

Command **Fixpoint** allows the definition of functions by structural recursion. The definition of **plus**, for summing two values of type **nat**, is straightforward. It should be noted that all functions defined in Coq must be total.

Besides declaring inductive types and functions, Coq allows us to define and prove theorems. In our example, we show a simple theorem about **plus**, that states that $\text{plus } n \ 0 = n$, for an arbitrary value **n** of type **nat**. Command **Theorem** allows the statement of a formula that we want to prove and starts the *interactive proof mode*, in which tactics can be used to produce the proof term that is the proof of such formula. In the example, various tactics are used to prove the desired result. The first tactic, **intros**, is used to move premisses and universally quantified variables from the goal to the hypothesis. Tactic **induction** is used to start an inductive proof over an inductively defined object (in our example, the natural number **n**), generating a case for each constructor and an induction hypothesis for each recursive branch in constructors. Tactic **reflexivity** proves trivial equalities up to conversion and **rewrite** is used to replace terms using some equality.

For each inductively defined data type, Coq generates automatically an in-

duction principle [22, Chapter 14]. For natural numbers, the following Coq term, called `nat_ind`, is created:

```
nat_ind
  : forall P : nat -> Prop,
    P 0 -> (forall n : nat, P n -> P (S n)) ->
    forall n : nat, P n
```

It expects a property (P) over natural numbers (a value of type `nat -> Prop`), a proof that P holds for zero (a value of type `P 0`) and a proof that if P holds for an arbitrary natural `n`, then it holds for `S n` (i.e. a value of type `forall n:nat, P n -> P (S n)`). Besides `nat_ind`, generated by the use of tactic `induction`, the term below uses the constructor of the equality type `eq_refl`, created by tactic `reflexivity`, and term `eq_ind_r`, inserted by the use of tactic `rewrite`. Term `eq_ind_r` allows concluding `P y` based on the assumptions that `P x` and `x = y` are provable.

```
Definition plus_0_r_term :=
  fun n : nat =>
    nat_ind
      (fun n0 : nat => plus n0 0 = n0) (eq_refl 0)
      (fun (n' : nat) (IHn' : plus n' 0 = n') =>
        eq_ind_r (fun n0 : nat => S n0 = S n')
                  (eq_refl (S n')) IHn') n
  : forall n : nat, plus n 0 = n
```

Instead of using tactics, one could instead write CIC terms directly to prove theorems. This can be however a complex task, even for simple theorems like `plus_0_r`, because it generally requires detailed knowledge of the CIC type system.

An interesting feature of Coq is the possibility of defining inductive types that mix computational and logical parts. Such types are usually called *strong specifications*, since they allow the definition of functions that compute values

together with a proof that this value has some desired property. As an example, consider type `sig` below, also called “subset type”, that is defined in Coq’s standard library as:

```
Inductive sig (A : Set) (P : A -> Prop) : Set :=
| exist : forall x : A, P x -> sig A P.
```

Type `sig` is usually expressed in Coq by using the following syntax: $\{x : A \mid P x\}$. Constructor `exist` has two parameters. Parameter `x : A` represents the computational part. The other parameter, of type `P x`, denotes the “certificate” that `x` has the property specified by predicate `P`. As an example, consider:

```
forall n : nat, n <> 0 -> {m | n = S m}
```

This type can be used to specify a function that returns the predecessor of a natural number `n`, together with a proof that the returned value really is the predecessor of `n`. The definition of a function of type `sig` requires the specification of a logical certificate. As occurs in the case of theorems, tactics can be used in the definition of such functions. For example, a definition of a function that returns the predecessor of a given natural number, if it is different from zero, can be given as follows:

```
Definition predcert : forall n : nat, n <> 0 -> {m | n = S m}.
  intros n H.
  destruct n.
  destruct H. reflexivity.
  exists n. reflexivity.
Defined.
```

Tactic `destruct` is used to start a proof by case analysis on structure of a value.

Another example of a type that can be used to provide strong specifications in Coq is `sumor`, that is defined in the standard library as follows:

```

1
2
3
4
5
6
7
8
9   Inductive sumor(A : Set) (B : Prop) : Set :=
10   | inleft : A -> sumor A B
11   | inright : B -> sumor A B.
12
13

```

Coq standard library also provides syntactic sugar (or, in Coq’s terminology,
865 notations) for using this type: “`sumor A B`” can be written as `A + {B}`. This
type can be used as the type of a function that returns either a value of type
A or a proof that some property specified by B holds. As an example, we can
specify the type of a function that returns a predecessor of a natural number or
a proof that the given number is equal to zero as follows, using type `sumor`:

```

23   {p | n = S p} + {n = 0}
24
25

```

870 A common problem when using rich specifications for functions is the need of
writing proof terms inside its definition body. A possible solution for this is to
use the `refine` tactic, which allows one to specify a term with missing parts
(knowns as “holes”) to be filled latter using tactics.

The next code piece uses the `refine` tactic to build the computational part
875 of a certified predecessor function. We use holes to mark positions where proofs
are expected. Such proof obligations are later filled by tactic `reflexivity`
which finishes `predcert` definition.

```

39   Definition predcert : forall n : nat, {p | n = S p} + {n = 0}.
40   refine (fun n =>
41     match n with
42     | 0 => inright _
43     | S n' => inleft _ (exist _ n' _)
44     end) ; reflexivity.
45
46   Defined.
47
48
49

```

The same function can be defined in a more suscint way using notations
introduced in [20].

```

55   Definition predcert : forall n : nat, {p | n = S p} + {n = 0}.
56   refine (fun n =>
57
58

```



```

match n with
| 0 => !!
| S n' => [| n' |]
end) ; reflexivity.

```

Defined.

880 The utility of notations is to hide the writing of constructors and holes in function definitions.

A detailed discussion on using Coq is out of the scope of this paper. Good introductions to Coq proof assistant are available elsewhere [22, 20].

Appendix B. Proof Sketchs

885 **Theorem** (Soundness). If $\langle e, s \rangle \rightsquigarrow^n (bs, s_p, s_r)$ then $s = s_p s_r$ and $s_p \in \llbracket e \rrbracket$.

Proof. The proof follows by well-founded induction on the complexity of (e, s) .

We will show some cases. The cases for *emptyset*, ϵ and a single symbol RE are immediate. In the case of the concatenation, we have that $e = e_1 e_2$, $\langle e_1, s \rangle \rightsquigarrow^{n_1} (bs_1, s_1, s_2)$ and $\langle e_2, s \rangle \rightsquigarrow^{n_2} (bs_2, s_3, s_4)$. By the induction hypothesis, we have
890 that $s_1 \in \llbracket e_1 \rrbracket$ $s = s_1 s_2$, $s_3 \in \llbracket e_2 \rrbracket$ $s_2 = s_3 s_4$. The result follows by using these equalities and rule *Cat*.

When $e = e_1 + e_2$, we need to consider two possibilities:

- Last rule used in derivation of $\langle e_1 + e_2, s \rangle \rightsquigarrow^n (bs, s_p, s_r)$ was *Ch1*: Then, $\langle e_1, s \rangle \rightsquigarrow^{n_1} (bs_1, s_p, s_r)$, $bs = 0_b bs_1$ and $n = 1 + n_1$. The conclusion follows
895 by using the induction hypothesis and rule *Left*.
- Last rule used in derivation of $\langle e_1 + e_2, s \rangle \rightsquigarrow^n (bs, s_p, s_r)$ was *Ch2*: Then, $\langle e_1, s \rangle \rightsquigarrow^{n_1}$, $\langle e_2, s \rangle \rightsquigarrow^m (bs_1, s_p, s_r)$, $bs = 1_b bs_1$ and $n = 1 + n_1 + m$. The conclusion follows by using the induction hypothesis and rule *Right*.

□

900 **Theorem** (Parsing result soundness). If $\langle e, s \rangle \rightsquigarrow^n (bs, s_p, s_r)$ then: 1) $bs \triangleright e$; 2) $\text{flatten}(\text{decode}(bs : e)) = s_p$; and 3) $\text{encode}(\text{decode}(bs : e) : e) = bs$.

Proof. The proof follows by well-founded induction on the complexity of (e, s) . We will show some cases. The cases for *emptyset*, ϵ and a single symbol RE are immediate. When $e = e_1 e_2$, we have that $\langle e_1, s \rangle \rightsquigarrow^{n_1} (bs_2, s_1, s_2)$ and $\langle e_2, s \rangle \rightsquigarrow^{n_2} (bs_2, s_3, s_4)$. By the induction hypothesis on e_1 we have that $bs_1 \triangleright e_1$, $\text{flatten}(\text{decode}(bs_1 : e_1)) = s_1$ and $\text{encode}(\text{decode}(bs_1 : e_1) : e_1) = bs_1$. By the induction hypothesis on e_2 we have that $bs_2 \triangleright e_2$, $\text{flatten}(\text{decode}(bs_2 : e_2)) = s_2$ and $\text{encode}(\text{decode}(bs_2 : e_2) : e_2) = bs_2$. The results follow by the definition of bit-codes typing and definitions of functions **flatten**, **encode** and **decode**. \square

Theorem (Determinism). If $\langle e, s \rangle \rightsquigarrow^n r$ and $\langle e, s \rangle \rightsquigarrow^m r'$ then $n = m$ and $r = r'$.

Proof. Induction on the step counter n and case analysis on the derivation of $\langle e, s \rangle \rightsquigarrow^m r$. We will show some cases. When $n = 0$, we have that $e = \emptyset$ and the result follows. When $n = 1$, we have that $e = \epsilon$ and again the result follows. Now suppose that $n \geq 2$ and $e = e_1 + e_2$. Consider the following cases for the last rule used to deduce $\langle e_1 + e_2, s \rangle \rightsquigarrow^n r$.

- Rule *Ch1*: Then, we have that $\langle e_1, s \rangle \rightsquigarrow^{n_1} (bs, s_1, s_2)$ and $n = 1 + n_1$. The result follows by case analysis on the derivation $\langle e_1 + e_2, s \rangle \rightsquigarrow^m r'$ and the induction hypothesis.
- Rule *Ch2*: Then, we have $\langle e_1, s \rangle \not\rightsquigarrow^{n_1}$, $\langle e_2, s \rangle \rightsquigarrow^{m_1} (bs, s_1, s_2)$ and $n = 1 + n_1 + m_1$. Now, we do a case analysis on r' . When r' is a failure, the result follows. When $r' = (bs', s'_1, s'_2)$, the result follows by the induction hypothesis.

Theorem. Let e be an arbitrary unproblematic expression and s arbitrary string. The execution time of $\langle e, s \rangle \rightsquigarrow r$ is $O(n)$, where $n = |s|$.

Proof. Induction on the structure of e . The only interesting case is for the star operator. In this case, we have that $e = e_1^*$. Since e is unproblematic, then

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65

⁹³⁰ $\epsilon \notin \llbracket e_1 \rrbracket$ and it consumes, at each iteration step, at least one symbol from input.
Since the input size is n , then the desired result follows. \square

*Potential Reviewers

Sérgio Medeiros – sergiomedeiros@ect.ufrn.br

Roberto Ierusalimsky – roberto@inf.puc-rio.br

Martin Sulzmann – martin.sulzmann@gmail.com

Declaration of interests

☒ The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

☐ The authors declare the following financial interests/personal relationships which may be considered as potential competing interests:

All authors contributed equality with the formalization, article writing and experiments.