


COMPUTER GRAPHICS



* Based on CISC 3620 material by Prof. Michael Mandel

JAVASCRIPT AND CANVAS DRAWING

Based on [this CS 307 reading](#) and [this CS 307 lecture](#)*


*copyright © Scott D. Anderson and licensed under a [Creative Commons BY-NC-SA License](#)

Drawing rectangles - Exercise

- Your result may look like [this](#)

Example: Drawing rectangles

- Start from [this codepen](#)
- Try to draw this picture using the above rectangle functions



Questions?



Answer: Drawing rectangles

- function draw() {
- var canvas =
document.getElementById('canvas');
- if (canvas.getContext) {
 - var ctx = canvas.getContext('2d');
 - ctx.fillRect(25, 25, 100, 100);
 - ctx.clearRect(45, 45, 60, 60);
 - ctx.strokeRect(50, 50, 50, 50);
- }
- }

Drawing paths

- A path is a list of points, connected by segments of lines
- Segments can be different shapes, curved, straight, different colors

Drawing paths


- To make shapes using paths:
 - Create the path using `beginPath()`
 - Use `moveTo(x,y)` to go to the start point
 - Add segments to the path
 - Using `lineTo(x,y)`
 - Call `closePath()`;
 - Draw it using either:
 - `fill()` - solid shape, or
 - `stroke()` - just outline

Example: Drawing a triangle

- `function draw() {`
 - `var canvas = document.getElementById('canvas');`
 - `if (canvas.getContext) {`
 - `var ctx = canvas.getContext('2d');`
 - `ctx.beginPath();`
 - `ctx.moveTo(75, 50);`
 - `ctx.lineTo(100, 75);`
 - `ctx.lineTo(100, 25);`
 - `ctx.closePath();` //closePath is optional when calling fill
 - `ctx.fill();`
 - `}`
- `}`

Example 2: drawing 2 triangles

- Start from this [CodePen](#)
- Try to draw this picture using the above path functions



Questions?



Answer: Drawing two triangles

- Function draw() {
- var canvas = document.getElementById('canvas');
- if (canvas.getContext) {
 - var ctx = canvas.getContext('2d'); // Filled triangle
 - ctx.beginPath();
 - ctx.moveTo(25, 25);
 - ctx.lineTo(105, 25);
 - ctx.lineTo(25, 105);
 - ctx.fill(); // Stroked triangle
 - ctx.beginPath();
 - ctx.moveTo(125, 125);
 - ctx.lineTo(125, 45);
 - ctx.lineTo(45, 125);
 - ctx.closePath();
 - ctx.stroke();
 - }
- }

Drawing arcs in paths


- There are two path functions to add arcs (portions of circles)
 - `arc(x, y, radius, startAngle, endAngle, anticlockwise)` draws an arc
 - centered at (x, y)
 - with radius r
 - starting at startAngle (in radians with 0 to the right)
 - ending at endAngle
 - going in the given direction indicated by anticlockwise (defaulting to clockwise)

Drawing arcs in paths

- `arcTo(x1, y1, x2, y2, radius)` draws an arc
 - starting at current point
 - going to (x1, y1) and then (x2, y2)
 - for a circle with radius `radius`
 - Angles in radians can be computed with
 - $radians = \left(\frac{\pi}{180}\right) * degrees$

Example: complete the smiley face

- Start from this [codepen](#)
- Complete the smiley face to match this picture (don't worry about the orange lines):



Questions?



Answer: complete the smiley face

- `Function draw() {`
- `var canvas = document.getElementById('canvas');`
- `if (canvas.getContext) {`
 - `var ctx = canvas.getContext('2d');`
 - `ctx.beginPath();`
 - `ctx.arc(75, 75, 50, 0, Math.PI * 2, true); // Outer circle`
 - `ctx.moveTo(110, 75);`
 - `ctx.arc(75, 75, 35, 0, Math.PI, false); // Mouth (clockwise)`
 - `ctx.moveTo(65, 65);`
 - `ctx.arc(60, 65, 5, 0, Math.PI * 2, true); // Left eye`
 - `ctx.moveTo(95, 65);`
 - `ctx.arc(90, 65, 5, 0, Math.PI * 2, true); // Right eye`
 - `ctx.stroke();`
 - `}`
- `}`

Coloring shapes


- Setting the context's fillStyle property affects all future shapes
 - until the property is set again
 - Same for strokeStyle
- Can use any CSS color specification
 - `ctx.fillStyle = 'orange';`
 - `ctx.fillStyle = '#FFA500';`
 - `ctx.fillStyle = 'rgb(255, 165, 0)';`
 - `ctx.fillStyle = 'rgba(255, 165, 0, 1)';`

Coloring shapes - RGBA

- `ctx.fillStyle = 'rgba(255, 165, 0, 1)';`
- Fourth parameter is alpha
 - Defines the opacity as a number between 0.0 (fully transparent) and 1.0 (fully opaque)


Example: coloring circles

- Function draw() {
- var ctx = document.getElementById('canvas').getContext('2d');
- for (var i = 0; i < 6; i++) {
 - for (var j = 0; j < 6; j++) {
 - ctx.fillStyle = 'rgb(0, ' + Math.floor(255 - 42.5 * i) + ', ' + Math.floor(255 - 42.5 * j) + ')';
 - ctx.beginPath();
 - ctx.arc(12.5 + j * 25, 12.5 + i * 25, 10, 0, Math.PI * 2, true);
 - ctx.fill();
 - }
 - }
- }



Example: rectangle grid

- Start from this [codepen](#)
- Try to match this picture



Answer:

- `function draw() {`
- `var ctx = document.getElementById('canvas').getContext('2d');`
- `for (var i = 0; i < 6; i++) {`
 - `for (var j = 0; j < 6; j++) {`
 - `ctx.fillStyle = 'rgb(' + Math.floor(255 - 42.5 * i) + ', ' + Math.floor(255 - 42.5 * j) + ', ' + 0 + ')';`
 - `ctx.fillRect(j * 25, i * 25, 25, 25);`
 - `}`
 - `}`
- `}`

Example: rectangle grid

- More info can be found [here](#)

Summary

- Get familiar with JavaScript syntax
- Data has a type
 - variables do not
- Functions are first-class objects
- Objects look like Java objects
- We can use the `<canvas>` element to draw many shapes

Questions?

