CISC 1003 - EXPLORING ROBOTICS

GEARS

Motors



- Compared with all other types of actuators, ***direct current (DC) motors*** are simple, inexpensive, easy to use, and easy to find.
- Motors have a copper wire wound in a way that creates magnetic fields
  - These “push" the rotor inside of the motor around in a circle.

Motors



- To make a motor run, you need to provide it with electrical power in the right voltage range.
  - Low voltage, slower movement.
  - Higher voltage, faster movement
    - but more wear on the motor and can burn out if run fast for too long.
    - Like a lightbulb on a battery. More voltage means a brighter light.

Gearing of motors

- Combining different *gears* is used to change the speed and torque (turning force) of motors.

http://www.jsumo.com/steel-gear-bundle-08-module-6421-reduction

SOME PHYSICS



http://theconversation.com/physics-is-taught-badly-because-teachers-struggle-with-basic-concepts-86083

Work, Force and Distance

- Energy is the ability to do work
- Measured in Joules
- Work: The action of a *force* to cause *displacement* of an object
  - Work(J) = Force (N) x distance (m)
    - 1 joule = 1 Newton * 1 meter



Work, Force and Distance

- Here, in this figure, we can say that, the work done upon the weight against gravity is
- (Mass × acceleration due to gravity) × Displacement
- = (25 x 2 × 9.8) × 2 = 980 J



Work, Force and Distance

- Who has done the most work?
  - Work = Force x Distance



http://www.clker.com/clipart-man-push.html

Work, Force and Distance

- Who has done the most work?
  - Work = Force x Distance



https://www.slideshare.net/gurustip/energy-work-power-10148820

Torque

- Torque is a measure of the force that can cause an object to rotate about an axis.
- TORQUE measures *ROTATIONAL FORCE*
- TORQUE = FORCE x DISTANCE
  - DISTANCE is equivalent to the RADIUS of the rotational circumference.



Figure 1: Opening a door with maximum torque.

Torque

- Example: opening a door:
  - Torque is the angular force that the person exerts



Gearing of motors

- Combining different *gears* is used to change the speed and torque (turning force) of motors.
- Work, as defined in physics, is the product of force and distance.
  - Work = force × distance
  - Distance moved in the direction of the force
- Gears rotate around their axis in a certain velocity
  - Rotational Velocity is specified in Rotations Per Minute.

Gearing of Motors

- Torque provided by motor is typically constant
- For a wheel on the ground, torque needed to turn wheel equals to overcome friction
  - $Torque = F_f * Distance$
    - Distance = wheel radius
- For a larger wheel, smaller rotational force will be provided by same engine
  - Harder to turn larger wheels
    - Think of a truck vs. car, who has the bigger engine?

Rotational and Linear Velocity

- Both wheels touch the ground and rotate at 120rpm
- Which wheel will travel further?
  - Larger wheel will travel further!
    - Can we calculate its linear velocity?



Rotational and Linear Velocity

- Rotational Velocity (RV) to Linear Velocity (LV) conversion:
  - Find the Circumference (C) of the circles:
  - $C = 2 \times \pi \times r$ inches (where r is the radius)

$$C_1 = 2 \times \pi \times 6 = 37.70\ inches$$

$$C_2 = 2 \times \pi \times 3 = 18.85\ inches$$

Rotational and Linear Velocity

- Rotational Velocity (RV) to Linear Velocity (LV) conversion:
  - Find the Circumference (C) of the circles:
  - $C = 2 \times \pi \times r$ inches (where r is the radius)

    $C_1 = 2 \times \pi \times 6 = 37.70\ inches$

    $C_2 = 2 \times \pi \times 3 = 18.85\ inches$
- $Linear\ Velocity = C\ x\ Rotational\ Velocity$

  (120 rpm speed of both circles)
  - $V_l = 37.70 * 120 = 4524\ inches/min$
  - $V_2 = 18.85 * 120 = 2262\ inches/min$

http://domarcompanies.com/velocity-business-systems/

Rotational and Linear Velocity

- Both wheels touch the ground and rotate at 120rpm
- Which wheel will travel further?
  - Larger wheel will travel further!
    - Can we calculate its linear velocity?
- Note:
  - Rotational Velocity is specified in Rotations Per Minute.
  - Linear Velocity is usually specified in Feet Per Minute.



GEARS

Gears



- Gears are wheels with teeth. Gears mesh together and make things turn.
- Gears are used to transfer motion or power from one moving part to another.
- Both the input gear (driven gear) and the output gear each have a set number of teeth
- The ratio between these two gears can be used to find the torque and speed of the output gear
  - if the input torque/speed to the driven gear is known.

Gears and Torque

- A motor that is VERY fast but has only a little bit of torque would not be suitable to lift a heavy load
- in these cases it is necessary to use gear ratios to change the outputs
  - to a more appropriate balance of torque and speed

Gears

- **Output Speed** = (*Input gear* / *Output gear*) * *Input Speed*
- **Output Torque** = (*Output gear* / *Input gear*) * *Input Torque*

Combining Gears



Combining Gears

- What happens to the speed?
- What happens to the torque?



Combining Gears

- What happens to the speed?
- What happens to the torque?



http://klinikrobot.com/product/gear-sets/plastic-gear-fs5-0508-000-gear-14-32t.html

Gears - example



- A motor is attached to a 10 tooth spur gear
  - Gear spins at 100 rpm (rotations per minute)
  - Gear has a torque of 1 joule
- 20 tooth gear attached to the 10 tooth gear
- What are the output speed and torque?

Gears - example



- A motor is attached to a 10 tooth spur gear
  - Gear spins at 100 rpm (rotations per minute)
  - Gear has a torque of 1 joule
- 20 tooth gear attached to the 10 tooth gear
- What are the output speed and torque?
  - Output speed = (10 /20) * 100 = 50 rpm
  - Output torque = (20 / 10) * 1 = 2 joules

Gears – The Purpose

Gears are generally used for one of four different reasons:

- To reverse the direction of rotation
- To increase or decrease the speed of rotation
- To move rotational motion to a different axis
- To keep the rotation of two axis synchronized

Gear System



- Compound Gears



Gear Ratio



$$\frac{\text{Driven}}{\text{Driving}} = \frac{75}{25} = \frac{3}{1} \rightarrow 3{:}1$$

Lab time!

- Let’s work with our robots!