

Contents

1 Data Structure

1.1	Fenwick Tree	1
1.2	Segment Tree	2
1.3	Segment Tree with lazy propagation	2
1.4	Persistent Segment Tree	3
1.5	Sparse Table	3
1.6	Treap	4
1.7	Union find	5

2 Graph Theory

2.1	Bellman Ford	5
2.2	Hopcroft Karp	5
2.3	Augmented Path for BPM	5
2.4	Binary Lifint	6
2.5	Bridges	6
2.6	Cut Vertices	6
2.7	Dijkstra	7
2.8	Dinic	7
2.9	Divide and Couquer on Trees	7
2.10	Dsu on Trees	8
2.11	Euler Cycle	8
2.12	Heavy-light Decomp	9
2.13	Hunarian	9
2.14	Tarjan's SCC	9
2.15	Two-edge-connected components	9

3 Math

3.1	Baby Step Giant Step	11
3.2	Chinese remainder Theorem	11
3.3	Euler	11
3.4	Extended Euclidean Algorithm	12
3.5	Factorial	12
3.6	Factorization	12
3.7	FFT	13
3.8	Gaussian elimination	13
3.9	Lucas Theorem	13
3.10	NFFT	13
3.11	Sieve	15
3.12	Simplex	15

4 String

4.1	Aho-Corasick Automaton	16
4.2	KMP	16
4.3	Manacher	17
4.4	Polynomial Hashing	17
4.5	Suffix Array	17
4.6	Suffix Automaton	18
4.7	Trie	18
4.8	Z-function	18

5 Geometry

5.1	Angle	18
5.2	Circle	18
5.3	Geometry	19

5.4	Line	22
5.5	Point	23
5.6	Polygon	23
5.7	Segment	24

6 Miscs

6.1		24
-----	--	----

1 Data Structure

1.1 Fenwick Tree

```

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

```

```

        sum1[i] += x, sum2[i] += v;
    }
public:
    void add(int l, int r, int x) {
        assert(l >= 0 && l <= r && r < n);
        add(l, x);
        if (r + 1 < n) add(r + 1, -x);
    }
    int64_t query(int p) {
        assert(p >= 0 && p < n);
        p++;
        int64_t res{};
        for (int i = p; i; i -= i & -i)
            res += (p + 1) * sum1[i] - sum2[i];
        return res;
    }
    int64_t query(int l, int r) {
        assert(l >= 0 && l <= r && r < n);
        return query(r) - (l ? query(l - 1) : 0);
    }
};

```

1.2 Segment Tree

```

template <typename T>
struct SegTree {
    int n;
    vector<T> t;
    SegTree(int n_) : n(n_), t(4 * n) {
        build(1, 0, n-1, vector(n, T()));
    }
    template<typename U>
    SegTree(const vector<T> &v) : SegTree((int)v.size()) {
        build(1, 0, n - 1, v);
    }
    void pull(int node) { t[node] = t[node << 1] + t[node << 1 | 1]; }
    template<typename U>
    void build(int node, int l, int r, const vector<U> &v) {
        if (l == r) {
            t[node] = T(v[l]);
            return;
        }
        int mid = (l + r) >> 1;
        build(node << 1, l, mid, v);
        build(node << 1 | 1, mid + 1, r, v);
        pull(node);
    }
    template<typename U>
    void add(int node, int i, U x, int l, int r) {
        if (l == r) {
            t[node] += x;
            return;
        }
        int mid = (l + r) / 2;
        if (i <= mid) add(node << 1, i, x, l, mid);
        else add(node << 1 | 1, i, x, mid + 1, r);
        pull(node);
    }
    void set(int node, int i, T x, int l, int r) {
        if (l == r) {
            t[node] = x;
            return;
        }
        int mid = (l + r) / 2;
        if (i <= mid) set(node << 1, i, x, l, mid);
        else set(node << 1 | 1, i, x, mid + 1, r);
        pull(node);
    }
};

```

```

    }
    T get(int node, int ql, int qr, int l, int r) {
        if (ql <= l && qr >= r) return t[node];
        int mid = (l + r) >> 1;
        if (qr <= mid) return get(node << 1, ql, qr, l, mid);
        if (ql > mid) return get(node << 1 | 1, ql, qr, mid+1, r);
        return get(node << 1, ql, qr, l, mid) + get(node << 1 | 1, ql, qr,
            mid+1, r);
    }
    // wrapper
    template <typename U>
    void add(int i, U x) {
        assert(i >= 0 && i < n);
        add(1, i, x, 0, n-1);
    }
    void set(int i, T x) {
        assert(i >= 0 && i < n);
        set(1, i, x, 0, n-1);
    }
    T get(int l, int r) {
        assert(l >= 0 && l <= r && r < n);
        return get(1, l, r, 0, n-1);
    }
};

struct node {
    int v=0; // value for leaves
    node() = default;
    // may need more constructor
    node operator+(const node& rhs) const { // used in get() and pull()
        return {v+rhs.v};
    }
    node& operator+=(const node& rhs) { // used in add()
        v+=rhs.v;
        return *this;
    }
};

```

1.3 Segment Tree with lazy propagation

```

// lazy propagation
template<typename T>
struct SegTree {
    int n;
    vector<T> t;
    SegTree(int n_) : n(n_), t(4 * n) {}
    template<typename U>
    SegTree(const vector<U> &v) : SegTree((int)v.size()) {
        build(1, 0, n - 1, v);
    }
    void pull(int node) { t[node] = t[node * 2] + t[node * 2 + 1]; }
    template<typename U>
    void build(int node, int l, int r, const vector<U> &v) {
        if (l == r) {
            return t[node].apply(l, r, v[l]);
        }
        int mid = (l + r) / 2;
        build(node * 2, l, mid, v);
        build(node * 2 + 1, mid + 1, r, v);
        pull(node);
    }
    void push(int p, int l, int r) {
        if (t[p].lazy) {
            int m = (l + r) / 2;
            t[p * 2].apply(l, m, t[p].lazy);
            t[p * 2 + 1].apply(m + 1, r, t[p].lazy);
            t[p].lazy = 0;
        }
    }
};

```

```

template<typename U>
void add(int node, int ql, int qr, int l, int r, U x) {
    if (r < ql || l > qr) return;
    if (ql <= l && qr >= r) return t[node].apply(l, r, x);
    push(node, l, r);
    int mid = (l + r) / 2;
    add(node * 2, ql, qr, l, mid, x);
    add(node * 2 + 1, ql, qr, mid + 1, r, x);
    pull(node);
}

T get(int node, int ql, int qr, int l, int r) {
    if (ql <= l && qr >= r) return t[node];
    push(node, l, r);
    int mid = (l + r) / 2;
    if (qr <= mid) return get(node << 1, ql, qr, l, mid);
    if (ql > mid) return get(node << 1 | 1, ql, qr, mid + 1, r);
    return get(node << 1, ql, qr, l, mid) + get(node << 1 | 1, ql, qr,
        mid + 1, r);
}

// wrapper
template <typename U>
void add(int l, int r, U x) {
    assert(l >= 0 && l <= r && r < n);
    add(1, l, r, 0, n-1, x);
}

T get(int l, int r) {
    assert(l >= 0 && l <= r && r < n);
    return get(1, l, r, 0, n-1);
}

};

struct node {
    int v=0; // don't forget to set default value (used for leaves), not
            // necessarily zero element
    int lazy=0;
    void apply(int l, int r, int x) {
        v+=x;
        lazy+=(r-l) * x;
    }
    node operator+(const node& b) const {
        node res;
        res.v=v+b.v;
        return res;
    }
};

```

1.4 Persistent Segment Tree

```

//find the nth biggest number
#include<bits/stdc++.h>
struct PST {
    int n, tot=0;
    vector<int> lc, rc, sum, roots; // left child, right child
    PST(int n_) : n(n_), lc(n<<5), rc(n<<5), sum(n<<5), roots(1) { //
        change the size to n<<6 if there are 2*n modification
        build(0, n-1, roots[0]); // the initial root node is 1!
    }
    void pushup(int rt) {
        sum[rt] = sum[lc[rt]] + sum[rc[rt]];
    }
    void build(int l, int r, int& rt) {
        rt = ++tot;
        if (l == r) return;
        int mid = (l + r) >> 1;
        build(l, mid, lc[rt]);
        build(mid + 1, r, rc[rt]);
        pushup(rt);
    }
    void update(int pos, int val, int l, int r, int old, int& rt) {

```

```

        rt = ++tot;
        lc[rt] = lc[old];
        rc[rt] = rc[old];
        if (l == r) {
            sum[rt] = sum[old] + val;
            return;
        }
        int mid = (l + r) >> 1;
        if (pos <= mid) update(pos, val, l, mid, lc[old], lc[rt]);
        else update(pos, val, mid + 1, r, rc[old], rc[rt]);
        pushup(rt);
    }

    int update(int pos, int val) { // return the root of the new version
        int new_root;
        update(pos, val, 0, n-1, roots.back(), new_root);
        roots.push_back(new_root);
        return new_root;
    }

    int query(int u, int v, int l, int r, int k) {
        if (l==r) return l;
        int mid=(l+r)/2, x=sum[lc[v]]-sum[lc[u]];
        if (k<=x) return query(lc[u], lc[v], l, mid, k);
        return query(rc[u], rc[v], mid+1, r, k-x);
    }
};

int main(){
    int n, q;
    cin>>n>>q;
    vector<int> a(n);
    for (auto& x : a) cin>>x;
    auto comp=a;
    sort(comp.begin(), comp.end());
    comp.erase(unique(comp.begin(), comp.end()), comp.end());
    PST tr(comp.size());
    vector<int> roots(n+1);
    roots[0]=1;
    for (int i=0; i<n; i++) {
        int p=lower_bound(comp.begin(), comp.end(), a[i])-comp.begin();
        roots[i+1]=tr.update(p, 1);
    }
    while (q--) {
        int l, r, k;
        cin>>l>>r>>k;
        cout<<comp[tr.query(roots[l-1], roots[r], 0, comp.size()-1, k)]<<'
            \n';
    }
}

```

1.5 Sparse Table

```

template <typename T> struct sparse {
    int n, logn;
    vector<vector<T>> v;
    function<T(T, T)> F;
    sparse(const vector<int>& a, function<T(T, T)> func)
        : n((int)a.size()), logn(__lg(n)), v(logn + 1, vector<T>(n + 1)),
          F(func) {
        v[0] = a;
        for (int i = 1; i <= logn; i++)
            for (int j = 0; j + (1 << i) - 1 < n; j++)
                v[i][j] = F(v[i - 1][j], v[i - 1][j + (1 << (i - 1))]);
    }
    int query(int x, int y) {
        int s = __lg(y - x + 1);
        return F(v[s][x], v[s][y - (1 << s) + 1]);
    }
};

```

1.6 Treap

```

// using treap to maintain a sequence that support multiple operation,
// index
// 0-based index, change pull(), add(), pushdown() according to the
// problem
#include<bits/stdc++.h>
mt19937 gen(chrono::high_resolution_clock::now().time_since_epoch().count
());
template <typename T> struct Treap {
    struct node {
        int ch[2], sz;
        unsigned k;
        T d, sum, lazy;
        node(T d_, int z = 1)
            : sz(z), k((unsigned)gen()), d(d_), sum(d), lazy() {
            ch[0] = ch[1] = 0;
        }
    };
    vector<node> nodes;
    int root=0, recyc=0;
    Treap(int size = 2e5) {
        nodes.reserve(size);
        nodes.emplace_back(0, 0);
    }
    inline int &ch(int rt, int r) { return nodes[rt].ch[r]; }
    int new_node(const T &d) {
        int id = (int)nodes.size();
        if (recyc) {
            id = recyc;
            if (ch(recyc, 0) && ch(recyc, 1))
                recyc = merge(ch(recyc, 0), ch(recyc, 1));
            else
                recyc = ch(recyc, ch(recyc, 0) ? 0 : 1);
            nodes[id] = node(d);
        } else
            nodes.push_back(node(d));
        return id;
    }
    int pull(int rt) {
        node &n = nodes[rt];
        n.sz = 1 + nodes[n.ch[0]].sz + nodes[n.ch[1]].sz;
        n.sum = n.d + nodes[n.ch[0]].sum + nodes[n.ch[1]].sum;
        return rt;
    }
    void add(int rt, const T &d) {
        node &n = nodes[rt];
        n.lazy = n.lazy + d;
        n.d = n.d + d;
        n.sum = n.sum + d * n.sz;
    }
    void pushdown(int rt) {
        node &n = nodes[rt];
        if (n.lazy) {
            add(n.ch[0], n.lazy);
            add(n.ch[1], n.lazy);
            n.lazy = T();
        }
    }
    int merge(int tl, int tr) {
        if (!tl) return tr;
        if (!tr) return tl;
        if (nodes[tl].k < nodes[tr].k) {
            pushdown(tl);
            ch(tl, 1) = merge(ch(tl, 1), tr);
            return pull(tl);
        } else {
            pushdown(tr);

```

```

            ch(tr, 0) = merge(tl, ch(tr, 0));
            return pull(tr);
        }
    }
    void split(int rt, int k, int &x, int &y) { // split out first k
        element
        if (!rt) {
            x = y = 0;
            return;
        }
        pushdown(rt);
        if (k <= nodes[ch(rt, 0)].sz) {
            y = rt;
            split(ch(rt, 0), k, x, ch(rt, 0));
            pull(y);
        } else {
            x = rt;
            split(ch(rt, 1), k - nodes[ch(rt, 0)].sz - 1, ch(rt, 1), y);
            pull(x);
        }
    }
    void remove(int &rt) {
        if (recyc == 0) recyc = rt;
        else recyc = merge(recyc, rt);
        rt = 0;
    }
    // interface
    int size() { return nodes[root].sz; }
    const T& operator[](int k) {
        assert(k>=0 && k<size());
        int x, y, z;
        split(root, k+1, y, z);
        split(y, k, x, y);
        root = merge(merge(x, y), z);
        return nodes[y];
    }
    void insert(int k, T v) { // insert at kth position
        assert(k>=0 && k<size());
        int l, r;
        split(root, k, l, r);
        int rt = new_node(v);
        root = merge(merge(l, rt), r);
    }
    void erase(int l, int r) {
        assert(l>=0 && l<=r && r<size());
        int x, y, z;
        split(root, r+1, y, z);
        split(y, l, x, y);
        remove(y);
        root = merge(x, z);
    }
    void range_add(int l, int r, T v) {
        assert(l>=0 && l<=r && r<size());
        int x, y, z;
        split(root, r+1, y, z);
        split(y, l, x, y);
        add(y, v);
        root = merge(merge(x, y), z);
    }
    T getsum(int l, int r) {
        assert(l>=0 && l<=r && r<size());
        int x, y, z;
        split(root, r+1, y, z);
        split(y, l, x, y);
        T ret = nodes[y].sum;
        root = merge(merge(x, y), z);
        return ret;
    }
};

```

1.7 Union find

```
struct UF {
    int n;
    vector<int> pa; // parent or size, positive number means parent,
                  // negative number means size
    explicit UF(int _n) : n(_n), pa(n, -1) {}
    int find(int x) {
        assert(0 <= x && x < n);
        return pa[x] < 0 ? x : pa[x]=find(pa[x]);
    }
    bool join(int x, int y) {
        assert(0 <= x && x < n && 0 <= y && y < n);
        x=find(x), y=find(y);
        if (x==y) return false;
        if (-pa[x] < -pa[y]) swap(x, y); // size of x is smaller than size
        // of y
        pa[x]+=pa[y];
        pa[y]=x;
        return true;
    }
    int size(int x) {
        assert(0 <= x && x < n);
        return -pa[x];
    }
    vector<vector<int>> groups() {
        vector<int> leader(n);
        for (int i=0; i<n; i++) leader[i]=find(i);
        vector<vector<int>> res(n);
        for (int i=0; i<n; i++) {
            res[leader[i]].push_back(i);
        }
        res.erase(remove_if(res.begin(), res.end(),
            [](const vector<int>& v) { return v.empty(); }), res.
            end());
        return res;
    }
};
```

2 Graph Theory

2.1 Bellman Ford

```
struct BellmanFord {
    static constexpr long long INF=1e18;
    int n, last_relaxed=-1;
    vector<tuple<int, int, int>> edges;
    vector<bool> bad; //has negative cycle on the path
    vector<int> pre;
    vector<ll> dis;
    BellmanFord(int _n) : n(_n), bad(n), pre(n), dis(n, INF) {}
    void add_edge(int u, int v, int w) {
        edges.emplace_back(u, v, w);
    }
    void run(int start) {
        dis[start]=0;
        for (int i=0; i<n-1; i++) {
            for (auto [u, v, w] : edges) {
                if (dis[u]<INF && dis[v]>dis[u]+w) {
                    dis[v]=dis[u]+w;
                    pre[v]=u;
                }
            }
        }
    }
};
```

```
for (auto [u, v, w] : edges) {
    if (dis[u]<INF && dis[v]>dis[u]+w) {
        dis[v]=dis[u]+w;
        bad[v]=true;
        last_relaxed=v;
        pre[v]=u;
    }
}
for (int i=0; i<n; i++) {
    for (auto [u, v, w] : edges) {
        if (bad[u]) bad[v]=true;
    }
}
vector<int> find_cycle() {
    dis.assign(n, 0); // without this, only cycle reachable from 0
                    // will be counted
    run(0);
    if (last_relaxed==-1) return {};
    int x=last_relaxed;
    for (int i=0; i<n; i++) x=pre[x];
    vector<int> cycle;
    for (int cur=x; ; cur=pre[cur]) {
        cycle.push_back(cur);
        if (cur==x && cycle.size()>1) break;
    }
    reverse(cycle.begin(), cycle.end());
    return cycle;
}
long long get_dis(int x) {
    return bad[x] ? -INF : dis[x];
}
};
```

2.2 Hopcroft Karp

```
struct HopcroftKarp {
    int n, m;
    Dinic flow;
    vector<int> l, r;
    HopcroftKarp(int n, int m) : n(n), m(m), flow(n+m+2), l(n, -1), r(m,
        -1) {}
    void add_edge(int u, int v) {
        flow.addEdge(u, n+v, 1);
    }
    int solve() {
        for (int i=0; i<n; i++)
            flow.addEdge(n+m, i, 1);
        for (int i=0; i<m; i++)
            flow.addEdge(n+i, n+m+1, 1);
        int res = flow.maxFlow(n+m, n+m+1);
        for (int i=0; i<n; i++) {
            if (flow.match[i]!=-1) {
                l[i]=flow.match[i]-n;
                r[flow.match[i]-n]=i;
            }
        }
        return res;
    }
};
int main() {
    ios::sync_with_stdio(false);
    int l, r, m;
    cin>>l>>r>>m;
    HopcroftKarp g(l, r);
    while (m-->0) {
        int u, v;
        cin>>u>>v;
```

```

    g.add_edge(u, v);
}
cout<<g.solve()<<'\\n';
for (int i=0; i<l; i++) {
    if (g.l[i]!=-1) cout<<i<<' '<<g.l[i]<<'\\n';
}
}

```

2.3 Augmented Path for BPM

```

// augmented path algorithm for maximum-cardinality bipartite matching
// Worst time complexity: O(nm), but very hard to hack (since we can
// shuffle),
// usually runs extremely fast, 2e5 vertices and edges in 60 ms.
mt19937 rng(1);
struct aug_path {
    vector<vector<int>> g;
    vector<int> L, R, vis;
    aug_path(int n, int m) : g(n), L(n, -1), R(m, -1), vis(n) {}
    void add_edge(int a, int b) { g[a].push_back(b); }
    bool match(int u) {
        if (vis[u]) return false;
        vis[u] = true;
        for (auto v : g[u]) {
            if (R[v] == -1) {
                L[u] = v;
                R[v] = u;
                return true;
            }
        }
        for (auto vec : g[u]) {
            if (match(R[vec])) {
                L[u] = vec;
                R[vec] = u;
                return true;
            }
        }
        return false;
    }
    int solve() {
        // shuffle to avoid counter test case, but may be slightly slower
        // for (auto& v : g)
        //     shuffle(v.begin(), v.end(), rng);
        // vector<int> order(L.size());
        // iota(order.begin(), order.end(), 0);
        // shuffle(order.begin(), order.end(), rng);
        bool ok = true;
        while (ok) {
            ok=false;
            fill(vis.begin(), vis.end(), 0);
            // for (auto i : order)
            for (int i = 0; i < (int)L.size(); ++i)
                if (L[i] == -1) ok |= match(i);
        }
        int ret = 0;
        for (int i = 0; i < L.size(); ++i)
            ret += (L[i] != -1);
        return ret;
    }
};
int main() {
    ios::sync_with_stdio(false);
    int l, r, m;
    cin>>l>>r>>m;
    aug_path g(l, r);
    while (m--) {
        int u, v;
        cin>>u>>v;
    }
}

```

```

    g.add_edge(u, v);
}
cout<<g.solve()<<'\\n';
for (int i=0; i<l; i++) {
    if (g.L[i]!=-1) cout<<i<<' '<<g.L[i]<<'\\n';
}
}

```

2.4 Binary Lifint

```

struct Binary_lifting {
    const int sz, level;
    const vector<vector<int>>& g;
    vector<vector<int>> pa;
    vector<int> dep;
    Binary_lifting(const vector<vector<int>>& g_) :
        sz((int)g_.size()),
        level(__lg(sz)+2),
        g(g_),
        pa(sz, vector<int>(level)),
        dep(g.size()) {}
    void dfs(int u, int p) {
        pa[u][0] = p;
        dep[u] = dep[p] + 1;
        for (int i = 1; i < level; i++) {
            pa[u][i] = pa[pa[u][i-1]][i-1];
        }
        for (auto v : g[u]) {
            if (v == p) continue;
            dfs(v, u);
        }
    };
    int jump(int u, int step) {
        for (int i=0; i<level; i++) {
            if (step>>i&1) u=pa[u][i];
        }
        return u;
    }
    int lca(int x, int y) {
        if (dep[x] > dep[y]) swap(x, y);
        y=jump(y, dep[y] - dep[x]);
        if (x == y) return x;
        for (int i=level-1; i>=0; i--) {
            if (pa[x][i] != pa[y][i]) {
                x = pa[x][i];
                y = pa[y][i];
            }
        }
        return pa[x][0];
    }
};

```

2.5 Bridges

```

struct Bridge {
    int n, pos=0;
    vector<vector<pair<int, int>>> g; // graph, component
    vector<int> ord, low, bridges; // order, low link, belong to which
    // component
    Bridge(int n) : n(n), g(n), ord(n, -1), low(n) {}
    void add_edge(int u, int v, int i) {
        g[u].emplace_back(v, i);
        g[v].emplace_back(u, i);
    }
    void dfs(int u, int p) {
        ord[u] = low[u] = pos++;
        int cnt = 0;
    }
};

```

```

    for (auto [v, i] : g[u]) {
        // in case there're repeated edges, only skip the first one
        if (v == p && cnt == 0) {
            cnt++;
            continue;
        }
        if (ord[v] == -1) dfs(v, u);
        low[u] = min(low[u], low[v]);
        if (low[v] > ord[u]) bridges.push_back(i);
    }
}

void solve() {
    for (int i = 0; i < n; i++)
        if (ord[i] == -1) dfs(i, i);
}
};

```

2.6 Cut Vertices

```

struct cut_vertex {
    int n, pos = 0;
    vector<vector<int>> g;
    vector<int> ord, low, cuts;
    cut_vertex(int n_) : n(n_), g(n), ord(n, -1), low(n) {}
    void add_edge(int u, int v) {
        g[u].push_back(v);
        g[v].push_back(u);
    }
    void dfs(int u, int pa) {
        low[u] = ord[u] = pos++;
        int cnt = 0, sz = 1, sum = 0;
        bool is_cut = 0;
        for (auto v : g[u]) {
            if (v == pa) continue;
            if (ord[v] == -1) {
                cnt++;
                dfs(v, u);
                if (low[v] >= ord[u]) {
                    if (u != pa || cnt > 1) is_cut = true;
                    // the subtree will be disconnected if we remove
                    // vertex u,
                    // do something if needed
                }
            }
            low[u] = min(low[u], low[v]);
        }
        if (is_cut) cuts.push_back(u);
    }
    void solve() {
        for (int i = 0; i < n; i++) {
            if (ord[i] == -1) dfs(i, i);
        }
    }
};

```

2.7 Dijkstra

```

constexpr long long INF=1e18;
template<typename G>
vector<long long> dijkstra(const G& g, int start) {
    vector dis(g.size(), INF);
    // vector<pii> pre[N];
    using node=pair<long long, int>;
    priority_queue<node, vector<node>, greater<>> q;
    dis[start] = 0;
    q.emplace(0, start);
    while (!q.empty()) {

```

```

        auto [d, u] = q.top();
        q.pop();
        if (d != dis[u]) continue;
        for (auto [v, cost] : g[u]) {
            if (dis[v] > dis[u] + cost) {
                dis[v] = dis[u] + cost;
                // pre[v].clear();
                // pre[v].pb({cost, u});
                q.emplace(dis[v], v);
            }
            // else if(dis[v]==dis[u]+cost)
            // pre[v].pb({cost, u});
        }
    }
    return dis;
}

// dijkstra for small edge weight (less than 10) aka 1-k bfs
vector<int> SmallDijkstra(const vector<vector<pair<int, int>>>& g, int src
, int lim) {
    vector<vector<int>> qs(lim);
    vector<int> dis(g.size(), -1);
    dis[src] = 0;
    qs[0].push_back(src);
    for (int d = 0, maxd = 0; d <= maxd; ++d) {
        for (auto& q = qs[d % lim]; q.size(); ) {
            int u = q.back();
            q.pop_back();
            if (dis[u] != d) continue;
            for (auto [v, c] : g[u]) {
                if (dis[v] != -1 && dis[v] <= d + c) continue;
                dis[v] = d + c;
                qs[(d + c) % lim].push_back(v);
                maxd = max(maxd, d + c);
            }
        }
    }
    return dis;
}

```

2.8 Dinic

```

// indexed from 0!
struct Dinic {
    static constexpr int INF = 1e9;
    int n;
    struct Edge {
        int to, cap;
        Edge(int to, int cap) : to(to), cap(cap) {}
    };
    vector<Edge> e;
    vector<std::vector<int>> g;
    vector<int> cur, h; // h = shortest distance from source, calculated
    // in bfs
    // after computing flow, edge (u, v) such that h[u]!=-1 and h[v]==-1
    // are part of min cut
    Dinic(int n) : n(n), g(n) {}
    bool bfs(int s, int t) {
        h.assign(n, -1);
        std::queue<int> que;
        h[s] = 0;
        que.push(s);
        while (!que.empty()) {
            int u = que.front();
            que.pop();
            for (int i : g[u]) {
                auto [v, c] = e[i];
                if (c > 0 && h[v] == -1) {
                    h[v] = h[u] + 1;

```

```

        if (v == t) return true;
        que.push(v);
    }
}
return false;
}
int dfs(int u, int t, int f) {
    if (u == t) return f;
    int r = f;
    for (int &i = cur[u]; i < int(g[u].size()); ++i) {
        int j = g[u][i];
        auto [v, c] = e[j];
        if (c > 0 && h[v] == h[u] + 1) {
            int a = dfs(v, t, std::min(r, c));
            e[j].cap -= a;
            e[j ^ 1].cap += a;
            r -= a;
            if (r == 0) return f;
        }
    }
    return f - r;
}
void addEdge(int u, int v, int c) {
    g[u].push_back((int)e.size());
    e.emplace_back(v, c);
    g[v].push_back((int)e.size());
    e.emplace_back(u, 0);
}
int maxFlow(int s, int t) {
    int ans = 0;
    while (bfs(s, t)) {
        cur.assign(n, 0);
        ans += dfs(s, t, INF);
    }
    return ans;
}
};

```

2.9 Divide and Couquer on Trees

```

vector<vector<pair<int,int>>> g;
vector<int> query, subtreeSize, parent;
vector<bool> blocked;
//calculate subtree size
void calSize(int u, int p) {
    parent[u] = p;
    subtreeSize[u] = 1;
    for (auto [v, w] : g[u]) {
        if (v == p || blocked[v]) continue;
        calSize(v, u);
        subtreeSize[u] += subtreeSize[v];
    }
}
//if needed solveTree can return value
void solveTree(int root) {
    queue<pii> cur; //store the result for current subtree
    for (auto [v, w] : g[root]) {
        if (blocked[v]) continue;
        queue<pair<int, int>> q; //change if type of element if needed
        q.push({v, w});
        while (!q.empty()) {
            auto [u, dis] = q.front();
            q.pop();
            //do ... to update answer
            cur.push({dis, len});
            for (auto [to, wei] : g[u]) {
                if (to == parent[u] || blocked[to]) continue;

```

```

                q.push({to, dis+wei});
            }
        }
    }
    while (!cur.empty()) {
        auto [dis, len] = cur.front();
        // do ... to update the result for the current tree
        cur.pop();
    }
}
// return some value if needed
void go(int entry) {
    calSize(entry, entry);
    int centroid = entry;
    int bestSize = subtreeSize[entry];
    queue<int> q;
    q.push(entry);
    while (!q.empty()) {
        int u = q.front();
        q.pop();

        int size = subtreeSize[entry] - subtreeSize[u];
        for (auto [v, w] : g[u]) {
            if (v == parent[u] || blocked[v]) continue;
            size = max(size, subtreeSize[v]);
            q.push(v);
        }
        if (size < bestSize) centroid = u, bestSize = size;
    }
    calSize(centroid, centroid);
    blocked[centroid] = true;
    // do ... to clear the previous result
    solveTree(centroid);
    for (auto [v, w] : g[centroid]) {
        if (!blocked[v]) go(v);
    }
}

```

2.10 Dsu on Trees

```

int main() {
    vector<int> bch(n, -1);
    int cur_big = -1;
    auto get_big = [&](auto &dfs, int u, int p) -> int {
        int sz = 1, mx = 0;
        for (auto v : g[u]) {
            if (v == p) continue;
            int csz = dfs(dfs, v, u);
            if (csz > mx) mx = csz, bch[u] = v;
            sz += csz;
        }
        return sz;
    };
    auto add = [&](auto &slf, int u, int p, int x) -> void {
        // update info of u here
        for (auto v : g[u]) {
            if (v == p || v == cur_big) continue;
            slf(slf, v, u, x);
        }
    };
    auto dfs = [&](auto &dfs, int u, int pa, bool keep) -> void {
        int big = bch[u];
        for (auto v : g[u]) {
            if (v != pa && v != big) dfs(dfs, v, u, 0);
        }
        if (big != -1) {
            dfs(dfs, big, u, 1);
            cur_big = big;
        }
    };
}

```



```

add(add, u, pa, 1);
// now you get all the info of subtree of u, answer queries about
// u
// here.
cur_big = -1;
if (!keep) add(add, u, pa, -1);
};
}

```

2.11 Euler Cycle

```

// add an edge (end, start) if to find Eulerian path, and remove it in the
// answer with:
// for (auto i : rep(1, ans.size())) {
//     if (ans[i-1]==n-1 && ans[i]==0) {
//         for (auto j : rep(i, ans.size()-1)) cout<<ans[j]+1<<' ';
//         for (auto j : rep(i)) cout<<ans[j]+1<<' ';
//         return;
//     }
// }
struct Euler_tour {
    int n, edge_cnt=0;
    vector<vector<pair<int, int>>> g;
    vector<pair<int, int>> circuit;
    vector<int> deg;
    vector<bool> used;
    // use in-degree and out-degree if directed graph
    // vector<int> indeg, oudeg;
    bool bad=0;
    Euler_tour(int _n) : n(_n), g(n), deg(n) {}
    void add_edge(int u, int v) { // change if directed graph
        g[u].emplace_back(v, edge_cnt);
        g[v].emplace_back(u, edge_cnt);
        deg[u]++, deg[v]++;
        edge_cnt++;
    }
    void dfs(int pre, int u) {
        while (!g[u].empty()) {
            auto [v, edge] = g[u].back();
            g[u].pop_back();
            if (used[edge]) continue;
            used[edge]=true;
            dfs(u, v);
        }
        if (!circuit.empty() && circuit.back().first!=u) bad=true;
        circuit.emplace_back(pre, u);
    }
    vector<int> solve(int start) {
        for (auto x : deg) if (x%2) return {}; // change if directed graph
        ;
        // for (int i=0; i<n; i++) if (indeg[i]!=oudeg[i]) return {};
        used.resize(edge_cnt);
        dfs(-1, start);
        if (circuit.size()!=edge_cnt+1 || bad) return {};
        vector<int> ans;
        for (auto [u, v] : circuit) ans.push_back(v);
        // reverse ans if directed
        // reverse(ans.begin(), ans.end());
        return ans;
    }
};

```

2.12 Heavy-light Decomp

```

#include "../DataStructure/fenwick.cpp"
struct Heavy_light {
    vector<vector<int>> g;

```

```

    vector<int> fa, dep, heavy, head, pos, posr; // initialize heavy with
    -1
    int cnt=0;
    fenwick<long long> tr;
    Heavy_light(int n) : g(n), fa(n), dep(n), heavy(n, -1), head(n), pos(n),
    posr(n), tr(n) {}
    void add_edge(int u, int v) {
        g[u].push_back(v);
        g[v].push_back(u);
    }
    int dfs(int u) {
        int size = 1;
        int mx = 0;
        for (int v : g[u]) {
            if (v != fa[u]) {
                fa[v] = u, dep[v] = dep[u] + 1;
                int csize = dfs(v);
                size += csize;
                if (csize > mx) mx = csize, heavy[u] = v;
            }
        }
        return size;
    }
    void dfs2(int u, int h) {
        head[u] = h, pos[u] = ++cnt; //1-based index, could change to 0
        based but less useful
        if (heavy[u] != -1) dfs2(heavy[u], h);
        for (int v : g[u]) {
            if (v != fa[u] && v != heavy[u])
                dfs2(v, v);
        }
        posr[u] = cnt;
    }
    long long pathsum(int u, int v) {
        long long res = 0;
        while (head[u] != head[v]) {
            if (dep[head[u]] < dep[head[v]]) swap(u, v);
            res += tr.query(pos[head[u]], pos[u]);
            u = fa[head[u]];
        }
        if (pos[u] > pos[v]) swap(u, v);
        res += tr.query(pos[u], pos[v]);
        return res;
    }
    int lca(int u, int v) {
        while (head[u] != head[v]) {
            if (dep[head[u]] > dep[head[v]]) u = fa[head[u]];
            else v = fa[head[v]];
        }
        return dep[u] > dep[v] ? v : u;
    }
};

```

2.13 Hunarian

```

// credits: https://github.com/the-tourist/algo/blob/master/flows/
// hungarian.cpp
// hungarian algorithm for bipartite graph matching, matches every node on
// the
// left with a node on the right and the sum of the weights is minimal.
// a[i][j] is the cost for i in L to be matched with j in R. (0-indexed)
// pa[i] is the node in R matched with i
// pb[j] is the node in L matched with j
// Negate the cost for max cost.
// Time: O(n^2M)
template<typename T>
struct Hungarian {
    int n, m;

```

```

vector< vector<T> > a;
vector<T> u, v;
vector<int> pa, pb, way;
vector<T> minv;
vector<bool> used;
T inf;
Hungarian(int _n, int _m) : n(_n), m(_m), a(n, vector<T>(m)), u(n+1),
    v(m+1), pa(n+1, -1), pb(m+1, -1), way(m, -1), minv(m), used(m+1) {
    assert(n <= m);
    inf = numeric_limits<T>::max();
}
inline void add_row(int i) {
    fill(minv.begin(), minv.end(), inf);
    fill(used.begin(), used.end(), false);
    pb[m] = i;
    pa[i] = m;
    int j0 = m;
    do {
        used[j0] = true;
        int i0 = pb[j0];
        T delta = inf;
        int j1 = -1;
        for (int j = 0; j < m; j++) {
            if (!used[j]) {
                T cur = a[i0][j] - u[i0] - v[j];
                if (cur < minv[j]) {
                    minv[j] = cur;
                    way[j] = j0;
                }
                if (minv[j] < delta) {
                    delta = minv[j];
                    j1 = j;
                }
            }
        }
        for (int j = 0; j <= m; j++) {
            if (used[j]) {
                u[pb[j]] += delta;
                v[j] -= delta;
            } else {
                minv[j] -= delta;
            }
        }
        j0 = j1;
    } while (pb[j0] != -1);
    do {
        int j1 = way[j0];
        pb[j0] = pb[j1];
        pa[pb[j0]] = j0;
        j0 = j1;
    } while (j0 != m);
}
inline T current_score() {
    return -v[m];
}
inline T solve() {
    for (int i = 0; i < n; i++) {
        add_row(i);
    }
    return current_score();
}
};

```

2.14 Tarjan's SCC

*// Note that strictly speaking this is not the original tarjan's algorithm
 // because we use a slightly different definition for lowlink. However
 this*

```

// algorithm is still correctly and easier to code.
// See: https://cs.stackexchange.com/questions/96635/tarjans-scc-example-
// showing-necessity-of-lowlink-definition-and-calculation-r?rq=1
struct SCC {
    int n, pos = 0;
    vector<vector<int>> g;
    vector<bool> on_stk;
    vector<int> low, ord, stk, color;
    vector<vector<int>> comp;
    SCC(int _n) : n(_n), g(n), on_stk(n), low(n), ord(n, -1), color(n) {}
    void add_edge(int u, int v) { g[u].push_back(v); }
    void dfs(int u) {
        low[u] = ord[u] = pos++;
        stk.push_back(u);
        on_stk[u] = true;
        for (auto v : g[u]) {
            if (ord[v] == -1) dfs(v);
            if (on_stk[v]) low[u] = min(low[u], low[v]);
        }
        if (low[u] == ord[u]) {
            comp.emplace_back();
            while (true) {
                int v = stk.back();
                stk.pop_back();
                on_stk[v] = false;
                comp.back().push_back(v);
                if (u == v) break;
            }
        }
    }
    void solve() {
        for (int i = 0; i < n; i++)
            if (ord[i] == -1) dfs(i);
        // reverse(comp.begin(), comp.end()); to sort components in
        // topological
        // order
        for (int i = 0; i < (int)comp.size(); i++) {
            for (int x : comp[i])
                color[x] = i;
        }
    }
};

```

2.15 Two-edge-connected components

```

struct TECC {
    int n, pos=0;
    vector<int> ord, low, color; // order, low link, belong to which
    // component
    vector<vector<int>> g, comp; // graph, component
    TECC(int n) : n(n), ord(n, -1), low(n), color(n, -1), g(n) {}
    void add_edge(int u, int v) {
        g[u].emplace_back(v);
        g[v].emplace_back(u);
    }
    bool is_bridge(int u, int v) {
        if (ord[u] > ord[v]) swap(u, v);
        return ord[u] < low[v];
    }
    void dfs(int u, int p) {
        ord[u] = low[u] = pos++;
        int cnt = 0;
        for (int v : g[u]) {
            // in case there're repeated edges, only skip the first one
            if (v == p && cnt == 0) {
                cnt++;
                continue;
            }
        }
    }
};

```

```

        if (ord[v] == -1) dfs(v, u);
        low[u] = min(low[u], low[v]);
    }
}

void fill_component(int u) {
    comp.back().emplace_back(u);
    for (int v : g[u]) {
        if (color[v] != -1 || is_bridge(v, u)) continue;
        color[v] = color[u];
        fill_component(v);
    }
}

int build() {
    for (int i = 0; i < n; i++)
        if (ord[i] == -1) dfs(i, i);
    int k = 0;
    for (int i = 0; i < n; i++) {
        if (color[i] != -1) continue;
        color[i] = k++;
        comp.emplace_back();
        fill_component(i);
    }
    return k;
}

int main() {
    int n, m;
    cin >> n >> m;
    TECC g(n);
    for (int i = 0; i < m; i++) {
        int a, b;
        cin >> a >> b;
        g.add_edge(a, b);
    }
    int k = g.build();
    cout << k << '\n';
    for (int i = 0; i < k; i++) {
        cout << g.comp[i].size() << ' ';
        for (int v : g.comp[i])
            cout << v << ' ';
    }
    return 0;
}

```

3 Math

3.1 Baby Step Giant Step

```

// solve a^x=b(mod n), 0<= x <n
#define MOD 76543
int hs[MOD], head[MOD], next[MOD], id[MOD], top;
void insert(int x, int y) {
    int k = x % MOD;
    hs[top] = x, id[top] = y, next[top] = head[k], head[k] = top++;
}

int find(int x) {
    int k = x % MOD;
    for (int i = head[k]; i != -1; i = next[i])
        if (hs[i] == x) return id[i];
    return -1;
}

int BSGS(int a, int b, int n) {
    memset(head, -1, sizeof(head));
    top = 1;

```

```

    if (b == 1) return 0;
    int m = sqrt(n * 1.0), j;
    long long x = 1, p = 1;
    for (int i = 0; i < m; ++i, p = p * a % n)
        insert(p * b % n, i);
    for (long long i = m; i += m) {
        if ((j = find(x = x * p % n)) != -1) return i-j;
        if (i > n) break;
    }
    return -1;
}

```

3.2 Chinese remainder Theorem

```

// a x + b y = gcd(a, b)
ll extgcd(ll a, ll b, ll &x, ll &y) {
    ll g = a; x = 1; y = 0;
    if (b != 0) g = extgcd(b, a % b, y, x), y -= (a / b) * x;
    return g;
}

// Solve linear congruences equation:
// a[i] * x = b[i] MOD m[i] (mi don't need to be co-prime)
// M - lcm, x - smallest integer solution
bool chinese(const vector<ll> &a, const vector<ll> &b, const vector<ll> &m
, ll &x, ll &M) {
    ll n = a.size();
    x = 0; M = 1;
    for (int i = 0; i < n; i++) {
        ll a_ = a[i] * M, b_ = b[i] - a[i] * x, m_ = m[i];
        ll y, t, g = extgcd(a_, m_, y, t);
        if (b_ % g) return false;
        b_ /= g; m_ /= g;
        x += M * (y * b_ % m_);
        M *= m_;
    }
    x = (x + M) % M;
    return true;
}

```

3.3 Euler

```

#define NEGPOW(e) ((e) % 2 ? -1 : 1)

int jacobi(int a, int m) {
    if (a == 0) return m == 1 ? 1 : 0;
    if (a % 2) return NEGPOW((a-1)*(m-1)/4)*jacobi(m%a, a);
    else return NEGPOW((m*m-1)/8)*jacobi(a/2, m);
}

int invMod(int a, int m) {
    int x, y;
    if (extgcd(a, m, x, y) == 1) return (x + m) % m;
    else return 0; // unsolvable
}

// No solution when: n(p-1)/2 = -1 mod p
int sqrtMod(int n, int p) {
    int S, Q, W, i, m = invMod(n, p);
    for (Q = p - 1, S = 0; Q % 2 == 0; Q /= 2, ++S);
    do { W = rand() % p; } while (W == 0 || jacobi(W, p) != -1);
    for (int R = powMod(n, (Q+1)/2, p), V = powMod(W, Q, p); ; ) {
        int z = R * R * m % p;
        for (i = 0; i < S && z % p != 1; z *= z, ++i);
        if (i == 0) return R;
        R = (R * powMod(V, 1 << (S-i-1), p)) % p;
    }
}

```

```

bool eulerCriterion(int n, int p) {
    if(powMod(n, (p-1)/2, p) == 1) return true;
    return false;
}

int powMod(int a, int b, int p) {
    int res=1;
    while(b) {
        if(b&1) res=int( res * 1ll * a % p), --b;
        else a=int( a * 1ll * a%p), b>>=1;
    }
    return res;
}

```

3.4 Extended Euclidean Algorithm

```

#include<bits/stdc++.h>
using ll=long long;
// {g, x, y}: ax+by=gcd(a,b)
tuple<ll, ll, ll> exgcd(ll a, ll b) {
    if (b==0) return {a, 1, 0};
    auto [g, x, y]=exgcd(b, a%b);
    return {g, y, x-a/b*y};
}
/*
solve ax+by=c, equivalently ax=c (mod b)
all solutions: x=x0+b/g*t, y=y0-a/g*t
smallest positive x=(x0%t+t)%t, where t=b/g
*/
bool liEu(ll a, ll b, ll c, ll& x, ll& y) {
    ll g;
    tie(g, x, y)=exgcd(a, b);
    if (c % g != 0) return false;
    ll k = c / g;
    x *= k;
    y *= k;
    // smallest positive x:
    // b/=g;
    // x=(x%b+b)%b;
    return true;
}

```

3.5 Factorial

```

namespace Factorial {
    vector<mint> fac, invfac;
    void init(int n) {
        fac.resize(n+1);
        invfac.resize(n+1);
        fac[0]=1;
        for (int i=1; i<=n; i++) fac[i]=fac[i-1]*i;
        invfac[n]=fac[n].inv();
        for (int i=n-1; i>=0; i--) invfac[i]=invfac[i+1]*(i+1);
    }
    mint C(int n, int m) { // n choose m
        return fac[n]*invfac[n-m]*invfac[m];
    }
    mint P(int n, int m) { // n choose m with permutation
        return fac[n]*invfac[n-m];
    }
}
using namespace Factorial;

```

3.6 Factorization

```

#include<bits/stdc++.h>
// factor using naive or Rho algorithm, also see Sieve.cpp for faster
// factorization for small numbers
namespace Fractorization {
    using u64 = uint64_t;
    using ul28 = __uint128_t;
    using ll = long long;
    u64 binPow(u64 a, u64 b, u64 mod){
        if(b == 0) return 1;
        if(b&1) return (ul28)a * binPow(a, b^1, mod) % mod;
        return binPow((ul28)a * a % mod, b>>1, mod);
    }
    bool checkComp(u64 n, u64 a, u64 d, int s){
        u64 x = binPow(a, d, n);
        if(x == 1 || x == n-1) return false;
        for (int r=1; r<s; r++) {
            x = (ul28)x * x % n;
            if(x == n-1) return false;
        }
        return true;
    }
    bool RabinMiller(u64 n){
        if(n < 2) return false;
        int r = 0;
        u64 d = n-1;
        while(!(d & 1))
            d >>= 1, r++;
        for(int a : {2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37}){
            if(n == a) return true;
            if(checkComp(n, a, d, r)) return false;
        }
        return true;
    }
    ll mult(ll a, ll b, ll mod){
        return (__int128)a * b % mod;
    }
    ll f(ll x, ll c, ll mod){
        return (mult(x, x, mod) + c) % mod;
    }
    ll rho(ll n){ // Works in O(n^(1/4) * log(n))
        ll x = 2, y = 2, g = 1;
        ll c = rand() % n + 1;
        while(g == 1){
            x = f(x, c, n);
            y = f(y, c, n);
            y = f(y, c, n);
            g = gcd(abs(x - y), n);
        }
        return g==n ? rho(n) : g;
    }
    vector<pair<ll, int>> factorRho(ll n) {
        map<ll, int> fact;
        function<void(ll)> factRho=[&](ll n){
            if(n == 1) return;
            if(RabinMiller(n)){
                fact[n]++;
                return;
            }
            ll factor = rho(n);
            factRho(factor);
            factRho(n/factor);
        };
        vector<pair<ll, int>> facts;
        for (auto& p : fact) facts.push_back(p);
        return facts;
    }
    vector<pair<int, int>> factor(int n) {
        vector<pair<int, int>> facts;
        for (int f=2; f*f<=n; f++) {

```

```

        if (n%f==0) {
            int c=0;
            while (n%f==0) {
                n/=f;
                c++;
            }
            facts.emplace_back(f, c);
        }
    }
    return facts;
}
}
using namespace Fractorization;

```

3.7 FFT

```

// for polynomial multiplication, tested with https://open.kattis.com/problems/polymul2
typedef double T;
typedef complex<T> C;

void fft(vector<C> &a, bool invert){
    int n = sz(a);
    for(int i=0, j=0; i<n; ++i) {
        if(i>j) swap(a[i], a[j]);
        for(int k=n>>1; (j^=k)<k; k>>=1);
    }
    for (int len=2; len<=n; len<=1){
        double ang = 2*M_PI/len*(invert?-1:1);
        C wlen(cos(ang), sin(ang));
        for (int i=0; i<n; i+=len){
            C w(1);
            for (int j=0; j<len/2; j++){
                // if((j & 511) == 511) w = C(cos(ang * j), sin(ang * j));
                C u = a[i+j], v = a[i+j+len/2]*w;
                a[i+j] = u+v;
                a[i+j+len/2] = u-v;
                w *= wlen;
            }
        }
    }
    if (invert){
        for (int i=0; i<n; i++) a[i] /= n;
    }
}

void conv(const vector<ll> &a, const vector<ll> &b, vector<ll> &res){
    vector<C> fa(all(a)), fb(all(b));
    int n = 1;
    while (n < max(sz(a), sz(b))) n <= 1; n <= 1;
    fa.resize(n); fb.resize(n);
    fft(fa, false); fft(fb, false);
    for (int i=0; i<n; i++) fa[i] *= fb[i];
    fft(fa, true);
    res.resize(n);
    for (int i=0; i<n; i++) res[i] = ((ll) (fa[i].real() + (fa[i].real()
        >0?0.5:-0.5)));
}

```

3.8 Gaussian elimination

```

const double EPS = 1e-9;
const int INF = 2;

int gauss (vector< vector<double> > a, vector<double> & ans) {
    int n = (int) a.size();
    int m = (int) a[0].size() - 1;

```

```

vector<int> where (m, -1);
for (int col=0, row=0; col<m && row<n; ++col) {
    int sel = row;
    for (int i=row; i<n; ++i)
        if (abs (a[i][col]) > abs (a[sel][col]))
            sel = i;
    if (abs (a[sel][col]) < EPS)
        continue;
    for (int i=col; i<=m; ++i)
        swap (a[sel][i], a[row][i]);
    where[col] = row;

    for (int i=0; i<n; ++i)
        if (i != row) {
            double c = a[i][col] / a[row][col];
            for (int j=col; j<=m; ++j)
                a[i][j] -= a[row][j] * c;
        }
    ++row;
}

ans.assign (m, 0);
for (int i=0; i<m; ++i)
    if (where[i] != -1)
        ans[i] = a[where[i]][m] / a[where[i]][i];
for (int i=0; i<n; ++i) {
    double sum = 0;
    for (int j=0; j<m; ++j)
        sum += ans[j] * a[i][j];
    if (abs (sum - a[i][m]) > EPS)
        return 0;
}

for (int i=0; i<m; ++i)
    if (where[i] == -1)
        return INF;
return 1;
}

```

3.9 Lucas Theorem

```

// when n and m are big but p is small
ll Lucas(ll n, ll m, ll p) {
    if (m == 0) return 1;
    return (C(n % p, m % p) * Lucas(n / p, m / p, p)) % p;
}

```

3.10 NFFT

```

using i64 = long long;
using u64 = unsigned long long;
using u32 = unsigned;
constexpr int P = 998244353;
std::vector<int> rev, roots{0, 1};
int power(int a, int b) {
    int res = 1;
    for (; b; b >>= 1, a = 1ll * a * a % P)
        if (b & 1)
            res = 1ll * res * a % P;
    return res;
}

void dft(std::vector<int> &a) {
    int n = a.size();
    if (int(rev.size()) != n) {
        int k = __builtin_ctz(n) - 1;
        rev.resize(n);

```

```

    for (int i = 0; i < n; ++i)
        rev[i] = rev[i >> 1] >> 1 | (i & 1) << k;
}
for (int i = 0; i < n; ++i)
    if (rev[i] < i)
        std::swap(a[i], a[rev[i]]);
if (int (roots.size()) < n) {
    int k = __builtin_ctz(roots.size());
    roots.resize(n);
    while ((1 << k) < n) {
        int e = power(3, (P - 1) >> (k + 1));
        for (int i = 1 << (k - 1); i < (1 << k); ++i) {
            roots[2 * i] = roots[i];
            roots[2 * i + 1] = 1ll * roots[i] * e % P;
        }
        ++k;
    }
}
for (int k = 1; k < n; k *= 2) {
    for (int i = 0; i < n; i += 2 * k) {
        for (int j = 0; j < k; ++j) {
            int u = a[i + j];
            int v = 1ll * a[i + j + k] * roots[k + j] % P;
            int x = u + v;
            if (x >= P)
                x -= P;
            a[i + j] = x;
            x = u - v;
            if (x < 0)
                x += P;
            a[i + j + k] = x;
        }
    }
}
void idft(std::vector<int> &a) {
    int n = a.size();
    std::reverse(a.begin() + 1, a.end());
    dft(a);
    int inv = power(n, P - 2);
    for (int i = 0; i < n; ++i)
        a[i] = 1ll * a[i] * inv % P;
}
struct Poly {
    std::vector<int> a;
    Poly() {}
    Poly(int a0) {
        if (a0)
            a = {a0};
    }
    Poly(const std::vector<int> &a1) : a(a1) {
        while (!a.empty() && !a.back())
            a.pop_back();
    }
    int size() const {
        return a.size();
    }
    int operator[](int idx) const {
        if (idx < 0 || idx >= size())
            return 0;
        return a[idx];
    }
    Poly mulxk(int k) const {
        auto b = a;
        b.insert(b.begin(), k, 0);
        return Poly(b);
    }
    Poly modxk(int k) const {

```

```

        k = std::min(k, size());
        return Poly(std::vector<int>(a.begin(), a.begin() + k));
    }
    Poly divxk(int k) const {
        if (size() <= k)
            return Poly();
        return Poly(std::vector<int>(a.begin() + k, a.end()));
    }
    friend Poly operator+(const Poly a, const Poly &b) {
        std::vector<int> res(std::max(a.size(), b.size()));
        for (int i = 0; i < int(res.size()); ++i) {
            res[i] = a[i] + b[i];
            if (res[i] >= P)
                res[i] -= P;
        }
        return Poly(res);
    }
    friend Poly operator-(const Poly a, const Poly &b) {
        std::vector<int> res(std::max(a.size(), b.size()));
        for (int i = 0; i < int(res.size()); ++i) {
            res[i] = a[i] - b[i];
            if (res[i] < 0)
                res[i] += P;
        }
        return Poly(res);
    }
    friend Poly operator*(Poly a, Poly b) {
        int sz = 1, tot = a.size() + b.size() - 1;
        while (sz < tot)
            sz *= 2;
        a.a.resize(sz);
        b.a.resize(sz);
        dft(a.a);
        dft(b.a);
        for (int i = 0; i < sz; ++i)
            a.a[i] = 1ll * a[i] * b[i] % P;
        idft(a.a);
        return Poly(a.a);
    }
    Poly &operator+=(Poly b) {
        return (*this) = (*this) + b;
    }
    Poly &operator-=(Poly b) {
        return (*this) = (*this) - b;
    }
    Poly &operator*=(Poly b) {
        return (*this) = (*this) * b;
    }
    Poly deriv() const {
        if (a.empty())
            return Poly();
        std::vector<int> res(size() - 1);
        for (int i = 0; i < size() - 1; ++i)
            res[i] = 1ll * (i + 1) * a[i + 1] % P;
        return Poly(res);
    }
    Poly integr() const {
        if (a.empty())
            return Poly();
        std::vector<int> res(size() + 1);
        for (int i = 0; i < size(); ++i)
            res[i + 1] = 1ll * a[i] * power(i + 1, P - 2) % P;
        return Poly(res);
    }
    Poly inv(int m) const {
        Poly x(power(a[0], P - 2));
        int k = 1;
        while (k < m) {
            k *= 2;

```

```

        x = (x * (2 - modxx(k) * x)).modxx(k);
    }
    return x.modxx(m);
}
Poly log(int m) const {
    return (deriv() * inv(m)).integr().modxx(m);
}
Poly exp(int m) const {
    Poly x(1);
    int k = 1;
    while (k < m) {
        k *= 2;
        x = (x * (1 - x.log(k) + modxx(k))).modxx(k);
    }
    return x.modxx(m);
}
Poly sqrt(int m) const {
    Poly x(1);
    int k = 1;
    while (k < m) {
        k *= 2;
        x = (x + (modxx(k) * x.inv(k)).modxx(k)) * ((P + 1) / 2);
    }
    return x.modxx(m);
}
Poly mult(Poly b) const {
    if (b.size() == 0)
        return Poly();
    int n = b.size();
    std::reverse(b.a.begin(), b.a.end());
    return ((*this) * b).divxx(n - 1);
}
std::vector<int> eval(std::vector<int> x) const {
    if (size() == 0)
        return std::vector<int>(x.size(), 0);
    const int n = std::max(int(x.size()), size());
    std::vector<Poly> q(4 * n);
    std::vector<int> ans(x.size());
    x.resize(n);
    std::function<void(int, int, int)> build = [&](int p, int l, int r) {
        if (r - l == 1) {
            q[p] = std::vector<int>{1, (P - x[l]) % P};
        } else {
            int m = (l + r) / 2;
            build(2 * p, l, m);
            build(2 * p + 1, m, r);
            q[p] = q[2 * p] * q[2 * p + 1];
        }
    };
    build(1, 0, n);
    std::function<void(int, int, int, const Poly &)> work = [&](int p,
        int l, int r, const Poly &num) {
        if (r - l == 1) {
            if (l < int(ans.size()))
                ans[l] = num[0];
        } else {
            int m = (l + r) / 2;
            work(2 * p, l, m, num.mult(q[2 * p + 1]).modxx(m - 1));
            work(2 * p + 1, m, r, num.mult(q[2 * p]).modxx(r - m));
        }
    };
    work(1, 0, n, mult(q[1].inv(n)));
    return ans;
}
};
};

```

3.11 Sieve

```

#include <vector>
namespace Sieve {
    vector<int> primes;
    vector<int> mn_factor;
    void get_primes(int N) {
        mn_factor.resize(N+1);
        for (int i = 2; i <= N; ++i) {
            if (mn_factor[i]==0) {
                primes.push_back(i);
                mn_factor[i]=i;
            }
            for (auto p : primes) {
                if ((long long)i * p > N) break;
                mn_factor[i * p] = p;
                if (i % p == 0) break;
            }
        }
    }
    bool is_prime(int n) {
        return mn_factor[n]==0;
    }
    vector<pair<int, int>> factor(int n) {
        vector<pair<int, int>> factors;
        while (n > 1) {
            int fac=mn_factor[n], cnt=0;
            while (n%fac==0) {
                cnt++;
                n/=fac;
            }
            factors.emplace_back(fac, cnt);
        }
        return factors;
    };
    vector<int> phi;
    void get_euler(int n) {
        phi.resize(n+1);
        phi[1] = 1;
        for (int i = 2; i <= n; i++) {
            if (phi[i]) continue;
            for (int j = i; j <= n; j += i) {
                if (!phi[j]) phi[j] = j;
                phi[j] = phi[j] / i * (i - 1);
            }
        }
    }
}
using namespace Sieve;

```

3.12 Simplex

```

/**
 * Author: Stanford
 * Source: Stanford Notebook
 * License: MIT
 * Description: Solves a general linear maximization problem: maximize $c^T x$ subject to $Ax \le b$, $x \ge 0$.
 * Returns -inf if there is no solution, inf if there are arbitrarily good solutions, or the maximum value of $c^T x$ otherwise.
 * The input vector is set to an optimal $x$ (or in the unbounded case, an arbitrary solution fulfilling the constraints).
 * Numerical stability is not guaranteed. For better performance, define variables such that $x = 0$ is viable.
 * Usage:
 * vvd A = {{1,-1}, {-1,1}, {-1,-2}};
 * vd b = {1,1,-4}, c = {-1,-1}, x;
 * T val = LPSolver(A, b, c).solve(x);
 * Time: $O(NM * \#\text{pivots})$, where a pivot may be e.g. an edge relaxation. $O(2^n)$ in the general case.
 */

```

```

    * Status: seems to work?
    */
#pragma once

typedef double T; // long double, Rational, double + mod<P>...
typedef vector<T> vd;
typedef vector<vd> vvd;

const T eps = 1e-8, inf = 1/.0;
#define MP make_pair
#define ltj(X) if(s == -1 || MP(X[j],N[j]) < MP(X[s],N[s])) s=j

struct LPSolver {
    int m, n;
    vi N, B;
    vvd D;

    LPSolver(const vvd& A, const vd& b, const vd& c) :
        m(sz(b)), n(sz(c)), N(n+1), B(m), D(m+2, vd(n+2)) {
        FOR(i,0,m) FOR(j,0,n) D[i][j] = A[i][j];
        FOR(i,0,m) { B[i] = n+i; D[i][n] = -1; D[i][n+1] =
            b[i]; }
        FOR(j,0,n) { N[j] = j; D[m][j] = -c[j]; }
        N[n] = -1; D[m+1][n] = 1;
    }

    void pivot(int r, int s) {
        T *a = D[r].data(), inv = 1 / a[s];
        FOR(i,0,m+2) if (i != r && abs(D[i][s]) > eps) {
            T *b = D[i].data(), inv2 = b[s] * inv;
            FOR(j,0,n+2) b[j] -= a[j] * inv2;
            b[s] = a[s] * inv2;
        }
        FOR(j,0,n+2) if (j != s) D[r][j] *= inv;
        FOR(i,0,m+2) if (i != r) D[i][s] *= -inv;
        D[r][s] = inv;
        swap(B[r], N[s]);
    }

    bool simplex(int phase) {
        int x = m + phase - 1;
        for (;;) {
            int s = -1;
            FOR(j,0,n+1) if (N[j] != -phase) ltj(D[x]);
            if (D[x][s] >= -eps) return true;
            int r = -1;
            FOR(i,0,m) {
                if (D[i][s] <= eps) continue;
                if (r == -1 || MP(D[i][n+1] / D[i][s], B[i]
                    ) < MP(D[r][n+1] / D[r][s], B[r]
                    )) r = i;
            }
            if (r == -1) return false;
            pivot(r, s);
        }
    }

    T solve(vd &x) {
        int r = 0;
        FOR(i,1,m) if (D[i][n+1] < D[r][n+1]) r = i;
        if (D[r][n+1] < -eps) {
            pivot(r, n);
            if (!simplex(2) || D[m+1][n+1] < -eps) return -inf;
        }
        FOR(i,0,m) if (B[i] == -1) {
            int s = 0;
            FOR(j,1,n+1) ltj(D[i]);
        }
    }
}

```

```

        pivot(i, s);
    }
}

bool ok = simplex(1); x = vd(n);
FOR(i,0,m) if (B[i] < n) x[B[i]] = D[i][n+1];
return ok ? D[m][n+1] : inf;
};

```

4 String

4.1 Aho-Corasick Automaton

```

/** Modified from:
 * https://github.com/kth-competitive-programming/kactl/blob/master/
 * content/strings/AhoCorasick.h
 * Try to handle duplicated patterns beforehand, otherwise change 'end'
 * to
 * vector; empty patterns are not allowed. Time: construction takes $O(26N)$,
 * where $N$ = sum of length of patterns. find(x) is $O(N)$, where $N$ =
 * length of
 * x. findAll is $O(N+M)$ where $M$ is number of occurrence of all pattern (
 * up to $N\sqrt{N}$) */
struct AhoCorasick {
    enum { alpha = 26, first = 'a' }; // change this!
    struct Node {
        // back: failure link, points to longest suffix that is in the
        // trie.
        // end: longest pattern that ends here, is -1 if no patten ends
        // here.
        // nmatches: number of (patterns that is a suffix of current
        // node)/(duplicated patterns), depends on needs.
        // output: output link, points to the longest pattern that is a
        // suffix
        // of current node
        int back, end = -1, nmatches = 0, output = -1;
        array<int, alpha> next;
        Node(int v = -1) { fill(next.begin(), next.end(), v); }
    };
    vector<Node> N;
    AhoCorasick() : N(1) {}
    void insert(string &s, int j) { // j: id of string s
        assert(!s.empty());
        int n = 0;
        for (char c : s) {
            int &m = N[n].next[c - first];
            if (m == -1) {
                m = (int)N.size();
                N.emplace_back();
            }
            n = m;
        }
        N[n].end = j;
        N[n].nmatches++;
    }

    void build() {
        N[0].back = (int)N.size();
        N.emplace_back(0);
        queue<int> q;
        q.push(0);
        while (!q.empty()) {
            int n = q.front();
            q.pop();
            for (int i = 0; i < alpha; i++) {

```



```

int pnx = N[N[n].back].next[i];
auto &nxt = N[N[n].next[i]];
if (N[n].next[i] == -1) N[n].next[i] = pnx;
else {
    nxt.back = pnx;
    // if prev is an end node, then set output to prev
    // node,
    // otherwise set to output link of prev node
    nxt.output = N[pnx].end == -1 ? N[pnx].output : pnx;
    // if we don't want to distinguish info of patterns
    // that is
    // a suffix of current node, we can add info to the
    // next
    // node like this: nxt.nmatches+=N[pnx].nmatches;
    q.push(N[n].next[i]);
}
}
}
// for each position, finds the longest pattern that ends here
vector<int> find(const string &text) {
    int len = (int)text.size();
    vector<int> res(len);
    int n = 0;
    for (int i = 0; i < len; i++) {
        n = N[n].next[text[i] - first];
        res[i] = N[n].end;
    }
    return res;
}
// for each position, finds the all that ends here
vector<vector<int>> find_all(const string &text) {
    int len = (int)text.size();
    vector<vector<int>> res(len);
    int n = 0;
    for (int i = 0; i < len; i++) {
        n = N[n].next[text[i] - first];
        res[i].push_back(N[n].end);
        for (int ind = N[n].output; ind != -1; ind = N[ind].output) {
            assert(N[ind].end != -1);
            res[i].push_back(N[ind].end);
        }
    }
    return res;
}
};

```

4.2 KMP

```

vector<int> prefix_function(const string& s) {
    int n = (int)s.length();
    vector<int> pi(n);
    for (int i = 1; i < n; i++) {
        int j = pi[i - 1];
        while (j > 0 && s[i] != s[j]) j = pi[j - 1];
        if (s[i] == s[j]) j++;
        pi[i] = j;
    }
    return pi;
}

```

4.3 Manacher

```

vector<int> manacher(const string& ss) {
    string s;
    for(auto ch:ss) s+="#",s+=ch;
    s+="#";
}

```

```

int n=(int)s.size();
vector<int> dl(n);
for (int i = 0, l = 0, r = -1; i < n; i++) {
    int k = (i > r) ? 1 : min(dl[l + r - i], r - i);
    while (0 <= i - k && i + k < n && s[i - k] == s[i + k]) k++;
    dl[i] = k--;
    if (i + k > r) l = i - k, r = i + k;
}
return dl;
}

```

4.4 Polynomial Hashing

```

#include<bits/stdc++.h>
using ll = long long;
struct PolyHash {
    static constexpr int mod = (int)1e9 + 123;
    static vector<int> pow;
    static constexpr int base = 233;
    vector<int> pref;
    PolyHash(const string &s) : pref(s.size() + 1) {
        assert(base < mod);
        int n = (int)s.size();
        while ((int)pow.size() <= n) {
            pow.push_back((ll)pow.back() * base % mod);
        }
        for (int i = 0; i < n; i++) {
            pref[i + 1] = ((ll)pref[i] * base + s[i]) % mod;
        }
    }
    int get_hash() {
        return pref.back();
    }
    int substr(int pos, int len) {
        return (pref[pos + len] - (ll)pref[pos] * pow[len] % mod + mod) %
            mod;
    }
};
vector<int> PolyHash::pow{1};

```

4.5 Suffix Array

```

#include<bits/stdc++.h>
//O(n log(n)), actually calculates cyclic shifts
vector<int> suffix_array(string s) {
    s+="#";
    int n = (int)s.size(), N = n + 256;
    vector<int> sa(n), ra(n);
    for(int i = 0; i < n; i++) sa[i] = i, ra[i] = s[i];
    for(int k = 0; k < n; k ? k *= 2 : k++) {
        vector<int> nsa(sa), nra(n), cnt(N);
        for(int i = 0; i < n; i++) nsa[i] = (nsa[i] - k + n) % n;
        for(int i = 0; i < n; i++) cnt[ra[i]]++;
        for(int i = 1; i < N; i++) cnt[i] += cnt[i - 1];
        for(int i = n - 1; i >= 0; i--) sa[--cnt[ra[nsa[i]]]] = nsa[i];

        int r = 0;
        for(int i = 1; i < n; i++) {
            if(ra[sa[i]] != ra[sa[i - 1]]) r++;
            else if(ra[(sa[i] + k) % n] != ra[(sa[i - 1] + k) % n]) r++;
            nra[sa[i]] = r;
        }
        ra = nra;
    }
    sa.erase(sa.begin());
    return sa;
}

```

```
vector<int> build_lcp(const string& s, const vector<int>& sa) { // lcp of
    suffix[i] ans suffix[i-1]
    int n=s.size();
    vector<int> pos(n);
    for (int i = 0; i < n; i++) pos[sa[i]] = i;
    vector<int> lcp(n);
    for (int i = 0, k = 0; i < n; i++) {
        if (pos[i] == 0) continue;
        if (k) k--;
        while (s[i+k] == s[sa[pos[i]-1]+k]) k++;
        lcp[pos[i]] = k;
    }
    return lcp;
}
```

4.6 Suffix Automaton

```
// source: https://cp-algorithms.com/string/suffix-automaton.html
struct SAM {
    struct state {
        int len = 0, link = -1;
        unordered_map<char, int> next;
    };
    int last = 0; // the index of the equivalence class of the whole
    string
    vector<state> st;
    void extend(char c) {
        int cur = (int)st.size();
        st.emplace_back();
        st[cur].len = st[last].len + 1;
        int p = last;
        while (p != -1 && !st[p].next.count(c)) {
            st[p].next[c] = cur;
            p = st[p].link;
        }
        if (p == -1) st[cur].link = 0;
        else {
            int q = st[p].next[c];
            if (st[p].len + 1 == st[q].len) {
                st[cur].link = q;
            } else {
                int clone = (int)st.size();
                st.push_back(st[q]);
                st[clone].len = st[p].len + 1;
                while (p != -1 && st[p].next[c] == q) {
                    st[p].next[c] = clone;
                    p = st[p].link;
                }
                st[q].link = st[cur].link = clone;
            }
        }
        last = cur;
    }
    SAM() { st.emplace_back(); }
    SAM(const string &s) : SAM() {
        for (auto c : s)
            extend(c);
    }
};
```

4.7 Trie

```
template<typename T>
struct Trie {
    vector<map<T, int>> child;
    vector<bool> is_leaf;
    Trie() { new_node(); }
```

```
int new_node() {
    child.emplace_back();
    is_leaf.emplace_back();
    return child.size()-1;
}
template<typename S> void insert(const S& s) {
    int p=0;
    for (auto ch : s) {
        if (!child[p].count(ch)) {
            child[p][ch]=new_node();
        }
        p=child[p][ch];
    }
    is_leaf[p]=true;
}
template<typename S> bool find(const S& s) {
    int p=0;
    for (auto ch : s) {
        if (!child[p].count(ch)) return false;
        p=child[p][ch];
    }
    return is_leaf[p];
};
```

4.8 Z-function

```
// In other words, z[i] is the length of the longest common prefix between
s and the suffix of s starting at i.
vector<int> z_function(const string& s) {
    int n = (int)s.size();
    vector<int> z(n);
    for (int i = 1, l = 0, r = 0; i < n; ++i) {
        if (i <= r) z[i] = min(r - i + 1, z[i - l]);
        while (i + z[i] < n && s[z[i]] == s[i + z[i]]) ++z[i];
        if (i + z[i] - 1 > r) l = i, r = i + z[i] - 1;
    }
    return z;
}
```

5 Geometry

5.1 Angle

```
double DEG_to_RAD(double d) { return d*M_PI/180.0; }
double RAD_to_DEG(double r) { return r*180.0/M_PI; }
double rad(P p1,P p2){
    return atan2l(p1.det(p2),p1.dot(p2));
}
bool inAngle(P a, P b, P c, P p) {
    assert(crossOp(a,b,c) != 0);
    if (crossOp(a,b,c) < 0) swap(b,c);
    return crossOp(a,b,p) >= 0 && crossOp(a,c,p) <= 0;
}
double angle(P v, P w) {
    return acos(clamp(v.dot(w) / v.abs() / w.abs(), -1.0, 1.0));
}
double orientedAngle(P a, P b, P c) { // BAC
    if (crossOp(a,b,c) >= 0) return angle(b-a, c-a);
    else return 2*M_PI - angle(b-a, c-a);
}
```

5.2 Circle

```

// double chord(double r, double ang) return sqrt(2*r*r*(1-cos(ang))); //
// or 2*r*sin(ang/2)
// double secarea(double r, double ang) {return (ang/2)*(r*r);} // rad
// double segarea(double r, double ang) {return secarea(r, ang) - r*r*sin(
ang)/2;}
int type(P o1,double r1,P o2,double r2){
    double d = o1.distTo(o2);
    if(cmp(d,r1+r2) == 1) return 4; // outside each other
    if(cmp(d,r1+r2) == 0) return 3; // touch outside
    if(cmp(d,abs(r1-r2)) == 1) return 2; // one inside another
    if(cmp(d,abs(r1-r2)) == 0) return 1; // touch inside
    return 0;
}
vector<P> isCL(P o,double r,P p1,P p2){
    if (cmp(abs((o-p1).det(p2-p1)/p1.distTo(p2)),r)>0) return {};
    double x = (p1-o).dot(p2-p1), y = (p2-p1).abs2(), d = x * x - y *
((p1-o).abs2() - r*r);
    d = max(d,0.0); P m = p1 - (p2-p1)*(x/y), dr = (p2-p1)*(sqrt(d)/y)
;
    return {m-dr,m+dr}; //along dir: p1->p2
}
vector<P> isCC(P o1, double r1, P o2, double r2) { //need to check whether
two circles are the same
    double d = o1.distTo(o2);
    if (cmp(d, r1 + r2) == 1) return {};
    if (cmp(d,abs(r1-r2))==-1) return {};
    d = min(d, r1 + r2);
    double y = (r1 * r1 + d * d - r2 * r2) / (2 * d), x = sqrt(r1 * r1
- y * y);
    P dr = (o2 - o1).unit();
    P q1 = o1 + dr * y, q2 = dr.rot90() * x;
    return {q1-q2,q1+q2}; //along circle 1
}
vector<P> tanCP(P o, double r, P p) {
    double x = (p - o).abs2(), d = x - r * r;
    if (sign(d) <= 0) return {}; // on circle => no tangent
    P q1 = o + (p - o) * (r * r / x);
    P q2 = (p - o).rot90() * (r * sqrt(d) / x);
    return {q1-q2,q1+q2}; //counter clock-wise
}
vector<L> extanCC(P o1, double r1, P o2, double r2) {
    vector<L> ret;
    if (cmp(r1, r2) == 0) {
        P dr = (o2 - o1).unit().rot90() * r1;
        ret.push_back(L(o1 + dr, o2 + dr)), ret.push_back(L(o1 -
dr, o2 - dr));
    } else {
        P p = (o2 * r1 - o1 * r2) / (r1 - r2);
        vector<P> ps = tanCP(o1, r1, p), qs = tanCP(o2, r2, p);
        for(int i = 0; i < min(ps.size(),qs.size());i++) ret.
push_back(L(ps[i], qs[i])); //c1 counter-clock wise
    }
    return ret;
}
vector<L> intanCC(P o1, double r1, P o2, double r2) {
    vector<L> ret;
    P p = (o1 * r2 + o2 * r1) / (r1 + r2);
    vector<P> ps = tanCP(o1,r1,p), qs = tanCP(o2,r2,p);
    for(int i = 0; i < min(ps.size(),qs.size()); i++) ret.push_back(L(
ps[i], qs[i])); //c1 counter-clock wise
    return ret;
}
double areaCT(double r, P p1, P p2){
    vector<P> is = isCL(P(0,0),r,p1,p2);
    if(is.empty()) return r*r*rad(p1,p2)/2;
    bool b1 = cmp(p1.abs2(),r*r) == 1, b2 = cmp(p2.abs2(), r*r) == 1;
    if(b1 && b2){
        if(sign((p1-is[0]).dot(p2-is[0])) <= 0 &&
sign((p1-is[0]).dot(p2-is[0])) <= 0)

```

```

return r*r*(rad(p1,is[0]) + rad(is[1],p2))/2 + is[0].det(
is[1])/2;
else return r*r*rad(p1,p2)/2;
    }
    if(b1) return (r*r*rad(p1,is[0]) + is[0].det(p2))/2;
    if(b2) return (p1.det(is[1]) + r*r*rad(is[1],p2))/2;
    return p1.det(p2)/2;
}
P inCenter(P A, P B, P C) {
    double a = (B - C).abs(), b = (C - A).abs(), c = (A - B).abs();
    return (A * a + B * b + C * c) / (a + b + c);
}
P circumCenter(P a, P b, P c) {
    P bb = b - a, cc = c - a;
    double db = bb.abs2(), dc = cc.abs2(), d = 2 * bb.det(cc);
    return a - P(bb.y * dc - cc.y * db, cc.x * db - bb.x * dc) / d;
}
P othroCenter(P a, P b, P c) {
    P ba = b - a, ca = c - a, bc = b - c;
    double Y = ba.y * ca.y * bc.y,
A = ca.x * ba.y - ba.x * ca.y,
x0 = (Y + ca.x * ba.y * b.x - ba.x * ca.y * c.x) / A,
y0 = -ba.x * (x0 - c.x) / ba.y + ca.y;
    return {x0, y0};
}
}

```

5.3 Geometry

```

typedef double T;
const double EPS = 1e-9;
inline int sign(double a) { return a < -EPS ? -1 : a > EPS; }
inline int cmp(double a, double b){ return sign(a-b); }
struct P {
    T x,y;
    P() {}
    P(T _x, T _y) : x(_x), y(_y) {}
    P operator+(P p) {return {x+p.x, y+p.y};}
    P operator-(P p) {return {x-p.x, y-p.y};}
    P operator*(T d) {return {x*d, y*d};}
    P operator/(T d) {return {x/d, y/d};} // only for floatingpoint
    bool operator<(P p) const {
        int c = cmp(x, p.x);
        if (c) return c == -1;
        return cmp(y, p.y) == -1;
    }
    bool operator==(P o) const{
        return cmp(x,o.x) == 0 && cmp(y,o.y) == 0;
    }
    double dot(P p) { return x * p.x + y * p.y; }
    double det(P p) { return x * p.y - y * p.x; }
    double distTo(P p) { return (*this-p).abs(); }
    double alpha() { return atan2(y, x); }
    void read() { cin>>x>>y; }
    void write() { cout<<"("<<x<<","<<y<<")"<<endl; }
    double abs() { return sqrt(abs2());}
    double abs2() { return x * x + y * y; }
    P rot90() { return P(-y,x);}
    P unit() { return *this/abs(); }
    int quad() const { return sign(y) == 1 || (sign(y) == 0 && sign(x) >= 0)
; }
    P rot(double an){ return {x*cos(an)-y*sin(an),x*sin(an) + y*cos(an)
}); }
};
#define cross(p1,p2,p3) ((p2.x-p1.x)*(p3.y-p1.y)-(p3.x-p1.x)*(p2.y-p1.y))
#define crossOp(p1,p2,p3) sign(cross(p1,p2,p3))
bool isConvex(vector<P> p) {
    bool hasPos=false, hasNeg=false;
    for (int i=0, n=p.size(); i<n; i++) {

```

```

    int o = cross(p[i], p[(i+1)%n], p[(i+2)%n]);
    if (o > 0) hasPos = true;
    if (o < 0) hasNeg = true;
}
return !(hasPos && hasNeg);
}
bool half(P p) {
    assert(p.x != 0 || p.y != 0); // (0, 0) is not covered
    return p.y > 0 || (p.y == 0 && p.x < 0);
}
void polarSortAround(P o, vector<P> &v) {
    sort(v.begin(), v.end(), [&o](P v, P w) {
        return make_tuple(half(v-o), 0) <
            make_tuple(half(w-o), cross(o, v, w));
    });
}
P proj(P p1, P p2, P q) {
    P dir = p2 - p1;
    return p1 + dir * (dir.dot(q - p1) / dir.abs2());
}
P reflect(P p1, P p2, P q) {
    return proj(p1, p2, q) * 2 - q;
}
// tested with https://open.kattis.com/problems/closestpair2
pair<P, P> closest(vector<P> v) {
    assert(sz(v) > 1);
    set<P> S;
    sort(v.begin(), v.end(), [](P a, P b) { return a.y < b.y; });
    pair<T, pair<P, P>> ret{{T}1e18, {P(), P()}};
    int j = 0;
    for(P p : v) {
        P d { 1 + (T) sqrt(ret.first), 0 };
        while(p.y - v[j].y >= d.x) S.erase(v[j++]);
        auto lo = S.lower_bound(p - d), hi = S.upper_bound(p + d);
        for(; lo != hi; ++lo) {
            ret = min(ret, {(p - (*lo)).abs2(), {*lo, p}});
        }
        S.insert(p);
    }
    return ret.second;
}
struct L {
    P ps[2]; P v; T c;
    L() {}
    P& operator[](int i) { return ps[i]; }
    // From direction vector v and offset c
    L(P v, T c) : v(v), c(c) {}
    // From equation ax+by=c
    L(T a, T b, T c) : v({b,-a}), c(c) {}
    // From points P and Q
    L(P p, P q) : v(q-p), c(cross(P(0, 0), v,p)) {
        ps[0] = p;
        ps[1] = q;
    }
    P dir() { return ps[1] - ps[0]; }
    bool include(P p) { return sign((ps[1] - ps[0]).det(p - ps[0])) > 0; }
    T side(P p) { return cross(P(0, 0), v,p)-c; }
    T dist(P p) { return abs(side(p)) / v.abs(); }
    T sqDist(P p) { return side(p)*side(p) / ((double)v.abs()); }
    L perpThrough(P p) { return L(p, p + v.rot90()); }
    bool cmpProj(P p, P q) {
        return v.dot(p) < v.dot(q);
    }
    L translate(P t) { return L(v, c + cross(P(0,0), v,t)); }
    L shiftLeft(double dist) { return L(v, c + dist*v.abs()); }
    L shiftRight(double dist) { return L(v, c - dist*v.abs()); }
};
bool chkLL(P p1, P p2, P q1, P q2) {

```

```

    double a1 = cross(q1, q2, p1), a2 = -cross(q1, q2, p2);
    return sign(a1+a2) != 0;
}
P isLL(P p1, P p2, P q1, P q2) {
    double a1 = cross(q1, q2, p1), a2 = -cross(q1, q2, p2);
    return (p1 * a2 + p2 * a1) / (a1 + a2);
}
P isLL(L l1, L l2) { return isLL(l1[0], l1[1], l2[0], l2[1]); }
bool parallel(L l0, L l1) { return sign( l0.dir().det( l1.dir() ) ) == 0; }
bool sameDir(L l0, L l1) { return parallel(l0, l1) && sign(l0.dir().dot(l1
.dir() ) ) == 1; }
bool cmp (P a, P b) {
    if (a.quad() != b.quad()) {
        return a.quad() < b.quad();
    } else {
        return sign( a.det(b) ) > 0;
    }
}
bool operator < (L l0, L l1) {
    if (sameDir(l0, l1)) {
        return l1.include(l0[0]);
    } else {
        return cmp( l0.dir(), l1.dir() );
    }
}
bool check(L u, L v, L w) {
    return w.include(isLL(u,v));
}
vector<P> halfPlaneIS(vector<L> &l) {
    sort(l.begin(), l.end());
    deque<L> q;
    for (int i = 0; i < (int)l.size(); ++i) {
        if (i && sameDir(l[i], l[i - 1])) continue;
        while (q.size() > 1 && !check(q[q.size() - 2], q[q.size()
- 1], l[i])) q.pop_back();
        while (q.size() > 1 && !check(q[q.size() - 1], q[0], l[i])) q.
pop_front();
        q.push_back(l[i]);
    }
    while (q.size() > 2 && !check(q[q.size() - 2], q[q.size() - 1], q
[0])) q.pop_back();
    while (q.size() > 2 && !check(q[q.size() - 1], q[0], q[q.size() - 1])) q.
pop_front();
    vector<P> ret;
    for (int i = 0; i < (int)q.size(); ++i) ret.push_back(isLL(q[i], q
[(i + 1) % q.size()]));
    return ret;
}
struct cmpX {
    bool operator() (P a, P b) const {
        return make_pair(a.x, a.y) < make_pair(b.x, b.y);
    }
};
bool intersect(double l1, double r1, double l2, double r2) {
    if (l1 > r1) swap(l1, r1); if (l2 > r2) swap(l2, r2);
    return !( cmp(r1, l2) == -1 || cmp(r2, l1) == -1 );
}
bool isSS(P p1, P p2, P q1, P q2) {
    return intersect(p1.x, p2.x, q1.x, q2.x) && intersect(p1.y, p2.y, q1.y,
q2.y) &&
        crossOp(p1, p2, q1) * crossOp(p1, p2, q2) <= 0 && crossOp(q1, q2, p1)
* crossOp(q1, q2, p2) <= 0;
}
bool isSS_strict(P p1, P p2, P q1, P q2) {
    return crossOp(p1, p2, q1) * crossOp(p1, p2, q2) < 0 && crossOp(q1, q2,
p1)
        * crossOp(q1, q2, p2) < 0;
}

```

```

bool isMiddle(double a, double m, double b) {
    return sign(a - m) == 0 || sign(b - m) == 0 || (a < m != b < m);
}
bool isMiddle(P a, P m, P b) {
    return isMiddle(a.x, m.x, b.x) && isMiddle(a.y, m.y, b.y);
}
bool onSeg(P p1, P p2, P q) {
    return crossOp(p1,p2,q) == 0 && isMiddle(p1, q, p2);
}
bool onSeg_strict(P p1, P p2, P q) {
    return crossOp(p1,p2,q) == 0 && sign((q-p1).dot(p1-p2)) * sign((q-p2).dot(p1-p2)) < 0;
}
double nearest(P p1,P p2,P q){
    P h = proj(p1,p2,q);
    if(isMiddle(p1,h,p2))
        return q.distTo(h);
    return min(p1.distTo(q),p2.distTo(q));
}
double disSS(P p1, P p2, P q1, P q2){
    if(isSS(p1,p2,q1,q2)) return 0;
    return min(min(nearest(p1,p2,q1),nearest(p1,p2,q2)), min(nearest(q1,q2,p1),nearest(q1,q2,p2)));
}
double DEG_to_RAD(double d) { return d*M_PI/180.0; }
double RAD_to_DEG(double r) { return r*180.0/M_PI; }
double rad(P p1,P p2){
    return atan2l(p1.det(p2),p1.dot(p2));
}
bool inAngle(P a, P b, P c, P p) {
    assert(crossOp(a,b,c) != 0);
    if (crossOp(a,b,c) < 0) swap(b,c);
    return crossOp(a,b,p) >= 0 && crossOp(a,c,p) <= 0;
}
double angle(P v, P w) {
    return acos(clamp(v.dot(w) / v.abs() / w.abs(), -1.0, 1.0));
}
double orientedAngle(P a, P b, P c) { // BAC
    if (crossOp(a,b,c) >= 0) return angle(b-a, c-a);
    else return 2*M_PI - angle(b-a, c-a);
}
// double chord(double r, double ang) return sqrt(2*r*r*(1-cos(ang))); //
// or 2*r*sin(ang/2)
// double secarea(double r, double ang) {return (ang/2)*(r*r);} // rad
// double segarea(double r, double ang) {return secarea(r, ang) - r*r*sin(ang)/2;}
int type(P o1,double r1,P o2,double r2){
    double d = o1.distTo(o2);
    if(cmp(d,r1+r2) == 1) return 4; // outside each other
    if(cmp(d,r1+r2) == 0) return 3; // touch outside
    if(cmp(d,abs(r1-r2)) == 1) return 2; // one inside another
    if(cmp(d,abs(r1-r2)) == 0) return 1; // touch inside
    return 0;
}
vector<P> isCL(P o,double r,P p1,P p2){
    if (cmp(abs((o-p1).det(p2-p1)/p1.distTo(p2)),r)>0) return {};
    double x = (p1-o).dot(p2-p1), y = (p2-p1).abs2(), d = x * x - y * ((p1-o).abs2() - r*r);
    d = max(d,0.0); P m = p1 - (p2-p1)*(x/y), dr = (p2-p1)*(sqrt(d)/y);
    return {m-dr,m+dr}; //along dir: p1->p2
}
vector<P> isCC(P o1, double r1, P o2, double r2) { //need to check whether
two circles are the same
    double d = o1.distTo(o2);
    if (cmp(d, r1 + r2) == 1) return {};
    if (cmp(d,abs(r1-r2))==-1) return {};
    d = min(d, r1 + r2);
    double y = (r1 * r1 + d * d - r2 * r2) / (2 * d), x = sqrt(r1 * r1
- y * y);
    P dr = (o2 - o1).unit();
    P q1 = o1 + dr * y, q2 = dr.rot90() * x;
    return {q1-q2,q1+q2}; //along circle 1
}
vector<P> tanCP(P o, double r, P p) {
    double x = (p - o).abs2(), d = x - r * r;
    if (sign(d) <= 0) return {}; // on circle => no tangent
    P q1 = o + (p - o) * (r * r / x);
    P q2 = (p - o).rot90() * (r * sqrt(d) / x);
    return {q1-q2,q1+q2}; //counter clock-wise
}
vector<L> extanCC(P o1, double r1, P o2, double r2) {
    vector<L> ret;
    if (cmp(r1, r2) == 0) {
        P dr = (o2 - o1).unit().rot90() * r1;
        ret.push_back(L(o1 + dr, o2 + dr)), ret.push_back(L(o1 - dr, o2 - dr));
    } else {
        P p = (o2 * r1 - o1 * r2) / (r1 - r2);
        vector<P> ps = tanCP(o1, r1, p), qs = tanCP(o2, r2, p);
        for(int i = 0; i < min(ps.size(),qs.size());i++) ret.
            push_back(L(ps[i], qs[i])); //c1 counter-clock wise
    }
    return ret;
}
vector<L> intanCC(P o1, double r1, P o2, double r2) {
    vector<L> ret;
    P p = (o1 * r2 + o2 * r1) / (r1 + r2);
    vector<P> ps = tanCP(o1,r1,p), qs = tanCP(o2,r2,p);
    for(int i = 0; i < min(ps.size(),qs.size()); i++) ret.push_back(L(
        ps[i], qs[i])); //c1 counter-clock wise
    return ret;
}
double areaCT(double r, P p1, P p2){
    vector<P> is = isCL(P(0,0),r,p1,p2);
    if(is.empty()) return r*r*rad(p1,p2)/2;
    bool b1 = cmp(p1.abs2(),r*r) == 1, b2 = cmp(p2.abs2(), r*r) == 1;
    if(b1 && b2){
        if(sign((p1-is[0]).dot(p2-is[0])) <= 0 &&
            sign((p1-is[0]).dot(p2-is[0])) <= 0)
            return r*r*(rad(p1,is[0]) + rad(is[1],p2))/2 + is[0].det(
                is[1])/2;
        else return r*r*rad(p1,p2)/2;
    }
    if(b1) return (r*r*rad(p1,is[0]) + is[0].det(p2))/2;
    if(b2) return (p1.det(is[1]) + r*r*rad(is[1],p2))/2;
    return p1.det(p2)/2;
}
P inCenter(P A, P B, P C) {
    double a = (B - C).abs(), b = (C - A).abs(), c = (A - B).abs();
    return (A * a + B * b + C * c) / (a + b + c);
}
P circumCenter(P a, P b, P c) {
    P bb = b - a, cc = c - a;
    double db = bb.abs2(), dc = cc.abs2(), d = 2 * bb.det(cc);
    return a - P(bb.y * dc - cc.y * db, cc.x * db - bb.x * dc) / d;
}
P othroCenter(P a, P b, P c) {
    P ba = b - a, ca = c - a, bc = b - c;
    double Y = ba.y * ca.y * bc.y,
    A = ca.x * ba.y - ba.x * ca.y,
    x0 = (Y + ca.x * ba.y * b.x - ba.x * ca.y * c.x) / A,
    y0 = -ba.x * (x0 - c.x) / ba.y + ca.y;
    return {x0, y0};
}
//polygon
double area(vector<P> ps){
    double ret = 0;

```

5.4 Line

```

    for(int i=0; i< ps.size(); i++) ret += ps[i].det(ps[(i+1)%ps.size()]);
    return ret/2;
}

int contain(vector<P> ps, P p) { //2:inside,1:on_seg,0:outside
    int n = ps.size(), ret = 0;
    for(int i = 0; i < n; i++) {
        P u=ps[i],v=ps[(i+1)%n];
        if(onSeg(u,v,p)) return 1;
        if(cmp(u.y,v.y)<=0) swap(u,v);
        if(cmp(p.y,u.y) > 0 || cmp(p.y,v.y) <= 0) continue;
        ret ^= crossOp(p,u,v) > 0;
    }
    return ret*2;
}

vector<P> convexHull(vector<P> ps) {
    int n = ps.size(); if(n <= 1) return ps;
    sort(ps.begin(), ps.end());
    vector<P> qs(n * 2); int k = 0;
    for (int i = 0; i < n; qs[k++] = ps[i++])
        while (k > 1 && crossOp(qs[k - 2], qs[k - 1], ps[i]) <= 0)
            --k;
    for (int i = n - 2, t = k; i >= 0; qs[k++] = ps[i--])
        while (k > t && crossOp(qs[k - 2], qs[k - 1], ps[i]) <= 0)
            --k;
    qs.resize(k - 1);
    return qs;
}

vector<P> convexHullNonStrict(vector<P> ps) {
    //caution: need to unique the Ps first
    int n = ps.size(); if(n <= 1) return ps;
    sort(ps.begin(), ps.end());
    vector<P> qs(n * 2); int k = 0;
    for (int i = 0; i < n; qs[k++] = ps[i++])
        while (k > 1 && crossOp(qs[k - 2], qs[k - 1], ps[i]) < 0)
            --k;
    for (int i = n - 2, t = k; i >= 0; qs[k++] = ps[i--])
        while (k > t && crossOp(qs[k - 2], qs[k - 1], ps[i]) < 0)
            --k;
    qs.resize(k - 1);
    return qs;
}

double convexDiameter(vector<P> ps) {
    int n = ps.size(); if(n <= 1) return 0;
    int is = 0, js = 0; for(int k = 1; k < n; k++) is = ps[k]<ps[is]?k:is;
    int i = is, j = js;
    double ret = ps[i].distTo(ps[j]);
    do{
        if((ps[(i+1)%n]-ps[i]).det(ps[(j+1)%n]-ps[j]) >= 0)
            (++j)%=n;
        else
            (++i)%=n;
        ret = max(ret,ps[i].distTo(ps[j]));
    }while(i!=is || j!=js);
    return ret;
}

vector<P> convexCut(const vector<P>&ps, P q1, P q2) {
    vector<P> qs;
    int n = ps.size();
    for(int i = 0; i<n; i++) {
        P p1 = ps[i], p2 = ps[(i+1)%n];
        int d1 = crossOp(q1,q2,p1), d2 = crossOp(q1,q2,p2);
        if(d1 >= 0) qs.push_back(p1);
        if(d1 * d2 < 0) qs.push_back(isLL(p1,p2,q1,q2));
    }
    return qs;
}

```

```

struct L {
    P ps[2]; P v; T c;
    L() {}
    P& operator[](int i) { return ps[i]; }
    // From direction vector v and offset c
    L(P v, T c) : v(v), c(c) {}
    // From equation ax+by=c
    L(T a, T b, T c) : v((b,-a)), c(c) {}
    // From points P and Q
    L(P p, P q) : v(q-p), c(cross(P(0, 0), v,p)) {
        ps[0] = p;
        ps[1] = q;
    }
    P dir() { return ps[1] - ps[0]; }
    bool include(P p) { return sign((ps[1] - ps[0]).det(p - ps[0])) > 0; }
    T side(P p) {return cross(P(0, 0), v,p)-c;}
    T dist(P p) {return abs(side(p)) / v.abs();}
    T sqDist(P p) {return side(p)*side(p) / (double)v.abs();}
    L perpThrough(P p) {return L(p, p + v.rot90());}
    bool cmpProj(P p, P q) {
        return v.dot(p) < v.dot(q);
    }
    L translate(P t) {return L(v, c + cross(P(0,0), v,t));}
    L shiftLeft(double dist) {return L(v, c + dist*v.abs());}
    L shiftRight(double dist) {return L(v, c - dist*v.abs());}
};

bool chkLL(P p1, P p2, P q1, P q2) {
    double a1 = cross(q1, q2, p1), a2 = -cross(q1, q2, p2);
    return sign(a1+a2) != 0;
}

P isLL(P p1, P p2, P q1, P q2) {
    double a1 = cross(q1, q2, p1), a2 = -cross(q1, q2, p2);
    return (p1 * a2 + p2 * a1) / (a1 + a2);
}

P isLL(L l1, L l2) { return isLL(l1[0],l1[1],l2[0],l2[1]); }
bool parallel(L l0, L l1) { return sign( l0.dir().det( l1.dir() ) ) == 0; }
bool sameDir(L l0, L l1) { return parallel(l0, l1) && sign(l0.dir().dot(l1.dir() ) ) == 1; }
bool cmp (P a, P b) {
    if (a.quad() != b.quad()) {
        return a.quad() < b.quad();
    } else {
        return sign( a.det(b) ) > 0;
    }
}

bool operator < (L l0, L l1) {
    if (sameDir(l0, l1)) {
        return l1.include(l0[0]);
    } else {
        return cmp( l0.dir(), l1.dir() );
    }
}

bool check(L u, L v, L w) {
    return w.include(isLL(u,v));
}

vector<P> halfPlaneIS(vector<L> &l) {
    sort(l.begin(), l.end());
    deque<L> q;
    for (int i = 0; i < (int)l.size(); ++i) {
        if (i && sameDir(l[i], l[i - 1])) continue;
        while (q.size() > 1 && !check(q[q.size() - 2], q[q.size() - 1], l[i])) q.pop_back();
        while (q.size() > 1 && !check(q[1], q[0], l[i])) q.pop_front();
        q.push_back(l[i]);
    }
}

```

```

    }
    while (q.size() > 2 && !check(q[q.size() - 2], q[q.size() - 1], q
        [0])) q.pop_back();
    while (q.size() > 2 && !check(q[1], q[0], q[q.size() - 1])) q.
        pop_front();
    vector<P> ret;
    for (int i = 0; i < (int)q.size(); ++i) ret.push_back(isLL(q[i], q
        [(i + 1) % q.size()]));
    return ret;
}

```

5.5 Point

```

typedef double T;
const double EPS = 1e-9;
inline int sign(double a) { return a < -EPS ? -1 : a > EPS; }
inline int cmp(double a, double b) { return sign(a-b); }
struct P {
    T x, y;
    P() {}
    P(T _x, T _y) : x(_x), y(_y) {}
    P operator+(P p) { return {x+p.x, y+p.y}; }
    P operator-(P p) { return {x-p.x, y-p.y}; }
    P operator*(T d) { return {x*d, y*d}; }
    P operator/(T d) { return {x/d, y/d}; } // only for floatingpoint
    bool operator<(P p) const {
        int c = cmp(x, p.x);
        if (c) return c == -1;
        return cmp(y, p.y) == -1;
    }
    bool operator==(P o) const {
        return cmp(x, o.x) == 0 && cmp(y, o.y) == 0;
    }
    double dot(P p) { return x * p.x + y * p.y; }
    double det(P p) { return x * p.y - y * p.x; }
    double distTo(P p) { return (*this-p).abs(); }
    double alpha() { return atan2(y, x); }
    void read() { cin >> x >> y; }
    void write() { cout << "(" << x << ", " << y << ")" << endl; }
    double abs() { return sqrt(abs2()); }
    double abs2() { return x * x + y * y; }
    P rot90() { return P(-y, x); }
    P unit() { return *this/abs(); }
    int quad() const { return sign(y) == 1 || (sign(y) == 0 && sign(x) >= 0)
        ? 1 : 0; }
    P rot(double an) { return {x*cos(an)-y*sin(an), x*sin(an) + y*cos(an)
        }; }
};
#define cross(p1,p2,p3) ((p2.x-p1.x)*(p3.y-p1.y)-(p3.x-p1.x)*(p2.y-p1.y))
#define crossOp(p1,p2,p3) sign(cross(p1,p2,p3))
bool isConvex(vector<P> p) {
    bool hasPos=false, hasNeg=false;
    for (int i=0, n=p.size(); i<n; i++) {
        int o = cross(p[i], p[(i+1)%n], p[(i+2)%n]);
        if (o > 0) hasPos = true;
        if (o < 0) hasNeg = true;
    }
    return !(hasPos && hasNeg);
}
bool half(P p) {
    assert(p.x != 0 || p.y != 0); // (0, 0) is not covered
    return p.y > 0 || (p.y == 0 && p.x < 0);
}
void polarSortAround(P o, vector<P> &v) {
    sort(v.begin(), v.end(), [&o](P v, P w) {
        return make_tuple(half(v-o), 0) <
            make_tuple(half(w-o), cross(o, v, w));
    });
}

```

```

}
P proj(P p1, P p2, P q) {
    P dir = p2 - p1;
    return p1 + dir * (dir.dot(q - p1) / dir.abs2());
}
P reflect(P p1, P p2, P q) {
    return proj(p1, p2, q) * 2 - q;
}
// tested with https://open.kattis.com/problems/closestpair2
pair<P, P> closest(vector<P> v) {
    assert(sz(v) > 1);
    set<P> S;
    sort(v.begin(), v.end(), [](P a, P b) { return a.y < b.y; });
    pair<T, pair<P, P>> ret{(T)1e18, {P(), P()}};
    int j = 0;
    for(P p : v) {
        P d { 1 + (T) sqrt(ret.first), 0 };
        while(p.y - v[j].y >= d.x) S.erase(v[j++]);
        auto lo = S.lower_bound(p - d), hi = S.upper_bound(p + d);
        for(; lo != hi; ++lo) {
            ret = min(ret, {(p - (*lo)).abs2(), {*lo, p}});
        }
        S.insert(p);
    }
    return ret.second;
}

```

5.6 Polygon

```

//polygon
double area(vector<P> ps) {
    double ret = 0;
    for(int i=0; i< ps.size(); i++) ret += ps[i].det(ps[(i+1)%ps.size()]);
    return ret/2;
}
int contain(vector<P> ps, P p) { //2:inside,1:on_seg,0:outside
    int n = ps.size(), ret = 0;
    for(int i = 0; i < n; i++) {
        P u=ps[i], v=ps[(i+1)%n];
        if(onSeg(u,v,p)) return 1;
        if(cmp(u.y,v.y)<=0) swap(u,v);
        if(cmp(p.y,u.y) > 0 || cmp(p.y,v.y) <= 0) continue;
        ret ^= crossOp(p,u,v) > 0;
    }
    return ret*2;
}
vector<P> convexHull(vector<P> ps) {
    int n = ps.size(); if(n <= 1) return ps;
    sort(ps.begin(), ps.end());
    vector<P> qs(n * 2); int k = 0;
    for (int i = 0; i < n; qs[k++] = ps[i++])
        while (k > 1 && crossOp(qs[k - 2], qs[k - 1], ps[i]) <= 0)
            --k;
    for (int i = n - 2, t = k; i >= 0; qs[k++] = ps[i--])
        while (k > t && crossOp(qs[k - 2], qs[k - 1], ps[i]) <= 0)
            --k;
    qs.resize(k - 1);
    return qs;
}
vector<P> convexHullNonStrict(vector<P> ps) {
    //caution: need to unique the Ps first
    int n = ps.size(); if(n <= 1) return ps;
    sort(ps.begin(), ps.end());
    vector<P> qs(n * 2); int k = 0;
    for (int i = 0; i < n; qs[k++] = ps[i++])
        while (k > 1 && crossOp(qs[k - 2], qs[k - 1], ps[i]) < 0)
            --k;
    for (int i = n - 2, t = k; i >= 0; qs[k++] = ps[i--])

```



```

        while (k > t && crossOp(qs[k - 2], qs[k - 1], ps[i]) < 0)
            --k;
        qs.resize(k - 1);
        return qs;
    }
    double convexDiameter(vector<P> ps) {
        int n = ps.size(); if (n <= 1) return 0;
        int is = 0, js = 0; for (int k = 1; k < n; k++) is = ps[k]<ps[is]?k:is;
        :is, js = ps[js] < ps[k]?k:js;
        int i = is, j = js;
        double ret = ps[i].distTo(ps[j]);
        do {
            if ((ps[(i+1)%n]-ps[i]).det(ps[(j+1)%n]-ps[j]) >= 0)
                (++j)%=n;
            else
                (++i)%=n;
            ret = max(ret, ps[i].distTo(ps[j]));
        } while (i!=is || j!=js);
        return ret;
    }
    vector<P> convexCut(const vector<P>&ps, P q1, P q2) {
        vector<P> qs;
        int n = ps.size();
        for (int i = 0; i < n; i++) {
            P p1 = ps[i], p2 = ps[(i+1)%n];
            int d1 = crossOp(q1, q2, p1), d2 = crossOp(q1, q2, p2);
            if (d1 >= 0) qs.push_back(p1);
            if (d1 * d2 < 0) qs.push_back(isLL(p1, p2, q1, q2));
        }
        return qs;
    }
}

```

5.7 Segment

```

struct cmpX {
    bool operator() (P a, P b) const {
        return make_pair(a.x, a.y) < make_pair(b.x, b.y);
    }
};
bool intersect(double l1, double r1, double l2, double r2) {
    if (l1 > r1) swap(l1, r1); if (l2 > r2) swap(l2, r2);
    return !(cmp(r1, l2) == -1 || cmp(r2, l1) == -1);
}
bool isSS(P p1, P p2, P q1, P q2) {
    return intersect(p1.x, p2.x, q1.x, q2.x) && intersect(p1.y, p2.y, q1.y, q2.y) &&
        crossOp(p1, p2, q1) * crossOp(p1, p2, q2) <= 0 && crossOp(q1, q2, p1) *
            crossOp(q1, q2, p2) <= 0;
}
bool isSS_strict(P p1, P p2, P q1, P q2) {
    return crossOp(p1, p2, q1) * crossOp(p1, p2, q2) < 0 && crossOp(q1, q2, p1) *
        crossOp(q1, q2, p2) < 0;
}
bool isMiddle(double a, double m, double b) {
    return sign(a - m) == 0 || sign(b - m) == 0 || (a < m != b < m);
}
bool isMiddle(P a, P m, P b) {
    return isMiddle(a.x, m.x, b.x) && isMiddle(a.y, m.y, b.y);
}
bool onSeg(P p1, P p2, P q) {
    return crossOp(p1, p2, q) == 0 && isMiddle(p1, q, p2);
}
bool onSeg_strict(P p1, P p2, P q) {
    return crossOp(p1, p2, q) == 0 && sign((q-p1).dot(p1-p2)) * sign((q-p2).dot(p1-p2)) < 0;
}
double nearest(P p1, P p2, P q) {

```

```

        P h = proj(p1, p2, q);
        if (isMiddle(p1, h, p2))
            return q.distTo(h);
        return min(p1.distTo(q), p2.distTo(q));
    }
    double disSS(P p1, P p2, P q1, P q2) {
        if (isSS(p1, p2, q1, q2)) return 0;
        return min(min(nearest(p1, p2, q1), nearest(p1, p2, q2)), min(nearest(q1, q2, p1), nearest(q1, q2, p2)));
    }
}

```

6 Miscs

6.1

```

// Mo's algorithm, solve m offline queries on array of length n in O(n sqrt(m))
struct MO {
    int n, m=0;
    struct node {
        int l, r, id;
    };
    vector<node> query;
    MO(int _n) : n(_n) {}
    void add_query(int l, int r) {
        query.push_back({l, r, m++});
    }
    template<typename F>
    vector<int> solve(F&& move) {
        const int BLOCK_SIZE = (n <= m ? ceil(sqrt(n)) : n / ceil(sqrt(m)));
        sort(query.begin(), query.end(), [&](const node& lhs, const node& rhs) {
            if (lhs.l / BLOCK_SIZE != rhs.l / BLOCK_SIZE) return lhs.l < rhs.l;
            return ((lhs.l / BLOCK_SIZE) & 1) ? lhs.r < rhs.r : lhs.r > rhs.r;
        });
        vector<int> ans(m);
        int l=0, r=-1, cur=0;
        for (const auto& [q1, qr, id] : query) {
            while (l > q1) move(--l, 1, cur);
            while (r < qr) move(++r, 1, cur);
            while (l < q1) move(l++, -1, cur);
            while (r > qr) move(r--, -1, cur);
            ans[id]=cur;
        }
        return ans;
    }
};
// example: find the most occurrence in ranges
int main() {
    int n, q;
    MO mo(n);
    vector<int> a(n), counter(n+1), freq(3e5+1);
    auto ans=mo.solve([&](int i, int dir, int& cur) {
        int val=a[i];
        int c=freq[val];
        counter[c]--;
        if (dir==1) {
            freq[val]++;
            counter[freq[val]]++;
            cur=max(cur, freq[val]);
        } else {
            freq[val]--;
            counter[freq[val]]++;
        }
    });
}

```



```
        if (counter[cur]==0) cur--;  
    });  
}
```