

BSc (Hons) in **Computer Science****SE3062 : Intelligent Systems**

Year 3 · Semester 1 · 2026 Semester 2

**Faculty of Computing****Practical 01**

**Objective & Lecture Mapping:** Recall that an intelligent agent acts within a continuous loop: Sensors generate percept sequences, and Actuators execute actions to maximize a Performance measure. Use this sheet to execute practical modifications and incrementally evaluate your design against Lecture 01 and 02 theory (from basic recall to analytical classification).

**Part 1: Code Analysis & PEAS Evaluation****Task 0 : Setting up and getting the starter Code**

1. Go to the [Git Hub Repo](#). Create a Fork of this Git Repo to your Personal Github Profile. Open it using your favourite IDE and follow the below instruction to complete the practical. The base code is in the "master" brach of the repo.

**Task 1.1: The Environment State (\_\_init\_\_)**

1. (Remember) List the four components of the PEAS framework discussed in Lecture 01.

performance measure  
environment  
actuators

2. (Understand) Look at the `VisualGridHuntGame.__init__` method. Which specific variables in this code represent the physical "Environment (E)" state?

walls  
food position  
opponents

3. (Analyze) Based on the variables initialized (specifically `self.opponents` ), classify this baseline environment as "Single-Agent" or "Multi-Agent". Briefly justify your choice.

this is a multi agent environment , because it's a pacman style game the Opponent actions actively oppose the agent's goals .

### Task 1.2: The Perception Subsystem (`get_percept`)

4. (Remember) Define what a "percept sequence" is according to Lecture 01.

The absolute, cumulative historical log of every single percept the agent has received from its initialization up to the current moment.

5. (Understand) Which component of the PEAS framework does the `get_percept()` method represent in our code?

Sensor PEAS framework

6. (Evaluate) Based on the exact dictionary returned by `get_percept()` , is this environment "Fully Observable" or "Partially Observable"? Explain why based on what the agent can and cannot see.

Partially Observable  
agent can only observe Food and wall near their position

### Task 1.3: Action Execution (`execute_action`)

7. (Understand) When `execute_action()` deducts points for hitting a wall, which PEAS component is being actively updated?

Performance PEAS component

8. (Evaluate) Why is it structurally important that this metric evaluates changes in the external environment state (hitting a wall) rather than the agent's internal processing effort?

in this game agent always depends on their environment , making walls as a challenge will make easy to increase the performance

## Part 2: Guided Modification & Deep Theory Mapping

Follow the implementation instructions to inject a new hazard, then answer the questions to map your code changes back to the theoretical nature of the environment.

### Step 2.1: Extending the Environment Initialization (`__init__`)

1. **Implementation Instructions:** Declare a new trap collection attribute (e.g., `self.toxic_traps = set()`) inside `__init__`. Populate it with coordinate tuples safely avoiding position `(0, 0)`, walls, and food.

9. (Understand) If you successfully add `self.toxic_traps` to the environment but intentionally **hide** this data from the agent's sensors, how does this specifically alter the environment's "Observability" classification?

observability does not change , it's still a Partially Observable to the agent

### Step 2.2: Updating the Perception Subsystem (`get_percept`)

1. **Implementation Instructions:** Locate `get_percept(self)` and add a new boolean sensor key (e.g., `'smells_toxin': tuple(self.agent_pos) in self.toxic_traps`) to the dictionary returned to the agent loop.

10. (Analyze) By adding `'smells_toxin'`, you expand the agent's percept sequence. Explain how this specific sensor helps the agent act with "Rationality" (maximizing expected utility).

Adding `'smells_toxin'` gives the agent information about dangerous locations. This helps the agent act rationally by avoiding toxic traps and choosing safer paths while searching for food. With this extra percept, the agent can maximize its expected utility by reducing penalties and increasing its chances of achieving a higher score.

### Step 2.3: Modifying Action Execution & Visual Rendering (`execute_action` & `draw_grid`)

1. **Implementation Instructions:** In `execute_action`, check if the updated `self.agent_pos` intersects with `self.toxic_traps` to decrement `self.score` by 15 points. In `draw_grid`, iterate through traps to render custom purple shapes on the canvas.

11. (Remember) You programmed a severe score penalty for stepping on a trap to avoid metric exploitation. What was the classic "Vacuum World Exploit" example discussed in Lecture 01 that illustrated the danger of faulty metrics?

The classic Vacuum World exploit was when an agent maximized its score by cleaning the same square repeatedly instead of actually cleaning the whole environment, because the reward metric was poorly designed. It showed that faulty metrics can cause agents to exploit the scoring system rather than achieve the intended goal.

Finalize and Lock Lab 01 Analytical Evaluation

**Lab 01 code analysis and theoretical evaluation complete and verified!**

