

```

1: #include<stdio.h>
2: #include<string.h>
3: main()
4: {
5:     char note[33]={};
6:     int i,j,len,dat[13][27]={},sum=0,max=0;
7:     gets(note);
8:     len=strlen(note);
9:
10:    for (i=0;i<len;i++)
11:    {
12:        switch (note[i])
13:        {
14:            case '1':
15:                dat[1][note[i+1]-64]=1; break;
16:            case '2':
17:                dat[2][note[i+1]-64]=1; break;
18:            case '3':
19:                dat[3][note[i+1]-64]=1; break;
20:            case '4':
21:                dat[4][note[i+1]-64]=1; break;
22:            case '5':
23:                dat[5][note[i+1]-64]=1; break;
24:            case '6':
25:                dat[6][note[i+1]-64]=1; break;
26:            case '7':
27:                dat[7][note[i+1]-64]=1; break;
28:            case '8':
29:                dat[8][note[i+1]-64]=1; break;
30:            case '9':
31:                dat[9][note[i+1]-64]=1; break;
32:            case 'A':
33:                dat[10][note[i+1]-64]=1; break;
34:            case 'B':
35:                dat[11][note[i+1]-64]=1; break;
36:            case 'C':
37:                dat[12][note[i+1]-64]=1; break;
38:        }
39:        i++;

```

```
40:     }
41:     for(i=1;i<13;i++)
42:     {
43:         for(j=1;j<27;j++)
44:         {
45:             sum=sum+dat[i][j];
46:         }
47:         printf("%d\n",sum);
48:         if (sum>max) max=sum;
49:         sum=0;
50:     }
51:     printf("%d",max);
52: }
```