JConnect | Entity relationships

41 tables / 331 columns / 17 foreign keys

api_client_scopes api_client_id	→	**api_clients** id
api_request_counts api_client_id	→	**api_clients** id
api_request_logs api_client_id	→	**api_clients** id
device_maintenance created_by	→	**ia_users** ia_users_id
device_maintenance device_id	→	**devices** id
device_templates category_id	→	**device_categories** id
devices category_id	→	**device_categories** id
devices created_by	→	**ia_users** ia_users_id
devices device_template_id	→	**device_templates** id
devices site_node_id	→	**site_nodes** id
health_check_logs health_check_id	→	**health_checks** id
notification_channel_nodes channel_id	→	**notification_channels** id
report_executions template_id	→	**report_templates** id
report_export_files schedule_id	→	**report_schedules** id
report_favorites template_id	→	**report_templates** id
site_nodes parent_id	→	**site_nodes** id
user_site_scopes ia_users_id	→	**ia_users** ia_users_id

Table directory

All tables in public, including tables without declared foreign keys

alarm_log_dispatch	7 columns	**event_logs**	8 columns	**report_categories**	7 columns
alarm_logs	17 columns	**health_check_logs**	6 columns	**report_executions**	7 columns
alarm_state	12 columns	**health_checks**	13 columns	**report_export_files**	10 columns
api_client_scopes	2 columns	**ia_custom_fields**	9 columns	**report_favorites**	4 columns
api_clients	11 columns	**ia_custom_fields_values**	5 columns	**report_schedules**	15 columns
api_request_counts	4 columns	**ia_email_templates**	5 columns	**report_templates**	10 columns
api_request_logs	12 columns	**ia_menu**	8 columns	**schema_migrations**	2 columns
dashboard_layout_items	11 columns	**ia_permission**	3 columns	**site_nodes**	10 columns
dashboard_layouts	10 columns	**ia_plugins**	7 columns	**user_dashboard_homes**	3 columns
device_categories	8 columns	**ia_sessions**	4 columns	**user_site_scopes**	2 columns
device_data	8 columns	**ia_setting**	3 columns	**widgets**	6 columns
device_latest	7 columns	**ia_users**	13 columns		
device_maintenance	13 columns	**lorawan_applications**	6 columns		
device_templates	13 columns	**notification_channel_nodes**	2 columns		
devices	18 columns	**notification_channels**	10 columns		

Table definitions

PK Primary key FK Foreign key UQ Unique constraint NN Not null

alarm_log_dispatch

id	integer	NN
alarm_log_id	integer	NN
channel_id	integer	NN
status	character varying(20)	NN
error	text	
sent_at	timestamp without time zone	
created_at	timestamp without time zone	

alarm_logs

id	integer	NN
device_id	integer	NN
metric_key	text	NN
message	text	
severity	text	
channel	text	
status	text	
error	text	
sent_at	timestamp without time zone	
created_at	timestamp with time zone	
trigger_type	character varying(20)	
channels	text	
duration_minutes	integer	
trigger_id	text	
value	text	
snapshot_path	text	
snapshot_camera_device_id	text	

alarm_state

device_id	integer	PK NN
metric_key	text	PK NN
active	boolean	
last_triggered	timestamp with time zone	
last_cleared	timestamp with time zone	
message	text	
severity	text	
acknowledged	boolean	
acknowledged_by	text	
acknowledged_at	timestamp without time zone	
acknowledge_note	text	
trigger_id	text	PK NN

api_client_scopes

api_client_id	integer	PK FK NN
site_node_id	integer	PK NN

api_clients

id	integer	PK NN
name	character varying(200)	NN
token_hash	character varying(64)	UQ NN
token_prefix	character varying(16)	NN
site_node_id	integer	
active	boolean	NN
expires_at	timestamp with time zone	
rate_limit_per_minute	integer	NN
created_at	timestamp with time zone	NN
last_used_at	timestamp with time zone	
created_by	integer	

Table definitions

PK Primary key FK Foreign key UQ Unique constraint NN Not null

api_request_counts

api_client_id	integer	PK FK NN
period	character varying(10)	PK NN
period_start	timestamp with time zone	PK NN
request_count	integer	NN

api_request_logs

id	bigint	PK NN
created_at	timestamp with time zone	NN
api_client_id	integer	FK
method	character varying(10)	NN
path	character varying(80)	NN
zone_id	integer	
site_id	integer	
device_id	integer	
status_code	integer	NN
error_code	character varying(40)	
client_ip	character varying(64)	
meta	jsonb	

dashboard_layout_items

id	integer	NN
layout_id	integer	
widget_id	integer	
x	integer	NN
y	integer	NN
w	integer	NN
h	integer	NN
config	jsonb	
position_x	integer	
position_y	integer	
position	jsonb	

dashboard_layouts

id	integer	NN
name	character varying(100)	
background_image	character varying(255)	
layout	jsonb	NN
is_home	boolean	
created_at	timestamp without time zone	
updated_at	timestamp without time zone	
created_by	integer	
description	text	
sort_order	integer	

device_categories

id	integer	PK NN
name	character varying(100)	UQ NN
description	text	
icon	character varying(50)	
color	character varying(20)	
is_active	boolean	
created_at	timestamp without time zone	
updated_at	timestamp without time zone	

device_data

id	bigint	NN
device_id	integer	NN
key	text	NN
value	double precision	
timestamp	timestamp with time zone	NN
value_text	text	
value_bool	boolean	
value_json	jsonb	

Table definitions

PK Primary key FK Foreign key UQ Unique constraint NN Not null

device_latest

device_id	integer	PK NN
key	text	PK NN
value	double precision	
value_text	text	
value_bool	boolean	
value_json	jsonb	
timestamp	timestamp with time zone	NN

device_maintenance

id	integer	PK NN
device_id	integer	FK NN
maintenance_type	character varying(50)	NN
scheduled_date	date	
completed_date	date	
technician	character varying(100)	
description	text	
cost	numeric(10,2)	
status	character varying(20)	
priority	character varying(20)	
created_at	timestamp without time zone	
updated_at	timestamp without time zone	
created_by	integer	FK

device_templates

id	integer	PK NN
name	character varying(100)	NN
description	text	
protocol	character varying(50)	NN
device_information	jsonb	
communication_config	jsonb	
metrics	jsonb	NN
default_dashboard_layout	jsonb	
is_active	boolean	
created_at	timestamp without time zone	
updated_at	timestamp without time zone	
image	character varying(255)	
category_id	integer	FK

devices

id	integer	PK NN
name	character varying(100)	NN
device_template_id	integer	FK NN
serial_number	character varying(100)	
location	text	
config	jsonb	
communication_config	jsonb	
metrics	jsonb	
dashboard_layout	jsonb	
is_active	boolean	
created_at	timestamp without time zone	
updated_at	timestamp without time zone	
description	text	
is_deleted	boolean	
image	character varying(255)	
created_by	integer	FK
category_id	integer	FK
site_node_id	integer	FK

Table definitions

PK Primary key FK Foreign key UQ Unique constraint NN Not null

event_logs

id	integer	PK NN
user_id	integer	
action_type	character varying(50)	NN
entity_type	character varying(50)	NN
entity_id	integer	
message	text	
created_at	timestamp with time zone	
metadata	jsonb	

health_check_logs

id	integer	PK NN
health_check_id	integer	FK NN
status	character varying(20)	NN
message	text	NN
channel_results	jsonb	NN
sent_at	timestamp with time zone	NN

health_checks

id	integer	PK NN
name	character varying(200)	NN
is_active	boolean	NN
schedule_type	character varying(20)	NN
schedule_config	jsonb	NN
timezone	character varying(64)	NN
channel_ids	jsonb	NN
rooms	jsonb	NN
message_template	text	NN
last_run_at	timestamp with time zone	
next_run_at	timestamp with time zone	
created_at	timestamp with time zone	NN
updated_at	timestamp with time zone	NN

ia_custom_fields

ia_custom_fields_id	integer	PK NN
rel_crud	character varying(250)	
name	character varying(250)	
type	character varying(250)	
required	integer	
options	character varying(250)	
status	character varying(250)	
show_in_grid	integer	
create_date	timestamp without time zone	NN

ia_custom_fields_values

ia_custom_fields_values_id	integer	PK NN
rel_crud_id	integer	
cf_id	integer	
curd	character varying(250)	
value	character varying(250)	

ia_email_templates

id	integer	PK NN
module	character varying(255)	
code	character varying(255)	
template_name	character varying(255)	
html	text	

Table definitions

PK Primary key FK Foreign key UQ Unique constraint NN Not null

ia_menu

id	integer	PK NN
menu_name	character varying(255)	
icon	character varying(255)	
slug	character varying(255)	
module_name	character varying(255)	
status	integer	NN
parent_id	integer	NN
sorting	character varying(255)	

ia_permission

id	integer	PK NN
user_type	character varying(250)	
data	text	

ia_plugins

plugins_id	integer	PK NN
name	character varying(250)	
db_tables	character varying(250)	
status	character varying(250)	
inst_date	timestamp without time zone	NN
rm_queries	text	
version	character varying(250)	

ia_sessions

id	character varying(128)	PK NN
ip_address	character varying(45)	NN
timestamp	bigint	NN
data	text	NN

ia_setting

id	integer	PK NN
keys	character varying(255)	
value	character varying(255)	

ia_users

ia_users_id	integer	PK NN
user_id	character varying(255)	
var_key	character varying(255)	
status	character varying(255)	
is_deleted	character varying(255)	
name	character varying(255)	
password	character varying(255)	
email	character varying(255)	
profile_pic	character varying(255)	
user_type	character varying(255)	
create_date	character varying(255)	
remember_code	character varying(255)	
access_level	character varying(20)	

lorawan_applications

id	integer	PK NN
application_id	uuid	UQ NN
name	character varying(255)	NN
description	text	
tenant_id	uuid	NN
created_at	timestamp without time zone	

Table definitions

PK Primary key FK Foreign key UQ Unique constraint NN Not null

notification_channel_nodes

channel_id	integer	PK FK NN
site_node_id	integer	PK NN

notification_channels

id	integer	PK NN
name	character varying(100)	NN
type	character varying(50)	NN
is_active	boolean	
message_template	text	
description	text	
config	jsonb	
created_at	timestamp without time zone	
updated_at	timestamp without time zone	
is_deleted	boolean	

report_categories

id	integer	PK NN
name	character varying(100)	NN
description	text	
icon	character varying(100)	
sort_order	integer	
is_active	boolean	
created_at	timestamp without time zone	

report_executions

id	integer	PK NN
template_id	integer	FK
execution_time	timestamp without time zone	
file_path	character varying(500)	
status	character varying(20)	
error_message	text	
execution_time_ms	integer	

report_export_files

id	integer	PK NN
template_id	integer	NN
schedule_id	integer	FK
file_path	character varying(500)	NN
file_name	character varying(255)	NN
file_size	bigint	
export_format	character varying(10)	NN
exported_at	timestamp with time zone	NN
exported_by	integer	
created_at	timestamp with time zone	

report_favorites

id	integer	PK NN
user_id	integer	
template_id	integer	FK
created_at	timestamp without time zone	

Table definitions

PK Primary key FK Foreign key UQ Unique constraint NN Not null

report_schedules

id	integer	PK NN
template_id	integer	NN
name	character varying(255)	NN
is_active	boolean	
schedule_type	character varying(20)	NN
schedule_config	jsonb	
timezone	character varying(50)	
export_format	character varying(10)	NN
recipients	jsonb	NN
report_params	jsonb	
last_run_at	timestamp with time zone	
next_run_at	timestamp with time zone	
created_by	integer	
created_at	timestamp with time zone	
updated_at	timestamp with time zone	

report_templates

id	integer	PK NN
name	character varying(255)	NN
description	text	
template_type	character varying(50)	
config	jsonb	
created_by	integer	
created_at	timestamp without time zone	
updated_at	timestamp without time zone	
html_content	text	NN
is_default	boolean	

schema_migrations

filename	text	PK NN
applied_at	timestamp with time zone	NN

site_nodes

id	integer	PK NN
parent_id	integer	FK
name	character varying(200)	NN
node_type	character varying(20)	NN
sort_order	integer	NN
latitude	double precision	
longitude	double precision	
dashboard_layout_id	integer	
created_at	timestamp with time zone	NN
updated_at	timestamp with time zone	NN

user_dashboard_homes

user_id	integer	PK NN
layout_id	integer	NN
updated_at	timestamp without time zone	

user_site_scopes

ia_users_id	integer	PK FK NN
site_node_id	integer	PK NN

widgets

id	integer	PK NN
name	character varying(100)	NN
widget_type	character varying(50)	NN
config	jsonb	NN
created_at	timestamp without time zone	
updated_at	timestamp without time zone	