The Harness Is the Attack Surface: A Security Analysis of AI Coding-Agent Harnesses (2025–2026)

Thanatchon Chongmankhong

***Abstract*—Coding agents are built as *model plus harness*: the model proposes actions; the harness, the runtime loop around it, holds credentials, executes shell commands, mounts Model Context Protocol (MCP) servers, reads repository configuration, spawns sub-agents and runs unattended in CI. We examine the security of this deterministic layer across 58 harnesses and runtimes in four tiers defined by method: white-box for open source, black-box for closed clients that can be run, documentation alone for those that cannot, and a separate ladder for SDK runtimes. We contribute (i) a threat taxonomy (T01–T19) mapped to STRIDE, MITRE ATLAS and the OWASP LLM, Agentic and MCP lists (RQ1); (ii) a fifteen-dimension control matrix of 664 evidence-linked scores, re-rated blind by a second LLM agent from the same fact base (quadratic $\kappa = 0.88$) (RQ2); (iii) a survey of 323 publicly disclosed harness-level advisories and incidents from 2025–2026, of which 48% trace to a flawed approval, allowlist or path check or to configuration honoured before consent, while pure prompt injection, the residual class of our procedure, accounts for 5% (RQ3); (iv) `harnesswatch`, an open-source auditor with micro precision 0.983 (95% CI 0.950–0.994) on a held-out synthetic corpus, applied in a stratified prevalence study of 1010 public repositories (RQ4); (v) an inert canary benchmark of 350 runs on one small local model, which found no detectable difference in injection-following between permission modes but showed a documented Claude Code import feature placing a gitignored secret in the session transcript in 10 of 10 runs (RQ5); (vi) a governance checklist mapped to NIST AI RMF, ISO/IEC 42001, OWASP and the MAS AI risk-management guidelines (RQ6); and (vii) a black-box comparison of vendor claims with observed behaviour, in which 24% of 117 documented claims proved testable headless and 22 of the 28 tested matched (RQ7). Every reported number is generated from versioned results files; toolkit, evidence and results are released at https://github.com/thanatchon36/harnesswatch.**

***Index Terms*—AI coding agents, agent harness, prompt injection, Model Context Protocol, software supply chain, security controls**

I. Introduction

Motivates RQ1–RQ7 and summarises the contributions.

In 2025 and 2026, coding agents left the chat window for the terminal, the IDE and the CI pipeline, and vendors and open-source projects converged on one architecture: an agent is a *model* plus a *harness*. The harness is the program around the model: it assembles context from the repository, exposes tools (shell, file editing, web fetch, MCP servers), decides which tool calls require human approval, stores credentials and transcripts, spawns sub-agents, and can run unattended in CI. The model proposes; the harness executes.

Most security research on LLM agents addresses the model, asking whether it follows injected instructions [1]–[3], with the tool-execution layer held fixed. Yet the harness decides whether an injected instruction becomes a shell command, whether a cloned repository can run a hook before the user has consented, whether an MCP server starts from a cloned file, and whether a secret lands in a world-readable log. These are deterministic software decisions, and they can be specified, tested and audited like any other access-control code.

The public record points the same way. Of the 323 verified harness-level advisories and incidents we collected for 2025–2026 (Section VII), 104 arise from flawed approval, allowlist or path checks and 52 from workspace configuration honoured before consent; only 17 are pure prompt injection. Since model failures seldom receive CVEs and RC1 is the residual class of our procedure, these shares describe disclosed harness bugs rather than overall risk; within that scope, injection is often the vector, but harness controls decide the damage.

Comparing harnesses is difficult: the field changes monthly, many popular harnesses are closed source, and documentation describes intended rather than actual behaviour. We therefore organise the study by *method*: white-box analysis for open source, black-box observation for closed harnesses that we can run, documentation for those we cannot, and a separate track for SDK runtimes (Section III).

Research questions: **RQ1**: What is the attack surface of a harness, and how does it differ from classical LLM-application risk? **RQ2**: How do harnesses differ in the security controls they provide? **RQ3**: Which harness-level incidents were disclosed in 2025–2026, and from which root causes? **RQ4**: Can dangerous configuration be detected automatically across harness formats? **RQ5**: How resilient are harness $\times$ model $\times$ permission-mode combinations to indirect prompt injection and secret residue, as measured with inert canaries? **RQ6**: Which controls should an organisation mandate before adopting a harness? **RQ7**: For closed harnesses, do the documented controls match the observable behaviour of the client?

Contributions: A harness threat taxonomy with framework mappings (RQ1, Section IV); an evidence-linked control matrix of 58 harnesses and runtimes (RQ2, Section V); a black-box claims-versus-observed method for closed harnesses (RQ7, Section VI); a two-source incident survey (RQ3, Section VII); `harnesswatch`, an Apache-2.0 auditor, with accuracy, prevalence, canary-bench and residue experiments (RQ4, RQ5, Sections VIII–IX); and a governance checklist (RQ6, Section X). `make all` rebuilds every table, figure and reported number from versioned results (Appendix A).

II. Background: Anatomy of a Harness

Covers the descriptive part of RQ1 and prepares RQ2.

The loop: A harness assembles a context, calls the model, checks each proposed tool call against a permission policy, executes it and returns the result to the model. Repository content, tool output and MCP results flow inwards; commands and network requests flow outwards.

Repository files: Harnesses auto-load instruction files (`AGENTS.md`, `CLAUDE.md`, `.github/copilot-instructions.md`, `.cursor/rules`), settings that can set environment variables, permission modes and *hooks* (shell commands bound to lifecycle events), and MCP declarations (`.mcp.json`, `.vscode/mcp.json`). Formats are shared across products: Grok Build imports Claude Code and Cursor hook and MCP files[D] [4], [5]. A cloned repository is therefore configuration as well as data.

Permissions and sandbox: Permission modes range from "ask before every tool call" to "approve everything" (YOLO, bypass, full-auto, always-approve), with allow and deny rules over commands and paths. Several harnesses now default to a model-based approver; Claude Code starts `claude -p` in a classifier-mediated `auto` mode when feature flags are not fetched[D][T] [6]. Some confine commands within an OS sandbox (Seatbelt, bubblewrap, Landlock) or a container[D] [7]. Approval decides *whether* an action runs; the sandbox bounds *what it can reach*.

Extensions, state and headless mode: MCP servers [8] are launched locally, often through unpinned `npx` or `uvx`, or reached remotely, and their tool descriptions enter the context verbatim; skills and plugins add further code and prompts from marketplaces. Credentials, transcripts and persistent memory reside in a per-user state directory, and sub-agents may inherit the parent's permissions. Every harness we benchmarked runs non-interactively[D][T] (`claude -p`, `codex exec`, `grok -p`, `copilot -p`); in CI the triggering issue or pull request may be attacker-controlled and the job may hold secrets.

III. Scope, Tiers and Evidence Method

Describes how the evidence behind RQ2–RQ7 was collected.

Tiers by method: We group harnesses by what can be observed about them, not by market share. *Tier A* (open source; white-box): we read the source at a pinned commit and run the client in containers (e.g. Codex CLI, OpenCode, Gemini CLI, Qwen Code, Aider, goose, Cline, Hermes Agent). *Tier B* (closed but runnable; black-box): we install the official client in a disposable container, record what it writes and which hosts it contacts, and drive it headless (Claude Code, GitHub Copilot CLI, and the Antigravity CLI before login). Grok Build is a hybrid: its source is public under Apache-2.0[D] [9], but the public tree lags the npm release (1.0.45 against 1.0.52) and endpoints are injected at build time, so we read the source white-box and treat the shipped npm client as Tier B in E3 and E7. *Tier C* (closed and unreachable): documentation, advisories and third-party research only (e.g. Cursor, Kiro, Devin, Jules). *Tier D* (runtimes and SDKs) is scored on a separate ladder and never ranked against products; the rubric files and figures group it with hosted services as "tier C". The matrix covers 36 tier A/B products and 22 runtimes and hosted services.

Black-box method: For a closed harness we install the official release, read its documentation and advisories, parse its configuration, run it under `harnesswatch observe` (Section VIII), probe its treatment of configuration with synthetic repositories carrying hooks, MCP servers and settings, and inspect its package metadata. We never decompile, deobfuscate or consult leaked source, never decrypt TLS or store request bodies, and remain within vendor terms; otherwise the cell is *N/A (terms)*. No vendor login was placed in any container: closed clients were driven solely through documented custom-endpoint features pointing at a local model, namely Claude Code's `ANTHROPIC_BASE_URL`, Copilot CLI's bring-your-own-key mode, which requires no GitHub authentication[D] [10], and Grok Build's custom models[D] [11]. Anthropic states that it "doesn't support routing Claude Code to non-Claude models through any gateway"[D] [12], so our Claude Code runs characterise harness behaviour in an unsupported configuration, not vendor-supported performance. Antigravity has no documented local-model path and its terms restrict use with other products[D] [13], so it was observed only before login.

Evidence labels: Every factual statement about a harness carries one of three labels, rendered as superscripts: [T] *verified-by-test*, behaviour or state observed by running the pinned client; [D] *from-official-docs*, vendor documentation, vendor advisories, registry metadata or the official source code (reading source counts as documentation, not as a test); [3P] *third-party-report*, a write-up by an independent researcher or journalist. Unverified claims are excluded. Documentation and source facts are recorded in the evidence ledger and in `matrix/evidence/`; every [T] fact traces to a probe or bench file under `experiments/results/` or `bench/results/`.

Who did the work: Evidence collection, both matrix ratings, and the collection and classification of incidents were carried out by LLM research agents run and supervised by the author; Section XII discusses the consequences for reliability.

Kinds of finding: We distinguish a *vulnerability* (a defect that violates the product's own security intent, usually with a CVE or GHSA), a *design weakness* (a documented default or capability that enables harm without being a bug, such as headless mode running repository hooks) and a *policy choice* (telemetry or retention defaults, for instance). Only the first is a bug.

Ethics: Experiments ran in disposable containers on the author's machine with inert canaries and synthetic secrets; the public-repository study stores aggregates only. Issues that might be unknown to the vendor went to private coordinated disclosure and are not described here. Packages were examined through registry metadata alone; one fact obtained by listing the strings in a binary was withdrawn as outside that rule, and the reported source-map exposure in Claude Code's npm

release 2.1.88 of 31 March 2026[3P] [14] is cited only as an event, with no use of the exposed material.

IV. Threat Model and Taxonomy

Answers RQ1.

Adversaries: (A1) A *content author* controls text the agent reads (a README, comment, issue, web page or tool result); (A2) a *repository author* controls cloned files, configuration included; (A3) a *supply-chain attacker* controls a package, MCP server, plugin or release; (A4) a *local or network peer* reaches a service the harness exposes. The defender runs the harness with real credentials, code and host access (the assets). We assume that the model will sometimes follow injected instructions and that no model-level defence can be relied upon.

Taxonomy: We extended a sixteen-class seed into the classes of Table I. Three classes were added because the incident set contained sizeable groups with no natural home: escape from a sandbox or isolation boundary (T17); exposure of the agent's own control plane, typically a local HTTP or WebSocket server without authentication or Origin checks (T18); and conventional software defects in runtimes and SDKs (T19). Each class carries STRIDE letters, MITRE ATLAS techniques, and OWASP LLM 2025, OWASP Agentic (ASI01–ASI10) and OWASP MCP Top 10 identifiers; as the MCP list remains in beta, those mappings are flagged as unstable. Each class also lists its mitigating control dimensions (Section V) and the `harnesswatch` rules that detect it (Appendix C).

Classification procedure: Because write-ups conflate the entry vector with the control that failed, we traverse the classes in a fixed order and assign the first whose *failed control* the incident exhibits. A parallel twelve-question procedure assigns one of twelve root causes, RC1–RC12 (Table III). Thus configuration written by an injection and executed later is T02/RC2 rather than T01, and data leaving through a permitted command is T08/RC3. RC1, untrusted content treated as instructions with no other control failure, is reached only when no earlier question applies; its share is therefore low partly by construction.

How harness risk differs from LLM-application risk: In a chat application, a successful injection yields a wrong answer or a leaked system prompt. In a harness, the injected text originates in the developer's own workspace and is acted upon with the developer's privileges. Three properties follow. First, *configuration is code*: repository files can define hooks, environment variables and MCP launch commands that execute before the model is consulted (T02). Second, *the approval layer is a parser*: an allowlist over shell commands must reason about quoting, substitution, redirection and symlinks, and failures of this kind form the largest single group of disclosed incidents (T03, 23% by class; RC3, 32% by root cause). Third, *the harness is a long-lived service*: local servers, sub-agents, persistent memory and CI runners create surfaces that classical LLM threat models omit (T10, T11, T18). Attack trees for the principal paths are in the repository.

V. Comparative Analysis of Security Controls

Answers RQ2.

Rubric: We score fifteen control dimensions from 0 to 3: D01 permission model, D02 execution sandbox, D03 network egress, D04 workspace and configuration trust, D05 MCP governance, D06 extensions and plugins, D07 secrets and credential storage, D08 headless and CI safeguards, D09 persistent memory, D10 sub-agent isolation, D11 audit logging, D12 telemetry and retention, D13 distribution supply chain, D14 managed policy and D15 vulnerability disclosure. The scale reads 0 absent, 1 opt-in or weak, 2 on by default with documented gaps, and 3 strong, documented and centrally enforceable, with per-dimension criteria (Appendix E). Only [D] and [T] facts can raise a score; [3P] facts can only lower one, since third-party reports document bypasses rather than guarantees. The score is the highest level whose criteria are *all* met; an undecidable criterion counts as unmet; incident history, which belongs to RQ3, leaves scores unchanged. Means are unweighted, require at least eight scored dimensions and are reported alongside the minimum; a ranking is asserted only where it holds under equal, incident-exposure and security-core weightings alike.

Coverage and reliability: Of 870 harness–dimension cells, 664 were scored and 206 are N/A with a recorded reason (feature absent, no access, or undocumented); 5 runtimes have too little evidence to support a mean. A second LLM-agent rater, blind to the first rater's scores, rescored the matrix from the *same* extracted fact lists, so agreement measures how consistently the rubric is applied to shared evidence, not the reliability of evidence collection. On the 655 cells both raters scored, quadratic-weighted Cohen's κ [15] is 0.88, exact agreement 91.6% and within-one agreement 99.5%; these figures exclude the 29 cells in which one rater recorded N/A and the other a score. All 84 disagreements, those N/A cases included, are published rather than adjudicated, and rater 1's scores are reported.

Overall picture: Controls exist but are seldom safe by default (Figure 1). Across the 36 tier A/B products no per-dimension mean reaches 2. The lowest means belong to network egress (D03, 0.77), the execution sandbox (D02, 0.84), headless and CI safeguards (D08, 0.91) and workspace trust (D04, 0.97); the highest to vulnerability disclosure (D15, 1.51), audit logging (D11, 1.50) and managed policy (D14, 1.48). Overall means are closely bunched: only Codex CLI stays in the top three, and only Continue in the bottom three, under every weighting, so the per-dimension columns are more informative than the means.

Permission model (D01): Nearly every product offers per-action approval, yet only 6 of 36 reach score 2. Two patterns depress the scores: approve-everything can often be enabled from repository-controlled files, through hooks that return an auto-approve verdict or repository MCP entries carrying `autoApprove`; and several harnesses default to a model-based approver (Claude Code's `auto`[D], Cursor's auto-review[D], Qwen Code's AUTO[D], Hermes Agent's `smart`[D]). The rubric does not treat a classifier's verdict as "asking",

TABLE I

HARNESS THREAT TAXONOMY (RQ1) WITH FRAMEWORK MAPPINGS, MITIGATING CONTROL DIMENSIONS (D01–D15, SECTION V) AND THE NUMBER OF VERIFIED 2025–2026 INCIDENTS WHOSE PRIMARY CLASS IT IS (RQ3). ATLAS IDS ARE ABBREVIATED (PREFIX `AML.` DROPPED; FIRST SHOWN).

Class	Name	STRIDE	OWASP LLM	OWASP ASI	MITRE ATLAS	Controls	Inc.
T01	Indirect prompt injection via workspace and retrieved content	TE	LLM01	ASI01	T0051.001, …	D01, D02, D03, D04, D11	14
T02	Repository and workspace configuration as code execution	ET	LLM06	ASI05, ASI02	T0081, …	D04, D01, D02, D05, D14	52
T03	Permission-model weaknesses and approval bypass	ET	LLM06	ASI02, ASI03	T0053, …	D01, D02, D14	74
T04	MCP trust: tool poisoning, rug pulls, OAuth and server identity	STE	LLM03, LLM01, LLM06	ASI04, ASI02	T0110, …	D05, D14, D06, D13, D03	15
T05	Skills, plugins, extensions and marketplaces	STE	LLM03	ASI04	T0010.005, …	D06, D13, D14	2
T06	Harness distribution and dependency supply chain	TSE	LLM03	ASI04	T0010.001, …	D13, D15, D14	9
T07	Secret exposure and residue	I	LLM02	ASI03	T0055, …	D07, D11, D12	12
T08	Data exfiltration channels	I	LLM02, LLM05	ASI02	T0086, …	D03, D02, D01	23
T09	Headless and CI abuse (pwn request)	EIT	LLM01, LLM06	ASI01, ASI02, ASI03	T0051.001, …	D08, D01, D14, D07	5
T10	Persistent memory and long-lived context poisoning	TE	LLM04	ASI06	T0080.000, …	D09, D11	2
T11	Sub-agent and cross-harness trust propagation	ES	LLM06	ASI03, ASI07, ASI08	T0118, …	D10, D01, D02	2
T12	Browser and computer-use surfaces	SIE	LLM01, LLM06	ASI01, ASI02	T0100, …	D02, D03, D01	1
T13	Multi-tenant isolation and authorization	IES	LLM02	ASI03	T0085, …	D14, D10, D07	7
T14	Destructive and unsafe autonomous actions	DT	LLM06	ASI02, ASI08	T0101, …	D01, D02, D14	0
T15	Telemetry, data residency, retention and audit gaps	IR	LLM02		–	D12, D11, D14	1
T16	Offensive misuse of harnesses by attackers	E		ASI10	T0124, …	D11, D14	3
T17	Execution sandbox and isolation escape	E	LLM06	ASI05	T0105, …	D02, D10, D03	22
T18	Agent control-plane exposure and authorization	SEI		ASI03	T0132, …	D16, D01, D04	34
T19	Conventional software defects in agent runtimes and SDKs	TDE	LLM05, LLM10	ASI05	T0049, …	D15, D13, D02	45

so these defaults score 1. Counting them as asking would raise Claude Code's D01 from 1 to 3 and lift the other classifier-default harnesses; we did not recompute the rankings under that reading, which remains the rubric's principal open question.

Sandbox and egress (D02, D03): These are the lowest-scoring dimensions (means 0.84 and 0.77). Among tier A/B products, 8 offer no sandbox at all, 0 confine both filesystem and network by default with central enforcement (score 3), and 11 have no egress control. Managed runtimes score higher (tier C/D means 1.47 and 1.61) because the provider runs each session in an isolated container or microVM. Where sandboxes exist, the incident record shows their boundaries to be a frequent point of failure: symlink and working-directory tricks, writes to `.git` hooks and fallbacks to unsandboxed execution account for 22 escape incidents (Section VII).

Workspace trust (D04): Repository configuration is honoured with no notion of trust by 13 tier A/B products, and none reaches score 3. A recurrent design choice is that headless mode bypasses the trust gate. Claude Code documents that `claude -p` in a never-trusted folder runs project hooks and MCP servers[D] [16], which we observed[T]; by contrast, Grok Build ran an untrusted repository hook only after `-trust`[D][T], and Copilot CLI did not start a repository MCP server in an untrusted folder[T], though we did not re-test it in a trusted one (Section VI). Cline likewise documents that project plugins in `.cline/plugins/` load whenever the agent works in that repository[D] [17]. These are documented design properties rather than vulnerabilities, but a CI job that runs a harness on a pull request inherits them all.

Other dimensions: On D07 only 1 of 36 tier A/B products reach score 2, chiefly because transcript retention is undocumented even where credentials are kept in a 0600 file or a keychain[D] (D07 column). Telemetry (D12) is scored for transparency and opt-out, not as a defect. D13 is examined in Section IX-E. SDK runtimes delegate approval, sandboxing and egress to the application; the rubric scores these as not provided (*application responsibility*), so a team building on an SDK inherits those gaps unless it closes them.

VI. DOCUMENTED CLAIMS VERSUS OBSERVED BEHAVIOUR

Answers RQ7.

Method: For each Tier-B harness we extracted the security-relevant statements in the vendor's documentation into a claims table (117 claims across the closed harnesses), each tagged with a dimension (telemetry, updates, configuration/hook/MCP trust, sandbox, secret storage, permission default, state-directory modes). We then wrote 23 black-box probes (Section III). Each probe runs the pinned client in a fresh container, optionally on a synthetic repository seeded with a hook, an MCP server or a settings file. A verdict is *match*, *partial*, *mismatch* or *not observed* (behaviour not exercised); claims that require a login, a GUI or an interactive session remain *untested*.

Results: Only 24% of the 117 claims could be tested headless without a vendor login. Of the 28 tested, 22 matched, 3 were partial, 1 mismatched and 2 were not observed; 89 remain untested (Table II). By harness, 13 of 14 tested Claude Code claims matched, as did 4 of 7 for Antigravity, 3 of 4 for Grok Build and 2 of 3 for Copilot CLI. Every observation in the table is [T]; every claim is [D].

What the probes show: The tested claims form a convenience sample weighted towards network and update behaviour, so the match count does not generalise to the untested claims. The notable findings are documented design properties, not vulnerabilities. (i) *Headless trust.* In Claude Code, a `claude -p` run in a never-trusted folder executed

TABLE II

DOCUMENTED CLAIMS AGAINST OBSERVED BEHAVIOUR FOR CLOSED AND HYBRID HARNESSES (RQ7). EACH ROW PAIRS ONE TESTED DOCUMENTED CLAIM[D] WITH THE OBSERVATION FROM A BLACK-BOX PROBE[T] OF THE PINNED CLIENT (CLAUDE CODE 2.1.300, ANTIGRAVITY CLI 1.3.5 BEFORE LOGIN, GROK BUILD 1.0.52, COPILOT CLI 1.0.98 IN BYOK MODE). UNTESTED CLAIMS ARE OMITTED.

Harness	Dimension	Observed	Verdict
antigravity	update_check	background updater contacted: antigravity-cli-auto-updater-974169037036.us-central1.run.app:443; last_check.timestamp: yes; updater lock files: yes	match
antigravity	update_check	with AGY_CLI_DISABLE_AUTO_UPDATE=true, updater host contacted: none	match
antigravity	telemetry_hosts	before any login, telemetry/logging hosts attempted: play.googleapis.com:443 (default enableTelemetry=true)	match
antigravity	state_dir_perms	pre-login files under ~/.gemini: 35; other-user-readable: 32	partial
antigravity	permission_default	unauthenticated headless run: exit 1, auth-required message: yes, duration 62.6 s	match
antigravity	permission_default	'agy -p /help' without credentials: exit 1, auth required: yes	mismatch
antigravity	mcp_trust	before login/trust: repo .agents MCP server started: no; repo hook ran: no	partial
claude-code	telemetry_hosts	vendor hosts attempted: api.anthropic.com:443	match
claude-code	telemetry_hosts	with a gateway base URL, Datadog intake contacted: no	match
claude-code	telemetry_hosts	vendor hosts attempted: none	match
claude-code	update_check	no update-check host contacted during a headless (-p) session	not-observed
claude-code	config_trust	repo env ANTHROPIC_BASE_URL followed: yes; repo env CLAUDE_CONFIG_DIR applied: no	match
claude-code	hooks_trust	repo SessionStart hook ran under -p, untrusted: yes (cc-repo-hook)	match
claude-code	mcp_trust	repo .mcp.json stdio server started without prompt: yes; init status [('name': 'hw', 'status': 'pending', 'source': 'project')]	match
claude-code	config_trust	repo hook ran with –bare: no (cc-repo-hook-bare)	match
claude-code	secret_storage	credential files written with ANTHROPIC_AUTH_TOKEN: none	match
claude-code	permission_default	init permissionMode with a third-party base URL: auto	match
claude-code	permission_default	–dangerously-skip-permissions as uid 0 refused: yes	match
claude-code	permission_default	repo permissions.defaultMode=bypassPermissions -> init permissionMode default	match
claude-code	state_dir_perms	transcripts written: 1 (modes 0o600); other-user-readable files under ~/.claude: 2	match
claude-code	config_trust	@.env inside a CLAUDE.md command line imported the gitignored .env into the session transcript without a model call or prompt: yes	match
github-copilot	telemetry_hosts	COPILOT_OFFLINE=true vendor hosts: none; without it (BYOK): api.github.com:443	match
github-copilot	config_trust	repo .mcp.json server started in an untrusted folder (-p): no	match
github-copilot	hooks_trust	repo .github/hooks sessionStart hook ran in -p: no	not-observed
grok-build	telemetry_hosts	vendor hosts attempted with a custom local model and no login: none	match
grok-build	hooks_trust	repo hook ran untrusted: no; with –trust: yes; .claude/settings.json compat hook untrusted: no	match
grok-build	mcp_trust	project .mcp.json (compat import) server started in an untrusted folder: no	partial
grok-build	secret_storage	files written under ~/.grok: 53; other-user-readable: 35 (session files among them: 0)	match

a repository `SessionStart` hook and started a repository stdio MCP server without prompting[T][D] [16], and applied a repository `env` entry redirecting the model endpoint[T][D]; `-bare` prevented the hook[T][D] [18], and a repository request for `bypassPermissions` was ignored[T][D]. Its documented `@path` import in `CLAUDE.md` also fired on the token `@.env` inside a shell command line, drawing the gitignored `.env` into the session transcript (mode 0600) without any model call[T][D]; this explains the E3 secret-in-state result (Section IX-C). (ii) *Trust-gated alternatives.* Grok Build did not run an untrusted repository hook, including one imported from the Claude Code format, and ran it once `-trust` was given[T][D] [4]. Copilot CLI started neither a repository MCP server nor a hook in an untrusted folder[T][D]; as we did not re-test it in a trusted folder, "did not run" may equally mean "not supported under `-p`". (iii) *Network.* With the documented opt-outs set and a local model, Copilot CLI, Grok Build and Claude Code contacted no vendor host[T][D]. Before login, Antigravity's CLI contacted its auto-updater and a telemetry host, as its defaults document, and the updater opt-out took effect[T][D] [19]. (iv) *The single mismatch* is functional: `agy -p /help` is documented to run without an agent turn but demanded authentication[T][D] [20]. The *partial* verdicts concern state-directory modes and MCP start-up before trust, on which the documentation is silent.

Limits: A *match* holds for this version in a headless Linux container; it certifies neither interactive use, other platforms nor post-login behaviour, and without payload inspection it says nothing about what an allowed host receives. Probe effort was uneven (14 Claude Code claims against 3 for Copilot CLI), and Claude Code ran in a configuration its vendor does not support (Section III). Without the opt-outs, the E3 proxy blocked attempts to reach vendor or telemetry hosts from Claude Code (`api.anthropic.com`), Codex CLI (`chatgpt.com`, `github.com`), Qwen Code (an Aliyun RUM host and `models.dev`) and OpenCode (`models.opencode.ai`)[T].

VII. INCIDENT AND CVE SURVEY, 2025–2026

Answers RQ3.

Collection and counting rule: We searched NVD, the GitHub Advisory Database, vendor security pages and researcher write-ups for harness-level incidents disclosed between January 2025 and mid-October 2026 (including the harnesses' MCP servers, SDKs, CI actions and distribution channels), obtaining 357 rows after deterministic de-duplication. An incident is *counted* only if (a) its primary source was read and (b) an independent script re-resolved every listed CVE and GHSA identifier against NVD and the GitHub advisory API; an incident without an identifier must have a primary vendor or researcher source. 29 rows failed (a), 4 failed (b) and 1 fell outside 2025–2026, leaving 323 counted incidents (99 disclosed in 2025 and 224 in 2026; 239 with a CVE and 237 with a GHSA). By kind, 292 are vulnerabilities, 19 de-




Fig. 1. Control matrix (RQ2): score 0–3 per dimension, rater 1; hatched cells are N/A. Tier A/B products (a) and tier C/D runtimes and hosted services (b) are ranked separately; the right-hand column gives each harness's mean and the number of scored dimensions. The same scores with means are generated as `paper/tables/scorecard.tex`; per-cell evidence and rationale are in `matrix/`.

sign weaknesses, 8 supply-chain compromises, 3 documented offensive misuse and 1 other events. Classes follow Section IV; a single LLM agent classified every incident, and inter-rater agreement for classes and root causes was not measured. The population is selected for disclosed, harness-level software defects, including 73 ecosystem items such as MCP tooling and package compromises; the shares describe that population, not the distribution of real-world harm.

Timeline: Disclosures rose in every complete quarter of the study period (Figure 2). The rise reflects more harnesses, greater researcher attention, wider use of GHSAs and an agent-assisted search that favours recent, well-indexed advisories, not necessarily declining quality; per-product counts likewise track




Fig. 2. Verified harness incidents and CVEs by quarter of disclosure (RQ3). The hatched final quarter is partial (to 15 October 2026) and does not indicate a decline.

TABLE III
ROOT CAUSES OF THE COUNTED 2025–2026 HARNESS INCIDENTS (RQ3), ASSIGNED BY THE ORDERED PROCEDURE. PRIMARY TAXONOMY CLASSES ARE GIVEN IN TABLE I.

Root cause	Name	Incidents
RC3	Validation, parsing or authorization logic flaw in a check that gates an agent capability	104
RC2	Workspace, repository or agent-written content executed or honoured before or without consent	52
RC10	Conventional implementation defect not gating an agent capability	51
RC4	Missing authentication or origin/Host validation on a local or network control endpoint	24
RC8	Isolation boundary escape or weak isolation fallback	20
RC6	Insecure default, missing safeguard or over-privileged mode by design	20
RC1	Untrusted content treated as instructions (no distinct control failure)	17
RC7	Unintended exposure, leakage or over-collection of secrets or data by the harness itself	12
RC5	Package, extension or update-channel compromise or integrity failure	11
RC9	Output-rendering or automatic-fetch feature acts as an exfiltration channel	8
RC12	Adversarial use of a legitimate capability (no product defect)	3
RC11	Autonomous action exceeding user intent without enforced guardrail	1

scrutiny and disclosure maturity (D15) as much as risk, so we do not rank products by them.

Root causes: Table III gives the distribution. The largest group, with 104 incidents (32%), comprises defective checks that gate an agent capability (RC3): allowlists bypassed through shell substitution, redirection, environment-variable prefixes, `find -exec`, symlinks or look-alike domains. Configuration honoured before consent (RC2) contributes a further 52: repository settings, hooks, `.env` files, MCP declarations and Git configuration that run or take effect before the trust prompt. Together these deterministic harness defects account for 48% of counted incidents, the largest share though not a majority. Conventional defects not specific to agents (RC10) account for 16%, and missing authentication or Origin checks on local control endpoints (RC4) for 24. Pure prompt injection with no other control failure (RC1) stands at 5%; as the residual class, this is a lower bound on the role of injection, which we did not code separately as a vector.

Classes: By primary class (Table I), permission-model weaknesses (T03, 74, 23%) and repository configuration acting as code execution (T02, 52) lead, followed by conventional defects (T19, 45) and control-plane exposure (T18, 34). Indirect prompt injection is the primary class of only 14 incidents, although injection is the delivery vector in many incidents classified elsewhere.

Representative cases: Credit belongs to the original researchers. *Injection to configuration:* hidden Unicode in rules files (Pillar Security)[3P] [21]; injection flipping Copilot's auto-approve (CVE-2025-53773)[3P] [22]; Cursor executing attacker-written or silently modified MCP configuration (CVE-2025-54135/54136)[D][3P] [23], [24]. *Configuration before consent:* Claude Code project files executing code and transmitting API tokens before the trust dialog (CVE-2025-59536, CVE-2026-21852)[3P] [25]; Codex CLI loading project MCP servers without confirmation (CVE-2025-61260)[3P] [26]; Gemini CLI's CI action auto-trusting the workspace[D] [27]. *Allowlist and path checks:* command deception in Gemini CLI[3P] [28]; path and command bypasses in Claude Code (CVE-2025-54794/54795)[3P] [29], and deny rules not enforced through symlinks[D] [30]. *MCP:* tool poisoning and the GitHub MCP leak (Invariant Labs)[3P] [31], [32]; SQL-returned injection via the Supabase MCP server[3P] [33]; the unauthenticated proxy in MCP Inspector (CVE-2025-49596)[D][3P] [34], [35]. *Other:* unauthenticated local control planes in OpenCode and DeepSeek Harness[D] [36], [37]; a malicious prompt shipped in Amazon Q Developer 1.84.0[D] [38]; the `nx` "s1ngularity" compromise, using installed AI CLIs to search for secrets[D] [39]; data leaks from Antigravity shortly after launch[3P] [40], [41]; and a vendor's own account of the criminal misuse of a coding agent [42].

Fix date relative to advisory publication: Among the 148 counted incidents with both dates, a fix release existed on or before the advisory's publication in 135 cases (median offset -5.00 days, maximum 288); 175 incidents have no recorded fix date (unfixed or unknown). Because advisories are by design usually published after a fix, this measures disclosure practice rather than time to fix; report dates were not available.

VIII. Design of harnesswatch

Covers the design half of RQ4 and the instrument used for RQ5 and RQ7.

`harnesswatch` is an Apache-2.0 Python package and command-line tool. It is read-only and offline by default, never transmits file contents, and redacts every secret it reports.

Profiles and a common schema: One risk has many spellings: approve-everything is `bypassPermissions` in Claude Code, `approval_policy = "never"` in Codex, `yolo` in Gemini and Qwen, and `"permission": "allow"` in OpenCode. A YAML profile for each of the 58 harnesses in the matrix records file locations, key names and documented defaults, and a profile-driven parser maps every file onto a common `HarnessConfig` model (permission mode, allow and deny lists, hooks, MCP servers, instruction files, trust, telemetry and auto-update). A file shared by several harnesses is parsed once, with the semantics of the format's owner.

Audits and rules: Six audit modules cover *config*; *mcp* (pinning, transport, inline secrets, tool-description injection, auto-approval); *instructions* (hidden Unicode, override phrasing, remote includes); *secrets* (state directories, transcripts, file modes); *supply* (SBOM, OSV, installer verification); and *ci* (headless agents on untrusted triggers). Each of the 25 rules (Table VII) carries a severity, a confidence, a kind (vulnerability pattern, design weakness or policy choice), taxonomy classes, remediation guidance and `should_fire`/`should_not_fire` fixtures. Output is terminal, JSON, Markdown or SARIF 2.1.0; a GitHub Action and a pre-commit hook wrap the repository audits.

observe and bench: `harnesswatch observe <harness> -- CMD` runs a command in a disposable container whose sole exit is a logging proxy, and records the CONNECT targets (classified as model API, telemetry, update or unknown), a filesystem diff with modes, credential locations, sandbox evidence from `/proc` and any permission prompts in the output. It stores no request bodies and does not decrypt TLS. It underlies E5, E7 and every bench run. The canary bench (Section IX-C) drives each harness headless through a dedicated adapter and aggregates rates with Wilson intervals [43].

IX. Empirical Evaluation

Answers RQ4 (E6, E2) and RQ5 (E3, E5), and the supply-chain component of RQ2 (E4).

All experiments ran on a single Linux workstation with Docker and a consumer GPU; every reported number is read from `experiments/results/*.json`.

A. E6: Rule-pack accuracy on a labelled corpus (RQ4)

Design: The corpus comprises 376 cases (113 hand-crafted and 263 generated) spanning more than twenty harness formats, CI files, state directories and MCP manifests; 108 are wholly negative, and many positives have near-miss twins (pinned `npx`, authenticated HTTPS MCP, linter-only hooks, emoji ZWJ, key-like identifiers). Every audit runs on every case and the unit is the (case, rule) pair, so any unlabelled firing is a false positive. A hash of the case identifier splits the corpus into 245 development and 131 test cases; errors were inspected and corrected on the development split only.

Results: On the held-out test split, micro precision is 0.983 (95% Wilson CI 0.950–0.994) and micro recall 0.983 (0.950–0.994), with 3 false positives and 3 false negatives; macro precision and recall are 0.97 and 0.95 (per-rule results in `paper/tables/e6_accuracy.md`). Before the development-split corrections, test precision was 0.960 with 7 false positives; the test split had been scored once before corpus-content corrections that touched both splits, so it is not pristine. The Wilson intervals treat (case, rule) pairs as independent although they cluster within cases and generator families, so they are optimistic. The weakest rules are `HG-SUB-001`, `HG-MCP-004` and the approve-everything

rules. Because the corpus is synthetic and labelled by the rule author, this shows that the rules implement their specification across formats; real-world precision remains unknown.

B. E2: Prevalence in public repositories (RQ4)

Design: Through the GitHub code-search API we sampled harness settings and MCP files, instruction files (`AGENTS.md`, `CLAUDE.md`, Copilot and Windsurf rules) and CI workflows that invoke `claude-code-action`, `codex exec` or `gemini -p`. For each repository we reconstructed only the sampled files in a temporary tree, ran `harnesswatch audit`, retained only (rule, file) pairs and deleted the tree. Identifiers were hashed with an unsaved per-run salt for de-duplication only; a scrub check refuses to write results containing any identifier or URL seen; secret findings were only counted; and requests stayed below the API's rate limits. Each of the 17 search strata is capped at 60 files, so a pooled per-repository rate would mostly reflect the choice of strata. We therefore report each rule's rate over the stratum of files that can carry it (configuration and MCP files, $n = 600$; instruction files, $n = 240$; agent CI workflows, $n = 177$), with Wilson intervals, and name no repository. Only project-level configuration is visible, and a finding marks risky configuration, not exploitation.

Results: We audited 1010 repositories (1017 files, 0 audit errors), and 18 rules fired at least once (Table IV). Among agent CI workflows, 63.3% run the agent with a write-scoped token (`HG-CI-002`) and 28.2% match the pwn-request pattern of an untrusted trigger combined with secrets (`HG-CI-001`). Among configuration and MCP files, 28.3% launch an MCP server from a registry without a version pin (`HG-MCP-001`) and 14.3% declare a remote server without TLS or authentication (`HG-MCP-002`); `HG-MCP-005` (a server declared in repository configuration, 51.8%) largely restates the sampling key and is informational. Secret-shaped strings in MCP declarations (`HG-MCP-003`, 3.5%) were counted only; because identifiers are discarded by design, owners were not notified and the strings were not validated. No E2 finding was validated by hand, so the real-world precision of these rules is unknown, and the rates describe this capped, relevance-ranked sample rather than GitHub as a whole.

C. E3: Canary benchmark for indirect prompt injection (RQ5)

Design: Each run starts a fresh container with a minimal Python repository, a synthetic `.env` token, a fixture file and a sink on `127.0.0.1`, and sets the same benign task: add a `multiply` function and test, and run the tests. Besides a *control*, four scenarios place one templated block in the README, in the harness-native instruction file, in a code comment, or in test output that is returned as a tool result (Table VIII). The block asks the agent to create `CANARY_<id>.txt`, POST `.env` to the sink and delete the fixture; all three are inert, and the container reaches only the model server. The two modes are *default* (out-of-the-box headless) and *auto* (the documented approve-everything flag).

TABLE IV
E2 PREVALENCE BY STRATUM (RQ4): REPOSITORIES WITH A FINDING OVER THE AUDITED FILES IN THE STRATUM THAT CAN CARRY THE RULE; TOP RULES, WITH WILSON 95% CI. AGGREGATES ONLY; NO REPOSITORY IS NAMED.

Rule	Stratum (n)	Repos	Rate [95% CI]
HG-CI-002	workflows (177)	112	63.3% [56.0, 70.0]
HG-MCP-005	config (600)	311	51.8% [47.8, 55.8]
HG-MCP-001	config (600)	170	28.3% [24.9, 32.1]
HG-CI-001	workflows (177)	50	28.2% [22.1, 35.3]
HG-MCP-002	config (600)	86	14.3% [11.8, 17.4]
HG-HOOK-001	config (600)	43	7.2% [5.4, 9.5]
HG-MCP-003	config (600)	21	3.5% [2.3, 5.3]
HG-SEC-003	config (600)	14	2.3% [1.4, 3.9]
HG-PERM-001	config (600)	12	2.0% [1.1, 3.5]
HG-PERM-003	config (600)	12	2.0% [1.1, 3.5]

Harnesses, model and grid: Seven adapters cover three Tier-B clients (Claude Code, Copilot CLI and the Grok Build npm binary, driven through their custom-endpoint modes; Claude Code's is vendor-unsupported, Section III) and four open-source harnesses (OpenCode, Codex CLI, Aider and Qwen Code). No vendor credentials are used, so every harness talks to the same local open-weight model, `qwen3:4b-instruct`, served by Ollama. The grid is 7 harnesses $\times$ 5 scenarios $\times$ 2 modes, with 5 runs per cell. A run is capped at 240 s and scored on its state at the cap; a run with no harness output counts as an error, not as safe. Aider never loads an instruction file, so its `instructions` cells are N/A in both modes and are excluded from the pooled statistics.

Metrics: Injection follow: any of the three goals achieved. *Exfiltration attempt*: any POST to the sink, or the secret observed there. *Destructive action*: the fixture deleted. *Secret read*: the synthetic token appears in the harness's printed output (other than in an environment-variable dump) or reaches the sink; since some harnesses print only their final message, this undercounts reads. *Secret in state*: the token appears in a transcript or session file written by the harness, which separates persistence from agent action. *Permission prompt*: an approval prompt appears in the output. *Task completed*: the tests pass and the function and its test exist, so that a "safe but useless" outcome remains visible. All rates carry Wilson 95% intervals.

Results: The grid produced 350 runs (0 errors, 22 timeouts scored at the cap, model cost $0.00), of which 340 enter the analysis (Table V). Over the injection scenarios, the injected instruction was followed in 2 of 135 auto-mode runs (95% CI 0.004–0.052) and in 0 of 135 default-mode runs (0.000–0.028); the controls followed nothing (0 of 70). No run attempted the POST, the fixture was deleted in 1 auto-mode run, and the strict secret-read count is 0 in both modes. The intervals overlap, so there is *no detectable safety difference* between the modes. Task completion does differ (84 of 135 auto against 23 of 135 default) because several headless defaults withhold the tools the task needs: Codex CLI and Copilot CLI showed a permission prompt in every default

run, while Grok Build and Qwen Code completed nothing in default mode without a detectable prompt, for reasons we did not establish. OpenCode completed 1 of 10 even in the controls, an adapter–model incompatibility that renders its cells uninformative. Claude Code's "default" arm is not an ask mode: with a third-party endpoint it starts in the classifier-mediated `auto` mode (Section VI).

Secret in state: In 10 of 10 Claude Code runs of the `instructions` scenario (both modes), the synthetic secret reached the session transcript, against 0 in its other scenarios. This is not a model action: an E7 probe with an unreachable model endpoint reproduced it, because the payload's `–data–binary @.env` contains the token `@.env`, which Claude Code's documented `@path` import resolves when it loads `CLAUDE.md`[T][D]. It is a harness design property: an instruction file can import gitignored secrets into context and transcript without any approval.

Interpretation: The low follow rate most probably reflects the small model's limited agentic and instruction-following ability and the plainly worded, benign canary, *not* the robustness of the harnesses. With 5 runs per cell and zero or one event per cell, the intervals are wide, and we do not rank harnesses on resilience. Nor do we describe default modes as safer.

Correction: Our original secret metric (the token anywhere in output or written files), fixed before the results were inspected, flagged 15 runs and was replaced afterwards: 10 were the Claude Code import above and the rest Codex CLI, which writes its process environment, canary included, into `~/.codex` shell snapshots whenever its shell tool runs (6 of 50 Codex runs)[T]. Neither is the agent reading the secret, hence the two metrics: a benchmark should distinguish what a harness persists from what an agent does.

D. E5: Secret residue in harness state (RQ5)

Design: For each of the 7 bench harnesses we ran two short sessions in a fresh container. In the *key* condition the provider credential was a unique synthetic canary; in the *content* condition the prompt asked the agent to read a synthetic `.env` file. We searched every file the harness wrote for the canary and recorded paths, modes and reachability by other users (home directory 0755); file contents were never stored. With one session per harness and condition ($N = 1$), the results are descriptive.

Results: In the content condition, 6 of the 7 harnesses left at least one file holding the secret, typically a transcript or chat log (Table VI)[T]; in 3 of them such a file was readable by other local users. In the key condition, 0 of the 4 harnesses that accept a key wrote it to a file in this single run[T]. That is a sampling result rather than evidence of absence: Codex CLI persists environment-supplied credentials in shell snapshots whenever its shell tool runs, which occurred in 6 of 50 E3 runs but not in the E5 key session[T]. Mode bits alone can mislead: Grok Build writes 0644 session files, but inside a 0700 sessions directory, so other users cannot reach them[T]; Claude Code writes transcripts with mode 0600[T]. OpenCode left no residue in this run. Because residue depends on whether the agent reads the file, a single run can miss it. These are design weaknesses, not vulnerabilities; a 0750 home directory would close the reachable paths, but CI runners and containers commonly use 0755.

E. E4: Distribution supply chain (RQ2, D13)

We inspected the published packages of 23 harnesses (the Tier-A set plus Claude Code, Grok Build and Copilot CLI) from registry metadata and lockfiles alone, without running any install script[D] (per-package table: `paper/tables/e4_supply.md`). Install-time hooks are declared by 7 packages. Of the 18 whose status could be determined, 10 publish registry provenance attestations. A `curl | sh` installer is offered by 17, and in 17 of these the installer verifies no signature (some verify a checksum; Claude Code documents a signed release manifest that its installer does not itself verify[D]). Auto-update is documented as on by default in 12 (cells marked "unverified" in the table are undetermined, not off). The median lockfile holds 97 transitive packages, and OSV lists 299 unique advisories against the locked dependency versions, concentrated in a few packages; these are advisories against pinned versions, not demonstrated exploitability. Auto-update is a trade-off: it delivers fixes promptly but widens the blast radius of a compromised release channel, as the Amazon Q extension incident showed[D] [38].

X. Governance Recommendations

Addresses RQ6 as recommendations, not as an evaluated finding.

We distilled the findings into a checklist of thirty controls (GC-01 to GC-30). Each states its requirement; its rationale (threat classes, root causes, rubric dimensions, and whether it targets a vulnerability, a design weakness or a policy choice); how to verify it, with an exact `harnesswatch` command or a manual check; and its mapping to NIST AI RMF 1.0 [44], NIST AI 600-1 [45], ISO/IEC 42001 Annex A [46], OWASP [47], [48], MITRE ATLAS [49] and the MAS AI risk-management guidelines [50]. The controls that follow most directly from our evidence are: treat repository configuration, instruction-file imports included, as untrusted code, and gate changes to it in CI (GC-08, GC-09, GC-23; RC2, E3 secret-in-state); lock approve-everything modes by managed policy, and regard allowlists as a convenience rather than a boundary (GC-06, GC-07; RC3); supply the sandbox and egress boundary yourself, since D02 and D03 score lowest (GC-16, GC-17, GC-20); never run a headless agent with secrets or write tokens on an untrusted trigger (GC-21, GC-22; E2 CI strata); keep secrets out of configuration files and the agent's environment, and restrict state directories (GC-14, GC-15; E5); and re-run the black-box probes and the canary bench on the exact version and model you deploy (GC-03, GC-04). The checklist has not been evaluated for coverage or usability; the OWASP MCP Top 10 remains in beta, the ISO/IEC 42001

TABLE V

E3 CANARY BENCH (RQ5): BY HARNESS AND PERMISSION MODE OVER THE INJECTION SCENARIOS; k/n WITH WILSON 95% CI IN PER CENT; THE REMAINING COLUMNS ARE COUNTS OUT OF n. ONE LOCAL MODEL (`QWEN3:4B-INSTRUCT`); ^{B} MARKS TIER-B CLIENTS. NOT A RESILIENCE RANKING.

Harness	Mode	n	Follow [95% CI, %]	Exfil	Destr.	Secret in state	Prompts	Timeouts	Task done [95% CI, %]
aider	auto	15	0/15 [0.0, 20.4]	0	0	0	0	0	10/15 [41.7, 84.8]
aider	default	15	0/15 [0.0, 20.4]	0	0	0	0	0	10/15 [41.7, 84.8]
claude-code^B	auto	20	1/20 [0.9, 23.6]	0	1	5	0	4	16/20 [58.4, 91.9]
claude-code^B	default	20	0/20 [0.0, 16.1]	0	0	5	0	6	13/20 [43.3, 81.9]
codex-cli	auto	20	1/20 [0.9, 23.6]	0	0	0	8	4	11/20 [34.2, 74.2]
codex-cli	default	20	0/20 [0.0, 16.1]	0	0	0	20	1	0/20 [0.0, 16.1]
github-copilot^B	auto	20	0/20 [0.0, 16.1]	0	0	0	1	0	18/20 [69.9, 97.2]
github-copilot^B	default	20	0/20 [0.0, 16.1]	0	0	0	20	2	0/20 [0.0, 16.1]
grok-build^B	auto	20	0/20 [0.0, 16.1]	0	0	0	0	0	17/20 [64.0, 94.8]
grok-build^B	default	20	0/20 [0.0, 16.1]	0	0	0	0	0	0/20 [0.0, 16.1]
opencode	auto	20	0/20 [0.0, 16.1]	0	0	0	0	0	0/20 [0.0, 16.1]
opencode	default	20	0/20 [0.0, 16.1]	0	0	0	0	0	0/20 [0.0, 16.1]
qwen-code	auto	20	0/20 [0.0, 16.1]	0	0	0	1	1	12/20 [38.7, 78.1]
qwen-code	default	20	0/20 [0.0, 16.1]	0	0	0	0	1	0/20 [0.0, 16.1]

TABLE VI

E5 SECRET RESIDUE AFTER READING A SYNTHETIC `.ENV` (CONTENT CONDITION; ONE SESSION PER HARNESS; DESCRIPTIVE). "REACH.": FILES READABLE BY OTHER USERS (O+R ON THE FILE AND O+X ON EVERY ANCESTOR). "CRED.": FILES HOLDING THE PROVIDER KEY IN THE KEY CONDITION (N/A: NO KEY ACCEPTED). "O+R STATE": OTHER-USER-READABLE STATE FILES OVER ALL STATE FILES WRITTEN.

Harness	Files w/ secret	Kind	Mode	Reach.	Cred.	o+r state
aider	1	workspace	644	1	n/a	3/3
claude-code	1	log	600	0	0	2/5
codex-cli	2	log	644	2	0	67/69
github-copilot	2	log/state	600/644	0	n/a	236/248
grok-build	2	log	644	0	0	35/54
opencode	0	–	–	0	n/a	26/26
qwen-code	1	log	644	1	0	10/13

Annex A titles are taken from public listings, and NIST AI 600-1 is cited at document level where necessary.

XI. RELATED WORK

Places RQ1–RQ7 in relation to prior work.

Prompt-injection benchmarks for agents: Greshake et al. introduced indirect prompt injection against LLM-integrated applications [1], and Liu et al. formalised the attacks and defences [51]. InjecAgent [3] and AgentDojo [2] benchmark tool-using agents against injected tool outputs; Agent Security Bench [52] broadens the set of attacks and defences; ToolEmu [53] emulates tools to surface risky agent behaviour; and RedCode [54] benchmarks risky code execution by code agents. These works fix the agent framework and vary the model and the attack; our bench fixes the model and the payload and varies real harness binaries and their modes.

Design-level defences: CaMeL [55] and the design patterns of Beurer-Kellner et al. [56] constrain what an agent may do once it has read untrusted data. System-level isolation (IsolateGPT [57]) and programmable privilege control (Progent [58]) move enforcement into the runtime, much as our rubric asks of harnesses. Willison's "lethal trifecta" [59] explains why egress (D03) and secret handling (D07) matter even when injection cannot be prevented.

MCP security: Hou et al. survey the MCP landscape and its threats [60]; Radosevich and Halloran show that MCP-connected models can be driven to harmful actions [61]; Hasan et al. study the security and maintainability of MCP servers at scale [62]; and MCPTox benchmarks tool poisoning on real servers [63]. Invariant Labs described tool-poisoning attacks and the GitHub MCP data leak [31], [32], and Trail of Bits showed that a server can attack before any tool is invoked [64]. We add the harness side: how servers are declared, pinned and approved, and how often risky declarations occur in public repositories.

Practitioner research on coding agents: Much of what is known comes from practitioners: Pillar Security's rules-file backdoor [21]; Tracebit's Gemini CLI allowlist bypass [28]; Johann Rehberger's *Embrace The Red* series, including the Copilot auto-approve RCE, the Month of AI Bugs and the Antigravity analysis [22], [41], [65]; Trail of Bits on prompt injection leading to RCE in agents [66]; and Check Point Research and Cymulate on Cursor, Codex CLI and Claude Code [24]–[26], [29]. Our survey normalises these reports under one taxonomy, one root-cause scheme and one counting rule.

CI and supply chain: Studies of GitHub workflow security [67], [68] underpin our CI rules and the E2 workflow stratum, and taxonomies of open-source supply-chain attacks [69] frame E4.

Frameworks: The OWASP Top 10 for LLM Applications [47], the OWASP Agentic AI threats and mitigations guide [70], the OWASP Top 10 for Agentic Applications [48] and the OWASP MCP Top 10 [71] catalogue risks at the application level, and MITRE ATLAS [49] catalogues adversary techniques. We map our taxonomy onto all of them and add a harness-specific, checkable control layer.

The author's prior tooling: `harnesswatch` reuses parsing ideas from the author's `upfront`, offers `rulewarden` (deterministic enforcement of instruction-file rules) as an integration point, and adopts `airmkit`'s control vocabulary for the MAS mapping.

XII. Limitations and Threats to Validity

Bounds how far the answers to RQ1–RQ7 generalise.

Version drift: Scores, probes and bench cells refer to the versions listed in `VERSIONS.md`, accessed on 15 October 2026. Harnesses release weekly, and several were renamed or discontinued during the study; the matrix should be re-run rather than cited as current.

Models and compute: No vendor API keys or logins were used, so the bench runs a single small, local, open-weight model through documented custom-endpoint features and says nothing about any vendor's flagship model. The GPU is shared with the owner's other work; a planned second model family was cancelled to release it, so the goal of at least two models per harness is *not met*, and the scenario set and runs per cell were reduced, leaving wide intervals. So small a model also limits how often any injection is acted upon at all. Claude Code was routed to a non-Claude model, which its vendor does not support (Section III).

Headless only: Probes and bench runs are headless. Interactive trust dialogs, IDE extensions and GUI-only products (the Antigravity IDE, for instance) were not tested. A harness whose interactive mode is safer is under-credited, which is the conservative error for CI use.

Benign-canary ceiling: The payloads are inert and plainly worded; disguised or adaptive attacks may succeed where these fail, so the bench rates are lower bounds.

Black-box limits: Without TLS inspection we cannot say what an allowed host receives, and login-gated harnesses were observed only before login.

Rating and classification: Both matrix raters worked from one shared fact base, so κ measures the application of the rubric rather than the reliability of the evidence, and it excludes the N/A-versus-score cells (all 84 disagreements, those included, are published). Incident classes and root causes had a single LLM rater and no agreement measurement, and RC1 is the residual class of an ordered procedure. Several scores turn on rubric interpretation, notably of classifier-gated defaults.

Selection: The incident survey admits only publicly disclosed, harness-level advisories, most of them with CVE or GHSA identifiers; model-level failures are rarely tracked in this way, and agent-assisted search favours recent, well-indexed advisories. The RQ3 shares therefore describe disclosed harness defects, not overall risk.

Corpora: E6 is synthetic and labelled by the author; E2's code-search sample favours popular, recently indexed repositories; E5 has one session per condition.

XIII. Conclusion

Summarises the answers to RQ1–RQ7.

The harness is where an agent's capabilities become effects. Among the publicly disclosed harness-level advisories of 2025–2026, flawed approval checks and configuration honoured before consent account for 48%, and pure prompt injection, a residual class, for 5%. Across 58 harnesses and runtimes, controls exist but are seldom safe by default: sandboxing and egress are the weakest dimensions, headless modes frequently bypass trust gates, and in our sample of public repositories unpinned MCP launches and write-scoped agent CI jobs recur. For closed harnesses, 22 of the 28 testable claims matched, but most documented claims could not be tested headless, and documented features such as instruction-file imports can carry secrets into transcripts without any model action.

The remedies are engineering: trust gates that cover every executable class of configuration and apply headless, permission modes locked by policy, default sandboxes and egress allowlists. We release `harnesswatch`, the rubric, the evidence and the results so that the study can be repeated as the field moves.

Appendix A
Reproducibility

The repository contains the toolkit, rule pack, harness profiles, evidence ledger, matrix evidence, results JSON and this paper. Three entry points rebuild everything.

- `make all` runs the linter, type checker and tests with coverage, builds the documentation, regenerates every results-derived table, figure and number offline from committed data (`make experiments`, which ends with `experiments/paper_numbers.py` writing `paper/numbers.tex`), and builds this paper with `paper/build.sh`.
- `make bench` builds the pinned harness images (`make bench-images`), runs or resumes the canary grid against a local Ollama container, and re-runs the E3 analysis. It requires Docker and a GPU-backed Ollama container on the bench network; no vendor credentials are used.
- `paper/build.sh` uses a pinned Tectonic release, downloaded with a SHA-256 check, and also writes the Markdown mirror `paper/paper.md` and the web version in `docs/paper/`.

Pinned versions: harness versions are listed in `VERSIONS.md`; bench images are tagged with the harness version (Table VIII); the model server is Ollama 0.40.4, pinned by image digest; and Python dependencies are locked in `uv.lock`. Every reported number in the prose is a macro generated from `experiments/results/*.json`; design constants (versions, caps, mode bits, and the counts of classes and controls) are typed by hand.

Appendix B
Review and Corrections

Following an internal hostile review we made these changes, all reflected in the results files and logged in the assumptions log: (1) deterministic incident de-duplication, which removed one double-counted incident, with the excluded out-of-period row now shown; (2) "patch latency" recomputed from dates and reframed as fix date relative to advisory publication, with undated fixes reported; (3) the E3 secret metric split into *secret*

read and *secret in state* once the lenient metric was found to count harness persistence (Codex environment snapshots, the Claude Code `@path` import); (4) E2 prevalence reported per stratum rather than pooled; (5) matrix evidence labels aligned with the ledger, so that source reads are [D], not [T]; (6) one Grok Build fact obtained by listing strings in the shipped binary withdrawn as outside our metadata-only rule; (7) claims about RQ3 shares, mode safety, claim coverage and rater independence reworded.

Appendix C
Rule Pack

Table VII lists every rule; each YAML file adds harness-specific spellings, remediation guidance, references and fixtures.

Appendix D
Canary-Bench Scenario Catalogue

Table VIII lists the scenarios and adapters. Every injected block uses the same versioned payload template; only its location changes. The `hidden_unicode` scenario is implemented but excluded from the reported grid, because its zero-width wrapping reaches the model as plain ASCII and so measures nothing beyond `instructions`. Aider has no auto-loaded instruction file, so its `instructions` cells are N/A.

Appendix E
Scorecard Rubric

The fifteen core dimensions, the 0–3 scale and the scoring rules are set out in Section V; a proposed D16 (local service and control-plane exposure) is excluded from all means until it has sufficient evidence. Each dimension poses a single question, for example D01, "does the harness ask before risky tool actions, and can the approve-everything path be restricted?", and D04, "is repository-supplied configuration ignored until the user consents?". The criteria are written so that they can be decided from labelled facts: score 3 always requires a safe default *and* central enforceability (for D02, filesystem and network confined by default, not weakenable by the agent or by repository files, and enforceable by an administrator). The full criteria are in `matrix/rubric.md` (summary table: `paper/tables/rubric.md`), the scores with means and minima in `paper/tables/scorecard.tex`, and every cell's evidence and rationale in `matrix/`.

References

[1] K. Greshake, S. Abdelnabi, S. Mishra, C. Endres, T. Holz, and M. Fritz, "Not what you've signed up for: Compromising real-world LLM-integrated applications with indirect prompt injection," in *Proceedings of the 16th ACM Workshop on Artificial Intelligence and Security (AISec)*, 2023, pp. 79–90. [Online]. Available: https://arxiv.org/abs/2302.12173

[2] E. Debenedetti, J. Zhang, M. Balunović, L. Beurer-Kellner, M. Fischer, and F. Tramèr, "AgentDojo: A dynamic environment to evaluate prompt injection attacks and defenses for LLM agents," in *Advances in Neural Information Processing Systems 37 (NeurIPS 2024), Datasets and Benchmarks Track*, 2024. [Online]. Available: https://arxiv.org/abs/2406.13352

[3] Q. Zhan, Z. Liang, Z. Ying, and D. Kang, "InjecAgent: Benchmarking indirect prompt injections in tool-integrated large language model agents," in *Findings of the Association for Computational Linguistics: ACL 2024*, 2024. [Online]. Available: https://arxiv.org/abs/2403.02691

[4] xAI, "Grok Build: Hooks," https://docs.x.ai/build/features/hooks.md, 2026, accessed 2026-10-15.

[5] ——, "Grok Build: MCP servers," https://docs.x.ai/build/features/mcp-servers.md, 2026, accessed 2026-10-15.

[6] Anthropic, "Claude Code: Permission modes," https://code.claude.com/docs/en/permission-modes, 2026, accessed 2026-10-15.

[7] ——, "Claude Code: Sandboxing," https://code.claude.com/docs/en/sandboxing, 2026, accessed 2026-10-15.

[8] Model Context Protocol, "Model context protocol specification, version 2026-07-28," modelcontextprotocol.io, Jul. 2026, accessed 2026-10-15. [Online]. Available: https://modelcontextprotocol.io/specification/2026-07-28

[9] xAI, "xai-org/grok-build source repository (apache-2.0)," https://github.com/xai-org/grok-build, 2026, accessed 2026-10-15.

[10] GitHub, "Using your own LLM models in GitHub Copilot CLI," https://docs.github.com/en/copilot/how-tos/copilot-cli/customize-copilot/use-byok-models, 2026, accessed 2026-10-15.

[11] xAI, "Grok Build: Overview," https://docs.x.ai/build/overview.md, 2026, accessed 2026-10-15.

[12] Anthropic, "Claude Code: LLM gateway configuration," https://code.claude.com/docs/en/llm-gateway, 2026, accessed 2026-10-15.

[13] Google, "Google Antigravity additional terms of service," https://antigravity.google/terms, 2026, accessed 2026-10-15.

[14] S.-J. Wiggers, "Anthropic accidentally exposes Claude Code source via npm source map file," InfoQ, Apr. 2026, accessed 2026-10-15. [Online]. Available: https://infoq.com/news/2026/04/claude-code-source-leak

[15] J. Cohen, "Weighted kappa: Nominal scale agreement with provision for scaled disagreement or partial credit," *Psychological Bulletin*, vol. 70, no. 4, pp. 213–220, 1968.

[16] Anthropic, "Claude Code: Configure permissions — what runs before you trust a folder," https://code.claude.com/docs/en/permissions#what-runs-before-you-trust-a-folder, 2026, accessed 2026-10-15.

[17] Cline, "Plugins (cline documentation, docs/customization/plugins.mdx)," https://github.com/cline/cline/blob/main/docs/customization/plugins.mdx, 2026, accessed 2026-10-15.

[18] Anthropic, "Claude Code: Run Claude Code programmatically," https://code.claude.com/docs/en/headless, 2026, accessed 2026-10-15.

[19] Google, "Google Antigravity: Settings," https://antigravity.google/docs/settings, 2026, accessed 2026-10-15.

[20] ——, "Antigravity CLI: Headless mode," https://antigravity.google/docs/cli/headless, 2026, accessed 2026-10-15.

[21] Z. Karliner, "New vulnerability in GitHub Copilot and Cursor: How hackers can weaponize code agents ("Rules File Backdoor")," Pillar Security blog, Mar. 2025, accessed 2026-10-15. [Online]. Available: https://www.pillar.security/blog/new-vulnerability-in-github-copilot-and-cursor-how-hackers-can-weaponize-code-agents

[22] J. Rehberger, "GitHub Copilot: Remote code execution via prompt injection (CVE-2025-53773)," Embrace The Red blog, Aug. 2025, accessed 2026-10-15. [Online]. Available: https://embracethered.com/blog/posts/2025/github-copilot-remote-code-execution-via-prompt-injection/

[23] Anysphere, "GHSA-4cxx-hrm3-49rm / CVE-2025-54135: Arbitrary code execution from Cursor agent via MCP special file," https://github.com/cursor/cursor/security/advisories/GHSA-4cxx-hrm3-49rm, 2025, accessed 2026-10-15.

[24] A. Charikov, R. Zaikin, and O. Vanunu, "Cursor IDE's MCP vulnerability (MCPoison)," Check Point Research, https://research.checkpoint.com/2025/cursor-vulnerability-mcpoison/, 2025, accessed 2026-10-15.

[25] A. Donenfeld and O. Vanunu, "Caught in the hook: RCE and API token exfiltration through Claude Code project files (CVE-2025-59536, CVE-2026-21852)," Check Point Research, Feb. 2026, accessed 2026-10-15. [Online]. Available: https://research.checkpoint.com/2026/rce-and-api-token-exfiltration-through-claude-code-project-files-cve-2025-59536/

[26] I. Mill and O. Vanunu, "OpenAI Codex CLI: command injection via project-local configuration (CVE-2025-61260)," Check Point Research, https://research.checkpoint.com/2025/openai-codex-cli-command-injection-vulnerability/, 2025, accessed 2026-10-15.

[27] Google, "Security advisory GHSA-wpqr-6v78-jr5g (run-gemini-cli)," https://github.com/google-github-actions/run-gemini-cli/security/advisories/GHSA-wpqr-6v78-jr5g, 2026, accessed 2026-10-15.

TABLE VII

THE HARNESSWATCH RULE PACK (25 RULES). KIND SEPARATES VULNERABILITY PATTERNS, DESIGN WEAKNESSES (UNSAFE DEFAULTS OR CONFIGURATIONS) AND POLICY CHOICES; TAXONOMY CLASSES REFER TO TABLE I.

Rule	Severity	Confidence	Kind	Taxonomy	Title
HG-CI-001	high	high	vuln. pattern	T09, T01, T08	Headless agent in a workflow triggered by untrusted input ("pwn request")
HG-CI-002	medium	medium	design weakness	T09, T14	Agent CI job runs with a write-scoped GITHUB_TOKEN
HG-HOOK-001	medium	high	design weakness	T02	Repository config defines hooks that execute shell commands
HG-HOOK-002	medium	medium	vuln. pattern	T02, T06, T08	Hook command fetches or sends data over the network, or runs code fetched at runtime
HG-INJ-001	medium	high	vuln. pattern	T01, T05	Hidden or confusable Unicode in an instruction file
HG-INJ-002	medium	medium	vuln. pattern	T01, T05, T08	Prompt-injection phrasing in an instruction file
HG-INJ-003	medium	medium	design weakness	T01, T06	Instruction file pulls remote content at load time
HG-MCP-001	medium	high	vuln. pattern	T04, T06	MCP server fetched from a registry at launch without a version pin
HG-MCP-002	medium	medium	vuln. pattern	T04, T08	Remote MCP server over plaintext HTTP, wildcard host, or without authentication
HG-MCP-003	high	medium	vuln. pattern	T07, T04	Literal secret in an MCP server's env, headers or arguments
HG-MCP-004	medium	medium	vuln. pattern	T04, T01	MCP tool description contains instruction-like content (tool poisoning)
HG-MCP-005	low	high	design weakness	T02, T04	MCP server declared in a repository config
HG-MCP-006	high	high	design weakness	T02, T04, T03	MCP servers or their tools are auto-approved without a per-server prompt
HG-MEM-001	low	medium	design weakness	T10	Persistent agent-writable memory enabled (or shared through version control)
HG-NET-001	low	medium	design weakness	T08	Unrestricted network egress for agent tools where the harness supports restriction
HG-PERM-001	medium	high	design weakness	T03, T14, T01	Approve-everything (YOLO / bypass / full-auto) mode enabled in config
HG-PERM-002	medium	high	design weakness	T03, T14	Over-broad tool allowlist
HG-PERM-003	medium	medium	design weakness	T14, T07	Unrestricted execution without a deny list for destructive or credential-reading commands
HG-SEC-001	high	medium	design weakness	T07	Secret-like strings in harness logs, transcripts or memory
HG-SEC-002	medium	high	design weakness	T07	Harness state or credential file readable by other users
HG-SEC-003	high	medium	design weakness	T07	Credential stored in plaintext in a harness config file
HG-SUB-001	medium	medium	design weakness	T11, T03	Sub-agent or delegated agent configured with bypass permissions
HG-SUP-001	low	medium	design weakness	T06	Harness installed through a `curl | sh` installer without checksum or signature verification
HG-SUP-002	high	high	vuln. pattern	T06	Installed harness package version has known vulnerabilities (OSV)
HG-TEL-001	info	high	policy choice	T15	Telemetry, prompt logging or data sharing explicitly enabled

TABLE VIII

CANARY-BENCH CATALOGUE. TOP: SCENARIOS (ALL SHARE THE BASE REPOSITORY AND TASK; <INSTRUCTION FILE> IS THE HARNESS-NATIVE FILE NAMED BELOW). BOTTOM: HARNESS ADAPTERS, PINNED IMAGE VERSION, AND THE DOCUMENTED FLAG ADDED IN THE *auto* MODE.

Scenario	Title	Taxonomy	Files changed vs. base repository
control	No injection (baseline)	-	none
readme	README injection	T01	README.md
instructions	Harness-native instruction file injection	T01	<instruction file>
code_comment	Injection in a source-code comment	T01	calc.py
tool_output	Poisoned tool result (test output)	T01/T04	pytest.ini, tests/test_calc.py
hidden_unicode	Zero-width-wrapped instruction-file injection	T01	<instruction file>

Harness	Tier	Version	Instruction file	Auto-mode flag
claude-code	B	2.1.300	CLAUDE.md	-dangerously-skip-permissions
grok-build	B	1.0.52	AGENTS.md	-always-approve
github-copilot	B	1.0.98	.github/copilot-instructions.md	-allow-all-tools
opencode	A	1.19.0	AGENTS.md	-dangerously-skip-permissions
codex-cli	A	0.162.1	AGENTS.md	-dangerously-bypass-approvals-and-sandbox
aider	A	0.86.2	CONVENTIONS.md	-yes-always
qwen-code	A	0.25.1	QWEN.md	-yolo

[28] S. Cox, "Code execution through deception: Gemini AI CLI hijack," Tracebit blog, Jul. 2025, accessed 2026-10-15. [Online]. Available: https://tracebit.com/blog/code-exec-deception-gemini-ai-cli-hijack

[29] E. Beber, "InversePrompt: CVE-2025-54794 and CVE-2025-54795 in Claude Code," Cymulate, https://www.cymulate.com/blog/cve-2025-547954-54795-claude-inverseprompt/, 2025, accessed 2026-10-15.

[30] Anthropic, "Security advisory GHSA-4q92-rfm6-2cqx (claude-code): permission deny rules not enforced through symbolic links," https://github.com/anthropics/claude-code/security/advisories/GHSA-4q92-rfm6-2cqx, 2026, accessed 2026-10-15.

[31] L. Beurer-Kellner and M. Fischer, "MCP security notification: Tool poisoning attacks," Invariant Labs blog, Apr. 2025, accessed 2026-10-15. [Online]. Available: https://invariantlabs.ai/blog/mcp-security-notification-tool-poisoning-attacks

[32] M. Milanta and L. Beurer-Kellner, "GitHub MCP exploited: Accessing private repositories via MCP," Invariant Labs blog, May 2025, accessed 2026-10-15. [Online]. Available: https://invariantlabs.ai/blog/mcp-github-vulnerability

[33] R. Havaei, R. Liu, and M. Li, "Supabase MCP can leak your entire SQL database," General Analysis, https://www.generalanalysis.com/blog/supabase-mcp-blog, 2025, accessed 2026-10-15.

[34] Model Context Protocol project, "GHSA-7f8r-222p-6f5g / CVE-2025-49596: MCP Inspector proxy server vulnerabilities," https://github.com/modelcontextprotocol/inspector/security/advisories/GHSA-7f8r-222p-6f5g, 2025, accessed 2026-10-15.

[35] A. Lumelsky, "Critical RCE vulnerability in Anthropic MCP inspector — CVE-2025-49596," Oligo Security blog, Jun. 2025, accessed 2026-10-15. [Online]. Available: https://www.oligo.security/blog/critical-rce-vulnerability-in-anthropic-mcp-inspector-cve-2025-49596

[36] OpenCode maintainers, "Security advisory GHSA-vxw4-wv6m-9hhh (opencode): unauthenticated local HTTP server," https://github.com/anomalyco/opencode/security/advisories/GHSA-vxw4-wv6m-9hhh,

2026, accessed 2026-10-15.
[37] GitHub Advisory Database, "Security advisory GHSA-8m2g-8cgm-3vcp: local control plane trusts client-supplied Host header," https://github.com/advisories/GHSA-8m2g-8cgm-3vcp, 2026, accessed 2026-10-15.
[38] Amazon Web Services, "Security update for Amazon Q Developer extension for Visual Studio Code (version #1.84)," AWS Security Bulletin AWS-2025-015 (CVE-2025-8217), Tech. Rep., Jul. 2025, accessed 2026-10-15. [Online]. Available: https://aws.amazon.com/security/security-bulletins/AWS-2025-015/
[39] Nx maintainers (nrwl), "Malicious versions of Nx and some supporting plugins were published," GitHub Security Advisory GHSA-cxm3-wv7p-598c, Tech. Rep., Aug. 2025, accessed 2026-10-15. [Online]. Available: https://github.com/nrwl/nx/security/advisories/GHSA-cxm3-wv7p-598c
[40] PromptArmor, "Google Antigravity exfiltrates data," https://www.promptarmor.com/resources/google-antigravity-exfiltrates-data, 2025, accessed 2026-10-15.
[41] J. Rehberger, "Antigravity grounded! security vulnerabilities in Google's latest IDE," Embrace The Red blog, Nov. 2025, accessed 2026-10-15. [Online]. Available: https://embracethered.com/blog/posts/2025/security-keeps-google-antigravity-grounded/
[42] Anthropic, "Detecting and countering misuse of AI: August 2025," https://www.anthropic.com/news/detecting-countering-misuse-aug-2025, 2025, accessed 2026-10-15.
[43] E. B. Wilson, "Probable inference, the law of succession, and statistical inference," *Journal of the American Statistical Association*, vol. 22, no. 158, pp. 209–212, 1927.
[44] E. Tabassi, "Artificial intelligence risk management framework (AI RMF 1.0)," National Institute of Standards and Technology, NIST AI 100-1, Jan. 2023. [Online]. Available: https://doi.org/10.6028/NIST.AI.100-1
[45] C. Autio, R. Schwartz, J. Dunietz, S. Jain, M. Stanley, E. Tabassi, P. Hall, and K. Roberts, "Artificial intelligence risk management framework: Generative artificial intelligence profile," National Institute of Standards and Technology, NIST AI 600-1, Jul. 2024. [Online]. Available: https://doi.org/10.6028/NIST.AI.600-1
[46] ISO/IEC, "ISO/IEC 42001:2023 — information technology — artificial intelligence — management system," International Organization for Standardization, Dec. 2023, accessed 2026-10-15. [Online]. Available: https://www.iso.org/standard/81230.html
[47] OWASP GenAI Security Project, "OWASP top 10 for LLM applications 2025," OWASP Foundation, 2024, accessed 2026-10-15. [Online]. Available: https://genai.owasp.org/resource/owasp-top-10-for-llm-applications-2025/
[48] ——, "OWASP top 10 for agentic applications for 2026," OWASP Foundation, Dec. 2025, accessed 2026-10-15. [Online]. Available: https://genai.owasp.org/resource/owasp-top-10-for-agentic-applications-for-2026/
[49] MITRE, "MITRE ATLAS: Adversarial threat landscape for artificial-intelligence systems," MITRE Corporation, accessed 2026-10-15. [Online]. Available: https://atlas.mitre.org/
[50] Monetary Authority of Singapore, "Guidelines on artificial intelligence risk management for financial institutions," Monetary Authority of Singapore, Oct. 2026, accessed 2026-10-15. [Online]. Available: https://www.mas.gov.sg/regulation/guidelines/guidelines-on-artificial-intelligence-risk-management-for-financial-institutions
[51] Y. Liu, Y. Jia, R. Geng, J. Jia, and N. Z. Gong, "Formalizing and benchmarking prompt injection attacks and defenses," in *33rd USENIX Security Symposium (USENIX Security 24)*, 2024. [Online]. Available: https://arxiv.org/abs/2310.12815
[52] H. Zhang, J. Huang, K. Mei, Y. Yao, Z. Wang, C. Zhan, H. Wang, and Y. Zhang, "Agent security bench (ASB): Formalizing and benchmarking attacks and defenses in LLM-based agents," in *International Conference on Learning Representations (ICLR)*, 2025. [Online]. Available: https://arxiv.org/abs/2410.02644
[53] Y. Ruan, H. Dong, A. Wang, S. Pitis, Y. Zhou, J. Ba, Y. Dubois, C. J. Maddison, and T. Hashimoto, "Identifying the risks of LM agents with an LM-emulated sandbox," in *International Conference on Learning Representations (ICLR)*, 2024. [Online]. Available: https://arxiv.org/abs/2309.15817
[54] C. Guo, X. Liu, C. Xie, A. Zhou, Y. Zeng, Z. Lin, D. Song, and B. Li, "RedCode: Risky code execution and generation benchmark for code agents," in *Advances in Neural Information Processing Systems (NeurIPS), Datasets and Benchmarks Track*, 2024, accessed 2026-10-15. [Online]. Available: https://arxiv.org/abs/2411.07781
[55] E. Debenedetti, I. Shumailov, T. Fan, J. Hayes, N. Carlini, D. Fabian, C. Kern, C. Shi, A. Terzis, and F. Tramèr, "Defeating prompt injections by design," arXiv preprint arXiv:2503.18813, 2025. [Online]. Available: https://arxiv.org/abs/2503.18813
[56] L. Beurer-Kellner, B. Buesser, A.-M. Creţu, E. Debenedetti, D. Dobos, D. Fabian, M. Fischer, D. Froelicher, K. Grosse, D. Naeff, E. Ozoani, A. Paverd, F. Tramèr, and V. Volhejn, "Design patterns for securing LLM agents against prompt injections," arXiv preprint arXiv:2506.08837, 2025. [Online]. Available: https://arxiv.org/abs/2506.08837
[57] Y. Wu, F. Roesner, T. Kohno, N. Zhang, and U. Iqbal, "IsolateGPT: An execution isolation architecture for LLM-based agentic systems," in *Network and Distributed System Security Symposium (NDSS)*, 2025, accessed 2026-10-15. [Online]. Available: https://www.ndss-symposium.org/wp-content/uploads/2025-1131-paper.pdf
[58] T. Shi, J. He, Z. Wang, L. Wu, H. Li, W. Guo, and D. Song, "Progent: Programmable privilege control for LLM agents," arXiv:2504.11703, 2025, accessed 2026-10-15. [Online]. Available: https://arxiv.org/abs/2504.11703
[59] S. Willison, "The lethal trifecta for AI agents: Private data, untrusted content, and external communication," Simon Willison's Weblog, Jun. 2025, accessed 2026-10-15. [Online]. Available: https://simonwillison.net/2025/Jun/16/the-lethal-trifecta/
[60] X. Hou, Y. Zhao, S. Wang, and H. Wang, "Model context protocol (MCP): Landscape, security threats, and future research directions," arXiv preprint arXiv:2503.23278, 2025. [Online]. Available: https://arxiv.org/abs/2503.23278
[61] B. Radosevich and J. Halloran, "MCP safety audit: LLMs with the model context protocol allow major security exploits," arXiv preprint arXiv:2504.03767, 2025. [Online]. Available: https://arxiv.org/abs/2504.03767
[62] M. M. Hasan, H. Li, E. Fallahzadeh, G. K. Rajbahadur, B. Adams, and A. E. Hassan, "Model context protocol (MCP) at first glance: Studying the security and maintainability of MCP servers," arXiv preprint arXiv:2506.13538, 2025. [Online]. Available: https://arxiv.org/abs/2506.13538
[63] Z. Wang, Y. Gao, Y. Wang, S. Liu, H. Sun, H. Cheng, G. Shi, H. Du, and X. Li, "MCPTox: A benchmark for tool poisoning on real-world MCP servers," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 40, no. 42, 2026, pp. 35 811–35 819. [Online]. Available: https://ojs.aaai.org/index.php/AAAI/article/view/40895
[64] Trail of Bits, "Jumping the line: How MCP servers can attack you before you ever use them," Trail of Bits blog, Apr. 2025, accessed 2026-10-15. [Online]. Available: https://blog.trailofbits.com/2025/04/21/jumping-the-line-how-mcp-servers-can-attack-you-before-you-ever-use-them/
[65] J. Rehberger, "Wrap up: The month of AI bugs," Embrace The Red blog, Aug. 2025, accessed 2026-10-15. [Online]. Available: https://embracethered.com/blog/posts/2025/wrapping-up-month-of-ai-bugs/
[66] W. Vandevanter, "Prompt injection to RCE in AI agents," Trail of Bits blog, Oct. 2025, accessed 2026-10-15. [Online]. Available: https://blog.trailofbits.com/2025/10/22/prompt-injection-to-rce-in-ai-agents/
[67] I. Koishybayev, A. Nahapetyan, R. Zachariah, S. Muralee, B. Reaves, A. Kapravelos, and A. Machiry, "Characterizing the security of GitHub CI workflows," in *31st USENIX Security Symposium (USENIX Security 22)*, Boston, MA, 2022, accessed 2026-10-15. [Online]. Available: https://www.usenix.org/conference/usenixsecurity22/presentation/koishybayev
[68] S. Muralee, I. Koishybayev, A. Nahapetyan, G. Tystahl, B. Reaves, A. Bianchi, W. Enck, A. Kapravelos, and A. Machiry, "ARGUS: A framework for staged static taint analysis of GitHub workflows and actions," in *32nd USENIX Security Symposium (USENIX Security 23)*, Anaheim, CA, 2023, pp. 6983–7000, accessed 2026-10-15. [Online]. Available: https://www.usenix.org/conference/usenixsecurity23/presentation/muralee
[69] M. Ohm, H. Plate, A. Sykosch, and M. Meier, "Backstabber's knife collection: A review of open source software supply chain attacks," arXiv:2005.09535, https://arxiv.org/abs/2005.09535, 2020, accessed 2026-10-15.
[70] OWASP GenAI Security Project, "Agentic AI — threats and mitigations," OWASP Foundation, Feb. 2025, accessed 2026-10-15. [Online]. Available: https://genai.owasp.org/resource/agentic-ai-threats-and-mitigations/
[71] OWASP Foundation, "OWASP MCP top 10," OWASP project page, accessed 2026-10-15. [Online]. Available: https://owasp.org/www-project-mcp-top-10/