EX.2

```
---1
SELECT COUNT (*)
FROM `workspace`.`default`.`employeMARCH22`;
```

dd parameter

Results 2 of 2 → Table +

	count(1)
	10

```
---2
SELECT SUM (Salary)
FROM `workspace`.`default`.`employeMARCH22`
Where `Department ` = 'IT';
```

d parameter

Results 3 of 3 → Table +

	sum(Salary)
	220

```
---3
SELECT AVG (Salary)
FROM `workspace`.`default`.`employeMARCH22`
Where `Department ` = 'HR';
```

rameter

ults 4 of 4 → Table +

1.2 avg(Salary)
49.5

```
---4
SELECT MIN (Salary) AS Lowest_salary
FROM `workspace`.`default`.`employeMARCH22`;
```

rameter

ults 5 of 5 → Table +

123 Lowest_salary
48

```
17
18  SELECT MAX (Salary) AS Highest_salary
19  FROM `workspace`.`default`.`employeMARCH22`;
```

Add parameter

← Results 6 of 6 → Table +

	123 Highest_salary
1	62

1 row | 3.08s runtime

---5

SELECT `Department `, SUM(Salary) AS total_salary

FROM `workspace`.`default`.`employeMARCH22`

GROUP BY `Department `;

Table +

	Department	total_salary
1	IT	220
2	HR	99
3	Finance	60
4	MARKETING	105
5	FINANCE	59

---6

```
SELECT City ,COUNT(*) AS count_emplyees
FROM `workspace`.`default`.`employeMARCH22`
GROUP BY City;
```

Table +

	City	count_emplyees
1	New York	2
2	Chicago	3
3	Los Angeles	2
4	San Francisco	2
5	Houston	1

---7

```
SELECT `Department `, AVG(Salary) AS total_salary
FROM `workspace`.`default`.`employeMARCH22`
GROUP BY `Department `
ORDER BY AVG (Salary) DESC;
```

Table

	Department	total_salary
1	Finance	60
2	FINANCE	59
3	IT	55
4	MARKETING	52.5
5	HR	49.5

8.

```
SELECT `Department `, SUM(Salary) AS Total_Salary
FROM `workspace`.`default`.`employeezzz`
GROUP BY `Department `
ORDER BY SUM(Salary)>100000;
```

rameter

Department	Total_Salary
null	null
HR	99
IT	220
Finance	60
MARKETING	105
FINANCE	59

9.

```sql
SELECT `Department `, AVG(Salary) AS Average_Salary
FROM `workspace`.`default`.`employeezzz`
GROUP BY `Department `
ORDER BY Average_Salary DESC
Limit 1;
```

parameter

Department	Average_Salary
Finance	60

10.

```sql
SELECT City, COUNT(*) AS Total_employees
FROM `workspace`.`default`.`employeezzz`
GROUP BY City
HAVING count(*)>1
ORDER BY Total_employees DESC;
```

parameter

City	Total_employees
Chicago	3
New York	2
Los Angeles	2
San Francisco	2