

SK417 BLOCK

Sarawak, Malaysia

 FAULT SEAL EVALUATION

Fault Seal Analysis

SK417 Block

Additional Prospect Evaluation | February 2019

 ZARINA-1 AREA — FAULT F8 / F9

•  BARONIA DEEP — FAULT F13

•  15 FEBRUARY 2019

Study Overview & Objectives

Fault seal integrity assessed across two key prospect areas using multi-method geomechanical analysis



PROSPECT AREAS

Zarina-1 & Baronia Deep

Zarina-1 area — Fault F8/F9 South across Intra C VIII, Lower C VIII & Upper C VII cycles. **Baronia Deep** — Fault F13 with Zarina-1 as analogue well (fully marine neritic EOD).



METHOD 1

Allen Diagram Analysis

Juxtaposition mapping of **sand-on-sand** and **shale contacts** across fault planes. Identifies seal vs. leak windows for each reservoir cycle at the fault interface.



METHOD 2

Shale Gouge Ratio (SGR)

SGR triangle methodology quantifies **fault seal capacity** and leakage risk. Hangingwall leakage analysis applied to assess hydrocarbon column height potential per cycle.




METHOD 3

Trap Risk Assessment

Fault aspect ratio analysis across **N = 129 faults** evaluates structural integrity and reactivation risk, providing a statistical basis for trap confidence ranking.

Gouge Ratio at reservoir overlaps



ALLEN DIAGRAM — FAULT F9 SOUTH

ALLEN DIAGRAM ANALYSIS

Fault F9 Seal Assessment

Zarina-1 Area — SK417 Block

METHODOLOGY

Allen Diagram juxtaposition analysis combined with Shale Gouge Ratio (SGR) triangles applied across three stratigraphic cycles: **Intra C VIII**, **Lower C VIII**, and **Upper C VII**. Well log hung at Hangingwall position.

SGR VALUES BY CYCLE

Stratigraphic Cycle	SGR Range	Seal Quality
Intra C VIII	0.47 – 0.62	Moderate – Good
Lower C VIII	0.28 – 0.67	Fair – Good
Upper C VII	0.45 – 0.82	Moderate – Strong

JUXTAPOSITION TYPES IDENTIFIED

Shale / Shale

Sand / Shale

Shale / Sand

Sand / Sand (SGR fill)

REGIONAL INFERENCE


KEY INSIGHT

By analogy with **Fault F8** (comparable fault throw), sealing properties of Fault F9 are inferred for surrounding faults in the Zarina-1 area, supporting regional trap integrity assessment.

Zarina-1 — HC Column Potential (Fault F9)

FAULT SEAL LEAKAGE ANALYSIS · HANGINGWALL · THREE RESERVOIR CYCLES

HYDROCARBON COLUMN POTENTIAL — MIN / MAX RANGE (METRES)



CYCLE METRICS SUMMARY

INTRA C VIII — STRONGEST SEAL

JUXTAPOSITION COS	SGR RANGE
0.67	0.47 – 0.62
OIL COLUMN	GAS COLUMN
524 – 687 m	189 – 247 m
RETENTION PRESSURE	
13.5–21 bar (Murray) · 16–21 bar (Yielding)	

LOWER C VIII — VARIABLE SEAL

JUXTAPOSITION COS	SGR RANGE
0.20	0.28 – 0.67
OIL COLUMN	GAS COLUMN
164 – 769 m	59 – 277 m
RETENTION PRESSURE	
4–23.5 bar (Murray) · 5–23 bar (Yielding)	

UPPER C VII — HIGH RETENTION RANGE

JUXTAPOSITION COS	SGR RANGE
0.06	0.45 – 0.82
OIL COLUMN	GAS COLUMN
491 – 1,015 m	177 – 365 m
RETENTION PRESSURE	
12.5–31 bar (Murray) · 15–27 bar (Yielding)	

KEY INSIGHT

Intra C VIII shows the highest COS (0.67), confirming the strongest seal integrity. Upper C VII offers the widest oil column range (up to 1,015 m) driven by elevated SGR.

Fault F13 Analysis

Deeper Rollover Anticline — Baronia Deep_A (Upper C VII)



Fault F13 Seals Baronia Deep Rollover Anticline

Fault F13 controls the structural closure of the Baronia Deep_A horizon (yellow reflector) in the hangingwall of the Baronia-19 well area.



Analogue Well: Zarina-1 (Marine Neritic EOD)

Zarina-1 used as calibration analogue due to equivalent depositional environment — fully marine neritic — ensuring comparable SGR and seal capacity estimates.



Maximum Gas Extent ~250m at Top Baronia Deep A

Retention pressure analysis constrains the maximum possible gas column to approximately 250m at the Top Baronia Deep_A structural crest.



Upper C VII Cycle — SGR 0.53–0.62 (Allen Diagram)

Allen Diagram juxtaposition and SGR analysis for Upper C VII confirms good seal integrity across Fault F13 with SGR values of 0.53–0.62.



Key Insight: Fault F13 demonstrates comparable sealing performance to Fault F9 (Intra C VIII), supporting viable HC column potential for the Baronia Deep_A prospect using Zarina-1 as a calibrated analogue.

mic Data in Oil and Gas Ex

SEISMIC INTERPRETATION

Fault F13 — Baronia Deep_A

Baronia Deep — HC Column Potential (Fault F13)

UPPER C VII · HANGINGWALL

JUXTAPOSITION COS

0.61

Chance of Seal — Upper C VII
Good seal integrity confirmed

SGR RANGE

0.53 – 0.62

Shale Gouge Ratio
Moderate–strong clay smear

OIL COLUMN POTENTIAL

596 – 701 m


Murray 2003 / Yielding 2002
Upper C VII cycle

GAS COLUMN POTENTIAL

214 – 252 m

Murray 2003 / Yielding 2002
Upper C VII cycle

RETENTION PRESSURE & HC COLUMN COMPARISON — FAULT F13 VS FAULT F9




Key Finding: Fault F13 (Upper C VII) demonstrates **comparable or superior sealing performance** to Fault F9 Intra C VIII — oil column potential of **596–701m** vs 524–687m, with retention pressures of **16.5–21.4 bar** confirming robust seal integrity for the Baronia Deep prospect.

Trap Risk — Fault Segmentation Assessment

ASPECT RATIO SCREENING FRAMEWORK · SK417 BLOCK

FAULTS ANALYZED

N = 129



Conceptual Basis: Continuous single fault = valid lateral seal and trap. Discontinuous en-echelon fault array with relay ramps = breached seal, no trap. This rapid screening framework was applied to all **N=129 SK417 faults** to systematically rank prospect risk.

Key Findings & Investment Highlights

SK417 BLOCK
February 2019



Zarina-1 Area — Fault F9

INTRA C VIII · LOWER C VIII · UPPER C VII

SGR RANGE

0.28–0.82

All cycles

MAX OIL COLUMN

1,015 m

Upper C VII

MAX GAS COLUMN

365 m

Upper C VII



Baronia Deep — Fault F13

UPPER C VII · ROLLOVER ANTICLINE

SGR RANGE

0.53–0.62

Upper C VII

OIL COLUMN

596–701 m

Murray / Yielding

GAS COLUMN

214–252 m

Murray / Yielding

✓ KEY CONCLUSIONS

- **Robust seal integrity** confirmed on both prospects via Allen Diagram, SGR, and leakage analysis.
- **Fault F9** (Zarina-1) delivers exceptional retention — up to **1,015m oil column** in Upper C VII.
- **Fault F13** (Baronia Deep) shows comparable sealing performance with **596–701m oil column** potential.
- Multiple **stacked reservoir targets** (3 cycles) with proven analogue well control from Zarina-1.

Systematic Trap Risk Framework



Aspect ratio screening of **N = 129 SK417 faults** provides a rapid, rigorous prospect risking methodology — enabling consistent portfolio-wide trap confidence ranking.

★ SK417 BLOCK — COMPELLING EXPLORATION UPSIDE SUPPORTED BY RIGOROUS GEOMECHANICAL ANALYSIS