


		T	Т	
1	Base	5-DWT-1685-01	A6061	1
2	Fixture for boot	5-DWT-1685-02	White	1
			POM	
3	Clamp	5-DWT-1685-03	White	1
			POM	
4	Fixture for adapter	5-DWT-1685-04	White	1
			POM	
5	Stopper	5-DWT-1546-05	White	1
			POM	
6	Jig_Tripping	5-DWT-1212	N/A	1
	cross-grooved			
7	Linear guide	SSEBV10-55	N/A	1
8	Toggle clamp	MC08-1	N/A	1
9	Cord head		N/A	1
10	Head socket cap screw	M3x10	SUS304	5
11	Plain washer	ISO 7092 - ST 5 - 140	SUS304	4
		HV		
12	Spring washer	DIN 128 - A5	SUS304	4
13	Head socket cap screw	M5x12	SUS304	4
14	Head socket cap screw	M3x16	SUS304	5
15	Head socket cap screw	M3x20	SUS304	4
16	Countersunk Flat	M3x10	SUS304	1
	Head Screw			
17	Set screw	M3x5	SUS304	2
18	Magnet	Ø12	N/A	1
19	Magnet	Ø4	N/A	2
20	Adapter		N/A	1
21	Plain washer	ISO 7092 - ST 3 - 140	SUS304	4
		HV		
22	Spring washer	DIN 128 - A3	SUS304	4
23	Shaft	D=2mm, L=22mm	Copper	1
No.	Part name/ Description	Model/ Part No.	Material	Quantit


FUJIKURA FIBER OPTICS VIETNAM						
Drawing number: 5-DWT-1685	Scale					
Housing tool for Meta product	1:2					





- No shape edge, no burr


Chamfer 0.2mm to all edges not mentioned
Refer 3D drawing with dimensions not mentioned


	Straightness, Fa	tness, Parallel	Angle tol	erance	Size tole	erance	Material	A6061	Scale	1:2.5
	Length (mm)	Deviation	Angle (°)	Tolerance	Length (mm)	Tolerance	FUJIKURA FIBER OPTICS VIETNA			
	0.5<,≤3	±0.2	≤10	±1°	0.5<,≤6	±0.05	Drawing nur		- 04	
	3<,≤6	±0.5	10<,≤50	±0°30'	6<,≤30	±0.1		5-DWT-168!	5-01	
Ì	>6	±1	50<,≤120	±0°20'	30<,≤120	±0.15	Drawing nar			
	70	11	120<,≤400	±0°10'	120<,≤400	±0.2		Base		











*Note:

- No shape edge, no burr Chamfer 0.2mm to all edges not mentioned Refer 3D drawing with dimensions not mentioned

Straightness, Fa	tness, Parallel	Angle tol	erance	Size tole	erance	Material White POM Sca		Scale	2:1
Length (mm)	Deviation	Angle (°)	Tolerance	Length (mm)	Tolerance	FUJIK	URA FIBER OPTI	CS VIET	NAM
0.5<,≤3	±0.2	≤10	±1°	0.5<,≤6	±0.05	Drawing nui		- 00	
3<,≤6	±0.5	10<,≤50	±0°30'	6<,≤30	±0.1	5-DWT-1685-03			
>6	±1	50<,≤120	±0°20'	30<,≤120	±0.15	Drawing nar			
>0		120<,≤400	±0°10'	120<,≤400	±0.2		Clamp		

