SCREEN GLOBAL

API Middleware SG 3.0

Integration Guide

Complete REST API reference for integrating client applications with the Avvanz Screen Global background verification platform.

Document Version	V1.9
API Version	v1
Authentication	OAuth 2.0 / Bearer Token
Date	24 Sep 2026
Classification	Confidential

Table of Contents

1. Introduction

2. Authentication & Security

- 2.1 OAuth 2.0 Client Credentials Grant
- 2.2 Token Expiry & Rotation
- 2.3 Passing Credentials
- 2.4 Security Requirements

3. API Environments

4. Request Headers & Formats

5. Rate Limits & Retry Policy

6. Error Handling

7. Pagination

8. Timezones

9. Pricing & Currency Rules

10. Case Lifecycle

11. Idempotency & Duplicate Case Prevention

12. Checks, Sub-Checks & Country Selection

13. Report API — Choosing the Right Stream

14. Polling vs Webhooks

15. API Reference

- 15.1 Get Token
- 15.2 Get Packages
- 15.3 Get Branches
- 15.4 Create Case - with Package
- 15.5 Get All Cases
- 15.6 Update Candidate Info
- 15.7 Get Case Status
- 15.8 Get Case Checks Status
- 15.9 Cancel Case
- 15.10 Case Final Report — PDF Stream
- 15.11 Case Final Report — Base64
- 15.12 Case Final Report — JSON
- 15.13 Get Case Price
- 15.14 Get Paid Invoice

15.15 List Check Categories
15.16 Get Checks by Category
15.17 Get Country Items for a Check
15.18 Get Sub-Checks for a Check
15.19 Create Case with Checks
15.20 Case Status Update Webhook

16. Webhook Registration & Event Catalogue

1. Introduction

API Middleware – SG 3.0 provides REST APIs that allow client applications, such as HRMS or ATS platforms, to integrate with ScreenGlobal to run background verification checks without leaving their own application. This guide covers authentication, environments, request requirements, error handling, rate limits, webhooks, and all API endpoints currently available in API Middleware – SG 3.0.

2. Authentication & Security

2.1 OAuth 2.0 Client Credentials Grant

API Middleware – SG 3.0 uses the OAuth 2.0 Client Credentials grant type (grant_type=client_credentials). This grant is designed for machine-to-machine (M2M) integrations where no end-user interaction is required. Your server-side application exchanges a client_id and client_secret directly for a Bearer access token.

> No user login is involved. The token represents your application (company account), not an individual user. Do not use Authorization Code or Implicit flows.

2.2 Token Expiry & Rotation

Property	Detail
Token lifetime	Tokens are valid for 480 minutes (8 hours) from the time of issuance.
Previous token revocation	Calling POST /api/v1/auth/token automatically revokes any previously active token for your account before issuing a new one. Only one active token exists per account at any time.
Recommended practice	Cache the token and reuse it until it expires. Re-request a new token when you receive a 401 Unauthorized response. Do not call Get Token on every API request.
Token revocation endpoint	POST /api/v1/auth/revoke — explicitly invalidates the current token. Call this on application shutdown or when rotating credentials.

2.3 Passing Credentials

Credentials are passed differently depending on the context:

Context	How to Pass
Obtaining a token (Get Token)	Send client_id and client_secret as a JSON body in a POST request to /api/v1/auth/token. Do not put them in the URL or query string.
All other API endpoints	Include the Bearer token in the Authorization header: Authorization: Bearer <access_token>
Webhook trigger endpoint (15.20)	Uses HTTP Basic Auth: Authorization: Basic base64(client_id:client_secret). This is separate from the Bearer token flow.

> Never include client_id, client_secret, or Bearer tokens in URLs, query strings, or client-side code. Always transmit over HTTPS.

2.4 Security Requirements

Requirement	Detail
Transport security	All API calls must use HTTPS (TLS 1.2 or higher). Plain HTTP requests will be rejected.
Credential storage	Store client_id and client_secret in environment variables or a secrets manager (e.g. AWS Secrets Manager, HashiCorp Vault). Never commit them to source control.
Token storage	Store access tokens in server-side memory or a secure cache. Do not persist tokens to disk or expose them to browser clients.
Webhook signature verification	When using HMAC auth type, always verify the X-Avvanz-Signature header before processing webhook payloads. Reject requests with invalid or missing signatures.
IP allowlisting	Contact Avvanz to restrict API access to your server IP ranges.
Credential rotation	Rotate client_secret periodically. Contact Avvanz to issue new credentials. Revoke the old token immediately after rotation.

3. API Environments

Environment	Base URL	Purpose
Production	https://middleware.avvanz.com	Live integration. Real cases and billing apply.
Staging	https://staging-middleware.avvanz.com	Development and testing. No real billing. Use separate staging credentials provided by Avvanz.

> Staging credentials are not valid on Production and vice versa. Always verify your base URL before deploying.

4. Request Headers & Formats

The Content-Type header value depends on the endpoint. Each endpoint in Section 15 explicitly states its request format. The table below summarises the two formats used across this API:

Format	Content-Type Header	When Used
JSON	application/json	All POST/PUT endpoints except where noted. Body is a JSON object.
Form Data	multipart/form-data	Not used in the current API version. All request bodies are JSON.

Header	Value	Description
Content-Type	application/json	Required for all POST/PUT requests with a body.
Accept	application/json	Specifies that the client expects a JSON response.
Authorization	Bearer <access_token>	Required for all endpoints except Get Token. Obtain the token via 15.1.

> All request bodies in this API are JSON. Despite any earlier ambiguity, multipart/form-data is not used. Always send Content-Type: application/json with a JSON-encoded body for POST and PUT requests.

5. Rate Limits & Retry Policy

Rate Limits

Limit Type	Limit	Scope
General API requests	60 requests / minute	Per company account (token)
Get Token	60 requests / minute	Per IP address
Create Case / Create Case with Checks	60 requests / minute	Per company account
Report endpoints (PDF/Base64/JSON)	60 requests / minute	Per company account

When a rate limit is exceeded, the API returns 429 Too Many Requests with a Retry-After header indicating the number of seconds to wait before retrying.

Client-Side Retry Policy

Scenario	Recommended Action
429 Too Many Requests	Wait for the value in the Retry-After header, then retry. Use exponential backoff if Retry-After is absent.
500 / 502 / 503 / 504 server errors	Retry up to 3 times with exponential backoff: 1s, 2s, 4s. If all retries fail, log and alert.
401 Unauthorized	Re-fetch a new token via Get Token, then retry the original request once.
400 / 422 validation errors	Do not retry. Fix the request payload based on the error details returned.
Network timeout	Retry up to 3 times with exponential backoff. Use event_id to prevent duplicate case creation (see Section 11).

> For case-creation endpoints, always include an event_id before retrying to prevent duplicate cases. See Section 11.

6. Error Handling

All error responses follow a consistent JSON structure:

```
{
    "success": false,
    "message": "Human-readable error description.",
    "errors": { "field_name": ["Validation message."] }, // present on 422 only
    "status_code": 422,
    "status text": "Unprocessable Entity"
}
```

HTTP Status	Meaning	Common Causes & Action
200 OK	Success	Request processed successfully.
201 Created	Resource created	Case or resource was created. Check data.case_id in the response.
400 Bad Request	Malformed request	Request body is not valid JSON, or required headers are missing. Fix the request before retrying.
401 Unauthorized	Authentication failed	Token is missing, expired, or revoked. Re-fetch a token via Get Token and retry.
403 Forbidden	Access denied	Your account does not have permission for this resource (e.g. accessing another company's case). Do not retry.
404 Not Found	Resource not found	The case_id, check_id, or other ID does not exist or does not belong to your account. Verify the ID.
409 Conflict	Duplicate resource	A case with the same event_id already exists. The existing case is returned. Do not create a new case.
422 Unprocessable Entity	Validation failed	One or more fields failed validation. The errors object contains field-level messages. Fix the payload.
429 Too Many Requests	Rate limit exceeded	Too many requests in the current window. Wait for Retry-After seconds and retry.
500 Internal Server Error	Server error	Unexpected server-side error. Retry with exponential backoff. If persistent, contact Avvanz support with the request timestamp.
502 Bad Gateway	Upstream error	The middleware could not reach an upstream service. Retry with backoff.
503 Service Unavailable	Maintenance / overload	Service is temporarily unavailable. Retry after the Retry-After interval.

> The errors field is only present on 422 responses and contains a map of field names to arrays of validation messages.

7. Pagination

Endpoints that return lists (Get All Cases, Get Paid Invoice) support cursor-based pagination via offset and limit query parameters.

Parameter	Type	Default	Maximum	Description
offset	Integer	0	—	Zero-based record offset. The first page starts at 0.
limit	Integer	20	100	Number of records to return per request. Values above 100 are clamped to 100.

To paginate through all records, increment offset by limit on each request until the returned data array is empty or contains fewer records than limit.

```
// Page 1: offset=0&limit=50
// Page 2: offset=50&limit=50
// Page 3: offset=100&limit=50 (stop when data.length < 50)
```

> The response does not include a total record count. Use the length of the returned data array to detect the last page.

8. Timezones

Context	Timezone
All API request/response timestamps	UTC (Coordinated Universal Time)
Date-only fields (e.g. date_from, date_to, paid_date)	Calendar date in UTC. Format: YYYY-MM-DD
DateTime fields (e.g. case_created_date, created_at)	UTC. Format: YYYY-MM-DD HH:MM:SS

> Convert all timestamps to your local timezone on the client side. When filtering by date range, account for UTC offset to avoid missing records near midnight boundaries.

9. Pricing & Currency Rules

Rule	Detail
Default currency	Each company account has a default currency configured by Avvanz. All pricing responses fall back to this currency when no currency parameter is provided or the provided code is invalid.
Currency parameter	Pass an ISO 4217 three-letter code (e.g. USD, SGD, MYR) in the currency query parameter on supported endpoints (Get Packages, Get Sub-Checks).
Exchange rates	Currency conversion uses exchange rates maintained by Avvanz. Rates are updated periodically. Converted prices are indicative; invoices are always issued in your account's billing currency.
Price format	All price values are returned as strings with two decimal places (e.g. "80.00"). Parse as decimal/float on the client side.
Discount pricing	Where applicable, both regular_price and discount_price are returned. The discount_price is the price your account will be charged.
Tax	Tax (GST/VAT) is shown separately in pricing breakdowns where applicable. The total_due field includes tax.
Invoice currency	Invoices are always issued in your account's billing currency regardless of the currency parameter used in API calls.

10. Case Lifecycle

A background verification case moves through the following statuses from creation to completion. Understanding the lifecycle helps you determine when to poll, when to expect webhooks, and which actions are permitted at each stage.

Status	Description	Permitted Actions
Insufficient Data	Case created. Candidate has not yet submitted their information (when candidate_data_entry=1).	Cancel Case, Update Candidate Info
Ready For Checkout	Candidate data is complete. Case is awaiting payment/checkout confirmation.	Get Case Price, Cancel Case
Processing	Case has been checked out and background verification is in progress.	Get Case Status, Get Case Checks Status, Poll or receive webhooks
Completed	All checks are finished. Final report is available.	Download Final Report (PDF/Base64/JSON)
Cancelled	Case was cancelled before processing began.	Read-only

```
Case Created (Insufficient Data) → Candidate submits data → Ready For Checkout → Checkout confirmed → Processing → All checks complete → Completed
→ [At any pre-processing stage] Cancel → Cancelled
```

> Cases that have reached Processing or Completed status cannot be cancelled via the API. Contact Avvanz support for exceptional cancellations.

> Individual checks within a case have their own statuses: Pending, In Progress, Completed, Unable to Verify. Use Get Case Checks Status (15.8) to monitor per-check progress.

11. Idempotency & Duplicate Case Prevention

Network failures or timeouts can cause your client to retry a case-creation request without knowing whether the original request succeeded. To prevent duplicate cases, use the event_id field.

Field	Endpoints	Behaviour
event_id	Create Case (15.4), Create Case with Checks (15.19)	A unique identifier from your system (e.g. your internal job ID or UUID). If a case with the same event_id already exists for your account, the API returns 409 Conflict with the existing case details instead of creating a duplicate.

> Best practice: Always generate a unique event_id (e.g. UUID v4) for every case-creation attempt. On retry after a timeout, reuse the same event_id. If you receive a 409, use the returned case_id to continue the workflow — the case was already created successfully.

```
// First attempt (or retry after timeout) - same event_id
{
  "first_name": "John",
  "last_name": "Doe",
  "email": "john.doe@example.com",
  "phone_no": "+6591234567",
  "package": "Basic Package",
  "event_id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890"
}

// If 409 is returned:
// { "success": false, "message": "Duplicate event_id.", "data": { "case_id": 733,
"case_ref_no": "tpj4913" } }
// Use case_id 733 to continue - no new case was created.
```

12. Checks, Sub-Checks & Country Selection

When building a case using Create Case with Checks (15.19), you must correctly specify checks, sub-checks, and countries. This section explains the hierarchy and selection rules.

Check Hierarchy

```
Check Category (e.g. "Education") → Check (e.g. "Education Verification", check_id=12) → Country (e.g. "Singapore", country_id=192) → Sub-Check (e.g. "Standard Education", subcheck_id=7)
```

How to Select Checks

Step	Endpoint	What You Get
1. Browse categories	GET /api/v1/checks/categories	List of check categories with category_id
2. Get checks	GET /api/v1/checks?category_id=X	List of checks with check_id and turnaround_days
3. Get country items	GET /api/v1/checks/{check_id}/country-items	Countries available for this check, including the worldwide country_id if applicable
4. Get sub-checks	GET /api/v1/checks/{check_id}/{country_id}/sub-checks	Sub-checks and pricing for the check+country combination

Check Selection Rules

Rule	Detail
One criterion per check	Each check in the checks array requires exactly one of: country_id, years_of_coverage, no_of_qualification, or no_of_employer — whichever that check accepts. Providing an unsupported field returns a 422 error.
Sub-check required when applicable	subcheck_id is required when using country_id and the check has a non-empty sub-check list for that country. If the sub-check list is empty, omit subcheck_id.
Worldwide checks	Some checks apply globally regardless of country. For these, use the worldwide country_id returned by Get Country Items. Do not use a specific country ID for worldwide checks.
years_of_coverage	Minimum value: 2. Used for checks like employment or credit history that cover a time period.
no_of_qualification	Minimum value: 1. Used for education checks where multiple qualifications are verified.
no_of_employer	Minimum: 1, Maximum: 5. Used for employment checks where multiple employers are verified.

> Use Get Sub-Checks (15.18) to confirm which fields a check accepts and what pricing applies before building your Create Case with Checks request.

13. Report API — Choosing the Right Stream

Three endpoints deliver the final verification report. All three require the case to be in Completed status. Choose based on your integration's needs:

Stream	Endpoint	Response Format	Best For
PDF Stream	GET /api/v1/case/final-report-pdf-stream/{case_id}	Raw binary PDF (application/pdf)	Displaying or downloading the report directly in a browser; saving to disk or cloud storage; sending as an email attachment. No JSON wrapper — the response body is the raw PDF bytes.
Base64	GET /api/v1/case/final-report-base64/{case_id}	JSON with Base64-encoded PDF string	Embedding the PDF in a JSON API response; storing in systems that do not support binary streams; transmitting the PDF within a larger JSON payload to another service.
JSON	GET /api/v1/case/final-report-json/{case_id}	Structured JSON with verified field values	Pulling verified results directly into your HRMS record without parsing a PDF; programmatic comparison of candidate-submitted vs verified data; building custom report views in your application.

Summary: Use PDF Stream when you need the formatted report document. Use Base64 when you need to embed the PDF in a JSON payload. Use JSON when you need machine-readable verified data to update your own records.

All three report endpoints return a 404 if the case is not yet Completed. Check case status via 15.7 before requesting the report.

14. Polling vs Webhooks

Two mechanisms are available to track case progress. The right choice depends on the event type and your integration architecture.

Mechanism	How It Works	Best For	Limitations
Polling	Your system periodically calls Get Case Status (15.7) or Get Case Checks Status (15.8) to check the current state.	Simple integrations; cases where near-real-time notification is not required; fallback when webhooks are unavailable.	Introduces latency proportional to polling interval; consumes rate limit quota; not suitable for high-volume integrations.
Webhooks	Avvanz pushes a notification to your registered URL when a case status changes.	Real-time or near-real-time notification of case completion; high-volume integrations; triggering downstream workflows automatically.	Requires a publicly accessible HTTPS endpoint on your side; requires webhook registration with Avvanz; delivery is not guaranteed without retry handling.

Recommended Polling Frequency

Case Stage	Recommended Interval	Rationale
Insufficient Data / Ready For Checkout	Every 5–10 minutes	Status changes depend on candidate action; frequent polling adds no value.
Processing (checks in progress)	Every 15–30 minutes	Background checks typically take hours to days. Polling more frequently wastes quota.
Awaiting Completed status	Every 30–60 minutes	Use webhooks instead if possible for immediate notification.

> Recommendation: Register a webhook for case.created, case.submitted, and case.completed events and use polling only as a fallback or for status checks during the Processing stage. See Section 16 for webhook registration.

15. API Reference

#	API	Method	Purpose
1	Get Token	POST	Authenticate and obtain a Bearer access token
2	Get Packages	GET	Retrieve available company packages with per-check pricing
3	Get Branches	GET	Retrieve available company branches
4	Create Case	POST	Create a background verification case using a package
5	Get All Cases	GET	Retrieve a paginated list of created cases
6	Update Candidate Info	PUT	Update candidate information on an existing case
7	Get Case Status	GET	Retrieve case status and details
8	Get Case Checks Status	GET	Retrieve status of all checks within a case
9	Cancel Case	PUT	Cancel a case (Insufficient Data / Ready For Checkout only)
10	Case Final Report — PDF Stream	GET	Download the final report as a PDF stream
11	Case Final Report — Base64	GET	Retrieve the final report Base64-encoded
12	Case Final Report — JSON	GET	Retrieve the final report as structured JSON
13	Get Case Price	GET	Retrieve case pricing / checkout breakdown
14	Get Paid Invoice	GET	Retrieve a list of paid invoices
15	List Check Categories	GET	Retrieve all active check categories
16	Get Checks by Category	GET	Retrieve available checks, optionally filtered by category
17	Get Country Items for a Check	GET	Retrieve available countries and pricing for a specific check
18	Get Sub-Checks for a Check	GET	Retrieve sub-checks and pricing for a specific check
19	Create Case with Checks	POST	Create a case using individually selected checks
20	Case Status Update Webhook	POST	Receive a case status update notification

15.1 Get Token

First required call for every integration. Exchanges your client_id and client_secret for a Bearer access token used on all subsequent requests. Any previously active token is automatically revoked before the new token is issued. See Section 2 for full authentication details.

```
POST /api/v1/auth/token
```

Request Format: application/json — No Authorization header required.

Request Body

Field	Type	Description	Required
client_id	String	Provided by Avvanz	**Yes**
client_secret	String	Provided by Avvanz	**Yes**

Sample Request

```
POST /api/v1/auth/token
Content-Type: application/json

{
    "client_id": "<your_client_id>",
    "client_secret": "<your_client_secret>"
}
```

Sample Response (200 OK)

```
{
    "success":  true,
    "message": "Login success",
    "token_type": "Bearer",
    "access_token": "<access_token>",
    "status_code": 200,
    "status_text": "OK"
}
```

> The access_token is valid for 60 minutes (1 hour). Cache it and reuse it. Do not call this endpoint on every request.

Error Responses

Status	Cause
401	Invalid client_id or client_secret.
422	Missing required fields.

15.2 Get Packages

Returns the list of packages configured for your company account, including a per-check pricing breakdown. Use the returned package_name or package_id in Create Case (15.4).

```
GET /api/v1/package
```

Request Format: No request body. Query parameters only.

Query Parameters

Field	Type	Description	Required
currency	String	ISO 4217 code (e.g. USD, SGD). Falls back to company default if invalid or omitted.	No

Package Rules

Rule	Detail
Package contents	Each package contains a pre-configured set of checks. The checks, countries, and coverage parameters are fixed by the package definition. You cannot add or remove checks from a package via the API.
Package pricing	Each check within a package shows both regular_price and discount_price. Your account is charged the discount_price.
Country in package	If a check in the package has a pre-selected country, the country field in the response shows that country. If country is null, you must supply the country field in Create Case.
Custom checks	To select checks individually (not from a package), use Create Case with Checks (15.19) instead.

Sample Response (200 OK)


```
{
    "success": true,
    "message": "Company packages has been retrieved.",
    "data": [
       {
         "package_id": 10,
         "package_name": "Basic Package",
         "checks": [
           {
             "check_id": 5,
             "check_name": "Employment Verification",
             "country": "Singapore",
             "years_of_coverage": null,
             "no_of_qualification": null,
             "no_of_employment": null,
             "currency": "SGD",
             "regular_price": "80.00",
             "discount_price": "60.00"
           }
         ]
       }
    ],
    "status_code": 200,
    "status_text": "OK"
}
```

15.3 Get Branches

Returns the list of active branches configured for your company account. Use the returned branch_id or branch_name in Create Case to associate a case with a specific branch.

```
GET /api/v1/company-branches
```

Request Format: No request body or query parameters.

Sample Response (200 OK)

```
{
    "success": true,
    "message": "Company branches has been retrieved.",
     "data": [
       { "branch_id": 1512, "branch_name": "Branch 1" }
    ],
    "status_code": 200,
    "status_text": "OK"
}
```

15.4 Create Case - with Package

Creates a new background verification case for a candidate using a selected package. If candidate_data_entry is 1, a welcome email is sent to the candidate with a link to fill in their own information.

```
POST /api/v1/case
```

Request Format: application/json

Request Body

Field	Type	Description	Required
first_name	String(100)	First name of the candidate	**Yes**
middle_name	String(100)	Middle name of the candidate	No
last_name	String(100)	Last name. Required unless no_last_name=1	**Conditional**
no_last_name	Enum(0,1)	1 = candidate has no last name	No
email	String(100)	Candidate email address	**Yes**
phone_no	String(50)	Candidate contact number	**Yes**
package	String(100)	Package name or ID from Get Packages	**Yes**

Field	Type	Description	Required
branch	String(100)	Branch name or ID from Get Branches	No
candidate_data_entry	Enum(1,2)	1 = candidate fills data (welcome email sent), 2 = employer fills data	No
country	String(200)	Candidate country. Required if the package has no pre-selected country.	**Conditional**
event_id	String(100)	Your unique internal event ID. Used for idempotency — prevents duplicate cases on retry. See Section 11.	No
event_ref_no	String(150)	Your internal event reference number	No
employee_id	String(100)	Your internal employee ID	No
cost_center	String(100)	Client cost centre	No
bu	String(150)	Business unit name	No
requestor_name	String(150)	Name of the person requesting the case	No
requestor_email	String(100)	Email of the person requesting the case	No

Sample Request

```
POST /api/v1/case
Authorization: Bearer <access_token>
Content-Type: application/json

{
    "first_name": "John",
    "middle_name": null,
    "last_name": "Doe",
    "no_last_name": 0,
    "email": "john.doe@example.com",
    "phone_no": "+6591234567",
    "package": "Basic Package",
    "branch": "Branch 1",
    "candidate_data_entry": 1,
    "country": "Singapore",
    "event_id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
    "event_ref_no": "REF-42345",
    "employee_id": "EMP-001",
    "cost_center": "Finance"
}
```

Sample Response (201 Created)

```
{
    "success": true,
    "message": "Case has been created.",
    "data": { "case_id": 733, "case_ref_no": "tpj4913" },
    "status_code": 201,
    "status_text": "Created"
}
```


Error Responses

Status	Cause
409	Duplicate event_id. Returns existing case details.
422	Validation failure (missing required fields, invalid package, etc.).

15.5 Get All Cases

Retrieves a filterable, paginated list of cases created by your company account. See Section 7 for pagination details.

```
GET /api/v1/case
```

Request Format: No request body. Query parameters only.

Query Parameters

Field	Type	Default	Description	Required
date_from	String(10)	—	Filter by case created date from (YYYY-MM-DD, UTC)	No
date_to	String(10)	—	Filter by case created date to (YYYY-MM-DD, UTC)	No
sort	String(3)	DESC	Sort order: ASC or DESC	No
offset	Integer	0	Zero-based record offset	No
limit	Integer	20	Records per request. Maximum: 100	No

Sample Response (200 OK)

```
{
    "success": true,
    "message": "Cases has been retrieved.",
    "data": [
        {
          "case_id": 739,
           "case_ref_no": "PFPAMY2",
          "first_name": "John",
          "middle_name": null,
          "last_name": "Doe",
          "email": "john.doe@example.com",
          "phone_no": "+6591234567",
          "case_created_date": "2025-10-01 03:14:34",
          "order_ref_no": "O-1759295135-75560",
          "order_checkout_date": "2025-10-01 05:05:35",
          "status": "Processing"
        }
    ],
    "status_code": 200,
    "status_text": "OK"
}
```


15.6 Update Candidate Info

Updates candidate information on an existing case. Only available while the case is in Insufficient Data status.

```
PUT /api/v1/case/{case_id}/candidate
```

Request Format: application/json

URL Parameters

Field	Type	Description	Required
case_id	Integer	Case ID from Create Case	**Yes**

Request Body

Field	Type	Description	Required
first_name	String(100)	Candidate first name	**Yes**
middle_name	String(100)	Candidate middle name	No
last_name	String(100)	Candidate last name. Required unless no_last_name=1	**Conditional**
no_last_name	Enum(0,1)	1 = candidate has no last name	No
email	String(100)	Candidate email address	**Yes**
phone_no	String(50)	Candidate phone number	No

Field	Type	Description	Required
employee_id	String(100)	Employee ID from client system	No

Sample Response (200 OK)

```
{
    "success": true,
    "message": "Case candidate has been updated."
    "status_code": 200,
    "status_text": "OK"
}
```

15.7 Get Case Status

Returns case-level status and details, including a summary of checks on the case. Use this for polling. See Section 14 for recommended polling frequency.

```
GET /api/v1/case/{case_id}
```

Request Format: No request body.

URL Parameters

Field	Type	Description	Required
case_id	Integer	Case ID from Create Case	**Yes**

Sample Response (200 OK)

```
{
    "success": true,
    "message": "Case status has been retrieved.",
    "data": {
      "case_id": 733,
      "ref_no": "tpj4913",
      "package_name": "Basic Package",
      "data_entry_by": "Candidate",
      "candidate": "John Doe",
       "email":
      "john.doe@example.com",
      "phone_no": "+6591234567",
      "position_applied": "TR053606",
      "status": "Processing",
       "order_id": null,
      "result": null,
       "checks": [
        {
          "check_id": 2241,
          "check_country_id": 2626,
          "check_name": "Criminal or Criminality Check - Australia (ACIC check)",
          "status": "In Progress",
          "remarks": "-"
        }
      ]
    },
    "status_code": 200,
}   "status_text": "OK"
```


Error Responses

Status	Cause
404	Case not found or does not belong to your account.

15.8 Get Case Checks Status

Returns the status of every individual check within a case, without the surrounding case details.

```
GET /api/v1/case/{case_id}/checks-status
```

Request Format: No request body.

URL Parameters

Field	Type	Description	Required
case_id	Integer	Case ID from Create Case	**Yes**

Sample Response (200 OK)

```
{
    "success": true,
    "message": "Case checks status has been retrieved.",
    "data": [
       {
         "check_id": 2241,
         "check_country_id": 2626,
         "check_name": "Criminal or Criminality Check - Australia (ACIC check)",
         "status": "In Progress",
         "remarks": "-"
       }
    ],
    "status_code": 200,
    "status_text": "OK"
}
```


15.9 Cancel Case

Cancels a case. Only cases with status Insufficient Data or Ready For Checkout can be cancelled. Cases that have already been converted to an order cannot be cancelled via this endpoint.

```
PUT /api/v1/case/{case_id}/cancel
```

Request Format: No request body.

URL Parameters

Field	Type	Description	Required
case_id	Integer	Case ID from Create Case	**Yes**

Sample Response (200 OK)


```
{
    "success": true,
    "message": "Case has been cancelled.",
    "status_code": 200,
    "status_text": "OK"
}
```


Error Responses

Status	Cause
404	Case not found.
422	Case is not in a cancellable status (already Processing or Completed).

15.10 Case Final Report — PDF Stream

Downloads the final verification report as a raw PDF byte stream. Use this to display or download the report directly in a browser or save it to disk. See Section 13 for guidance on choosing the right report stream.

```
GET /api/v1/case/final-report-pdf-stream/{case_id}
```

Request Format: No request body. Response Content-Type: application/pdf (raw binary, no JSON wrapper).

URL Parameters

Field	Type	Description	Required
case_id	Integer	Case ID from Create Case	**Yes**

> Only available when case status is Completed. Returns 404 for any other status.

Error Responses

Status	Cause
404	Case not found or report not yet available (case not Completed).

15.11 Case Final Report — Base64

Returns the final report as a Base64-encoded string, suitable for embedding in JSON payloads or storing in systems that do not support binary streams. See Section 13 for guidance.

```
GET /api/v1/case/final-report-base64/{case_id}
```

Request Format: No request body.

URL Parameters

Field	Type	Description	Required
case_id	Integer	Case ID from Create Case	**Yes**

Sample Response (200 OK)

```
{
    "success": true,
    "message": "Case final report base64 encode.",
    "data": "<Base64_encoded_PDF_string>",
    "status_code": 200,
    "status_text": "OK"
}
```


> Only available when case status is Completed.

15.12 Case Final Report — JSON

Returns the final report as structured JSON with candidate details, check-by-check verified results, and remarks. Use this to pull results directly into your HRMS record. See Section 13 for guidance.

```
GET /api/v1/case/final-report-json/{case_id}
```

Request Format: No request body.

URL Parameters

Field	Type	Description	Required
case_id	Integer	Case ID from Create Case	**Yes**

Sample Response (200 OK) — Full

```
{
    "success": true,
    "message": "Report data has been generated.",
    "data": {
        "candidate": { "label": "Candidate/Employee Full Name", "value": "James Matias" },
        "company_name": { "label": "Company Name", "value": "Example Company Pte Ltd" },
        "branch_name": { "label": "Branch Name", "value": "Branch 1" },
        "report_date": { "label": "Date of Report", "value": "2026-01-20" },
        "package_name": { "label": "Package Code/Level (if any)", "value": "Basic Package"
},
        "cost_center": { "label": "Cost Centre", "value": "-" },
        "mom_ref_no": { "label": "Case Reference No.", "value": "tpj4913" },
        "status_text": { "label": "Status", "value": "Completed" },
        "result": { "label": "Result", "value": "green" },
        "personal": {
            "first_name": { "label": "First Name", "candidate_value": "James",
"verified_value": null },
            "last_name": { "label": "Last Name", "candidate_value": "Matias",
"verified_value": null, "remarks": null },
            "middle_name": { "label": "Middle Name", "candidate_value": null,
"verified_value": null, "remarks": null },
            "aka": { "label": "Alias or Nick Name", "candidate_value": null,
"verified_value": null, "remarks": null },
            "birth_date": { "label": "Date of Birth", "candidate_value": "2001-01-01",
"verified_value": null, "remarks": null },
            "birth_country": { "label": "Country of Birth", "candidate_value":
"Philippines", "verified_value": null, "remarks": null },
            "citizenship": { "label": "Citizenship", "candidate_value": null,
"verified_value": null, "remarks": null },
            "phone_no": { "label": "Home Phone Number", "candidate_value": "+63-
9123456789", "verified_value": null, "remarks": null },
            "alter_phone_no": { "label": "Alternate Phone Number", "candidate_value": null,
"verified_value": null, "remarks": null },
            "primary_id_card_no": { "label": "Unique ID Number1", "candidate_value": "124-
124-12412", "verified_value": null, "remarks": null },
            "primary_id_card_no_2": { "label": "Unique ID Number2", "candidate_value":
null, "verified_value": null, "remarks": null },
            "email": { "label": "Email Address", "candidate_value":
"james.matias@example.com", "verified_value": null, "remarks": null },
            "gender": { "label": "Gender", "candidate_value": "Male", "verified_value":
null, "remarks": null },
            "civil_status": { "label": "Marital Status", "candidate_value": null,
"verified_value": null, "remarks": null },
            "position_applied": { "label": "Position Applied For", "candidate_value": null,
"verified_value": null, "remarks": null },
            "status": { "label": "Verified Status", "verified_value": "In Progress" },
            "candidate_files": [
                { "doc_type": "consent", "filename": "consent-form.png", "url":
"https://middleware.avvanz.com/case/733/candidate/document/465/download" }
            ],
            "verified_files": []
        },
        "address": {
            "Address Verification - 1": {
                "address_line_1": { "label": "Address Line1", "candidate_value": "1 Example
Street", "verified_value": "", "verified_remarks": null },
                "address_line_2": { "label": "Address Line2", "candidate_value": null,
"verified_value": "", "verified_remarks": null },
```

```
                "postal_code": { "label": "Postal Code/Zip Code", "candidate_value": null,
"verified_value": "", "verified_remarks": null },
                "stay_date_from": { "label": "Stay From Date", "candidate_value": "2015-
01", "verified_value": "", "verified_remarks": null },
                "stay_date_to": { "label": "Stay To Date", "candidate_value": "2025-01",
"verified_value": "", "verified_remarks": null },
                "house_owner_name": { "label": "House Owner Name (if you are a tenant)",
"candidate_value": null, "verified_value": "", "verified_remarks": null },
                "house_owner_contact_no": { "label": "Contact # of House Owner (if you are
a tenant)", "candidate_value": null, "verified_value": "", "verified_remarks": null },
                "neighbor_name": { "label": "Name of Neighbour", "candidate_value": null,
"verified_value": "", "verified_remarks": null },
                "neighbor_contact_no": { "label": "Contact # of Neighbour",
"candidate_value": null, "verified_value": "", "verified_remarks": null },
                "country": { "label": "Country", "candidate_value": "Philippines",
"verified_value": null, "verified_remarks": null },
                "status": { "label": "Verified Status", "verified_value": "Clear",
"remarks": "Verified by neighbour, obtained verbally." }
            },
            "candidate_files": [],
            "verified_files": []
        },
        "employment": {
            "Employment Details Verification - 1": {
                "company_name": { "label": "Company Name", "candidate_value": "Company A",
"verified_value": "Company A", "verified_remarks": null },
                "annual_salary": { "label": "Annualised Salary", "candidate_value": null,
"verified_value": "1425678", "verified_remarks": null },
                "salary_currency": { "label": "Employment Currency", "candidate_value":
null, "verified_value": "SGD", "verified_remarks": null },
                "position": { "label": "Designation", "candidate_value": "Retailer",
"verified_value": "Retailer", "verified_remarks": null },
                "employment_status": { "label": "Employment Status", "candidate_value":
"Full-Time Employee", "verified_value": "Full-Time Employee", "verified_remarks": null },
                "date_from": { "label": "Tenure (from)", "candidate_value": "2016-08",
"verified_value": "2016-08", "verified_remarks": null },
                "date_to": { "label": "Tenure (to)", "candidate_value": "2020-08",
"verified_value": "2020-08", "verified_remarks": null },
                "country": { "label": "Country", "candidate_value": "Philippines",
"verified_value": "Philippines", "verified_remarks": null },
                "reason_for_leaving": { "label": "Reason for Leaving", "candidate_value":
"Resignation", "verified_value": "Resignation", "verified_remarks": null },
                "postal_code": { "label": "Postal Code/Zip Code", "candidate_value": null,
"verified_value": "", "verified_remarks": null },
                "address_line_1": { "label": "Address Line1", "candidate_value": null,
"verified_value": "", "verified_remarks": null },
                "address_line_2": { "label": "Address Line2", "candidate_value": null,
"verified_value": "", "verified_remarks": null },
                "hr_first_name": { "label": "HR First Name", "candidate_value": null,
"verified_value": null, "verified_remarks": null },
                "hr_last_name": { "label": "HR Last Name", "candidate_value": null,
"verified_value": null, "verified_remarks": null },
                "hr_email": { "label": "HR Email Address", "candidate_value": null,
"verified_value": null, "verified_remarks": null },
                "hr_personnel_position": { "label": "HR Designation", "candidate_value":
null, "verified_value": null, "verified_remarks": null },
                "hr_contact_no": { "label": "HR Contact No.", "candidate_value": null,
"verified_value": null, "verified_remarks": null },
```

```
                "eligible_for_rehire": { "label": "Eligible for Rehire?",
"candidate_value": null, "verified_value": "Yes", "verified_remarks": null },
                "agency_name": { "label": "Agency Name", "candidate_value": null,
"verified_value": null, "verified_remarks": null },
                "status": { "label": "Verified Status", "verified_value": "Clear",
"remarks": "Verified by HR, obtained verbally." }
            },
            "candidate_files": [],
            "verified_files": []
        },
        "employment_performance": {
            "Employment Performance Verification - 1": {
                "company_name": { "label": "Company", "candidate_value": "Company B",
"verified_value": "Company B", "verified_remarks": null },
                "position": { "label": "Designation", "candidate_value": null,
"verified_value": "", "verified_remarks": null },
                "address_line_1": { "label": "Address Line1", "candidate_value": null,
"verified_value": null, "verified_remarks": null },
                "address_line_2": { "label": "Address Line2", "candidate_value": null,
"verified_value": null, "verified_remarks": null },
                "supervisor_first_name": { "label": "Supervisor Firstname",
"candidate_value": "Marc", "verified_value": "Marc", "verified_remarks": null },
                "supervisor_last_name": { "label": "Supervisor Lastname",
"candidate_value": null, "verified_value": "", "verified_remarks": null },
                "supervisor_email": { "label": "Supervisor Email Address",
"candidate_value": "marc.santiago@example.com", "verified_value":
"marc.santiago@example.com", "verified_remarks": null },
                "postal_code": { "label": "Postal Code/Zip Code", "candidate_value": null,
"verified_value": null, "verified_remarks": null },
                "supervisor_position": { "label": "Supervisor Designation",
"candidate_value": "Manager", "verified_value": "Manager", "verified_remarks": null },
                "country": { "label": "Country", "candidate_value": "Philippines",
"verified_value": null, "verified_remarks": null },
                "contact_no": { "label": "Contact Number", "candidate_value": "(063) 912-
3456789", "verified_value": "(063) 912-3456789", "verified_remarks": null },
                "reference_relationship": { "label": "Relationship", "candidate_value":
null, "verified_value": null, "verified_remarks": null },
                "status": { "label": "Verified Status", "verified_value": "Clear",
"remarks": "Verified by Operations Manager." }
            },
            "candidate_files": [],
            "verified_files": []
        },
        "education": {
            "Education Verification - 1": {
                "institution_name": { "label": "Institution Name", "candidate_value":
"University A", "verified_value": "", "verified_remarks": null },
                "qualification_attained": { "label": "Qualification Attained ",
"candidate_value": null, "verified_value": "", "verified_remarks": null },
                "course": { "label": "Course", "candidate_value": "Course A",
"verified_value": "", "verified_remarks": null },
                "date_graduated": { "label": "Date Graduated", "candidate_value": null,
"verified_value": "", "verified_remarks": null },
                "date_from": { "label": "Date Attended from", "candidate_value": "2010-08",
"verified_value": "", "verified_remarks": null },
                "date_to": { "label": "Date Attended to", "candidate_value": "2011-06",
"verified_value": "", "verified_remarks": null },
                "country": { "label": "Country", "candidate_value": "Philippines",
```

```
"verified_value": null, "verified_remarks": null },
                "address_line_1": { "label": "Address Line1", "candidate_value": "Unit 508
Example Condominium", "verified_value": "", "verified_remarks": null },
                "address_line_2": { "label": "Address Line2", "candidate_value": null,
"verified_value": "", "verified_remarks": null },
                "postal_code": { "label": "Postal Code/Zip Code", "candidate_value": null,
"verified_value": "", "verified_remarks": null },
                "institution_contact_no": { "label": "Institution Contact Number",
"candidate_value": null, "verified_value": "", "verified_remarks": null },
                "institution_email": { "label": "Institution Email", "candidate_value":
null, "verified_value": "", "verified_remarks": null },
                "status": { "label": "Verified Status", "verified_value": "Clear",
"remarks": "Verified online." }
            },
            "candidate_files": [],
            "verified_files": []
        },
        "professional_qualification": {
            "Professional Qualification Verification - 1": {
                "certificate_issuing_authority": { "label": "Certificate Issuing
Authority", "candidate_value": "Company C", "verified_value": "Company C",
"verified_remarks": null },
                "qualification_attained": { "label": "Qualification Attained",
"candidate_value": "Qualification A", "verified_value": "Qualification A",
"verified_remarks": null },
                "certificate_number": { "label": "Certificate Number", "candidate_value":
"2623-72372-352", "verified_value": "2623-72372-352", "verified_remarks": null },
                "date_granted": { "label": "Date Granted", "candidate_value": "2021-08",
"verified_value": "2021-08", "verified_remarks": null },
                "country": { "label": "Country", "candidate_value": "Philippines",
"verified_value": null, "verified_remarks": null },
                "status": { "label": "Verified Status", "verified_value": "Clear",
"remarks": "Verified via site visit." }
            },
            "candidate_files": [],
            "verified_files": []
        }
    },
    "status_code": 200,
    "status_text": "OK"
}
```


> Only available when case status is Completed.

15.13 Get Case Price

Returns the price breakdown for a case's selected checks in the company's default currency. Use this before checkout to confirm the amount due.

```
GET /api/v1/case/{case_id}/price
```

Request Format: No request body.

URL Parameters

Field	Type	Description	Required
case_id	Integer	Case ID from Create Case	**Yes**

Sample Response (200 OK)


```
{
    "success": true,
    "message": "Case price details has been retrieved.",
    "data": {
      "items": [
         { "check_name": "Credit Check - Malaysia (Standard Credit Check)", "price":
"20.00" },
         { "check_name": "Criminal or Criminality Check - Malaysia", "price": "30.00" }
      ],
      "currency": "USD",
      "sub_total": "50.00",
      "additional_cost_total": "0.00",
      "discount_total": "0.00",
      "tax": "0.00",
      "total_due": "50.00"
    },
    "status_code": 200,
    "status_text": "OK"
}
```


15.14 Get Paid Invoice

Returns a filterable, paginated list of published invoices for your company account, including amounts, payment status, and a direct link to the invoice PDF. See Section 7 for pagination details.

```
GET /api/v1/invoice
```

Request Format: No request body. Query parameters only.

Query Parameters

Field	Type	Default	Description	Required
date_from	String(10)	—	Invoice created date from (YYYY-MM-DD, UTC)	No
date_to	String(10)	—	Invoice created date to (YYYY-MM-DD, UTC)	No
sort	String(3)	DESC	Sort order: ASC or DESC	No
offset	Integer	0	Zero-based record offset	No
limit	Integer	20	Records per request. Maximum: 100	No

Sample Response (200 OK)

```
{
    "success": true,
    "message": "Invoices has been retrieved.",
    "data": [
       {
         "invoice_id": 193,
         "invoice_no": "AVNZ-1760421128-1",
         "company_name": "EXAMPLE COMPANY",
         "branch_name": "Branch 1",
         "currency": "USD",
         "sub_total": "380.00",
         "discount_amount": "0.00",
         "additional_charges": "0.00",
         "tax_amount": "23.00",
         "total_amount_due": "403.00",
         "status": "Paid",
         "paid_date": "2025-10-14",
         "invoice_pdf_link": "https://middleware.avvanz.com/invoices/report/193"
       }
    ],
    "status_code": 200,
}
```


15.15 List Check Categories

Returns all active check categories with their category_id. Use the returned category_id as a filter in Get Checks by Category (15.16) to narrow down checks by type.

```
GET /api/v1/checks/categories
```

Request Format: No request body.

Sample Response (200 OK)


```
{
    "success": true,
    "message": "Check categories has been retrieved.",
    "data": [
       { "category_id": 1, "category_name": "Employment" },
       { "category_id": 2, "category_name": "Education" },
       { "category_id": 3, "category_name": "Criminal" }
    ],
    "status_code": 200,
    "status_text": "OK"
}
```


Error Responses

Status	Cause
401	Unauthenticated.

15.16 Get Checks by Category

Returns all active background check types. Optionally filter by category_id. Use the returned check_id in Get Country Items (15.17) and Create Case with Checks (15.19). See Section 12 for the full check selection workflow.

```
GET /api/v1/checks
```

Request Format: No request body. Query parameters only.

Query Parameters

Field	Type	Description	Required
category_id	Integer	Filter checks by category ID (from GET /api/v1/checks/categories)	No

Sample Response (200 OK)


```
{
    "success": true,
    "message": "Checks has been retrieved.",
    "data": [
        {
          "category": "Education",
          "check_id": 12,
          "check_name": "Education Verification",
          "turnaround_days": 15
        }
    ],
    "status_code": 200,
    "status text": "OK"
}
```


15.17 Get Country Items for a Check

Returns all available countries for a specific check, including pricing per country. Use the returned country_id in Get Sub-Checks (15.18) and Create Case with Checks (15.19). See Section 12 for the full check selection workflow.

```
GET /api/v1/checks/{check_id}/country-items
```

Request Format: No request body.

URL Parameters

Field	Type	Description	Required
check_id	Integer	Check ID from Get Checks by Category (15.16)	**Yes**

Query Parameters

Field	Type	Description	Required
currency	String	ISO 4217 code (e.g. USD, SGD). Falls back to company default if invalid or omitted.	No

Sample Response (200 OK)


```
{
    "success": true,
    "message": "Country items retrieved.",
     "data": {
      "check_id": 5,
      "check_name": "Employment Verification",
      "countries": [
        { "country_id": 12, "country": "Singapore", "currency": "SGD", "price": "50.00",
         "turnaround_days": 7 },
        { "country_id": 192, "country": "Malaysia", "currency": "SGD", "price": "40.00",
"turnaround_days":10 }
       ]
    },
    "status_code": 200,
    "status_text": "OK"
}
```


Error Responses

Status	Cause
401	Unauthenticated.
404	Check not found.

15.18 Get Sub-Checks for a Check

Returns all active sub-checks for a specific check and country combination, with pricing. Use the returned subcheck_id and country_id in Create Case with Checks (15.19). See Section 12 for selection rules.

```
GET  /api/v1/checks/{check_id}/{country_id}/sub-checks
```

Request Format: No request body.

URL Parameters

Field	Type	Description	Required
check_id	Integer	Check ID from Get Checks by Category	**Yes**
country_id	Integer	Country ID from GET /api/v1/checks/{check_id}/country-items	**Yes**

Query Parameters

Field	Type	Description	Required
currency	String	ISO 4217 code (e.g. USD, SGD). Falls back to company default if invalid or omitted.	No

Sample Response (200 OK)


```
{
    "success": true,
    "message": "Check sub-checks has been retrieved.",
    "data": [
       {
         "check_id": 5,
         "check_name": "Employment Verification",
         "subcheck_id": 3,
         "subcheck_name": "Standard Employment",
         "country_id": 12,
         "country": "Singapore",
         "currency": "SGD",
         "price": "50.00"
       }
    ],
    "status_code": 200,
     "status_text": "OK"
}
```


Error Responses

Status	Cause
404	Check not found or not available for the specified country.

15.19 Create Case with Checks

Creates a new background verification case by specifying individual checks directly, instead of using a pre-configured package. Each check can be selected with a country, sub-check, years of coverage, number of qualifications, or number of employers depending on what that check accepts. See Section 12 for the full check selection workflow and rules.

```
POST /api/v1/case/create-with-checks
```

Request Format: application/json

Request Body

Field	Type	Description	Required
first_name	String	Candidate first name	**Yes**
last_name	String	Candidate last name. Required unless no_last_name is true.	**Conditional**
no_last_name	Boolean	Set true to skip last name validation	No
email	String	Valid candidate email address	**Yes**
phone_no	String	Digits, spaces, +, -, (,) only	**Yes**
checks	Array	Array of check objects, minimum 1 item	**Yes**
checks.*.check_id	Integer	Valid check ID from Get Checks by Category (15.16)	**Yes**
checks.*.country_id	Integer	Country ID from Get Country Items (15.17). Use worldwide country_id for worldwide checks.	**Conditional**
checks.*.subcheck_id	Integer	Required if the check has a non-empty sub-check list for the given country	**Conditional**
checks.*.no_of_qualification	Integer	Min 1. Only for checks that accept this field.	**Conditional**
checks.*.no_of_employer	Integer	Min 1, max 5. Only for checks that accept this field.	**Conditional**
checks.*.years_of_coverage	Integer	Min 2. Only for checks that accept this field.	**Conditional**
candidate_data_entry	Integer	1 = candidate fills in (default), 2 = employer fills in	No
branch	String/Integer	Branch ID or branch name	No
event_id	String	Your unique internal event ID. Used for idempotency. See Section 11.	No
event_ref_no	String	Your internal event reference number	No
employee_id	String	Your internal employee ID	No
cost_center	String	Client cost centre	No
bu	String	Business unit name	No

Check Selection Rules

Rule	Detail
Rule 1 — One criterion per check	Each check requires exactly one of country_id, years_of_coverage, no_of_qualification, or no_of_employer — whichever that check accepts.
Rule 2 — Sub-check when applicable	subcheck_id is required only when using country_id and the check has a non-empty sub-check list for that country.

Rule	Detail
Rule 3 — Worldwide checks	Use the worldwide country_id (from Get Country Items (15.17)) for checks that apply globally.

Full Sample Request

```
POST  /api/v1/case/create-with-checks
Authorization: Bearer <access_token>
Content-Type: application/json

{
    "first_name": "Jane",
    "last_name": "Smith",
    "email": "jane.smith@example.com",
    "phone_no": "+6598765432",
    "candidate_data_entry": 1,
    "branch": "Branch 1",
    "event_id": "b2c3d4e5-f6a7-8901-bcde-f12345678901",
    "employee_id": "EMP-002",
    "checks": [
      {
        "check_id": 5,
        "country_id": 12,
        "subcheck_id": 3
      },
      {
        "check_id": 12,
        "country_id": 192,
        "subcheck_id": 7,
        "no_of_qualification": 2
      },
      {
        "check_id": 8,
        "years_of_coverage": 5
      }
    ]
}
```

> In this example: check 5 (Employment Verification) uses country+subcheck; check 12 (Education Verification) uses country+subcheck+qualification count; check 8 uses years of coverage. Each check uses exactly one selection criterion.

Sample Response (201 Created)

```
{
    "success": true,
    "message": "Case has been created.",
    "data": { "case_id": 1001, "case_ref_no": "ABC1234" },
    "status_code": 201,
    "status_text": "Created"
}
```

Error Responses

Status	Cause
409	Duplicate event_id. Returns existing case details.
422	Validation failure. The errors object contains field-level messages, e.g. unsupported field for a check.

Sample Validation Error (422)

```
{
    "success": false,
    "message": "The given data was invalid.",
    "errors": {
      "checks.0.check_id": [
        "Check 'Employment Verification' does not accept 'years_of_coverage'."
      ]
    }
}
```

15.20 Case Status Update Webhook

This endpoint receives a case update notification from the Screen Global platform and dispatches the current case status to your registered webhook URL. When called, the endpoint validates the request signature, updates the internal API case status, and asynchronously POSTs the payload to your configured webhook_url.

```
POST /api/v1/webhooks/case-updated
```

Request Format: application/json — Authenticated via HTTP Basic Auth (not Bearer token).

Request Headers

Header	Value	Description
Authorization	Basic base64(client_id:client_secret)	HTTP Basic Auth using the same credentials issued for your OAuth2 access token. This endpoint does not use Bearer tokens.
Content-Type	application/json	Request body format

Request Body

Field	Type	Description	Required
case_id	Integer	The Screen Global case ID to trigger the webhook for	**Yes**

Payload Dispatched to Your Registered Webhook URL

When triggered, the middleware POSTs the following JSON payload to your registered webhook_url:

```
{
    "case_id": 1001,
    "case_ref_no": "ABC1234",
    "candidate_name": "John Doe",
    "candidate_id": 501,
    "status": "Completed"
}
```

Sample Response (200 OK)

```
{
    "success": true,
    "message": "Case status webhook dispatched.",
     "data": { "case_id": 1001, "status": "Completed"
    }, "status_code": 200,
    "status_text": "OK"
}
```

Error Responses

Status	Cause
401	Invalid or missing Basic Auth credentials.
404	Case not found.

Webhook Delivery Authentication Types

When Avvanz dispatches the payload to your registered webhook_url, the outbound request is authenticated using whichever scheme is configured on your account (auth_type). You must configure your endpoint to accept and validate the corresponding header.

auth_type	Header(s) Sent by Avvanz	Description & How to Verify
api_key	X-API-Key: <your_api_key>	A static API key issued for your account. On your endpoint, compare the received X-API-Key value against your stored key. Reject requests where the key is missing or does not match.
basic	Authorization: Basic base64(client_id:client_secret)	HTTP Basic Auth using your registered webhook credentials (separate from your main API credentials). Decode the Base64 value and verify the client_id and client_secret match your registered webhook credentials.
oauth2	Authorization: Bearer <access_token>	A token is fetched via a client_credentials grant from your configured token URL immediately before each delivery attempt. Validate the Bearer token on your endpoint using your token introspection or public key.

auth_type	Header(s) Sent by Avvanz	Description & How to Verify
hmac	X-Avvanz-Signature: sha256=<hex-hmac>	HMAC-SHA256 of the raw JSON request body, keyed with your registered hmac_secret. On your endpoint, compute HMAC-SHA256(raw_body, hmac_secret) and compare it to the received signature using a constant-time comparison. Reject requests where the signature is missing or does not match.

> Contact Avvanz to register or update your webhook_url and choose one of the above authentication schemes. Your auth_type and associated credentials are configured per company account.

> Always verify the incoming authentication header before processing any webhook payload. Failing to do so may allow spoofed requests to trigger actions in your system.

HMAC Signature Verification Example

```
// PHP example
$rawBody = file_get_contents('php://input');
$secret = '<your_hmac_secret>';
$received = $_SERVER['HTTP_X_AVVANZ_SIGNATURE']; // "sha256=abc123..."
$computed = 'sha256=' . hash_hmac('sha256', $rawBody, $secret);
if (!hash_equals($computed, $received)) {
    http_response_code(401);
    exit('Invalid signature');
}
```

Retry Mechanism & Failure Notification

If your endpoint does not return a successful response — defined as an HTTP 2xx status code with a JSON body that does not contain "success": false — the delivery is automatically retried.

Property	Detail
Max attempts	3 total (1 initial + 2 retries)
Retry delay	60 seconds between each attempt
Failure condition	Non-2xx HTTP status, connection timeout, or a JSON body containing "success": false
After all retries fail	A failure notification email is sent once to your registered company email address
Logging	Every attempt (success or failure) is recorded in the webhook delivery log with HTTP status, attempt number, and error message

Retry Flow

```
Webhook triggered → Attempt 1 → Success (2xx, no "success":false) → Logged as "success" → Done
→ Failure → Wait 60s → Attempt 2 → Success → Logged as "success" → Done
→ Failure → Wait 60s → Attempt 3 → Success → Logged as "success" → Done
→ Failure → Logged as "failed" + Failure email sent → Done
```

> Your webhook endpoint must respond within 30 seconds. If it does not respond in time, the attempt is treated as a failure and retried. For long-running processing, respond with 200 OK immediately and process the payload asynchronously.

Webhook Delivery Log Fields

Field	Type	Description
id	Integer	Log entry ID
webhook_url	String	The URL the webhook was dispatched to
case_id	Integer	The case ID associated with this delivery
case_ref_no	String	The case reference number
case_status	String	The case status value sent in the payload
attempt	Integer	Attempt number (1, 2, or 3)
http_status	Integer	HTTP status code returned by your endpoint
status	String	success or failed
error_message	String	Error detail if delivery failed, otherwise null
email_sent	Boolean	Whether a failure notification email was sent
created_at	DateTime	Timestamp of the delivery attempt (UTC)

Delivery logs can be retrieved for troubleshooting missed or failed notifications. Contact Avvanz support or use the internal logs endpoint (GET /api/v1/webhooks/logs) to access delivery history.

16. Webhook Registration & Event Catalogue

16.1 Registration

Webhook delivery is not automatic. You must register your endpoint with Avvanz before any webhook payloads will be dispatched to your system. Registration is performed out-of-band (not via an API endpoint) by contacting Avvanz.

Registration Detail	Description
webhook_url	The publicly accessible HTTPS URL on your server that will receive POST requests from Avvanz. Must be reachable from the internet. Plain HTTP URLs are not accepted.
auth_type	The authentication scheme Avvanz will use when calling your endpoint. Choose one of: api_key, basic, oauth2, hmac. See Section 15.20 for details on each type.
Auth credentials	Depending on auth_type: your API key, webhook Basic Auth credentials, OAuth2 token URL and client credentials, or HMAC secret. Provided by you to Avvanz at registration time.
Events subscribed	Specify which events you want to receive (see Section 16.2). You may subscribe to all events or a subset.

> To update your webhook_url, change your auth_type, or rotate your webhook credentials, contact Avvanz support. Changes take effect on the next delivery attempt.

16.2 Webhook Event Catalogue

The following events trigger a webhook delivery to your registered URL:

Event	Trigger Condition	Payload status Value	Recommended Action
case.created	A new background verification case has been successfully created.	Created	Store the case_id and case_ref_no in your system. Send candidate onboarding communications if needed.
case.submitted	The candidate has submitted their information and the case has been submitted for processing.	Submitted	Update your system status. Notify the responsible team that verification is underway.

Event	Trigger Condition	Payload status Value	Recommended Action
case.completed	All checks in the case have finished and the final report is available.	Completed	Fetch the final report via 15.10, 15.11, or 15.12. Update your HRMS record.

16.3 Webhook Payload Structure

All events use the same payload structure:

```
{
    "case_id": 1001,
    "case_ref_no": "ABC1234",
    "candidate_name": "John Doe",
    "candidate_id": 501,
    "status": "Completed"
}
```

16.4 Webhook Retry on Your Side

Avvanz retries failed deliveries up to 3 times (see Section 15.20). However, if all 3 attempts fail, no further automatic retries occur. To recover missed events:

Recovery Method	Detail
Poll as fallback	Use Get Case Status (15.7) or Get All Cases (15.5) to reconcile any cases whose webhook was not received.
Delivery log review	Check webhook delivery logs (GET /api/v1/webhooks/logs) to identify failed deliveries and their error details.
Manual re-trigger	Call POST /api/v1/webhooks/case-updated with the case_id to manually re-dispatch the webhook for a specific case.

> Idempotency on your endpoint: Because retries may deliver the same event multiple times, your webhook handler must be idempotent. Use the case_id and status combination to detect and safely ignore duplicate deliveries.