

ZYVORAI LABS · CUSTOMER DOCUMENTATION

Machina

Admin Basics

2026-08-29

Ports

Port	Service
5092	<code>machina-daemon</code> — HTTPS UI + <code>/api/v1</code> + WebSocket
5093	Optional controller (multi-host)
3000	Vite dev (<code>web/</code>) proxying to <code>:5092</code>

Auth

- Default: PAM against host accounts.
- Optional: LDAP, OIDC SSO.
- Set strong `MACHINA_JWT_SECRET` ; replace self-signed TLS for production.
- Never enable `MACHINA_DAEMON_SKIP_AUTH` / `MACHINA_SKIP_AUTH` outside labs.
- Configure `roles.json` so not everyone is Admin.

Install sketch

Use `./machinactl deploy / install.sh` from the customer bundle or repo docs. Verify health on `:5092` .

Vessel (containers)

Podman or Docker on the host is optional but enabled by default:

```
[vessel]  
enabled = true  
socket = "/run/podman/podman.sock"  
auto_discover = true
```

If the engine is down, the daemon still starts; use **Infrastructure → Containers** or `POST /api/v1/vessel/reconnect` after fixing the socket.

Related

- [Getting Started](#)
- Handbook admin guide in `docs/handbook/` when present